

ASSESSMENT TOOL-HACKER RANK

C01-AT1

P Rohini (192524147)

1.

Task

In this challenge, you must read 3 integers from stdin and then print them to stdout. Each integer must be printed on a new line. To make the problem a little easier, a portion of the code is provided for you in the editor below.

Submitted Code

Language: Java 7

```
1 import java.util.Scanner;
2
3 public class Solution {
4
5     public static void main(String[] args) {
6         Scanner Sc=new Scanner(System.in);
7         int a=Sc.nextInt();
8         int b=Sc.nextInt();
9         int c=Sc.nextInt();
10        System.out.println(a);
11        System.out.println(b);
12        System.out.println(c);
13    }
14 }
15
```

Test case 0

Compiler Message

Success

Test case 1

Test case 2

Input (stdin)

1	42
2	100
3	125

Expected Output

1	42
2	100
3	125

2.

Task

Given an integer, n , perform the following conditional actions:

- If n is odd, print **Weird**
- If n is even and in the inclusive range of 2 to 5, print **Not Weird**
- If n is even and in the inclusive range of 6 to 20, print **Weird**
- If n is even and greater than 20, print **Not Weird**

Complete the stub code provided in your editor to print whether or not n is weird.

Submitted Code

Language: Java 7

```
1 import java.io.*;
2 import java.math.*;
3 import java.security.*;
4 import java.text.*;
5 import java.util.*;
6 import java.util.concurrent.*;
7 import java.util.regex.*;
8
9 public class Solution {
10
11
12
13     private static final Scanner scanner = new Scanner(System.in);
14
15     public static void main(String[] args) {
```

✓ Test case 0

✓ Test case 1

✓ Test case 2

✓ Test case 3

✓ Test case 4

✓ Test case 5

✓ Test case 6

Compiler Message

Success

Input (stdin)

```
1 3
```

Expected Output

```
1 Weird
```

3. JAVA IF ELSE

Submitted Code

Language: Java 7

```
1 import java.util.Scanner;
2
3 public class Solution {
4
5     public static void main(String[] args) {
6         Scanner sc =new Scanner(System.in);
7         int i = sc.nextInt();
8         double d=sc.nextDouble();
9         sc.nextLine();
10        String s=sc.nextLine();
11
12        System.out.println("String: " + s);
13        System.out.println("Double: " + d);
14        System.out.println("Int: " + i);
15    }
16 }
```

✓ Test case 0

Compiler Message

✓ Test case 1

Success

✓ Test case 2

Input (stdin)

```
1 42
2 3.1415
3 Welcome to HackerRank's Java tutorials!
```

✓ Test case 3

✓ Test case 4

Expected Output

```
1 String: Welcome to HackerRank's Java tutorials!
2 Double: 3.1415
3 Int: 42
```

4. Java Stdin and Stdout II

Submitted Code

Language: Java 7

```
1 import java.util.Scanner;
2
3 public class Solution {
4
5     public static void main(String[] args) {
6         Scanner sc=new Scanner(System.in);
7         System.out.println("=====");
8         for(int i=0;i<3;i++){
9             String s=sc.next();
10            int n=sc.nextInt();
11            System.out.printf("%-15s%03d%n",s,n);
12        }
13        System.out.println("=====");
14    }
15 }
```

✓ Test case 0

Compiler Message

✓ Test case 1

Success

✓ Test case 2 

Input (stdin)

```
1 java 100
2 cpp 65
3 python 50
```

✓ Test case 3 

Expected Output

```
1 =====
2 java          100
3 cpp           065
4 python        050
```

5. JAVA OUTPUT FORMATTING

Submitted Code

Language: Java 7

```
1 import java.io.*;
2 import java.util.*;
3 import java.text.*;
4 import java.math.*;
5 import java.util.regex.*;
6
7 public class Solution{
8     public static void main(String[] args){
9
10         Scanner in = new Scanner(System.in);
11         int testCases = Integer.parseInt(in.nextLine());
12         while(testCases>0){
13             String line = in.nextLine();
14
15             Pattern pattern = Pattern.compile("<(.+)>([^<]+)</\\1>");
```

✓ Test case 0

✓ Test case 1 

✓ Test case 2 

✓ Test case 3 

✓ Test case 4 

✓ Test case 5 

✓ Test case 6 

Compiler Message

Success

Input (stdin)

1	8
2	Julia
3	Samantha
4	Samantha_21
5	1Samantha
6	Samantha?10_2A
7	JuliaZ007
8	Julia@007
9	_Julia007

6.JAVA LOOPS 1

Submitted Code

Language: Java 7

```
2
3 class UsernameValidator {
4     /*
5      * Write regular expression here.
6      */
7     public static final String regularExpression = "[A-Za-z]\\w{7,29}$";
8 };
9
10
```

✓ Test case 0

Compiler Message

✓ Test case 1 

Success

✓ Test case 2 

Input (stdin)

✓ Test case 3 

✓ Test case 4 

✓ Test case 5 

✓ Test case 6 

```
1 5
2 Goodbye bye bye world world world
3 Sam went went to to to his business
4 Reya is is the the best player in eye eye game
5 in inthe
6 Hello hello Ab aB
```

Expected Output

```
1 Goodbye bye world
```

7.JAVA LOOPS 11

Submitted Code

Language: Java 7

[Open in editor](#)

```
16
17
18 class MyRegex {
19     String pattern = "([0]?\\d\\d?|2[0-4]\\d|25[0-5])\\.([0]?\\d\\d?|2[0-4]\\d|25[0-5])\\.([0]?\\d\\d?|2[0-
20 4]\\d|25[0-5])\\.([0]?\\d\\d?|2[0-4]\\d|25[0-5])";
21 }
```

✓ Test case 0

Compiler Message

Success

✓ Test case 1

✓ Test case 2

Input (stdin)

```
1 000.12.12.034
2 121.234.12.12
3 23.45.12.56
4 00.12.123.123123.123
5 122.23
6 Hello.IP
```

Expected Output

```
1 true
```

8.JAVA DATATYPES

Submitted Code

Language: Java 7

```
1 import java.util.Scanner;
2 import java.util.regex.*;
3
4 public class Solution
5 {
6     public static void main(String[] args){
7         Scanner in = new Scanner(System.in);
8         int testCases = Integer.parseInt(in.nextLine());
9         while(testCases>0){
10             String pattern = in.nextLine();
11             try {
12                 Pattern.compile(pattern);
13                 System.out.println("Valid");
14             } catch (PatternSyntaxException e) {
15                 System.out.println("Invalid");
16             }
17         }
18     }
19 }
```

✓ Test case 0

Compiler Message

Success

✓ Test case 1

✓ Test case 2

Input (stdin)

```
1 3
2 ([A-Z])(.+)
3 [AZ[a-z](a-z)
4 batcatpat(nat
```

✓ Test case 3

✓ Test case 4

✓ Test case 5

Expected Output

✓ Test case 6

```
1 Valid
2 Invalid
3 Invalid
```


9.JAVA END-OF-FILE

Submitted Code

Language: Java 7

```
1 import java.util.Scanner;
2 import java.util.regex.*;
3
4 public class Solution
5 {
6     public static void main(String[] args){
7         Scanner in = new Scanner(System.in);
8         int testCases = Integer.parseInt(in.nextLine());
9         while(testCases>0){
10             String pattern = in.nextLine();
11             try {
12                 Pattern.compile(pattern);
13                 System.out.println("Valid");
14             } catch (PatternSyntaxException e) {
15                 System.out.println("Invalid");
16             }
17         }
18     }
19 }
```

✓ Test case 0

Compiler Message

Success

✓ Test case 1

✓ Test case 2

Input (stdin)

```
1 3
2 ([A-Z])(.+)
3 [AZ[a-z](a-z)
4 batcatpat(nat
```

✓ Test case 3

✓ Test case 4

✓ Test case 5

Expected Output

✓ Test case 6

```
1 Valid
2 Invalid
3 Invalid
```

10.JAVA STATIC INITIALIZER BLOCK

Submitted Code

Language: Java 7

```
1 import java.io.*;
2 import java.util.*;
3
4 public class Solution {
5
6     public static void main(String[] args) {
7         Scanner scan = new Scanner(System.in);
8         String s = scan.nextLine();
9         if (s.trim().isEmpty()) {
10             System.out.println(0);
11         } else {
12             String[] tokens = s.trim().split("[!?._'@]+");
13             System.out.println(tokens.length);
14             for (String token : tokens) {
15                 System.out.println(token);
16             }
17         }
18     }
19 }
```

✓ Test case 0

Compiler Message

Success

✓ Test case 1

✓ Test case 2

Input (stdin)

```
1 He is a very very good boy, isn't he?
```

✓ Test case 3

Expected Output

✓ Test case 4

```
1 10
2 He
3 is
4 a
5 very
6 very
```

✓ Test case 5

✓ Test case 6

11.JAVA INT TO STRING

Submitted Code

Language: Java 7

```
4
5
6     static boolean isAnagram(String a, String b) {
7         a = a.toLowerCase();
8         b = b.toLowerCase();
9
10        char[] x = a.toCharArray();
11        char[] y = b.toCharArray();
12
13        java.util.Arrays.sort(x);
14        java.util.Arrays.sort(y);
15
16        return java.util.Arrays.equals(x, y);
17    }
18
19
```

✓ Test case 0

Compiler Message

Success

✓ Test case 1

✓ Test case 2

Input (stdin)

1 anagram

2 margana

✓ Test case 3 

✓ Test case 4 

Expected Output

1 Anagrams

✓ Test case 5 

✓ Test case 6 

12.JAVA DATE AND TIME

Submitted Code

Language: Java 7

```
1 import java.io.*;
2 import java.util.*;
3
4 public class Solution {
5
6     public static void main(String[] args) {
7
8         Scanner sc=new Scanner(System.in);
9         String A=sc.next();
10        String rev = "";
11
12        for (int i = A.length() - 1; i >= 0; i--) {
13            rev = rev + A.charAt(i);
14        }
15
16        if (A.equals(rev)) {
17            System.out.println("Yes");
18        } else {
19            System.out.println("No");
20        }
21    }
22 }
```

✓ Test case 0

Compiler Message

✓ Test case 1

Success

✓ Test case 2

Input (stdin)

```
1 madam
```

✓ Test case 3

Expected Output

✓ Test case 4

```
1 Yes
```

✓ Test case 5

13.JAVA CURRENCY FORMATTER

Language: Java 7

```
6
7
8     public static String getSmallestAndLargest(String s, int k) {
9         String smallest = "";
10        String largest = "";
11
12        smallest = s.substring(0, k);
13        largest = s.substring(0, k);
14
15        for (int i = 1; i <= s.length() - k; i++) {
16            String sub = s.substring(i, i + k);
17
18            if (sub.compareTo(smallest) < 0) {
19                smallest = sub;
20            }
21        }
```

✓ Test case 0

Compiler Message

✓ Test case 1 

Success

✓ Test case 2 

Input (stdin)

```
1  welcometojava
2  3
```

✓ Test case 3 

✓ Test case 4 

Expected Output

```
1  ava
2  wel
```

✓ Test case 5 

✓ Test case 6 

14.JAVA STRINGS INTRODUCTION

Submitted Code

Language: Java 7

```
1 import java.io.*;
2 import java.util.*;
3 import java.text.*;
4 import java.math.*;
5 import java.util.regex.*;
6
7 public class Solution {
8
9     public static void main(String[] args) {
10         Scanner in = new Scanner(System.in);
11         String S = in.next();
12         int start = in.nextInt();
13         int end = in.nextInt();
14         System.out.println(S.substring(start, end));
15     }
16 }
```

✓ Test case 0

Compiler Message

Success

✓ Test case 1

✓ Test case 2

Input (stdin)

1 **Helloworld**

✓ Test case 3

2 **3 7**

✓ Test case 4

Expected Output

1 **lowo**

✓ Test case 5

15.JAVA SUBSTRING

Submitted Code

Language: Java 7

```
1 import java.io.*;
2 import java.util.*;
3
4 public class Solution {
5
6     public static void main(String[] args) {
7
8         Scanner sc=new Scanner(System.in);
9         String A=sc.next();
10        String B=sc.next();
11        System.out.println(A.length() + B.length());
12
13    if (A.compareTo(B) > 0) {
14        System.out.println("Yes");
15    } else {
16        System.out.println("No");
17    }
18 }
```

✓ Test case 0

Compiler Message

Success

✓ Test case 1

✓ Test case 2

Input (stdin)

1 **hello**

✓ Test case 3

2 **java**

✓ Test case 4

Expected Output

1 **9**

✓ Test case 5

2 **No**

3 **Hello Java**

16.JAVA SUBSTRING COMPARISONS

Submitted Code

Language: Java 7

```
1 import java.util.*;
2 import java.text.*;
3
4 public class Solution {
5
6     public static void main(String[] args) {
7         Scanner scanner = new Scanner(System.in);
8         double payment = scanner.nextDouble();
9         scanner.close();
10        Locale indiaLocale=new Locale("en","IN");
11        NumberFormat us=NumberFormat.getCurrencyInstance(Locale.US);
12        NumberFormat india=NumberFormat.getCurrencyInstance(indiaLocale);
13        NumberFormat china=NumberFormat.getCurrencyInstance(Locale.CHINA);
14        NumberFormat france=NumberFormat.getCurrencyInstance(Locale.FRANCE);
15        System.out.println("US: " + us.format(payment));
16        System.out.println("India: " + india.format(payment));
17        System.out.println("China: " + china.format(payment));
18        System.out.println("France: " + france.format(payment));
19    }
20 }
```

✓ Test case 0

✓ Test case 1 

✓ Test case 2 

✓ Test case 3 

✓ Test case 4 

✓ Test case 5 

✓ Test case 6 

Compiler Message

Success

Input (stdin)

```
1 12324.134
```

Expected Output

```
1 US: $12,324.13
2 India: Rs.12,324.13
3 China: ¥12,324.13
4 France: 12 324,13 €
```


17.JAVA STRING REVERSE

Submitted Code

Language: Java 7

```
10
11
12 class Result {
13     public static String findDay(int month, int day, int year) {
14         Calendar cal = Calendar.getInstance();
15         cal.set(year, month - 1, day);
16
17         String[] days = {
18             "SUNDAY", "MONDAY", "TUESDAY",
19             "WEDNESDAY", "THURSDAY", "FRIDAY", "SATURDAY"
20         };
21
22         return days[cal.get(Calendar.DAY_OF_WEEK) - 1];
23     }
24
25 }
```

✓ Test case 0

Compiler Message

Success

✓ Test case 1

✓ Test case 2

Input (stdin)

```
1 08 05 2015
```

✓ Test case 3

Expected Output

✓ Test case 4

```
1 WEDNESDAY
```

✓ Test case 5

18.JAVA ANAGRAMS

Submitted Code

Language: Java 7

```
13
14 String s = Integer.toString(n);
15
16
```

✓ Test case 0

Compiler Message

Success

✓ Test case 1 

✓ Test case 2 

Input (stdin)

1 100

✓ Test case 3 

Expected Output

1 Good job

19.JAVA STRING TOKENS

Submitted Code

Language: Java 7

```
1 import java.io.*;
2 import java.math.*;
3 import java.security.*;
4 import java.text.*;
5 import java.util.*;
6 import java.util.concurrent.*;
7 import java.util.regex.*;
8
9
10
11 public class Solution {
12     public static void main(String[] args){
13         Scanner sc=new Scanner(System.in);
14         int n=sc.nextInt();
15         for(int i=1;i<=10;i++)
16             r
```

✓ Test case 0

✓ Test case 1

✓ Test case 2

✓ Test case 3 

✓ Test case 4 

✓ Test case 5 

✓ Test case 6 

Compiler Message

Success

Input (stdin)

```
1 4
2 <h1>Nayeem loves counseling</h1>
3 <h1><h1>Sanjay has no watch</h1></h1><par>So wait for a while<par>
4 <Amees>safat codes like a ninja</amees>
5 <SA premium>Imtiaz has a secret crash</SA premium>
```

Expected Output

```
1 Nayeem loves counseling
2 Sanjay has no watch
```

20.PATTERN SYNTAX CHECKER

Submitted Code

Language: Java 7

```
20
21
22     @Override
23     void getNumberOfTeamMembers() {
24         System.out.println("Each team has 11 players in " + getName());
25     }
26
27
28
```

✓ Test case 0

Compiler Message

Success

✓ Test case 1

✓ Test case 2

Input (stdin)

1 6

✓ Test case 3

Expected Output

✓ Test case 4

1 I implemented: AdvancedArithmetic

✓ Test case 5

2 12

21.JAVA REGEX

Submitted Code

Language: Java 7

```
5
6
7 // Class MyCalculator implements the AdvancedArithmetic interface
8 class MyCalculator implements AdvancedArithmetic {
9     // Implementing the divisor_sum method
10    public int divisor_sum(int n) {
11        int sum = 0;
12
13        // Loop from 1 to n to find all divisors
14        for (int i = 1; i <= n; i++) {
15            if (n % i == 0) {
16                sum += i; // Add divisor to the sum
17            }
18        }
19    }
20}
```

✓ Test case 0

Compiler Message

✓ Test case 1

Success

✓ Test case 2 

Input (stdin)

```
1 A tale of two cities
```

Expected Output

```
1 The title is: A tale of two cities
```

22.JAVA REGEX-2

Submitted Code

Language: Java 7

```
9
10
11 // Class MyBook that extends the abstract class Book
12 class MyBook extends Book {
13     // Implementing the abstract setTitle method
14     @Override
15     void setTitle(String s) {
16         this.title = s;
17     }
18 }
19
20
21
```

✓ Test case 0

Compiler Message

Success

Expected Output

```
1  My superclass is: Arithmetic
2  42 13 20
```

23.VALID USERNAME REGULAR EXPRESSI

Submitted Code

Language: Java 7

```
1 import java.io.*;
2 import java.util.*;
3 import java.text.*;
4 import java.math.*;
5 import java.util.regex.*;
6
7 public class Solution {
8
9     public static void main(String[] args) {
10         Scanner sc = new Scanner(System.in);
11
12         int N = sc.nextInt();
13         int M = sc.nextInt();
14
15         BitSet b1 = new BitSet(N);
16         BitSet b2 = new BitSet(M);
```

✓ Test case 0

✓ Test case 1

✓ Test case 2

✓ Test case 3

✓ Test case 4

✓ Test case 5

✓ Test case 6

Compiler Message

Success

Input (stdin)

```
1 5 4
2 AND 1 2
3 SET 1 4
4 FLIP 2 2
5 OR 2 1
```

Expected Output

```
1 0 0
2 1 0
```

24.TAG CONTENT EXTRACTOR

Submitted Code

Language: Java 7

```
1  import java.util.*;
2
3  public class test {
4
5      public static void main(String[] args) {
6          Scanner in = new Scanner(System.in);
7
8          int n = in.nextInt();
9          int m = in.nextInt();
10
11         Deque<Integer> deque = new ArrayDeque<Integer>();
12         HashMap<Integer, Integer> map = new HashMap<Integer, Integer>();
13
14         int max = 0;
15
16         for (int i = 0; i < n; i++) {
```

✓ Test case 0

✓ Test case 1 

✓ Test case 2 

✓ Test case 3 

✓ Test case 4 

✓ Test case 5 

✓ Test case 6 

Compiler Message

Success

Input (stdin)

```
1  6 3
2  5 3 5 2 3 2
```

Expected Output

```
1  3
```


25.JAVA BIGDECIMAL

Submitted Code

Language: Java 7

```
1 import java.util.*;
2
3 class Student {
4     private int id;
5     private String fname;
6     private double cgpa;
7
8     public Student(int id, String fname, double cgpa) {
9         this.id = id;
10        this.fname = fname;
11        this.cgpa = cgpa;
12    }
13
14    public int getId() {
15        return id;
16    }
17 }
```

✓ Test case 0

Compiler Message

✓ Test case 1 

Success

✓ Test case 2 

Input (stdin)

✓ Test case 3 

✓ Test case 4 

✓ Test case 5 

✓ Test case 6 

```
1 5
2 33 Rumpa 3.68
3 85 Ashis 3.85
4 56 Samiha 3.75
5 19 Samara 3.75
6 22 Fahim 3.76
```

Expected Output

```
1 Ashis
```

26.JAVA PRIMALITY TEST

Submitted Code

Language: Java 7

```
2
3
4 class Checker implements Comparator<Player>
5 {
6     public int compare(Player a, Player b)
7     {
8         if (a.score < b.score)
9             return 1;
10        else if (a.score > b.score)
11            return -1;
12        else
13            return a.name.compareTo(b.name);
14    }
15 }
16
17
```

✓ Test case 0

Compiler Message

✓ Test case 1

Success

✓ Test case 2

Input (stdin)

✓ Test case 3

✓ Test case 4

✓ Test case 5

```
1 5
2 amy 100
3 david 100
4 heraldo 50
5 aakansha 75
6 aleksa 150
```

Expected Output

```
1 aleksa 150
```

27.JAVA 1D ARRAY

Submitted Code

Language: Java 7

```
6
7
8 class Printer
9 {
10     public <T> void printArray(T[] array)
11     {
12         for (T element : array)
13         {
14             System.out.println(element);
15         }
16     }
17 }
18
19
```

✓ Test case 0

Compiler Message

Success

Expected Output

1	1
2	2
3	3
4	Hello
5	World

28.JAVA 2D ARRAY

Submitted Code

Language: Java 7

```
10 Stack<Character> stack = new Stack<>();
11
12 boolean balanced = true;
13
14 for (char ch : input.toCharArray()) {
15     if (ch == '(' || ch == '{' || ch == '[') {
16         stack.push(ch);
17     } else {
18         if (stack.isEmpty()) {
19             balanced = false;
20             break;
21         }
22     }
23
24     char top = stack.pop();
25 }
```

✓ Test case 0

Compiler Message

✓ Test case 1

Success

✓ Test case 2

Input (stdin)

1	{ } ()
2	({ () })
3	{ } (
4	[]

Expected Output

1	true
2	true
3	false

29.JAVA SUB ARRAY

Submitted Code

Language: Java 7

```
1 //Complete this code or write your own from scratch
2 import java.util.*;
3 import java.io.*;
4
5 class Solution{
6     public static void main(String []argh)
7     {
8         Scanner in = new Scanner(System.in);
9
10        int n = in.nextInt();
11        in.nextLine();
12
13        HashMap<String, Integer> map = new HashMap<>();
14
15        for (int i = 0; i < n; i++) {
```

✓ Test case 0

Compiler Message

✓ Test case 1 

Success

✓ Test case 2 

Input (stdin)

✓ Test case 3 

✓ Test case 4 

```
1 3
2 uncle sam
3 99912222
4 tom
5 11122222
6 harry
7 12299933
8 uncle sam
9 uncle tom
```

30.JAVA ARRAYLIST

Submitted Code

Language: Java 7

```
1 import java.io.*;
2 import java.util.*;
3 import java.text.*;
4 import java.math.*;
5 import java.util.regex.*;
6
7 public class Solution {
8
9     public static void main(String[] args) {
10         Scanner sc = new Scanner(System.in);
11
12         int n = sc.nextInt();
13         ArrayList<Integer> list = new ArrayList<Integer>();
14
15         for (int i = 0; i < n; i++) {
16             int x = sc.nextInt();
17         }
```

✓ Test case 0 

✓ Test case 1 

✓ Test case 2 

✓ Test case 3

✓ Test case 4 

✓ Test case 5 

✓ Test case 6 

Compiler Message

Success

31.JAVA 1D ARRAY

Submitted Code

Language: Java 7

```
1 import java.util.*;
2
3 public class Solution {
4
5     public static boolean canWin(int leap, int[] game) {
6         return canWin(leap, game, 0);
7     }
8
9     private static boolean canWin(int leap, int[] game, int i) {
10
11         if (i < 0 || game[i] == 1)
12             return false;
13
14         if (i >= game.length - 1 || i + leap >= game.length)
15             return true;
```

✓ Test case 0

✓ Test case 1 

✓ Test case 2 

✓ Test case 3 

✓ Test case 4 

✓ Test case 5 

✓ Test case 6 

Compiler Message

Success

Input (stdin)

```
1 4
2 5 3
3 0 0 0 0 0
4 6 5
5 0 0 0 1 1 1
6 6 3
7 0 0 1 1 1 0
8 3 1
9 0 1 0
```

32.JAVA LIST

Submitted Code

Language: Java 7

```
1 import java.io.*;
2 import java.util.*;
3 import java.text.*;
4 import java.math.*;
5 import java.util.regex.*;
6 public class Solution {
7     public static void main(String[] args) {
8         Scanner sc = new Scanner(System.in);
9
10        int n = sc.nextInt();
11        ArrayList<ArrayList<Integer>> list = new ArrayList<>();
12
13        for (int i = 0; i < n; i++) {
14            int d = sc.nextInt();
15            ArrayList<Integer> row = new ArrayList<>();
16        }
```

✓ Test case 0

Compiler Message

✓ Test case 1

Success

✓ Test case 2

Input (stdin)

```
1 5
2 5 41 77 74 22 44
3 1 12
4 4 37 34 36 52
5 0
6 3 20 22 33
7 5
8 1 3
9 3 4
```

✓ Test case 3

✓ Test case 4

✓ Test case 5

33.JAVA MAP

Submitted Code

Language: Java 7

```
1 import java.io.*;
2 import java.util.*;
3 import java.text.*;
4 import java.math.*;
5 import java.util.regex.*;
6
7 public class Solution {
8     public static void main(String[] args) {
9
10         Scanner sc = new Scanner(System.in);
11
12         int n = sc.nextInt();
13         int[] arr = new int[n];
14
15         for (int i = 0; i < n; i++) {
```

✓ Test case 0

Compiler Message

Success

✓ Test case 1

✓ Test case 2

Input (stdin)

1	5
2	1 -2 4 -5 1

✓ Test case 3

✓ Test case 4

Expected Output

1	9
---	---

✓ Test case 5

34.JAVA STACK

Submitted Code

Language: Java 7

```
1 import java.io.*;
2 import java.math.*;
3 import java.security.*;
4 import java.text.*;
5 import java.util.*;
6 import java.util.concurrent.*;
7 import java.util.regex.*;
8 import java.util.*;
9 public class Solution {
10
11     public static void main(String[] args) throws IOException {
12
13         BufferedReader bufferedReader = new BufferedReader(new InputStreamReader(System
14
15         List<List<Integer>> arr = new ArrayList<>();
16
```

✓ Test case 0 

✓ Test case 1

✓ Test case 2 

Compiler Message

Success

35.JAVA GENERICS

Submitted Code

Language: Java 7

```
10
11 Scanner Scan = new Scanner(System.in);
12
13 int[] a = new int[n];
14
15 for (int i = 0; i < n; i++) {
16     a[i] = scan.nextInt();
17 }
18
```

✓ Test case 0

Compiler Message

Success

✓ Test case 1 

Input (stdin)

1	5
2	10
3	20
4	30
5	40
6	50

Expected Output

1	10
---	----

36.JAVA COMPARATOR

Submitted Code

Language: Java 7

[Open](#)

```
1 import java.io.*;
2 import java.math.*;
3 import java.security.*;
4 import java.text.*;
5 import java.util.*;
6 import java.util.concurrent.*;
7 import java.util.regex.*;
8
9
10
11 public class Solution {
12     public static void main(String[] args) throws IOException {
13         BufferedReader bufferedReader = new BufferedReader(new InputStreamReader(System.in));
14
15         String n = bufferedReader.readLine();
16         BigInteger prime = BigInteger.ONE;
```

✓ Test case 0

Compiler Message

Success

✓ Test case 1

✓ Test case 2

Input (stdin)

1 | **13**

✓ Test case 3

Expected Output

1 | **prime**

✓ Test case 4

✓ Test case 5

✓ Test case 6

37.JAVA SORT

Submitted Code

Language: Java 7

 Open

```
1 import java.io.*;
2 import java.math.*;
3 import java.security.*;
4 import java.text.*;
5 import java.util.*;
6 import java.util.concurrent.*;
7 import java.util.regex.*;
8
9
10
11 public class Solution {
12     public static void main(String[] args) throws IOException {
13         BufferedReader bufferedReader = new BufferedReader(new InputStreamReader(System.in));
14
15         String n = bufferedReader.readLine();
```

✓ Test case 0

Compiler Message

Success

✓ Test case 1 

✓ Test case 2 

Input (stdin)

1 | 13

✓ Test case 3 

Expected Output

1 | prime

✓ Test case 4 

✓ Test case 5 

✓ Test case 6 

38.JAVA DEQUEUE

Submitted Code

Language: Java 7

```
14
15 Arrays.sort(s, 0, n, new Comparator<String>() {
16     @Override
17     public int compare(String a, String b) {
18         BigDecimal bd1 = new BigDecimal(a);
19         BigDecimal bd2 = new BigDecimal(b);
20         return bd2.compareTo(bd1);
21     }
22 });
23
24
25
```

✓ Test case 0

✓ Test case 1

✓ Test case 2 

✓ Test case 3 

✓ Test case 4 

✓ Test case 5 

✓ Test case 6 

Compiler Message

Success

Input (stdin)

1	9
2	-100
3	50
4	0
5	56.6
6	90
7	0.12
8	.12
9	02.34

39.JAVA BITSET

Submitted Code

Language: Java 7

```
1 import java.io.*;
2 import java.util.*;
3 import java.text.*;
4 import java.math.*;
5 import java.util.regex.*;
6
7 public class Solution{
8     public static void main(String[] args){
9
10         Scanner in = new Scanner(System.in);
11         int testCases = Integer.parseInt(in.nextLine());
12         while(testCases>0){
13             String line = in.nextLine();
14
15             Pattern pattern = Pattern.compile("<(.)+>([^<]+)</\\1>");
```

✓ Test case 0

✓ Test case 1

✓ Test case 2

✓ Test case 3 

✓ Test case 4 

✓ Test case 5 

✓ Test case 6 

Compiler Message

Success

Input (stdin)

```
1 4
2 <h1>Nayeem loves counseling</h1>
3 <h1><h1>Sanjay has no watch</h1></h1><par>So wait for a while<par>
4 <Amees>safat codes like a ninja</amees>
5 <SA premium>Imtiaz has a secret crash</SA premium>
```

Expected Output

```
1 Nayeem loves counseling
2 Sanjay has no watch
```

40.JAVA INHERITANCE II

Submitted Code

Language: Java 7

```
2
3 class UsernameValidator {
4     /*
5      * Write regular expression here.
6      */
7     public static final String regularExpression = "[A-Za-z]\\w{7,29}$";
8 };
9
10
```

✓ Test case 0

Compiler Message

Success

Expected Output

- 1 **Generic Sports**
- 2 **Each team has n players in Generic Sports**
- 3 **Soccer Class**
- 4 **Each team has 11 players in Soccer Class**

41.JAVA ABSTRACT CLASS

Submitted Code

Language: Java 7

```
8
9 class Add {
10
11     public void add(int... numbers) {
12         int sum = 0;
13
14         for (int i = 0; i < numbers.length; i++) {
15             sum += numbers[i];
16             System.out.print(numbers[i]);
17
18             if (i != numbers.length - 1) {
19                 System.out.print("+");
20             }
21         }
22
23         System.out.println("\n");
24     }
25 }
```

✓ Test case 0

Compiler Message

Success

✓ Test case 1

Input (stdin)

1	3 5
2	2 4
3	0 0
4	-1 -2
5	-1 3

Expected Output

1	243
2	16

42.JAVA INTERFACE

Submitted Code

Language: Java 7

```
3
4 class MyCalculator {
5     long power(int n, int p) throws Exception
6     {
7         if (n == 0 && p == 0)
8         {
9             throw new Exception("n and p should not be zero.");
10        }
11
12        if (n < 0 || p < 0)
13        {
14            throw new Exception("n or p should not be negative.");
15        }
16
17        return (long)Math.pow(n, p);
18    }
```

✓ Test case 0

Compiler Message

Success

Expected Output

```
1 Hello I am a motorcycle, I am a cycle with an engine.
2 My ancestor is a cycle who is a vehicle with pedals.
```

43.JAVA METHOD OVERRIDING

Submitted Code

Language: Java 7

```
18  
19  
20 String temp = super.define_me();  
21  
22
```

✓ Test case 0

Compiler Message

Success

Expected Output

```
1 Generic Sports  
2 Each team has n players in Generic Sports  
3 Soccer Class  
4 Each team has 11 players in Soccer Class
```

44. JAVA METHOD OVERRIDING-2

Submitted Code

Language: Java 7

```
20
21
22     @Override
23     void getNumberOfTeamMembers() {
24         System.out.println("Each team has 11 players in " + getName());
25     }
26
27
28
```

✓ Test case 0

Compiler Message

✓ Test case 1

Success

✓ Test case 2

Input (stdin)

1 6

✓ Test case 3 

✓ Test case 4 

Expected Output

1 I implemented: AdvancedArithmetic

2 12

✓ Test case 5 

45.JAVA EXCEPTION HANDLING

Submitted Code

Language: Java 7

```
5
6
7 // Class MyCalculator implements the AdvancedArithmetic interface
8 class MyCalculator implements AdvancedArithmetic {
9     // Implementing the divisor_sum method
10    public int divisor_sum(int n) {
11        int sum = 0;
12
13        // Loop from 1 to n to find all divisors
14        for (int i = 1; i <= n; i++) {
15            if (n % i == 0) {
16                sum += i; // Add divisor to the sum
17            }
18        }
19    }
20 }
```

✓ Test case 0

Compiler Message

✓ Test case 1

Success

✓ Test case 2 

Input (stdin)

```
1 | A tale of two cities
```

Expected Output

```
1 | The title is: A tale of two cities
```

46.JAVA VARARGS

Submitted Code

Language: Java 7

```
9
10
11 // Class MyBook that extends the abstract class Book
12 class MyBook extends Book {
13     // Implementing the abstract setTitle method
14     @Override
15     void setTitle(String s) {
16         this.title = s;
17     }
18 }
19
20
21
```

✓ Test case 0

Compiler Message

Success

✓ Test case 1

✓ Test case 2

Input (stdin)

1 1

✓ Test case 3

2 2

3 3

✓ Test case 4

4 4

5 5

6 6

Expected Output

1 1+2=3

47.JAVA REFLECTION

Submitted Code

Language: Java 7

```
84
85
86 public class Solution {
87
88     public static void main(String[] args){
89         Class student = Student.class;
90         Method[] methods = student.getDeclaredMethods();
91
92         ArrayList<String> methodList = new ArrayList<>();
93         for(Method method : methods){
94             methodList.add(method.getName());
95         }
96         Collections.sort(methodList);
97         for(String name: methodList){
98             System.out.println(name);
99         }
100     }
101 }
```

✓ Test case 0

Compiler Message

Success

48.CAN U ACCESS?

Submitted Code

Language: Java 7

```
3 import java.io.*;
4 import java.util.*;
5 import java.text.*;
6 import java.math.*;
7 import java.util.regex.*;
8 import java.lang.reflect.*;
9
10
11 class Singleton {
12
13     // Public instance variable
14     public String str;
15
16     // Single instance of Singleton
17     private static Singleton instance = null;
18 }
```

Test case 0

Compiler Message

Success

Test case 1

Test case 2

Input (stdin)

Download

1 7

Test case 3

Expected Output

Download

1 7 is not a power of 2

2 An instance of class: Solution.Inner.Private has been created

Test case 5

Test case 6

49.JAVA SINGLETON PATTERN

Submitted Code

Language: Java 7

[Open](#)

```
17
18 Inner inner = new Inner();
19 Inner.Private p = inner.new Private();
20
21 System.out.println(num + " is " + p.powerof2(num));
22 o = p;
23
```

✓ Test case 0

Compiler Message

Success

✓ Test case 1 [Open](#)

Input (stdin)

[Download](#)

```
1 hello world
```

Expected Output

[Download](#)

```
1 Hello I am a singleton! Let me say hello world to
you
```

50.JAVA LAMBDA EXPRESSIONS

Submitted Code

Language: Java 7

```
1 import java.io.*;
2 import java.util.*;
3 import java.text.*;
4 import java.math.*;
5 import java.util.regex.*;
6 import java.util.*;
7 import java.io.*;
8
9 interface PerformOperation {
10     boolean check(int a);
11 }
12
13 class MyMath {
14
15     public PerformOperation isOdd() {
```

✓ Test case 0

Compiler Message

✓ Test case 1 

Success

✓ Test case 2 

Input (stdin)

1	5
2	1 4
3	2 5
4	3 898
5	1 3
6	2 12