

SIMATS ENGINEERING
ASSESSMENT TOOL 3
MCQ Test

19

COURSE NAME: Computer Networks

COURSE CODE: CSA07

COURSE OUTCOME COVERED

CO3: *Analyze the performance of core network protocols such as TCP, UDP, HTTP, and DNS under varying conditions*

Assessment Tool Weightage: 20%

QUESTIONS:20

Total Marks:20

1. Which TCP mechanism reduces the congestion window by half upon detecting packet loss via duplicate ACKs?

- a) Slow Start
- b) Fast Retransmit
- ☒ c) Fast Recovery
- d) Tahoe Reset

(BL4)(1)

2. A TCP sender has CWND = 8 MSS and SSTHRESH = 16. After one RTT with no loss, CWND becomes:

- a) 9 MSS
- ☒ b) 16 MSS
- c) 12 MSS
- d) 8 MSS

(BL4)(1)

3. Which field in the TCP header is used to implement flow control at the receiver side?

- a) Sequence number
- b) Acknowledgement number
- ☒ c) Window size
- d) Urgent pointer

(BL4)(1)

4. Nagle's algorithm causes increased latency primarily because it:

- a) Disables ACK piggybacking
- ☒ b) Buffers small segments until ACK arrives
- c) Reduces CWND on every packet

d) Increases SYN backlog
(BL4)(1)

5. In a high-latency satellite link (600 ms RTT), TCP throughput is primarily limited by:

- a) MTU size
- ☒ b) CWND growth rate relative to RTT
- c) DNS resolution time
- d) UDP competition

(BL4)(1)

6. UDP is preferred over TCP for DNS queries primarily because:

- a) UDP supports fragmentation
- ☒ b) DNS responses are small and connection overhead is unnecessary
- c) TCP cannot use port 53
- d) UDP has better error correction

(BL4)(1)

7. A UDP-based streaming application experiences 15% packet loss. The best application-layer mitigation is:

- a) Increase UDP buffer size
- b) Switch to TCP
- ☒ c) Implement Forward Error Correction (FEC)
- d) Reduce frame rate to 1 fps

(BL4)(1)

8. What is the maximum UDP payload size without IP-level fragmentation on a standard Ethernet link (MTU = 1500 bytes)?

- a) 1480 bytes
- ☒ b) 1472 bytes
- c) 1460 bytes
- d) 1500 bytes

(BL4)(1)

9. QUIC protocol uses UDP as its transport. The key advantage over TCP-based TLS is:

- a) Eliminating IP header overhead
- ☒ b) 0-RTT or 1-RTT connection setup
- c) Removing encryption
- d) Native multicast support

(BL4)(1)

10. HTTP/1.1 persistent connections reduce latency by:

- a) Enabling UDP fallback
- ☒ b) Reusing the same TCP connection for multiple requests
- c) Compressing HTTP headers
- d) Sending requests without waiting for DNS

(BL4)(1)

11. Head-of-line blocking in HTTP/1.1 occurs when:

- a) The DNS server is slow

- ☒ b) A response blocks subsequent responses on the same connection
- c) TCP CWND drops to zero
- d) The server rejects pipelined requests

(BL4)(1)

12. HTTP/2 multiplexing solves HOL blocking at the HTTP layer but not at the:

- a) Application layer
- b) DNS layer
- ☒ c) TCP layer
- d) IP layer

(BL4)(1)

13. Which HTTP status code indicates that a resource has permanently moved and browsers should update bookmarks?

- ☒ a) 301
- b) 302
- c) 304
- d) 307

(BL4)(1)

14. In HTTP caching, the Cache-Control: no-cache directive means:

- a) Never cache this resource
- ☒ b) Validate with the server before using a cached copy
- c) Cache for 0 seconds
- d) Disable all caching headers

(BL4)(1)

15. Which DNS record type maps a domain name to an IPv6 address?

- a) A
- b) CNAME
- ☒ c) AAAA
- d) MX

(BL4)(1)

16. A DNS resolver switches from UDP to TCP when:

- a) The query type is MX
- ☒ b) The response is truncated (TC bit set)
- c) TTL exceeds 3600 s
- d) The authoritative server is unreachable

(BL4)(1)

17. Which attack exploits the UDP-based DNS protocol by sending forged responses with a matching transaction ID?

- a) ARP poisoning
- ☒ b) DNS cache poisoning
- c) SYN flooding
- d) BGP hijacking

(BL4)(1)

18. Setting a very low TTL (e.g., 30 s) for a DNS record primarily increases:

- a) Cache hit ratio

- b) Recursive resolver query load
- c) DNSSEC signature validity
- d) Zone transfer frequency

(BL4)(1)

19. A user browses to a new website. The correct sequence of protocol interactions for the first byte of the page is:

- a) HTTP → TCP → DNS
- b) DNS → TCP handshake → HTTP GET
- c) TCP → DNS → HTTP
- d) DNS → HTTP → TCP

(BL4)(1)

20. Under 20% packet loss, which protocol combination gives the best performance for a real-time multiplayer game?

- a) TCP for game state, HTTP for assets
- b) UDP with application-layer sequencing for game state, HTTP/3 for assets
- c) HTTP/2 for all traffic
- d) TCP with Nagle enabled for all traffic

(BL4)(1)

RUBRICS FOR CALCULATION:

Criteria	Weightage (%)	Level 4 (Exemplary)	Level 3 (Proficient)	Level 2 (Developing)	Level 1 (Beginning)
Conceptual Understanding	30%	Demonstrates thorough understanding; answers all questions accurately	Shows good understanding with few errors	Partial understanding; several incorrect responses	Lacks understanding; majority of answers incorrect
Accuracy of Answers	25%	All answers are correct	Most answers are correct with minor mistakes	Some correct answers; frequent errors	Mostly incorrect answers
Application of Knowledge	20%	Correctly applies concepts to problem-based questions	Applies concepts with minor errors	Limited ability to apply concepts	Unable to apply concepts
Time Management	15%	Completes quiz well within time efficiently	Completes on time with minor delays	Requires extra time or rushes through questions	Unable to complete within given time
Question Interpretation	10%	Interprets all questions correctly and responds appropriately	Misinterprets a few questions	Often misinterprets questions	Unable to understand questions