SIMATS ENGINEERING

C Programming

JESUVA ABISHEK R
192524218

Write a C program that swaps the values of two variables based on user input.

Testcases:
6.6

Run Save

```
#include<stdio.h>
int main()
{
  int a,b,c;
  printf("enter two numbers:");
  scanf("%d %d",&a,&b);
  c=a+b;
  printf("c=%d",c);
  return 0;
}
```

```
50 100
```

```
enter two numbers:c=150
```

Max-Min Sum-Avg

Run Save

```
#include<stdio.h>
int main()
{
  int side,area;
  printf("enter the side value:");
  scanf("%d",&side);
  area= side*side;
  printf("%d",area);
  return 0;
}
```

```
10
```

```
enter the side value:100
```

SIMATS ENGINEERING

C Programming

JESUVA ABISHEK R
192524218

Max-Min | Sum-Avg

Run | Save

```c
// addition of two float
#include<stdio.h>
int main()
{
  float a,b,c;
  printf("enter the values:");
  scanf("%f %f",&a,&b);
  c=a+b;
  printf("c=%f",c);
  return 0;
}

```

```
10.55 5.3
```

```
enter the values:c=15.850000
```

Sample input and output:

Example 1:
Input:

Max-Min

Sum-Avg

Run

Save

```c
#include<stdio.h>
int main()
{
  int r;
  float a;
  printf("enter the r value:");
  scanf("%d",&r);
  a=3.14*r*r;
  printf("%f",a);
  return 0;
}
```

```
2
```

```
enter the r value:12.560000
```

Run Save

```c
// only two digits after decimal point
#include<stdio.h>
int main()
{
  float a,b,c;
  printf("enter two numbers:");
  scanf("%f %f",&a,&b);
  c=a+b;
  printf("c=%.2f\n",c);
  return 0;
}
```

```
10.15 5.63
```

```
enter two numbers:c=15.78
```

SIMATS ENGINEERING

C Programming

JESUVA ABISHEK R
192524218

Run Save

```c
// area of rectangle
#include<stdio.h>
int main()
{
  int a,b,l;
  printf("enter the values:");
  scanf("%d %d",&b,&l);
  a=l*b;
  printf("%d",a);
  return 0;
}

```

```
5 4
```

```
enter the values:20
```

Run Save

```c
#include<stdio.h>
int main()
{
  int a=20;
  printf("octal number =%o\n",a);
  printf("hexa decimal=%x\n",a);
  return 0;
}
```

```
Your INPUT go's here! Give only values. d
not give like a=10
```

```
octal number =24
hexa decimal=14
```

SIMATS ENGINEERING

C Programming

JESUVA ABISHEK R
192524218

Max-Min | Sum-Avg

Run | Save

```c
// aiphanumerical order
#include<stdio.h>
int main()
{
  int a=20;
  printf("octal number =%o\n",a);
  printf("hexa decimal =%X\n",a);
  return 0;
}

```

```
Your INPUT go's here! Give only values. do
not give like a=10
```

```
octal number =24
hexa decimal =14
```

SIMATS ENGINEERING

C Programming

JESUVA ABISHEK R
192524218

Run Save

```c
// PRINT ASCII VALUE
#include<stdio.h>
void main()
{
  char ch='g';
  printf("ch=%c\n",ch);
  printf("ch=%d,hence an integer/n",ch);
  printf("ch1=%c\n",ch+1);
  printf("ch1=%d,hence an integer\n",ch+1);
}
```

Your INPUT go's here! Give only values. do not give like a=10

```
ch=g
ch=103,hence an integer/nch1=h
ch1=104,hence an integer
```

Run Save

```c
// positive or negative
#include<stdio.h>
int main()
{
  int a;
  printf("enter the value:");
  scanf("%d",&a);
  if (a>0)
  {
    printf("%d is a positive number",a);
    }
  else
  {
    printf("%d is a negative number",a);
    }
  return 0;
}
```

```
10
```

```
enter the value:10 is a positive number
```

SIMATS ENGINEERING

C Programming

JESUVA ABISHEK R
192524218

Run Save

```c
// eligible to vote
#include<stdio.h>
int main()
{
  int age;
  age=15;
  scanf("%d",&age);
  if(age>18)
  {
    printf("%d is eligible to vote",age);
  }
  else
  {
    printf("%d is not eligible to vote",age);
  }
  return 0;
}

```

Your INPUT go's here! Give only values. do not give like a=10

```
15 is not eligible to vote
```

Multiple Grade

Run Save

```c
//even or odd
#include<stdio.h>
int main()
{
  int number;
  number=14;
  scanf("%d",&number);
  if(number%2==0)
  {
    printf("%d is even number",number);
  }
  else
  {
    printf("%d is odd number",number);
  }
  return 0;
}
```

Your INPUT go's here! Give only values. do not give like a=10

```
14 is even number
```

Run Save

```c
//with in range
#include<stdio.h>
int main()
{
  int a;
  scanf("%d",&a);
  if(a>=1 && a<=100)
  {
    printf("%d is with in range",a);
  }
  else
  {
    printf("%d is not with in the range",a);
  }
  return 0;
}
```

```
Your INPUT go's here! Give only values. do not give like a=10
```

```
25 is with in range
```

Run Save

```c
//pass or fail
#include<stdio.h>
int main()
{
  int marks;
  scanf("%d",&marks);
  if(marks>=50)
  {
    printf("%d is pass",marks);
  }
  else
  {
    printf("%d is fail",marks);
  }
  return 0;
}
```

```
51
```

```
51 is pass
```

ENGINEERING

Run Save

```c
//divisible
#include<stdio.h>
int main()
{
  int a;
  scanf("%d",&a);
  if(a%3==0 || a%5==0)
  {
    printf("%d is divisible",a);
  }
  else
  {
    printf("%d is not divisible",a);
  }
  return 0;
}
```

```
11
```

```
11 is not divisible
```

```c
//greatest among three
#include<stdio.h>
int main()
{
  int a,b,c;
  scanf("%d %d %d",&a,&b,&c);
  if(a>b && a>c)
  {
    printf("%d is the greatest number",a);
  }
  else if(b>c)
  {
    printf("%d is the greatest number",b);
  }
  else
  {
    printf("%d is the greatest number",c);
  }
  return 0;
}
```

```
10 20 5
```

```
20 is the greatest number
```

SIMATS ENGINEERING

C Programming

JESUVA ABISHEK R
192524218

Pyramid | Diamond

Run | Save

```c
//alphabet
#include<stdio.h>
int main()
{
  char ch;
  scanf("%c",&ch);
  if(ch>=65 && ch<=91)
  {
    printf("%c is a Alphabet",ch);
  }
  else
  {
    printf("%c is not a alphabet",ch);
  }
  return 0;
}
```

Your INPUT go's here! Give only values. do not give like a=10

```
a is not a alphabet
```

SIMATS ENGINEERING

C Programming

JESUVA ABISHEK R
192524218

Fibonacci | Factorial | Pyramid | Diamond

Run | Save | Changes Updated, Saved 19

```c
#include<stdio.h>
int main()
{
  int x,i;
  x=10;
  i=x++;
  printf("x:%d",x);
  printf("i:%d",i);
  return 0;
}
```

Your INPUT go's here! Give only values. do not give like a=10

```
x:11i:10
```

estcases:
5.6

Run Save

```c
#include<stdio.h>
int main()
{
  int a,l,b;
  printf("enter the value");
  scanf("%d%d",&l,&b);
  a=l*b;
  printf(" a=%d",a);
  return 0;
}
```

```
2 3
```

```
enter the value a=6
```

Run Save

```c
#include<stdio.h>
int main()
{
  int c,l,b;
  printf("enter the value");
  scanf("%d%d",&l,&b);
  c=2*(l+b);
  printf("c=%d",c);
  return 0;
}
```

```
2 3
```

```
enter the valuec=10
```

Run Save

```c
#include<stdio.h>
int main()
{
  int c;
  float f;
  scanf("%d",&c);
  f=(c*1.8)+32;
  printf("f=%f",f);
  return 0;
}
```

```
36
```

```
f=96.800
```

Run Save

```c
#include <stdio.h>
int main()
{
  int b,h;
  float a;
  scanf("%d%d",&b,&h);
  a=0.5*b*h;
  printf("a=%.2f",a);
  return 0;
}
```

```
6 5
```

```
a=15.00
```

Run Save

```c
#include <stdio.h>
int main()
{
  int a,p,t,r;
  scanf("%d%d%d",&p,&t,&r);
  a=p*t*r/100;
  printf("a=%d",a);
  return 0;
}
```

```
200 10 3
```

```
a=60
```

Run Save

```c
#include <stdio.h>
int main()
{
  int a,s;
  scanf("%d",&a);
  s=a*a;
  printf("s=%d",s);
  return 0;
}
```

```
10
```

```
s=25
```

Run Save

```c
#include<stdio.h>
int main()
{
  int a=10,b=20;
  a=a+b;
  b=a-b;
  a=a-b;
  printf("a=%d b=%d",a,b);
  return 0;
}
```

```
Your INPUT go's here! Give only values.
not give like a=10
```

```
a=20 b=10
```

Run Save

```c
#include<stdio.h>
void main()
{
  int a;
  scanf("%d",&a);
  printf("oct num=%o\n",a);
  printf("hexa num=%x",a);
}
```

```
20
```

```
oct num=24
hexa num=14
```

Run Save

```c
#include <stdio.h>
int main()
{
  int a=10,b=20,t;
  t=a;
  a=b;
  b=t;
  printf("a=%d b=%d",a,b);
  return 0;
}
```

```
Your INPUT go's here! Give onl
not give like a=10
```

```
a=20 b=10
```

Run Save

```c
#include<stdio.h>
void main()
{
  int a;
  scanf("%d",&a);
  printf("decimal num=%d\n",a);
}
```

```
015
```

```
decimal num=15
```

Run Save

```c
#include<stdio.h>
void main()
{
  int a;
  scanf("%d",&a);
  printf("dec num=%d\n",a);
}
```

```
0xA
```

Your OUTPUT go's here!

Run Save

```
1 #include<stdio.h>
2 void main()
3 {
4   char ch='g';
5   printf("ch=%d",ch);
6 }
```

```
Your INPUT go's here
not give like a=10
```

```
ch=103
```

Run Save

```c
#include<stdio.h>
void main()
{
  int a=1;
  int q,r;
  q=a/2;
  r=a%2;
  printf("qut=%d\n",q);
  printf("rem=%d\n",r);
}
```

```
Your INPUT go's here! Give on
not give like a=10
```

```
qut=0
rem=1
```

Run Save

```c
#include<stdio.h>
void main()
{
  int test;
  scanf("%d",&test);
  if(test<10)
  {
    printf("valid");
  }
  else
  {
    printf("invalid");
  }
}
```

```
11
```

```
invalid
```

Run Save

```c
#include<stdio.h>
void main()
{
  int num;
  scanf("%d",&num);
  if(num%2==0)
  {
    printf("it is even");
  }
  else
  {
    printf("it is odd");
  }
}
```

```
111
```

```
it is odd
```

Run Save

```c
#include<stdio.h>
void main()
{
  int a,b,c;
  scanf("%d%d%d",&a,&b,&c);
  if(a>b)
  {
    if(a>c)
    {
      printf("%d is greatest",a);
    }
    else
    {
      printf("%d is greatest",c);
    }
  }
  else
  {
    printf("%d is greatest",b);
  }
}
```

```
11 12 10
```

```
12 is greatest
```

Run Save

```c
#include<stdio.h>
void main()
{
  int grade;
  scanf("%d",&grade);
  if(grade>=90)
    {
      printf("A grade");
    }
  else if(grade>=80&&grade<90)
  {
    printf("B grade");
  }
  else if(grade>=70&&grade<80)
  {
    printf("C grade");
    }
}
```

```
70
```

```
C grade
```

Run Save

```c
#include<stdio.h>
void main()
{
  int num1,num2,num3;
  scanf("%d%d%d",&num1,&num2,&num3);
  if(num1>num2&&num1>num3)
  {
    printf("num1 is biggest");
  }
  else if(num2>num3)
  {
    printf("num2 is biggest");
  }
  else
  {
    printf("num3 is biggest");
  }
}
```

```
14 11 12
```

```
num1 is biggest
```

Run Save

```c
#include<stdio.h>
void main()
{
  int num;
  scanf("%d",&num);
  if(num<=100&&num>=0)
  {
    printf("in range");
  }
  else
  {
    printf("out of range");
  }
}
```

```
73
```

```
in range
```

Run Save

```c
#include<stdio.h>
void main()
{
  int a;
  scanf("%d",&a);
  if(a%3==0||a%5==0)
  {
    printf("it is divisible");
  }
  else
  {
    printf("not divisible");
  }
}
```

```
49
```

```
not divisible
```

Run Save

```c
#include <stdio.h>
void main()
{
  char ch;
  scanf("%c",&ch);
  if(ch>=65&&ch<=91)
  {
    printf("it is in range");
  }
  else
  {
    printf("it is not in range");
  }
}
```

```
S
```

```
it is in range
```

Run Save

```c
#include<stdio.h>
void main()
{
  int x,i;
  x=10;
  i=x++;
  printf("x:%d\n",x);
  printf("i:%d",i);
}
```

```
Your INPUT go's here! Give only
not give like a=10
```

```
x:11
i:10
```

```c
//to display 1 to 10
#include<stdio.h>
void main()
{
  int i=1;
  while(i<=10)
  {
    printf("%d\n",i);
    i++;
  }
  printf("end");
}

```

```
your input go's here. give only values. do
not give like a=10
```

```
1
2
3
4
5
6
7
8
9
10
end
```

SIMATS ENGINEERING

C Programming

JESUVA ABISHEK R
192524218

Pyramid Diamond

Run Save

```c
#include <stdio.h>
int main()
{
  int i;
  for(i=1;i<=10;i++)
  {
    if(i==5)
      break;
    printf("%d\n",i);
  }
  return 0;
}
```

Your INPUT go's here! Give only values. do not give like a=10

```
1
2
3
4
```

SIMATS ENGINEERING

C Programming

JESUVA ABISHEK R
192524218

Armstrong | Perfect

Run | Save

```c
#include<stdio.h>
void main()
{
  int i,j;
  for(i=1;i<=5;i++)
  {
    for(j=1;j<=5;j++)
    {
      printf("*");
    }
    printf("\n");
  }
}
```

Your INPUT go's here! Give only values. do not give like a=10

```
*****
*****
*****
*****
*****
```

```c
#include<stdio.h>
void main()
{
  int i=10;
  while(i>=1)
  {
    printf("%d\n",i);
    i--;
  }
  printf("END");
}
```

```
not give like a=10
```

```
10
9
8
7
6
5
4
3
2
1
END
```

Run Save

```c
#include<stdio.h>
void main()
{
  int n,i,j;
  scanf("%d",&n);
  for(i=1;i<=n;i++)
  {
    for(j=1;j<=n;j++)
    {
      if(i==1 || i==n || j==1 || j==n)
      {
        printf("*");
      }
      else
      {
        printf(" ");
      }
    }
    printf("\n");
  }
}
```

```
5
```

```
*****
*   *
*   *
*   *
*****
```

SIMATS ENGINEERING

C Programming

JESUVA ABISHEK R
192524218

Run Save

```c
#include<stdio.h>
void main()
{
  int i,j;
  for(i=1;i<=5;i++)
  {
    for(j=1;j<=i;j++)
    {
      printf("*");
    }
    printf("\n");
  }
}
```

Your INPUT go's here! Give only values. do not give like a=10

```
*
**
***
****
*****
```

Zigzag | Spiral pattern

Run | Save

```c
#include<stdio.h>
void main()
{
  int i,j;
  for(i=1;i<=5;i++)
  {
    for(j=1;j<=i;j++)
    {
      printf("%d",i);
    }
    printf("\n");
  }
}
```

Your INPUT go's here! Give only values. do not give like a=10

```
1
22
333
4444
55555
```

SIMATS ENGINEERING

C Programming

JESUVA ABISHEK R
192524218

Run Save

```c
#include<stdio.h>
void main()
{
  int i,j;
  for(i=5;i>=1;i--)
  {
    for(j=1;j<=i;j++)
    {
      printf("*");
    }
    printf("\n");
  }
}
```

Your INPUT go's here! Give only values. do not give like a=10

```
*****
****
***
**
*
```

SIMATS ENGINEERING

C Programming

JESUVA ABISHEK R
192524218

Run Save

```c
#include<stdio.h>
void main()
{
  int i,j;
  for(i=5;i>=1;i--)
  {
    for(j=1;j<=i;j++)
    {
      printf("%d",i);
    }
    printf("\n");
  }
}

```

Your INPUT go's here! Give only values. do not give like a=10

```
55555
4444
333
22
1
```

SIMATS ENGINEERING

C Programming

JESUVA ABISHEK R
192524218

Run Save

```c
#include<stdio.h>
void main()
{
  int i,j;
  for(i=1;i<=5;i++)
  {
    for(j=1;j<=i;j++)
    {
      printf("%d",j);
    }
    printf("\n");
  }
}
```

Your INPUT go's here! Give only values. do not give like a=10

```
1
12
123
1234
12345
```

SIMATS ENGINEERING

C Programming

JESUVA ABISHEK R
192524218

Run Save

```c
#include<stdio.h>
void main()
{
  int i,j;
  for(i=5;i>=1;i--)
  {
    for(j=1;j<=i;j++)
    {
      printf("%d",i);
    }
    printf("\n");
  }
}

```

Your INPUT go's here! Give only values. do not give like a=10

```
55555
4444
333
22
1
```

SIMATS ENGINEERING

C Programming

JESUVA ABISHEK R
192524218

Run | Save | Changes Updated, Saved 35

```c
#include<stdio.h>
void main()
{
  int i,j;
  for(i=1;i<=5;j++)
  {
    for(int s=1;s<=5-i;s++)
    {
      printf(" ");
    }
    for(j=1;j<=i;j++)
    {
      printf("*");
    }
    printf("\n");
  }
}
```

Your INPUT go's here! Give only values. do not give like a=10

Loading...