SIMATS ENGINEERING

C Programming

AAKASH R
192524462

Pyramid | Diamond

Run | Save

```c
#include<stdio.h>
int main()
{
  int n;
  printf("enter the number:");
  scanf("%d",&n);
  if(n%2==0 || n%7==0)
    printf("the number is even or divisible by 7\n");
  else
    printf("not even and not divisible by 7");
  return 0;
}
```

16

```
enter the number:the number is even or
divisible by 7
```

26°C Sunny | Search | ENG IN | 9:45 AM 3/13/2026

Run Save

zigzag | Spiral pattern | Armstrong | Perfect

```c
#include<stdio.h>
int main()
{
  int a;
  printf("enter an integer:");
  scanf("%d",&a);

  printf("result of(a<2):%d\n",a<2);
  printf("result of (a>>2):%d\n",a>>2);
  return 0;
}
```

8

```
enter an integer:result of(a<2):0
result of (a>>2):2
```

26°C Sunny Search ENG IN 9:45 AM 3/13/2026

Run Save

Pyramid Diamond

```
#include<stdio.h>
int main()
{
  int a=10;
  printf("before increment:%d\n",a);
  a++;
  printf("after increment:%d\n",a);
  return 0;
}
```

Your INPUT go's here! Give only va
not give like a=10

```
before increment:10
after increment:11
```

Sort A-Z 2nd Max

Run Save

```c
//take three marks of the student and check if wether passed or not
#include<stdio.h>
void main()
{
  int m1,m2,m3,passmark=50;
  printf("enter the test marks:");
  scanf("%d %d %d",&m1,&m2,&m3);
  if(m1>=passmark && m2>=passmark && m3>=passmark)
    printf("student got passed");
  else
    printf("student got fail");
}
```

```
50 51 50
```

```
enter the test marks:student got passed
```

Run Save

```c
//toggle bit
#include<stdio.h>
void main()
{
  int num=5;//binary=0101
  int position=1;
  printf("original number:%d",num);
  num=num^(1<<position);
  printf("number after toggle:%d",num);//binary=0111
}


```

```
Your INPUT go's here! Give only values. do
not give like a=10
```

```
original number:5number after toggle:7
```

Run Save

```c
//iterate loop 5 times
#include<stdio.h>
void main()
{
  int i;
  for(i=1;i<=5;i++)
  {
    printf("%d\n",i);
  }
  printf("END");
}

```

```
Your INPUT go's here! Give only values. do
not give like a=10
```

```
1
2
3
4
5
END
```

Run Save

```c
//to print armstrong number from 100 to 999
#include<stdio.h>
void main()
{
  int i,originalnum,remainder,result;
  printf("the armstrong number between 100 to 999 are:\n");
  for(i=100;i<=999;i++)
  {
    originalnum=i;
    result=0;
    while(originalnum!=0)
    {
      remainder=originalnum%10;
      result+=remainder*remainder*remainder;
      originalnum/=10;
    }
    if (result==i)
    {
      printf("%d\n",i);
    }
  }
  printf("\n");
```

Your INPUT go's here! Give only values. do not give like a=10

```
the armstrong number between 100 to 999
are:
153
370
371
407
```