

Cursors:

```
mysql> CREATE PROCEDURE display_employee()
-> BEGIN
->   DECLARE done INT default 0;
->   DECLARE e_id int;
->   DECLARE e_name varchar(40);
->   DECLARE e_salary decimal(10,2);
->   DECLARE emp_cursor CURSOR FOR
->     SELECT emp_id, emp_name, salary
->     FROM employee;
->   DECLARE CONTINUE HANDLER FOR NOT FOUND SET done = 1;
->   OPEN emp_cursor;
->   read_loop : LOOP
->     FETCH emp_cursor into e_id,e_name,e_salary;
->     IF done = 1 THEN
->       LEAVE read_loop;
->     END IF;
->     SELECT e_id AS Employee_ID,
->            e_name AS Employee_Name,
->            e_salary AS Salary;
->   END LOOP;
->   CLOSE emp_cursor;
-> END //
```

Query OK, 0 rows affected (0.01 sec)

```
mysql> DELIMITER ;
```

```
mysql> CALL display_employee();
```

Employee_ID	Employee_Name	Salary
101	Priya	30000.00

1 row in set (0.01 sec)

Employee_ID	Employee_Name	Salary
102	Pooja	40000.00

1 row in set (0.01 sec)

Employee_ID	Employee_Name	Salary
103	Rahul	35000.00

1 row in set (0.01 sec)

Employee_ID	Employee_Name	Salary
104	Arun	45000.00

1 row in set (0.02 sec)

Query OK, 0 rows affected (0.02 sec)