

1.Alter the table STUDENT2 with following structure.

```
mysql> alter table student add primary key(regno);
Query OK, 0 rows affected (0.05 sec)
Records: 0 Duplicates: 0 Warnings: 0

mysql> desc student;
```

Field	Type	Null	Key	Default	Extra
regno	int	NO	PRI	NULL	
name	varchar(20)	YES		NULL	
gender	char(1)	YES		NULL	
mobilen	int	YES		NULL	
city	varchar(15)	YES		NULL	

```
5 rows in set (0.00 sec)
```

2.Alter the table name FACULTY with following structure.

```
mysql> use faculty;
Database changed
mysql> alter table faculty add primary key(facno);
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near ')' at line 1
mysql> alter table faculty add primary key(facno);
Query OK, 0 rows affected (0.05 sec)
Records: 0 Duplicates: 0 Warnings: 0

mysql> alter table faculty add check(gender='M' or 'F');
Query OK, 0 rows affected (0.06 sec)
Records: 0 Duplicates: 0 Warnings: 0

mysql> desc faculty;
```

Field	Type	Null	Key	Default	Extra
facno	int	NO	PRI	NULL	
facname	varchar(20)	YES		NULL	
gender	char(1)	YES		NULL	
DOB	date	YES		NULL	
DOJ	date	YES		NULL	
mobilen	int	YES		NULL	
dept	char(10)	YES		NULL	

```
7 rows in set (0.00 sec)
```

3.Alter the table name DEPARTMENT with following structure.

```
mysql> alter table department add primary key (depno);
Query OK, 0 rows affected (0.05 sec)
Records: 0 Duplicates: 0 Warnings: 0

mysql> desc department;
```

Field	Type	Null	Key	Default	Extra
depno	varchar(4)	NO	PRI	NULL	
deptname	varchar(15)	YES		NULL	
depthead	varchar(4)	YES		NULL	

```
3 rows in set (0.00 sec)
```

4.Alter the table name COURSE with following structure.

```
mysql> alter table course add primary key(courseno);
Query OK, 0 rows affected (0.05 sec)
Records: 0 Duplicates: 0 Warnings: 0

mysql> alter table course add check(semno>=1&&semno<=6);
Query OK, 0 rows affected, 1 warning (0.05 sec)
Records: 0 Duplicates: 0 Warnings: 1

mysql> desc course;
+-----+-----+-----+-----+-----+-----+
| Field      | Type      | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| courseno   | varchar(3) | NO   | PRI | NULL    |       |
| coursedesc | varchar(14) | YES  |     | NULL    |       |
| coursetype | char(1)    | YES  |     | NULL    |       |
| semno      | char(1)    | YES  |     | NULL    |       |
| hallno     | varchar(4) | YES  |     | NULL    |       |
| facno      | varchar(4) | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
6 rows in set (0.00 sec)
```

5.Alter the table name STUDENT2 with following structure.

```
mysql> alter table student add unique key(name);
Query OK, 0 rows affected (0.02 sec)
Records: 0 Duplicates: 0 Warnings: 0

mysql> desc student;
+-----+-----+-----+-----+-----+-----+
| Field      | Type      | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| regno      | int       | NO   | PRI | NULL    |       |
| name       | varchar(20) | YES  | UNI | NULL    |       |
| gender     | char(1)    | YES  |     | NULL    |       |
| mobileno   | int       | YES  |     | NULL    |       |
| city       | varchar(15) | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
5 rows in set (0.00 sec)
```

6.After the STUDENT2 & STUDENT3 tables are successfully created, test if you can add a constraint FOREIGN KEY to the RegNo of this table.

```
mysql> alter table student1 modify address int not null;
Query OK, 0 rows affected (0.09 sec)
Records: 0 Duplicates: 0 Warnings: 0

mysql> desc student1;
+-----+-----+-----+-----+-----+-----+
| Field      | Type      | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| regno      | int       | NO   | PRI | NULL    |       |
| s1name     | varchar(20) | YES  |     | NULL    |       |
| age        | char(2)    | YES  | UNI | NULL    |       |
| DOB        | date      | YES  |     | NULL    |       |
| address    | int       | NO   |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
5 rows in set (0.00 sec)
```