

Triggers:

```
mysql> use employee;
Database changed
mysql> select * from employee;
+-----+-----+-----+
| emp_id | emp_name | salary |
+-----+-----+-----+
| 101    | Priya    | 30000.00 |
| 102    | Pooja    | 40000.00 |
| 103    | Rahul    | 35000.00 |
| 104    | Arun     | 45000.00 |
+-----+-----+-----+
4 rows in set (0.00 sec)
```

AFTER INSERT

```
mysql> create table employee_log(emp_id int, emp_name varchar(30), action varchar(20));
Query OK, 0 rows affected (0.07 sec)

mysql> DELIMITER //
mysql> CREATE TRIGGER after_employee_insert
-> AFTER INSERT ON employee
-> FOR EACH ROW
-> BEGIN
->     INSERT INTO employee_log
->     VALUES(NEW.emp
->     _id, NEW.emp_name,'INSERT')
-> END //
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server vers
ion for the right syntax to use near '_id, NEW.emp_name,'INSERT')
END' at line 7
mysql> DELIMITER //
mysql> CREATE TRIGGER after_employee_insert
-> AFTER INSERT ON employee
-> FOR EACH ROW
-> BEGIN
->     INSERT INTO employee_log
->     VALUES(NEW.emp_id,NEW.emp_name,'INSERT')
-> ;
-> END //
Query OK, 0 rows affected (0.02 sec)

mysql> DELIMITER ;
mysql> insert into employee values(105,'mani',50000);
```

```
mysql> DELIMITER ;
mysql> insert into employee values(105,'mani',50000);
Query OK, 1 row affected (0.01 sec)
```

```
mysql> select * from employee;
```

emp_id	emp_name	salary
101	Priya	30000.00
102	Pooja	40000.00
103	Rahul	35000.00
104	Arun	45000.00
105	mani	50000.00

```
5 rows in set (0.00 sec)
```

```
mysql> select * from employee_log;
```

emp_id	emp_name	action
105	mani	INSERT

```
1 row in set (0.00 sec)
```

BEFORE INSERT:

```
mysql> DELIMITER //
mysql> CREATE TRIGGER before_employee_insert
  -> BEFORE INSERT ON employee
  -> FOR EACH ROW
  -> BEGIN
  ->     IF NEW.salary<10000 THEN
  ->         SET NEW.salary=10000;
  ->     END IF;
  -> END //
Query OK, 0 rows affected (0.01 sec)

mysql> DELIMITER ;
mysql> insert into employee values(101,'Priya',8000);
Query OK, 1 row affected (0.01 sec)

mysql> insert into employee values(102,'Pooja',25000);
Query OK, 1 row affected (0.01 sec)
```

```
mysql> select * from employee;
+-----+-----+-----+
| emp_id | emp_name | salary |
+-----+-----+-----+
| 101    | Priya    | 30000.00 |
| 102    | Pooja    | 40000.00 |
| 103    | Rahul    | 35000.00 |
| 104    | Arun     | 45000.00 |
| 105    | mani     | 50000.00 |
| 101    | Priya    | 10000.00 |
| 102    | Pooja    | 25000.00 |
+-----+-----+-----+
7 rows in set (0.00 sec)
```