CO1 - AT2 - EXPERIMENTS

Back

QUESTIONS

Q1
Decision Making
10 marks

Q2
Decision Making
10 marks

Q3
Looping
10 marks

Q4
Looping
10 marks

Q5
Lopping
10 marks

5/5 answered

Q5 Lopping

10 marks

Write a program to print the reverse of the number

Your Code

```c
#include<stdio.h>
int main(){
    int n,rev=0,r;
    printf("enter a number: ");
    scanf("%d",&n);
    while(n!=0){
        r=n%10;
        rev=rev*10+r;
        n/=10;
    }
    printf("reversed number=%d\n",rev);
    return 0;
}
```

Input

```
123
```

Output

```
enter a number: reversed number=321
```

Visible Test Cases

CO1 - AT2 - EXPERIMENTS

← Back

QUESTIONS

Q1
Decision Making
10 marks

Q2
Decision Making
10 marks

Q3
Looping
10 marks

Q4
Looping
10 marks

Q5
Lopping
10 marks

5/5 answered

Q4 Looping

10 marks

Write a program to check the given number is Armstron number or not.

Your Code

```
#include<stdio.h>
int main(){
int n,temp,rem,sum=0;
scanf("%d",&n);
temp=n;
while(temp>0){
    rem=temp%10;
    sum+=rem*rem*rem;
    temp/=10;
}
    if(sum==n)
        printf("Armstrong number");
    else
        printf("mot armstrong number");
    return 0;
}
```

Input

153

Output

```
Armstrong number
```

Visible Test Cases

Test Case 1

CO1 - AT2 - EXPERIMENTS

Back

QUESTIONS

Q1
Decision Making
10 marks

Q2
Decision Making
10 marks

Q3
Looping
10 marks

Q4
Looping
10 marks

Q5
Lopping
10 marks

5/5 answered

Q3 **Looping** 10 marks

Write a program to generate the fibonacci series upto N terms

Your Code

```
#include<stdio.h>
int main(){
    int n,a=0,b=1,c;
    scanf("%d",&n);
    for(int i=0;i<=n;i++){
        printf("%d ",a);
        c=a+b;
    a=b;
    b=c;}

return 0;
}
```

Input

4

Output

```
0 1 1 2 3
```

Visible Test Cases

Test Case 1

CO1 - AT2 - EXPERIMENTS

← Back

QUESTIONS

Q1
Decision Making
10 marks

Q2
Decision Making
10 marks

Q3
Looping
10 marks

Q4
Looping
10 marks

Q5
Lopping
10 marks

5/5 answered

Q2 Decision Making

10 marks

Write a proram to find the factorial of a given number

Your Code

```c
#include <stdio.h>
int main(){
    int a,fact=1;
    scanf("%d",&a);
    for(int i=1;i<=a;i++){
        fact*=i;
    }
    printf("%d",fact);

    return 0;
}
```

Input

3

Output

6

Visible Test Cases

QUESTIONS

Q1
Decision Making
10 marks

Q2
Decision Making
10 marks

Q3
Looping
10 marks

Q4
Looping
10 marks

Q5
Lopping
10 marks

5/5 answered

Q1 **Decision Making**

10 marks

Write a program to find the Maximum among three numbers

Your Code

```c
#include<stdio.h>
int main(){
    int a,b,c;
   // printf("enter the 3 numbers");
    scanf("%d %d %d",&a,&b,&c);
    if(a>b&&a>c){
        printf( "max is %d",a);
    }
    else if(b>c){
printf("max is %d",b);
    }
    else{
printf("max is c",c);}
return 0;}
```

Input

```
120 89 9
```

Output

```
max is 120
```

Visible Test Cases