

Student 25 **Rommala Varshini** 192525349RB

4 / 4 submitted

Level 2 — 25 marks/question

L2-Q1. product (M)

c

CODE

```
#include<stdio.h>
int main()
{
    int a[100];
    int n,i,j,p;
    scanf("%d",&n);
    for(i=0;i<n;i++)
        scanf("%d",&a[i]);
    for(i=0;i<n;i++)
    {
        p=1;
        for(j=0;j<n;j++)
        {
            if(i!=j)
                p*=a[j];
        }
        printf("%d ",p);
    }
    return 0;
}
```

INPUT

```
4
1 2 3 4
```

OUTPUT

```
24 12 8 6
```

c

CODE

```
#include<stdio.h>
struct account{
    int no;
    char name[50];
    float bal;
};
int main(){
    struct account a;
    float d,w;
    scanf("%s%d%f%f",a.name,&a.no,&a.bal,&d,&w);
    a.bal=a.bal+d-w;
    printf("%s\n",a.name);
    printf("%d\n",a.no);
    printf("%.0f",a.bal);
    return 0;
}
```

INPUT

Mary
10001
5000
2000
1500

OUTPUT

Mary
10001
\$5500

c

CODE

```
#include<stdio.h>
#include<string.h>
int main()
{
    char s[50],c,t;
    int i,n,l=0;
    scanf("%49s",s);
    while(s[l]!='\0')
        l++;
    scanf("%c",c);
    scanf("%d",&n);
    n=n%l;
    while(n--)
    {
        if(c=='R')
        {
            t=s[l-1];
            for(i=l-1;i>0;i--)
                s[i]=s[i-1];
            s[0]=t;
        }
        else
        {
            t=s[0];
            for(i=0;i<l-1;i++)
                s[i]=s[i+1];
            s[l-1]=t;
        }
    }
    printf("%s",s);
    return 0;
}
```

INPUT

```
hello
R
2
```

OUTPUT

error: Program terminated abnormally with no output (exit code -1073741819) – likely a crash (invalid memory access, stack overflow, or similar).

c

CODE

```
#include<stdio.h>
int main()
{
    int a[10][10],n,i,j,sum=0;
    scanf("%d",&n);
    for(i=0;i<n;i++)
    for(j=0;j<n;j++)
    scanf("%d",&a[i][j]);
    for(i=0;i<n;i++)
        sum+=a[i][i];
    printf("%d",sum);
    return 0;
}
```

INPUT

```
3
1 2 3
4 5 6
7 8 9
```

OUTPUT

```
15
```