

Student 25 **Rommala Varshini** 192525349RB

4 / 4 submitted

Q1. CASE STUDY 1

CODE

```
#include<stdio.h>
struct employee{
    int id;
    char name[30];
    char dept[20];
    float salary;
    char status[20];
};
int main()
{
    struct employee e={101,"varshini","cse",35000,"full-time"};
    printf("%d\n",e.id);
    printf("%s\n",e.name);
    printf("%s\n",e.dept);
    printf("%.2f\n",e.salary);
    printf("%s\n",e.status);
    return 0;
}
```

OUTPUT

(no output)

Q2. CASE STUDY 2

CODE

```
#include<stdio.h>
struct bug{
    int id;
    char desc[20];
    struct{char dev[20];}developer;
    struct{char tester[20];}test;
    union{char status[10];}s;
};
int main(){
    struct bug b={1,"loginbug",{"ravi"},"anu",{"open"}};
    printf("%d\n %s\n %s\n %s\n %s\n",b.id,b.desc,b.developer.dev,b.test.tester,b.s.status);
    return 0;
}
```

141 / 220

OUTPUT

(no output)

Q3. CASE STUDY 3

CODE

```
#include<stdio.h>
struct product{
    int id;
    char name[20];
    float price;
    int stock;
    struct{char name[20];}supplier;
    union{char type[15];}category;
};
int main()
{
    struct product p={101,"laptop",5000,10,{"abc"},"electronics"};
    printf("%d\n %s\n %.0f\n %d\n %s\n %s\n",p.id,p.name,p.price,p.stock,p.supplier.name,p.category.type);
    return 0;
}
```

OUTPUT

(no output)

Q4. CASE STUDY 4

CODE

```
#include<stdio.h>
struct patient{
    int id,age;
    char name[20],blood[5];
    struct{
        char doctor[20],diagnosis[30];
        float cost;
    }visit;
    union{
        char status[20];
    }s;
};
int main()
{
    struct patient p={101,20,"ravi","0+","kumar","fever",500,{"admitted"}};
    printf("%d %s %d %s\n",p.id,p.name,p.age,p.blood);
    printf("%s %s %.0f %s",p.visit.doctor,p.visit.diagnosis,p.visit.cost,p.s.status);
    return 0;
}
```

OUTPUT

(no output)