

Student 24 **Prakash Balaji R** 192525379RB

4 / 4 submitted

Q1. ARRAYS**CODE**

```
#include<stdio.h>
int main(){
    int arr[]={0,1,9,8,0,2};
    int mov[] = {}, n = (sizeof(arr)/sizeof(arr[0]))-1;
    int temp, z = 0;
    printf("Input array: ");
    for(int i=0; i<=n;i++){
        printf("%d ", arr[i]);
    }
    printf("\n");
    for(int i=0;i<n;i++){
        if(arr[i] == 0){
            temp = arr[i+1];
            mov[i] = temp;
            z++;
        }
        else {
            mov[i]=arr[i];
        }
    }
    printf("Sorted array: ");
    for(int i=1; i<n;i++){
        printf("%d ", mov[i]);
    }
    for(int i=1; i<=z;i++){
        printf("%d ");
    }
}
```

OUTPUT

(no output)

Q2. ARRAYS**CODE**

```
#include<stdio.h>

int main(){
    int arr[]={2,2,1,5,1,3,3};
    int n = sizeof(arr)/sizeof(arr[0])-1;
    for(int i=0;i<n;i++){
        int seen=0;
        for(int j=0;j<=n;j++){
            if(arr[i]==arr[j]){
                seen=1;
            }
        }
        int count=0;
        if (seen){
            for(int j=0; j<=n;j++){
                if(arr[i]==arr[j]){
                    count++;
                }
            }
        }
        printf("%d is %d times\n",arr[i], count);
    }
}
```

OUTPUT

(no output)

Q3. ARRAYS**CODE**

```
#include<stdio.h>
int main(){
    int arr[]={1,2,3,4,5};
    int n = (sizeof(arr)/sizeof(arr[0]))-1;
    int temp;
    printf("Input Array: ");
    for(int j =0;j<=n;j++){
        printf("%d ", arr[j]);
    }
    printf("\n");
    temp = arr[n];
    printf("Output Array: ");
    printf("%d ", temp);
    for(int i=0; i<n;i++){
        printf("%d ", arr[i]);
    }
}
```

OUTPUT

(no output)

Q4. ARRAYS

CODE

```
#include<stdio.h>
int main(){
    int arr[3][3]={{1,2,3},
                  {4,5, 6},
                  {7,8,9}};

    int n= 3;
    // printf("%d", n);
    for(int i=0;i<n;i++){
        for(int j=i+1;j<n;j++){
            int temp = arr[i][j];
            arr[i][j]=arr[j][i];
            arr[j][i]=temp;
        }
    }

    for(int i=0;i<n;i++){
        for(int j=0; j<n/2;j++){
            int temp = arr[i][j];
            arr[i][j] = arr[j][n-1-i];
            arr[i][n-1-i] = temp;
        }
    }

    for(int i=0;i<n;i++){
        for(int j=0;j<n;j++){
            printf("%d ", arr[i][j]);
        }
        printf("\n");
    }
    return 0;
}
```

OUTPUT

(no output)