CSA0607 – Design and Analysis of Algorithms: CO2 Debugging and Optimisation Task

SentinelOps SOC Alert-Triage Module


Course	CSA0607 – Design and Analysis of Algorithms
Assessment	CO2 – Debugging and Optimisation Task (50 marks)
Student Reg. No. / Name	_____RITHIKA.G/ (192571027)_____
GitHub repository	https://github.com/192571027/CSA0607-
Python / platform	Python 3.12, standard library only for the module; matplotlib, Pygments, Pillow only for graphs/screenshots

All outputs, counts and timings in this report were produced by the code in Source_Code/ and are stored in Supporting_Files/ (logs, CSV/JSON). Timings are machine-dependent; operation counts are exact.

Part (a) – Reproduce and identify the defects (10 marks)

a.1 Expected vs actual output (original module, course test data)

The original module was run unchanged (python original_sentinelops.py, log: Supporting_Files/log_1_original_run.txt).



Original module on the course test data

Function	Input	Expected output	Actual output (original)	Symptom
sort_alerts	A1:3, A2:9, A3:5, A4:9, A5:1	[A2:9, A4:9, A3:5, A1:3, A5:1]	[A4:9, A3:5, A3:5, A5:1, A5:1]	A1, A2 **disappeared**; A3, A5 **duplicated**; order wrong

Function	Input	Expected output	Actual output (original)	Symptom
is_blocked	queries 10.0.0.9, 10.0.0.5, 8.8.8.8	True, True, False	False, False, False	blocked IPs **got through**
find_signature	"FAILFAIXFAIL", "FAIL"	[0, 8]	[0, 4]	signature at the end **missed**; FAIX at 4 reported as a **false hit**
closest_logins	6 events (km)	((0, 5), 1.4142 km)	((0, 2), 60.44 km)	returns the **farthest** pair, not the closest

```
def sort_alerts(alerts):            # insertion sort by severity, highest first
    for i in range(1, len(alerts)):
        key = alerts[i]
        j = i - 1
        while j > 0 and alerts[j][1] < key[1]:
            alerts[j + 1] = alerts[j]
            j -= 1
        alerts[j] = key
    return alerts

def is_blocked(blocklist, ip):      # sequential search
    for i in range(len(blocklist)):
        if blocklist[i] == ip:
            return False
        else:
            return False

def find_signature(log, pattern):   # brute-force string matching, all occurrences
    n, m = len(log), len(pattern)
    hits = []
    for i in range(n - m):
        for j in range(m):
            if log[i + j] != pattern[j]:
                break
        if j == m - 1:
            hits.append(i)
    return hits

def closest_logins(events):         # brute-force closest pair of login locations
    min_dist = 0
    pair = None
    for i in range(len(events)):
        for j in range(len(events)):
            d = math.sqrt((events[i][0] - events[j][0]) ** 2 +
                          (events[i][1] - events[j][1]) ** 2)
            if d > min_dist:
                min_dist = d
                pair = (i, j)
    return pair, min_dist
```

Original source code (the four functions)

a.2 The nine defects

Fault lines are quoted exactly as they appear in the original code.

#	Function	Faulty line (original)	Nature of the error	Effect
D1	sort_alerts	while j > 0 and alerts[j][1] < key[1]:	Off-by-one loop bound: index 0 is never compared or shifted	alerts[0] is never moved; key overwrites it
D2	sort_alerts	alerts[j] = key	Wrong insertion index: after the shifts the free slot is j + 1	The key overwrites a live element → alerts lost / duplicated
D3	is_blocked	if blocklist[i] == ip: → return False	Inverted result on a match	A blocked IP is reported clean
D4	is_blocked	else: return False	Premature return inside the loop (only blocklist[0] is ever tested); there is also no terminal return, so an empty blocklist returns None	Search ends after one element
D5	find_signature	for i in range(n - m):	Off-by-one: the last window i = n - m is skipped	Signature at the end of the log missed; pattern equal to the log missed
D6	find_signature	if j == m - 1:	Wrong match test: j is also m-1 when the **last character mismatches** (break at j = m-1)	False hits such as FAIX
D7	closest_logins	min_dist = 0	Wrong initial value for a minimum search (must be +∞)	No distance is ever smaller than the start value
D8	closest_logins	if d > min_dist:	Wrong comparison direction – this is a **maximum** search	Returns the farthest pair
D9	closest_logins	for j in range(len(events)):	Inner loop covers all j: self pairs (i,i) (d = 0) and each pair twice	n^2 instead of $n(n-1)/2$ distance computations; self pair d = 0 would win once D7/D8 are fixed

Counting note. The missing terminal return False of is_blocked sits on the same lines as D4, so it is counted inside D4. One additional **latent boundary defect (H1)** was found by the boundary tests and is not one of the nine: with an empty pattern the original raises UnboundLocalError (j is never assigned) and, after D6 is fixed, a naïve for…else would report every index – the corrected code returns [].

a.3 Which defect explains which production symptom

Production symptom	Defects
Alerts disappeared or duplicated	D1, D2
Blocked IP addresses got through	D3, D4
Signatures at the end of a log missed	D5
False signatures reported	D6
“Closest logins” hundreds of km apart	D7, D8 (and D9 for the self/duplicate pairs)

Part (b) – Root causes and systematic debugging (12 marks)

Method. The code was *not* rewritten. Source_Code/debug_session.py reads the original source text and applies each fix as one exact text substitution, cumulatively, re-running the probes of the affected function after every single fix (full log: Supporting_Files/log_2_debug_session.txt). The final patched source is checked to behave identically to corrected_sentinelops.py.

b.1 sort_alerts – D1 and D2

Root cause. Insertion sort shifts every element that is *strictly smaller* than key one place to the right, then drops key into the gap. The gap is at index j + 1 (the loop stops when alerts[j] is **not** smaller, or when j = −1). The original (i) stops at j = 1 so alerts[0] can never be compared, and (ii) writes the key to alerts[j], which still holds a live element.

Insertion trace – original (j > 0, alerts[j] = key):

i	key	shifts	write position	list after the step
start				[A1:3, A2:9, A3:5, A4:9, A5:1]
1	A2:9	0	alerts[0]	[A2:9, A2:9, A3:5, A4:9, A5:1] ← **A1 lost, A2 duplicated**
2	A3:5	0	alerts[1]	[A2:9, A3:5, A3:5, A4:9, A5:1] ← A2 (second copy) lost
3	A4:9	2	alerts[0]	[A4:9, A3:5, A3:5, A3:5, A5:1]

i	key	shifts	write position	list after the step
4	A5:1	0	alerts[3]	[A4:9, A3:5, A3:5, A5:1, A5:1] ← final (wrong) output


Insertion trace – corrected (j >= 0, alerts[j + 1] = key):

i	key	shifts	write position	list after the step
start				[A1:3, A2:9, A3:5, A4:9, A5:1]
1	A2:9	1 (A1)	alerts[0] (j ended at −1)	[A2:9, A1:3, A3:5, A4:9, A5:1]
2	A3:5	1 (A1)	alerts[1]	[A2:9, A3:5, A1:3, A4:9, A5:1]
3	A4:9	2 (A1, A3)	alerts[1] – stops at A2 because 9 < 9 is false	[A2:9, A4:9, A3:5, A1:3, A5:1]
4	A5:1	0	alerts[4]	[A2:9, A4:9, A3:5, A1:3, A5:1]

Stability: at i = 3 the new 9 stops *behind* the existing 9 because the shift condition is the strict <.

Re-test after each fix (from the debug session):

After fix	course alerts → actual	Result
none (original)	[A4:9, A3:5, A3:5, A5:1, A5:1]	FAIL
D1 only	[A1:3, A1:3, A1:3, A1:3, A4:9]	FAIL (still corrupts – D2 pending; shows D1 alone is not enough)
D1 + D2	[A2:9, A4:9, A3:5, A1:3, A5:1]	**PASS**



Debug session – sort_alerts steps

b.2 is_blocked – D3 and D4

Root cause. A sequential search must (1) return True the moment an element matches, (2) keep scanning on a mismatch, and (3) return False only after the whole list was examined. The original does (1) wrong (False), and (2)+(3) wrong (else: return False ends the call at index 0; falling off an empty loop returns None).

After fix	course queries [10.0.0.9, 10.0.0.5, 8.8.8.8]	empty list	last element	Result
none	[False, False, False]	None	False	FAIL
D3	[False, True, False] – only the *first* IP (10.0.0.5) is found	None	False	FAIL (D4 pending)
D3 + D4	[True, True, False]	False	True	**PASS**

b.3 find_signature – D5, D6 (and H1)

Root cause. For text length n and pattern length m, the valid start positions are 0 … n−m, i.e. n−m+1 windows – range(n−m) drops the last. After the inner loop, j holds the index where the loop *stopped*; j == m−1 is true both for a full match (loop ran to the end) and for a mismatch **at the last character** (loop breaks with j = m−1). The reliable test is "the loop never broke" (for … else).

Alignment table – log = FAILFAIXFAIL (n = 12), pattern = FAIL (m = 4):

i	window	comparisons (log vs pattern)	original (range(8), j == m-1)	corrected (range(9), for…else)
0	FAIL	F=F A=A I=I L=L	HIT	HIT
1	AILF	A≠F	no hit	no hit
2	ILFA	I≠F	no hit	no hit
3	LFAI	L≠F	no hit	no hit
4	FAIX	F=F A=A I=I **X≠L**	**HIT – false positive (D6)**	no hit
5	AIXF	A≠F	no hit	no hit
6	IXFA	I≠F	no hit	no hit
7	XFAI	X≠F	no hit	no hit
8	FAIL	F=F A=A I=I L=L	**not scanned (D5)**	HIT

After fix	course log	pattern at very end (xxxxFAIL)	empty pattern	Result
none	[0, 4]	[]	UnboundLocalError	FAIL
D5	[0, 4, 8] (end found, false hit remains)	[4]	UnboundLocalError	FAIL
D5 + D6	[0, 8]	[4]	[0, 1, 2, 3, 4] (every index – wrong)	FAIL for empty pattern
D5 + D6 + H1	[0, 8]	[4]	[]	**PASS**

b.4 closest_logins – D7, D8, D9

Root cause. A minimum search must start from +∞, replace the best value only when a candidate is **smaller**, and visit every unordered pair {i, j} exactly once. With min_dist = 0 and d > min_dist the function actually computes the **maximum** distance (the pair (0, 2), 60.44 km below, is the farthest pair in the data); with j over all indices it also compares each point with itself.

Pair table for the course data (15 pairs = 6·5/2):

pair	d (km)		pair	d (km)		pair	d (km)
(0,1)	28.79		(1,3)	29.83		(2,5)	59.03
(0,2)	**60.44** (farthest – what the original returned)		(1,4)	20.00		(3,4)	11.40
(0,3)	3.61		(1,5)	27.51		(3,5)	3.61
(0,4)	12.21		(2,3)	60.22		(4,5)	10.82
(0,5)	**1.41 (closest)**		(2,4)	48.83			
(1,2)	34.41						

After fix	course events	one event	identical points (5,5),(9,9),(5,5)	Result
none	((0,2), 60.44)	(None, 0)	((0,1), 5.66)	FAIL
D7	(None, inf) – d > inf is never true	(None, inf)	(None, inf)	FAIL
D7 + D8	((0,0), 0.0) – the self pair wins	((0,0), 0.0)	((0,0), 0.0)	FAIL
D7 + D8 + D9	((0,5), 1.4142)	(None, inf)	((0,2), 0.0)	**PASS**

The three fixes are only meaningful together: D7 alone makes the function return nothing, D7 + D8 exposes D9 (the (i,i) pair has d = 0), and D9 completes the repair.

b.5 Boundary tests (original vs corrected)

Boundary case	Input	Expected	Original	Corrected
Empty blocklist	[], 1.1.1.1	False	None	False

Boundary case	Input	Expected	Original	Corrected
Blocked IP is last element	172.16.4.2	True	False	True
Pattern at the very end	xxxxFAIL, FAIL	[4]	[]	[4]
Pattern equals the log	FAIL, FAIL	[0]	[]	[0]
Pattern longer than the log	FAI, FAIL	[]	[]	[]
Overlapping occurrences	AAAAAA, AAAA	[0,1,2]	[0,1]	[0,1,2]
Empty pattern	FAIL, ""	[]	UnboundLocalError	[]
Equal severities	B1..B4, all 5	B1,B2,B3,B4 (arrival order)	[B2,B3,B4,B4]	[B1,B2,B3,B4]
Fewer than two events	[], [(1,1)]	(None, ∞)	(None, 0)	(None, inf)
Identical locations	(5,5),(9,9),(5,5)	((0,2), 0.0)	((0,1), 5.66)	((0,2), 0.0)
Tie for closest pair	(0,0),(1,0),(10,0),(11,0)	((0,1), 1.0)	–	((0,1), 1.0)

```python
def sort_alerts(alerts):
    """Sort alerts by severity, highest first; equal severities keep arrival order.

    Insertion sort (stable because elements are shifted only while STRICTLY
    smaller than the key).  Sorts the list in place and also returns it.

    Args:
        alerts: list of (alert_id, severity) tuples.
    Returns:
        The same list, ordered by severity descending.
    """
    for i in range(1, len(alerts)):
        key = alerts[i]
        j = i - 1
        while j >= 0 and alerts[j][1] < key[1]:      # D1: was  j > 0
            alerts[j + 1] = alerts[j]
            j -= 1
        alerts[j + 1] = key                          # D2: was  alerts[j] = key
    return alerts


def is_blocked(blocklist, ip):
    """Sequential search: is `ip` on the blocklist?

    Args:
        blocklist: list of IP strings.
        ip: IP string to look up.
    Returns:
        True if `ip` is in `blocklist`, otherwise False (also for an empty list).
    """
    for i in range(len(blocklist)):
        if blocklist[i] == ip:
            return True                              # D3: was  return False
        # D4: the  else: return False  branch is removed - it ended the search
        #     after the first element.
    return False                                     # D4: terminal return added
```

Corrected code – sort_alerts and is_blocked

```python
def find_signature(log, pattern):
    """Brute-force string matching: every start index of `pattern` in `log`.


    Overlapping occurrences are reported.  An empty pattern matches nothing.

    Args:
        log: the log line (str).
        pattern: the attack signature (str).
    Returns:
        List of 0-based start indices in increasing order.
    """
    n, m = len(log), len(pattern)
    hits = []
    if m == 0:                                       # H1: empty pattern guard
        return hits
    for i in range(n - m + 1):                       # D5: was  range(n - m)
        for j in range(m):
            if log[i + j] != pattern[j]:
                break
        else:                                        # D6: was  if j == m - 1
            hits.append(i)                           #     (inner loop never broke => full match)
    return hits


def closest_logins(events):
    """Brute-force closest pair of login locations.


    Args:
        events: list of (x, y) coordinates in km.
    Returns:
        ((i, j), distance) with i < j, the indices of the closest pair and their
        Euclidean distance.  Ties go to the lexicographically smallest (i, j).
        With fewer than two events: (None, math.inf).
    """
    min_dist = math.inf                              # D7: was  0
    pair = None
    for i in range(len(events)):
        for j in range(i + 1, len(events)):          # D9: was  range(len(events))
            d = math.sqrt((events[i][0] - events[j][0]) ** 2 +
                          (events[i][1] - events[j][1]) ** 2)
            if d < min_dist:                         # D8: was  d > min_dist
                min_dist = d
                pair = (i, j)
    return pair, min_dist
```

Corrected code – find_signature and closest_logins



Corrected module run

Test-suite result: the same 42 checks run on all three modules – **original 10 pass / 32 fail** (the failures are the defects), **corrected 42/42**, **optimised 42/42**, plus a 3,000-trial randomised differential test with 0 mismatches.



Test harness – summary

Part (c) – Optimising the corrected module (10 marks)

Every optimisation was required to leave the output unchanged; this is enforced by test_harness.py (42 fixed checks per module and the randomised differential test against independent reference implementations). Pseudocode for each corrected/optimised pair is in Pseudocode/.

c.1 sort_alerts – is insertion sort still suitable?

Insertion sort costs (n − 1) + I comparisons, where I is the number of inversions (pairs in the wrong order). For **nearly sorted** alert streams I is small, so it is linear, in place (O(1) extra space) and stable – a good fit. But the production module must survive any batch: an out-of-order burst of 50,000 alerts has $I \approx 0.225 \cdot n^2 \approx 5.6 \cdot 10^8$ (severity 1–10) up to $n(n-1)/2 \approx 1.25 \cdot 10^9$ (reverse order). Measured: 1.49 s for 10,000 random alerts, so quadratic scaling projects to ≈ 37 s for 50,000 (extrapolation, not measured).

Chosen approach: Python's built-in Timsort through alerts.sort(key=itemgetter(1), reverse=True). It is *adaptive* (detects already-ordered runs → ≈ n comparisons on nearly sorted data), has an O(n log n) worst case, and is *stable* – reverse=True keeps equal keys in arrival order. It still sorts in place and returns the list, so the interface and output are unchanged. Trade-off: O(n) temporary space.

c.2 is_blocked – repeated lookups

A sequential search is O(b) per query, i.e. O(q·b) for q lookups. The blocklist changes rarely and is queried constantly, so it is indexed **once** in a hash set (build_blocklist_index, O(b)), after which is_blocked(index, ip) is an expected-O(1) membership test. The function still accepts a plain list, so it is a drop-in replacement. Trade-off: O(b) memory, and the index must be updated (add/discard) when the list changes.

c.3 find_signature – no redundant comparisons

The corrected brute-force scan already abandons a window at its first mismatch. The optimised version additionally:

- returns immediately for an empty pattern or m > n (no scan at all);
- tries only the n − m + 1 windows that can contain the pattern (no out-of-range indices);
- tests log[i] against the first pattern character once and drops the window at once if it differs, and starts the inner loop at j = 1 so pattern[0] is never compared twice;
- removes the per-window for…else set-up of the inner range iterator (pure interpreter overhead).

An **optional extension**, find_signature_horspool, skips alignments with a bad-character table (average ≈ n/m comparisons). It is not needed for correctness and is clearly separated from the brute-force function.

c.4 closest_logins – three optimisations

1. **No self or repeated pairs** (done in the correction): n(n−1)/2 pairs instead of n^2.
2. **No unnecessary square roots**: √ is monotonic, so squared distances are compared and math.sqrt is called once at the end.
3. **Pruning**: events are sorted by x. For each point a, the scan to its right stops as soon as $(x_b - x_a)^2 >$ best, because that point and every later one are already farther away in x than the best distance, so they cannot be closer. The test is strict (>) so pairs that *tie* with the best are still examined, which preserves the brute-force tie-break (smallest (i, j)); indices refer to the original event order.

```python
def sort_alerts(alerts):
    """Sort alerts by severity, highest first; equal severities keep arrival order.

    Uses Python's Timsort: it detects already-ordered runs, so nearly sorted
    alert streams cost about n comparisons, while the worst case stays
    O(n log n) (insertion sort is O(n^2)).  `reverse=True` preserves the
    original order of equal keys, so the sort is stable exactly as required.
    Sorts in place and also returns the list, like the corrected version.

    Args:
        alerts: list of (alert_id, severity) tuples.
    Returns:
        The same list, ordered by severity descending.
    """
    alerts.sort(key=itemgetter(1), reverse=True)
    return alerts


# ---------------------------------------------------------------------------
# 2. Blocklist lookups
# ---------------------------------------------------------------------------
def build_blocklist_index(blocklist):
    """Build a hash index of the blocklist once (O(b)) for O(1) lookups.

    Args:
        blocklist: iterable of IP strings.
    Returns:
        A frozenset of the blocked IPs.
    """
    return frozenset(blocklist)


def is_blocked(blocklist, ip):
    """Is `ip` on the blocklist?

    Pass the frozenset from build_blocklist_index() for repeated lookups
    (expected O(1) each).  A plain list still works (sequential search, O(b)),
    so the function is a drop-in replacement for the corrected version.

    Args:
        blocklist: list of IP strings, or a set/frozenset index of them.
        ip: IP string to look up.
    Returns:
        True if blocked, else False (also for an empty blocklist).
    """
    return ip in blocklist
```

Optimised code – sort_alerts and is_blocked

```python
def find_signature(log, pattern):
    """Brute-force string matching with no redundant comparisons.

    Compared with the corrected version:
      * O(1) guards: an empty pattern or a pattern longer than the log
        returns immediately without entering the scan;
      * only the n - m + 1 windows that can hold the pattern are tried;
      * the first character is tested once and a window that fails it is
        abandoned immediately (no inner-loop set-up);
      * a window is abandoned at its FIRST mismatch and no matched prefix is
        ever re-compared inside that window.
    Overlapping occurrences are reported.

    Args:
        log: the log line (str).
        pattern: the attack signature (str).
    Returns:
        List of 0-based start indices in increasing order.
    """
    n, m = len(log), len(pattern)
    if m == 0 or m > n:
        return []
    hits = []
    first = pattern[0]
    for i in range(n - m + 1):
        if log[i] != first:
            continue
        j = 1
        while j < m and log[i + j] == pattern[j]:
            j += 1
        if j == m:
            hits.append(i)
    return hits


def find_signature_horspool(log, pattern):
    """Optional extension: Horspool scan - skips alignments using a
    bad-character table.  Same output as find_signature (all, overlapping
    occurrences); average-case ~ n/m comparisons, worst case O(n*m).

    Args / Returns: as find_signature.
    """
    n, m = len(log), len(pattern)
    if m == 0 or m > n:
        return []
    shift = {pattern[k]: m - 1 - k for k in range(m - 1)}   # distance to last char
    hits = []
    i = 0
    last_start = n - m
    while i <= last_start:
        j = m - 1
        while j >= 0 and log[i + j] == pattern[j]:
            j -= 1
        if j < 0:
            hits.append(i)
        i += shift.get(log[i + m - 1], m)
    return hits
```

Optimised code – find_signature (and optional Horspool)

```python
def closest_logins(events):
    """Closest pair of login locations - pruned brute force.

    Optimisations over the corrected version (output is identical):
      * pairs are generated once (i < j) - no self / repeated pairs;
      * squared distances are compared, so math.sqrt is called ONCE at the end
        instead of once per pair;
      * the events are sorted by x; for each point the scan to the right stops
        as soon as (dx)^2 exceeds the best squared distance found so far,
        because every later point is even further away in x and therefore
        cannot be closer (strict '>' keeps pairs that tie, so the same
        tie-break as brute force is preserved).

    Args:
        events: list of (x, y) coordinates in km.
    Returns:
        ((i, j), distance) with i < j (indices into `events`); ties go to the
        lexicographically smallest (i, j).  With fewer than two events:
        (None, math.inf).
    """
    n = len(events)
    if n < 2:
        return None, math.inf
    order = sorted(range(n), key=lambda k: events[k][0])       # indices by x
    xs = [events[k][0] for k in order]
    ys = [events[k][1] for k in order]

    best = math.inf             # best SQUARED distance so far
    best_pair = None
    for a in range(n - 1):
        xa, ya, ia = xs[a], ys[a], order[a]
        for b in range(a + 1, n):
            dx = xs[b] - xa
            dx2 = dx * dx
            if dx2 > best:       # prune: this and all later points are too far in x
                break
            dy = ys[b] - ya
            d2 = dx2 + dy * dy
            if d2 <= best:
                ib = order[b]
                cand = (ia, ib) if ia < ib else (ib, ia)
                if d2 < best or (best_pair is not None and cand < best_pair):  # tie -> smaller (i, j)
                    best = d2
                    best_pair = cand
    return best_pair, math.sqrt(best)
```

Optimised code – closest_logins

```
terminal - CO2_Debugging_Optimisation/Source_Code

$ python optimised_sentinelops.py
sort_alerts    : [('A2', 9), ('A4', 9), ('A3', 5), ('A1', 3), ('A5', 1)]
is_blocked     : [('10.0.0.9', True), ('10.0.0.5', True), ('8.8.8.8', False)]
find_signature : [0, 8]
horspool       : [0, 8]
closest_logins : ((0, 5), 1.4142135623730951)
```

Optimised module run on the course data

Part (d) – Analysis before and after (10 marks)

n = alerts / log length / events, b = blocklist size, q = number of queries, m = pattern length, I = inversions.

d.1 Operation counts and time complexity

Function	Version	Basic operation	Count	Time	Space
sort_alerts	corrected insertion sort	key comparison	best $n-1$; general $(n-1)+I$; worst $n(n-1)/2$	O(n) best / $O(n^2)$ worst	O(1)
	optimised Timsort	key comparison	best $\approx n-1$; worst $\leq n\lceil \log_2 n \rceil$	O(n) best / O(n log n) worst	O(n)
is_blocked	corrected sequential	string comparison	hit at position k: k; miss: b; q queries $\approx q \cdot b$ worst	O(b) per query, O(qb) total	O(1)
	optimised hash set	hash probe	build b inserts + q probes	O(b + q) expected	O(b)
find_signature	corrected brute force	character comparison	per window = matched prefix + 1 (or m); best $\approx n-m+1$, worst $(n-m+1) \cdot m$	O(nm) worst	O(1) + hits
	optimised scan	character comparison	same count as corrected (already minimal for a left-to-right scan); no guard/loop-set-up overhead	O(nm) worst	O(1) + hits
	optional Horspool	character comparison	average $\approx n/m$; worst O(nm)		$O(\sigma)$
closest_logins	original (buggy)	distance + √	n^2 (incl. n self pairs)	$\Theta(n^2)$	O(1)
	corrected brute force	distance + √	exactly $n(n-1)/2$	$\Theta(n^2)$	O(1)
	optimised sweep	squared distance	sort O(n log n) + unpruned pairs; **1** √; worst $n(n-1)/2$ (all same x)	O(n log n) + pairs; worst $\Theta(n^2)$	O(n)

Derivations. *Insertion sort:* for element i the while loop makes one comparison per shift plus one failing comparison (none if it reaches the front), so total comparisons = shifts + (n−1) − r with shifts = I; I = 0 for sorted input and n(n−1)/2 for reversed. For random data with k equally likely severity levels, $E[I] = n^2(1 - 1/k)/4$ (a pair is an inversion iff the earlier alert has a *strictly* lower severity, probability $(1 - 1/k)/2$, over n(n−1)/2 pairs). *Brute-force pairs:* the double loop i < j has $\Sigma_{i=0}^{n-2}(n-1-i) = n(n-1)/2$ iterations; the original had n·n. *Signature scan:* the windows i = 0…n−m are n−m+1; a window costs between 1 and m comparisons.


d.2 Measurements

Sorting – insertion-sort comparisons, nearly sorted vs random (severity 1–10)

"Nearly sorted" = alerts sorted by severity with ≈ 1 % of the alerts swapped with another alert up to n/20 positions away.

n	input	insertion comparisons	inversions I (= shifts)	(n−1)+I	Timsort comparisons	predicted I for random: 0.225 n^2
1,000	random	217,547	216,551	217,550	6,756	225,000
1,000	nearly sorted	1,339	340	1,339	2,329	–
2,000	random	888,391	886,394	888,393	13,831	900,000
2,000	nearly sorted	3,355	1,356	3,355	4,805	–
5,000	random	5,595,663	5,590,665	5,595,664	35,285	5,625,000
5,000	nearly sorted	13,261	8,262	13,261	10,112	–
10,000	random	22,403,533	22,393,537	22,403,536	70,945	22,500,000
10,000	nearly sorted	41,214	31,215	41,214	20,010	–


Running time at n = 10,000: insertion sort 1.494 s (random) vs 0.0028 s (nearly sorted); Timsort 0.0012 s (random) and 0.0002 s (nearly sorted).



sort_alerts – comparisons and time

Blocklist – sequential search vs hash set (2,000 queries, 50 % hits)

Blocklist size b	Sequential comparisons	Hash set operations (build b + 2,000 probes)	Sequential time	Hash build + lookup time
1,000	1,500,500	3,000	0.0371 s	0.0002 s
5,000	7,538,876	7,000	0.2124 s	0.0010 s
20,000	30,149,489	22,000	0.9916 s	0.0028 s



is_blocked – operations and time

Signature scan – character comparisons

Case	n	m	Hits	Windows: original / correct	Brute force	Optimised	Horspool (optional)
random log	10,000	4	4	9,996 / 9,997	10,270	10,270	2,681
random log	100,000	4	4	99,996 / 99,997	102,624	102,624	26,647


Case	n	m	Hits	Windows: original / correct	Brute force	Optimised	Horspool (optional)
random log	200,000	4	4	199,996 / 199,997	205,160	205,160	53,298
worst case AAA…A / AAAAAAAB	20,000	8	0	19,992 / 19,993	159,944	159,944	19,993

Times (random log, n = 200,000): brute force 26.9 ms, optimised 7.3 ms, Horspool 8.3 ms.

Closest pair – distance computations (events uniform in a 1000 km × 1000 km square, seed 2026)

Batch size n	Original n²	Brute force n(n−1)/2	Optimised (pruned)	Reduction	√ calls (brute → opt.)	Time brute	Time optimised
1,000	1,000,000	499,500	1,694	295×	499,500 → 1	0.101 s	0.0006 s
2,000	4,000,000	1,999,000	2,856	700×	1,999,000 → 1	0.445 s	0.0010 s
4,000	16,000,000	7,998,000	7,552	1,059×	7,998,000 → 1	1.548 s	0.0023 s
8,000	64,000,000	31,996,000	5,646	5,667×	31,996,000 → 1	6.494 s	0.0040 s

For every size the optimised function returned the same pair and distance as brute force. Degenerate input (2,000 events all with the same x): brute force 1,999,000 and optimised 1,999,000 distance computations – no pruning is possible.



closest_logins – distance computations and time

```
terminal - CO2_Debugging_Optimisation/Source_Code

$ python experiments.py   (closest_logins section)
[4] closest_logins: distance computations
{'n': 1000, 'original_pairs_n_squared': 1000000, 'brute_distance_computations': 499500, 'brute_sqrt_calls': 499500, 'optimised_distance_computation...
    {'n': 2000, 'original_pairs_n_squared': 4000000, 'brute_distance_computations': 1999000, 'brute_sqrt_calls': 1999000, 'optimised_distance_compu...
    {'n': 4000, 'original_pairs_n_squared': 16000000, 'brute_distance_computations': 7998000, 'brute_sqrt_calls': 7998000, 'optimised_distance_comp...
    {'n': 8000, 'original_pairs_n_squared': 64000000, 'brute_distance_computations': 31996000, 'brute_sqrt_calls': 31996000, 'optimised_distance_co...
    {'case': 'degenerate: all events share one x', 'n': 2000, 'brute_distance_computations': 1999000, 'optimised_distance_computations': 1999000}

Saved results to Supporting_Files/ and graphs to Report/graphs/
```

Experiment output – closest_logins

d.3 Do the measurements agree with the analysis?

- **Insertion sort.** Comparisons equal (n−1) + I exactly for the nearly sorted inputs and differ from it by only a few units for random data (the few units are r, insertions that reach the front). The measured random inversions are within 4 % of the predicted 0.225 n^2 (3.8 % at n = 1,000, 0.5 % at n = 10,000: 22.39 M vs 22.5 M), and the 10,000-alert random run is ≈ 25× the 2,000-alert one in comparisons (22.4 M / 0.89 M), as the n^2 law predicts (25×). Nearly sorted input is orders of magnitude cheaper (41 k vs 22.4 M comparisons) – insertion sort is adaptive, as analysed.
- **Timsort vs insertion sort on nearly sorted data – a nuance.** On the *least* disordered inputs (n = 1,000–2,000) insertion sort used **fewer** comparisons than Timsort (1,339 vs 2,329) because it pays only for the inversions, whereas Timsort pays for run detection and merging. As the disorder grows with n (here I ≈ 3n), Timsort overtakes it (20,010 vs 41,214 at n = 10,000). Timsort's real advantage is the guarantee: 70,945 comparisons on 10,000 random alerts versus 22.4 M, and it is also faster in wall-clock time for every case measured because its inner loops run in C. Timsort's random count is below n $\log_2$ n (132,877) because severities take only 10 distinct values.
- **Blocklist.** Sequential comparisons match the model: with 50 % hits at a random position and 50 % misses, the expected cost is q·(b/2·0.5 + b·0.5) = 0.75·q·b, i.e. 1.5 M for b = 1,000 (measured 1,500,500) and 30.1 M for b = 20,000 (measured 30,149,489); it grows linearly with b, whereas

the hash set needs b + q operations. Wall-clock time follows (0.99 s vs 2.8 ms at b = 20,000, ≈ 350×).


- **Signature scan.** On random text over a 40-character alphabet, almost every window fails on its first comparison, so the count is ≈ 1.026·n (10,270 for n = 10,000 – 2.7 % more than the 9,997 windows), as the model predicts; the adversarial case reaches exactly (n−m+1)·m = 19,993 × 8 = 159,944. **The optimised scan performs exactly the same number of character comparisons as the corrected one** – the corrected scan was already minimal for a left-to-right search – so its measured gain (≈ 3.7× faster, 7.3 ms vs 26.9 ms) comes from lower interpreter overhead, not fewer comparisons, and in the adversarial case it is not faster (9.5 ms vs 8.8 ms). Only the optional Horspool variant reduces the comparison count (≈ n/m on random text: 26,647 vs 102,624), and its worst case remains O(nm) in theory.
- **Closest pair.** The brute-force counts equal n(n−1)/2 exactly (499,500 … 31,996,000), a 4× increase per doubling of n, as $\Theta(n^2)$ predicts, and the original would have needed n^2 (twice as many). The pruned sweep needed 0.3 %–0.02 % as many distance computations and one square root instead of tens of millions; its time grew from 0.6 ms to 4 ms. For uniformly spread events the best distance found so far quickly becomes small (of the order of the spacing between neighbouring events), so only a handful of points lie within $|dx| \leq \sqrt{best}$ and the scan after the sort is close to linear; this is an empirical/heuristic observation (the counts are not strictly monotonic, e.g. 7,552 at n = 4,000 vs 5,646 at n = 8,000, because the number of pruned pairs depends on how early a close pair is met in the sweep), not a worst-case bound. The degenerate vertical-line test confirms the analysis that the worst case stays $\Theta(n^2)$; the sort-by-x pruning is an effective heuristic on spread-out locations, and a divide-and-conquer closest-pair algorithm would be needed for a guaranteed O(n log n).

Production implication (50,000 alerts and 8,000 login events per day): sorting drops from a worst case of ≈ $1.25 \cdot 10^9$ comparisons to < 10^6, each blocklist lookup becomes constant time, and the login-clustering report drops from ≈ 32 million distance evaluations (≈ 6.5 s here) to a few thousand (≈ 4 ms) for realistic data.

Part (e) – Production-quality code (8 marks)

- **Source_Code/optimised_sentinelops.py** – final module: module and function docstrings (arguments, returns, tie-break rules, complexity), comments tagged with the optimisation applied, no global state.

- **Source_Code/corrected_sentinelops.py** – the minimally patched original; every changed line carries a D1…D9 / H1 comment saying what it was before.
- **Source_Code/test_harness.py** – 42 checks per module (every function, the course data and all boundary cases of part (b)), run against the original (to prove the tests detect the defects), the corrected and the optimised module, plus a 3,000-trial randomised differential test against independent references (sorted with a negated key, regular-expression look-ahead, itertools.combinations + math.dist, and in). It exits with a non-zero status if anything unexpected happens.
- **Source_Code/debug_session.py, trace_demo.py, experiments.py** – reproduce every table in this report.



Test harness – first checks of the original suite (failures = defects)

```
def suite(label, m, fast_lookup):
    """Run every test against module `m`.  `fast_lookup` -> build a set index."""
    print(f"\n=== {label} " + "=" * (60 - len(label)))
    r = Runner(label)
    lookup = (lambda bl: m.build_blocklist_index(bl)) if fast_lookup else (lambda bl: bl)

    # ---------------------------------------------------------- sort_alerts
    print(" sort_alerts")
    exp = [("A2", 9), ("A4", 9), ("A3", 5), ("A1", 3), ("A5", 1)]
    r.raises_nothing("course data", lambda: m.sort_alerts(list(ALERTS)), exp)
    r.raises_nothing("no alert lost / duplicated (same multiset)",
                     lambda: sorted(m.sort_alerts(list(ALERTS))), sorted(ALERTS))
    r.raises_nothing("empty list", lambda: m.sort_alerts([]), [])
    r.raises_nothing("single alert", lambda: m.sort_alerts([("X", 4)]), [("X", 4)])
    eq = [("B1", 5), ("B2", 5), ("B3", 5), ("B4", 5)]
    r.raises_nothing("all equal severities keep arrival order",
                     lambda: m.sort_alerts(list(eq)), eq)
    r.raises_nothing("already sorted (highest first)",
                     lambda: m.sort_alerts([("a", 9), ("b", 5), ("c", 1)]),
                     [("a", 9), ("b", 5), ("c", 1)])
    r.raises_nothing("reverse order (lowest first)",
                     lambda: m.sort_alerts([("c", 1), ("b", 5), ("a", 9)]),
                     [("a", 9), ("b", 5), ("c", 1)])
    r.raises_nothing("maximum arrives last, must reach index 0",
                     lambda: m.sort_alerts([("a", 1), ("b", 2), ("c", 9)]),
                     [("c", 9), ("b", 2), ("a", 1)])
    r.raises_nothing("two elements, swap needed (j reaches -1)",
                     lambda: m.sort_alerts([("a", 1), ("b", 2)]), [("b", 2), ("a", 1)])
    r.raises_nothing("duplicates of max interleaved (stability)",
                     lambda: m.sort_alerts([("a", 2), ("b", 9), ("c", 2), ("d", 9), ("e", 2)]),
                     [("b", 9), ("d", 9), ("a", 2), ("c", 2), ("e", 2)])

    # ---------------------------------------------------------- is_blocked
    print(" is_blocked")
    r.raises_nothing("course queries (blocked, blocked, clean)",
                     lambda: [m.is_blocked(lookup(BLOCKLIST), q) for q in QUERIES],
                     [True, True, False])
    r.raises_nothing("empty blocklist -> False (not None)",
                     lambda: m.is_blocked(lookup([]), "1.1.1.1"), False)
    r.raises_nothing("match is the LAST element",
                     lambda: m.is_blocked(lookup(BLOCKLIST), "172.16.4.2"), True)
    r.raises_nothing("match is the middle element",
                     lambda: m.is_blocked(lookup(BLOCKLIST), "10.0.0.9"), True)
    r.raises_nothing("single-element list, match",
                     lambda: m.is_blocked(lookup(["9.9.9.9"]), "9.9.9.9"), True)
    r.raises_nothing("single-element list, no match",
```

Test harness source (excerpt)

Reproduce everything:

cd Source_Code

python original_sentinelops.py # the failing behaviour

python debug_session.py # one fix at a time, re-tested

python test_harness.py # 42 checks x 3 modules + 3,000 random trials

python experiments.py # part (d) measurements, graphs and CSV/JSON

Limitations and assumptions

- Severity is numeric and higher = more severe; events are numeric (x, y) pairs. Distances are Euclidean on the given km coordinates (no geodesic correction).
- Two distinct squared distances that round to the same float sqrt could in principle be ordered differently by the brute-force and the squared-distance comparison; this does not occur for the integer and 2-decimal coordinates tested (3,000 randomised comparisons, 0 mismatches).

- Timings were taken on one machine and vary run to run; operation counts are deterministic. The 50,000-alert figures in c.1 and d.3 are extrapolations from the measured 10,000-alert runs, not separate measurements.
- The screenshots in Report/screenshots/ were rendered from the real source files and the real program output by Supporting_Files/make_screenshots.py; replace them with captures from your own editor/terminal if your instructor requires literal screen grabs.

Code of conduct

I _____RITHIKA.G(192571027)_____ (Name / Reg. No.) certify that this submission is my original work and that I have adhered to the guidelines specified for this assessment.

Signature: _  _____ Date: _____30/10/2026___