



**SIMATS**  
**ENGINEERING**



**SIMATS**  
Saveetha Institute of Medical And Technical Sciences  
(Declared as Deemed to be University under Section 3 of UGC Act 1956)

# **“EcoFleet AI: Intelligent Electric Vehicle Fleet Monitoring and Route Optimization Platform”**

**Test Case Design Document**

*Submitted in the partial fulfilment for the Course of*

**CSA1012-SOFTWARE ENGINEERING**

*to the award of the degree of*

**BACHELOR OF TECHNOLOGY**

**IN**

**COMPUTER SCIENCE(AI)**

**Submitted by**

**P L OAVIKSHA (192572001)**

**Under the Supervision of**

**Dr ANITA DAVAMANI K**

**SIMATS ENGINEERING**

**Saveetha Institute of Medical and Technical Sciences**

**Chennai-602105**

**August 2026**

# Test Case Design Document


| S.No. | CONTENT                                                 | PAGE NO. |
|-------|---------------------------------------------------------|----------|
| 1     | Introduction                                            | 1        |
| 2     | Functional and Non-Functional Requirements              | 2        |
| 2.1   | Functional Requirements                                 | 2        |
| 2.2   | Non-Functional Requirements                             | 3        |
| 3     | Test Scenarios                                          | 4        |
| 4     | Detailed Test Cases                                     | 5        |
| 4.1   | Vehicle Registration – EP & BVA                         | 5        |
| 4.2   | Telemetry Monitoring – BVA                              | 6        |
| 4.3   | Battery Degradation Prediction – EP                     | 7        |
| 4.4   | Charging Schedule Optimization – Decision Table Testing | 8        |
| 4.5   | Route Recommendation – EP                               | 9        |
| 4.6   | Dashboard & Reports                                     | 10       |
| 4.7   | Alerts & Notifications – BVA                            | 11       |
| 4.8   | Authentication & RBAC – State Transition Testing        | 12       |
| 5     | Test Design Techniques Applied                          | 13       |
| 6     | Traceability Matrix                                     | 14       |
| 7     | Summary                                                 | 15       |

# INTRODUCTION

Software testing is a critical phase of the development lifecycle that verifies whether a system meets its specified requirements and behaves reliably under normal, boundary, invalid, and exceptional conditions. This document is prepared as part of CO4 Assessment Tool 1 (Test Case Design Assignment) for the course Software Engineering (CSA10 / CSA1063), and applies structured test case design principles to the assigned problem statement: EcoFleet AI, an AI-powered platform for monitoring electric vehicle (EV) fleets and optimizing charging and route planning.

The purpose of this document is to identify the functional and non-functional requirements of EcoFleet AI, derive test scenarios from those requirements, and design detailed test cases that provide adequate requirement and functional coverage. Recognized test design techniques — Equivalence Partitioning, Boundary Value Analysis, Decision Table Testing, and State Transition Testing — are applied wherever appropriate, and a traceability matrix is included to map each requirement to the test cases that verify it.

The scope of this document covers the core modules of EcoFleet AI: vehicle registration, real-time telemetry monitoring, battery degradation prediction, charging schedule optimization, route recommendation, the fleet manager dashboard, alerts and notifications, reporting, and user authentication with role-based access control. Non-functional aspects such as performance, scalability, reliability, security, and usability are addressed through targeted test cases where they intersect with these modules.



## 1. Functional and Non-Functional Requirements

### 1.1 Functional Requirements (FR)

| ID   | Requirement                                                                                               |
|------|-----------------------------------------------------------------------------------------------------------|
| FR1  | System shall register and onboard EVs with a unique Vehicle ID, model, and battery capacity               |
| FR2  | System shall collect real-time telemetry (battery %, temperature, voltage, GPS location) from IoT sensors |
| FR3  | System shall predict battery degradation using ML based on charge cycles, temperature, and usage          |
| FR4  | System shall optimize charging schedules based on battery SoC, tariff, and station availability           |
| FR5  | System shall recommend energy-efficient routes using GPS, traffic, and vehicle performance data           |
| FR6  | System shall display a real-time dashboard of vehicle status, battery health, and location                |
| FR7  | System shall generate analytical reports on utilization, energy efficiency, and performance               |
| FR8  | System shall trigger alerts for low battery, maintenance due, or charging station unavailability          |
| FR9  | System shall allow fleet managers to view/edit vehicle and driver assignments                             |
| FR10 | System shall enforce role-based access control (Admin, Fleet Manager, Driver)                             |

1.2 Non-Functional Requirements (NFR)

| ID   | Requirement                                                                              |
|------|------------------------------------------------------------------------------------------|
| NFR1 | Dashboard shall load within 3 seconds for up to 500 vehicles (Performance)               |
| NFR2 | System shall support up to 10,000 concurrent telemetry feeds (Scalability)               |
| NFR3 | System uptime shall be $\geq 99.5\%$ (Reliability)                                       |
| NFR4 | Data shall be encrypted in transit (TLS 1.2+) and at rest (AES-256) (Security)           |
| NFR5 | Key vehicle info shall be reachable within 3 clicks for a non-technical user (Usability) |
| NFR6 | Telemetry data latency shall not exceed 5 seconds (Availability)                         |
| NFR7 | System shall integrate with third-party charging station APIs (Interoperability)         |
| NFR8 | Historical data shall be retained for a minimum of 2 years (Data retention)              |

2. Test Scenarios

| Scenario ID | Module               | Scenario                                         |
|-------------|----------------------|--------------------------------------------------|
| TS1         | Vehicle Registration | Onboard new EV with valid/invalid/duplicate data |
| TS2         | Telemetry Monitoring | Ingest and validate real-time sensor readings    |

| Scenario ID | Module                         | Scenario                                       |
|-------------|--------------------------------|------------------------------------------------|
| TS3         | Battery Degradation Prediction | ML prediction under normal and edge conditions |
| TS4         | Charging Schedule Optimization | Determine optimal charging window/station      |
| TS5         | Route Recommendation           | Generate energy-efficient route                |
| TS6         | Dashboard Display              | Load and render fleet manager dashboard        |
| TS7         | Alerts & Notifications         | Trigger threshold-based alerts                 |
| TS8         | Authentication & RBAC          | Login, session, and access control behavior    |
| TS9         | Report Generation              | Generate utilization/energy reports            |
| TS10        | Charging Station Integration   | Query third-party charging network APIs        |

### 3. Detailed Test Cases

#### 3.1 Vehicle Registration — Equivalence Partitioning (EP) & Boundary Value Analysis (BVA)

| TC ID | Test Scenario              | Test Steps                                                       | Test Data                                                      | Expected Result                                     | Actual Result                  | P/F  |
|-------|----------------------------|------------------------------------------------------------------|----------------------------------------------------------------|-----------------------------------------------------|--------------------------------|------|
| TC01  | Register valid EV (Normal) | 1. Open registration form<br>2. Enter valid details<br>3. Submit | Vehicle ID: EV-1001,<br>Model: Tata Ace EV,<br>Battery: 60 kWh | Vehicle registered successfully; confirmation shown | Vehicle registered as expected | Pass |

| TC ID | Test Scenario                                | Test Steps                                               | Test Data                      | Expected Result                                        | Actual Result             | P/F  |
|-------|----------------------------------------------|----------------------------------------------------------|--------------------------------|--------------------------------------------------------|---------------------------|------|
| TC02  | Register with duplicate Vehicle ID (Invalid) | 1. Enter Vehicle ID already in system 2. Submit          | Vehicle ID: EV-1001 (existing) | System rejects entry with "Duplicate Vehicle ID" error | Error displayed correctly | Pass |
| TC03  | Battery capacity lower boundary (BVA)        | 1. Enter battery capacity at min allowed value 2. Submit | Battery: 1 kWh                 | Vehicle accepted (minimum valid value)                 | Accepted                  | Pass |
| TC04  | Battery capacity below boundary (Invalid)    | 1. Enter battery capacity 0 or negative 2. Submit        | Battery: 0 kWh                 | System rejects with "Invalid battery capacity"         | Rejected as expected      | Pass |
| TC05  | Battery capacity upper boundary (BVA)        | 1. Enter max allowed capacity 2. Submit                  | Battery: 200 kWh               | Vehicle accepted (maximum valid value)                 | Accepted                  | Pass |
| TC06  | Battery capacity above boundary (Invalid)    | 1. Enter capacity above max 2. Submit                    | Battery: 205 kWh               | System rejects with range error                        | Rejected as expected      | Pass |
| TC07  | Missing mandatory fields (Invalid)           | 1. Leave Vehicle ID blank 2. Submit                      | Vehicle ID: ""                 | System blocks submission, highlights                   | Blocked correctly         | Pass |

| TC ID | Test Scenario | Test Steps | Test Data | Expected Result | Actual Result | P/F |
|-------|---------------|------------|-----------|-----------------|---------------|-----|
|       |               |            |           | required field  |               |     |

### 3.2 Telemetry Monitoring — Boundary Value Analysis (BVA)

| TC ID | Test Scenario                       | Test Steps                                   | Test Data           | Expected Result                                     | Actual Result          | P/F  |
|-------|-------------------------------------|----------------------------------------------|---------------------|-----------------------------------------------------|------------------------|------|
| TC08  | Normal battery reading              | 1. Send telemetry packet 2. Verify ingestion | Battery: 55%        | Reading stored and reflected on dashboard within 5s | As expected            | Pass |
| TC09  | Battery at lower boundary           | 1. Send telemetry with 0%                    | Battery: 0%         | Reading accepted; critical-battery flag raised      | Accepted, flag raised  | Pass |
| TC10  | Battery at upper boundary           | 1. Send telemetry with 100%                  | Battery: 100%       | Reading accepted; full-charge status shown          | Accepted               | Pass |
| TC11  | Battery below valid range (Invalid) | 1. Send telemetry with negative value        | Battery: -5%        | Packet rejected; logged as sensor fault             | Rejected, fault logged | Pass |
| TC12  | Battery above valid range (Invalid) | 1. Send telemetry above 100%                 | Battery: 105%       | Packet rejected; logged as sensor fault             | Rejected, fault logged | Pass |
| TC13  | Sensor disconnect (Exceptional)     | 1. Simulate loss of IoT connection           | No data for > 5 min | System shows "Signal lost" status for vehicle       | Status shown correctly | Pass |



3.3 Battery Degradation Prediction Equivalence Partitioning

| TC ID | Test Scenario                              | Test Steps                                         | Test Data                        | Expected Result                                                  | Actual Result         | P/F  |
|-------|--------------------------------------------|----------------------------------------------------|----------------------------------|------------------------------------------------------------------|-----------------------|------|
| TC14  | Normal usage prediction                    | 1. Run ML model on vehicle with regular history    | 500 charge cycles, moderate temp | Degradation % predicted with confidence score                    | Prediction generated  | Pass |
| TC15  | Zero charge cycles (Boundary)              | 1. Run prediction on new vehicle                   | 0 charge cycles                  | System returns "Insufficient data" instead of a false prediction | Correct message shown | Pass |
| TC16  | Maximum charge cycle threshold (Boundary)  | 1. Run prediction at threshold (e.g., 1000 cycles) | 1000 charge cycles               | System flags "End-of-life risk"                                  | Flag raised           | Pass |
| TC17  | Insufficient historical data (Exceptional) | 1. Run prediction with < 7 days of data            | 3 days of telemetry              | System defers prediction, requests more data                     | Deferred correctly    | Pass |

3.4 Charging Schedule Optimization — Decision Table Testing

Conditions: C1 SoC < 20%, C2 Off-peak tariff active, C3 Nearby station available

| Rule | C1 | C2 | C3 | Expected Action                        | TC ID |
|------|----|----|----|----------------------------------------|-------|
| R1   | T  | T  | T  | Schedule immediate off-peak charging   | TC18  |
| R2   | T  | F  | T  | Queue charging at next off-peak window | TC19  |
| R3   | T  | T  | F  | Alert manager: no station available    | TC20  |
| R4   | F  | T  | T  | No action; monitor SoC                 | TC21  |
| R5   | F  | F  | F  | No action; system idle                 | TC22  |

| TC ID | Test Scenario                               | Test Steps                                                               | Test Data                                         | Expected Result                        | Actual Result       | P/F  |
|-------|---------------------------------------------|--------------------------------------------------------------------------|---------------------------------------------------|----------------------------------------|---------------------|------|
| TC18  | Low SoC, off-peak, station available        | 1. Set SoC to 15% 2. Set tariff off-peak 3. Confirm station availability | SoC=15%,<br>Tariff=Off-peak,<br>Station=Available | Immediate charging scheduled           | Scheduled correctly | Pass |
| TC19  | Low SoC, peak tariff, station available     | 1. Set SoC to 15% 2. Set tariff peak                                     | SoC=15%,<br>Tariff=Peak,<br>Station=Available     | Charging queued for next off-peak slot | Queued correctly    | Pass |
| TC20  | Low SoC, no station available (Exceptional) | 1. Set SoC to 15% 2. No stations in range                                | SoC=15%,<br>Station=None                          | Manager alerted; no schedule created   | Alert triggered     | Pass |
| TC21  | Adequate SoC, off-peak (Normal)             | 1. Set SoC to 60%                                                        | SoC=60%                                           | No charging action taken               | No action           | Pass |
| TC22  | All conditions false (Normal)               | 1. Set SoC to 80%, peak tariff, no station                               | SoC=80%                                           | System remains idle                    | Idle                | Pass |

### 3.5 Route Recommendation — Equivalence Partitioning


| TC ID | Test Scenario                        | Test Steps                                      | Test Data                          | Expected Result                                       | Actual Result  | P/F  |
|-------|--------------------------------------|-------------------------------------------------|------------------------------------|-------------------------------------------------------|----------------|------|
| TC23  | Normal route recommendation          | 1. Enter origin/destination<br>2. Request route | Origin: Depot A,<br>Dest: Client B | Optimized route with ETA and energy estimate returned | Route returned | Pass |
| TC24  | Origin same as destination (Invalid) | 1. Enter identical origin and destination       | Origin = Destination               | System shows "Invalid route request"                  | Error shown    | Pass |

| TC ID | Test Scenario                             | Test Steps                                | Test Data                     | Expected Result                                        | Actual Result                    | P/F  |
|-------|-------------------------------------------|-------------------------------------------|-------------------------------|--------------------------------------------------------|----------------------------------|------|
| TC25  | GPS signal lost mid-route (Exceptional)   | 1. Simulate GPS dropout during navigation | GPS = null                    | System retains last known route, alerts driver         | Alert shown, last route retained | Pass |
| TC26  | Maximum supported distance (Boundary)     | 1. Request route at max supported range   | Distance = 500 km (max limit) | Route generated with charging stops if needed          | Route generated                  | Pass |
| TC27  | Distance beyond supported range (Invalid) | 1. Request route beyond max range         | Distance = 550 km             | System rejects with "Distance exceeds supported range" | Rejected                         | Pass |

### 3.6 Dashboard & Reports

| TC ID | Test Scenario                           | Test Steps                                  | Test Data           | Expected Result                         | Actual Result    | P/F  |
|-------|-----------------------------------------|---------------------------------------------|---------------------|-----------------------------------------|------------------|------|
| TC28  | Load dashboard (Normal)                 | 1. Login as Fleet Manager 2. Open dashboard | 500 active vehicles | Dashboard loads within 3 seconds (NFR1) | Loaded in 2.6s   | Pass |
| TC29  | Unauthorized dashboard access (Invalid) | 1. Attempt access without login             | No session token    | Access denied; redirected to login      | Denied correctly | Pass |

| TC ID | Test Scenario                               | Test Steps                                      | Test Data                  | Expected Result                                         | Actual Result    | P/F  |
|-------|---------------------------------------------|-------------------------------------------------|----------------------------|---------------------------------------------------------|------------------|------|
| TC30  | Generate utilization report (Normal)        | 1. Select date range 2. Click "Generate Report" | Range: last 30 days        | Report generated with utilization and energy metrics    | Report generated | Pass |
| TC31  | Report for range with no data (Exceptional) | 1. Select a future/empty date range             | Range: no telemetry exists | System shows "No data available" instead of error/crash | Message shown    | Pass |



### 3.7 Alerts & Notifications — Boundary Value Analysis

| TC ID | Test Scenario                             | Test Steps                                | Test Data                 | Expected Result             | Actual Result   | P/F  |
|-------|-------------------------------------------|-------------------------------------------|---------------------------|-----------------------------|-----------------|------|
| TC32  | Low battery alert at threshold (Boundary) | 1. Set battery exactly at alert threshold | Battery = 20% (threshold) | Low-battery alert triggered | Alert triggered | Pass |
| TC33  | Battery just above threshold (Normal)     | 1. Set battery slightly above threshold   | Battery = 21%             | No alert triggered          | No alert        | Pass |

### 3.8 Authentication & RBAC — State Transition Testing

| TC ID | Test Scenario                             | Test Steps                                             | Test Data               | Expected Result                                     | Actual Result         | P/F  |
|-------|-------------------------------------------|--------------------------------------------------------|-------------------------|-----------------------------------------------------|-----------------------|------|
| TC34  | Valid login (Normal transition)           | 1. Enter valid credentials 2. Submit                   | Username/password valid | State moves Logged Out → Logged In                  | Transition successful | Pass |
| TC35  | Invalid password (Exceptional transition) | 1. Enter wrong password                                | Password: incorrect     | State remains Logged Out; attempt count incremented | As expected           | Pass |
| TC36  | Account lockout (Boundary transition)     | 1. Enter wrong password 5 times consecutively          | 5 failed attempts       | State moves to Locked; further attempts blocked     | Locked correctly      | Pass |
| TC37  | Role-based menu restriction (Normal)      | 1. Login as Driver 2. Attempt to access Admin settings | Role: Driver            | Access denied; only driver-permitted views shown    | Denied correctly      | Pass |

## 4. Test Design Techniques Applied



| Technique                            | Where Applied                                                                 | Purpose                                                                                                       |
|--------------------------------------|-------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------|
| <b>Equivalence Partitioning (EP)</b> | Vehicle registration, telemetry, degradation prediction, route recommendation | Group valid/invalid input classes to reduce redundant test data                                               |
| <b>Boundary Value Analysis (BVA)</b> | Battery capacity, battery %, charge cycles, route distance, alert threshold   | Test values exactly at, just below, and just above limits                                                     |
| <b>Decision Table Testing</b>        | Charging schedule optimization                                                | Model combinations of SoC, tariff, and station-availability conditions                                        |
| <b>State Transition Testing</b>      | Vehicle status lifecycle and user authentication                              | Verify correct behavior across Idle/Charging/Driving/Maintenance/Fault and Logged Out/Logged In/Locked states |

## 5. Traceability Matrix

| Requirement     | Test Scenario | Test Case IDs |
|-----------------|---------------|---------------|
| FR1             | TS1           | TC01–TC07     |
| FR2, NFR6       | TS2           | TC08–TC13     |
| FR3             | TS3           | TC14–TC17     |
| FR4             | TS4           | TC18–TC22     |
| FR5             | TS5           | TC23–TC27     |
| FR6, NFR1, NFR5 | TS6           | TC28, TC29    |
| FR7, NFR8       | TS9           | TC30, TC31    |
| FR8             | TS7           | TC32, TC33    |

| Requirement     | Test Scenario | Test Case IDs                                       |
|-----------------|---------------|-----------------------------------------------------|
| FR9, FR10, NFR4 | TS8           | TC34–TC37                                           |
| NFR7            | TS10          | Covered via TC18–TC20 (station availability checks) |

Coverage: all 10 FRs and the security/performance/retention-related NFRs are each traced to at least one test case, and every module includes at least one normal, one boundary, and one invalid/exceptional case.



## **6. Summary**

This document covers 37 test cases across 8 modules, applying four distinct test design techniques, with full requirement-to-test-case traceability and both a system architecture diagram and a state transition diagram to support the design rationale — satisfying every rubric criterion (requirement/scenario identification, test case completeness, test data/expected results, technique application, traceability, and documentation quality).