

Name : K. Sampath Chaitanya
Reg No: 192572006

Simple programming using REPEAT and WHILE

Program-1:

Write a function that uses WHILE statement to build a string repeatedly until the value of the variable becomes x greater than 5. Then, we display the final string using a SELECT statement.

```
Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql> create database collegedb;
Query OK, 1 row affected (0.09 sec)

mysql> use collegedb;
Database changed
mysql> delimiter //
mysql> create function while_demo() returns varchar(100) deterministic begin declare x int default 1; declare result varchar(100) default ''; while x <=
5 do set result = concat(result,x, ' '); set x = x + 1; end while; return result; end //
Query OK, 0 rows affected (0.07 sec)

mysql> delimiter ;
mysql> select while_demo();
+-----+
| while_demo() |
+-----+
| 1 2 3 4 5 |
+-----+
1 row in set (0.14 sec)
```

Program-2:

Write a function that uses REPEAT statement which would repeat the loop until income is greater than or equal to 4000, at which point the REPEAT loop would be terminated.

```
mysql> delimiter //
mysql> create function repeat_demo() returns int deterministic begin declare income int default 1000; repeat set income = income + 1000; until income
>= 4000 end repeat; return income; end //
Query OK, 0 rows affected (0.13 sec)

mysql> delimiter ;
mysql> select repeat_demo();
+-----+
| repeat_demo() |
+-----+
| 4000 |
+-----+
1 row in set (0.04 sec)
```