

Name : K. Sampath Chaitanya
Reg no : 192572006

High Level Programming Extensions – Cursors

Problem- 1

Write a Cursor program using MySQL to retrieve the email-ids(build an email list) of employees from employees table.

```
mysql> create database collegedb;
Query OK, 1 row affected (0.10 sec)

mysql> use collegedb;
Database changed
mysql> create table employees(id integer,Name varchar(100),email varchar(100));
Query OK, 0 rows affected (0.13 sec)

mysql> insert into employees(id,Name,email) values(1,'Harry Potter','pharry@warnerbros.com');
Query OK, 1 row affected (0.16 sec)

mysql> insert into employees(id,Name,email)values(2,'Clark Kent','kclark@dccomics.com');
Query OK, 1 row affected (0.05 sec)

mysql> insert into employees(id,Name,email)values(3,'Tony Stark','stony@marvel.com');
Query OK, 1 row affected (0.13 sec)

mysql> select * from employees;
+----+-----+-----+
| id | Name   | email                |
+----+-----+-----+
| 1  | Harry Potter | pharry@warnerbros.com |
| 2  | Clark Kent  | kclark@dccomics.com  |
| 3  | Tony Stark  | stony@marvel.com     |
+----+-----+-----+
3 rows in set (0.05 sec)

mysql> delimiter $$
mysql> create procedure build_email_list(INOUT email_list varchar(4000)) begin declare v_finished integer default 0; declare v_email varchar(100) default '';
declare email_cursor cursor for select email from employees; declare continue handler for not found set v_finished = 1;open email_cursor; get_email: loop fetch
email_cursor into v_email; if v_finished = 1 then leave get_email; end if; set email_list = concat(v_email,',',email_list); end loop get_email; close email_
cursor; end$$
Query OK, 0 rows affected (0.12 sec)

mysql> delimiter ;
mysql> set @email_list = '';
Query OK, 0 rows affected (0.00 sec)

mysql> call build_email_list(@email_list);
Query OK, 0 rows affected (0.01 sec)

mysql> select @email_list;
+-----+
| @email_list |
+-----+
| stony@marvel.com;kclark@dccomics.com;pharry@warnerbros.com; |
+-----+
1 row in set (0.00 sec)
```