3. Scenario: You are working on a project that involves analyzing a dataset containing information

about houses in a neighborhood. The dataset is stored in a CSV file, and you have imported it into a

NumPy array named house_data. Each row of the array represents a house, and the columns

contain various features such as the number of bedrooms, square footage, and sale price.

Question: Using NumPy arrays and operations, how would you find the average sale price of houses with more than four bedrooms in the neighborhood?

Code;

```
import numpy as np

house_data = np.array([

    [3, 1200, 200000],
    [5, 1800, 350000],
    [4, 1500, 250000],
    [6, 2200, 450000],
    [5, 2000, 400000]
])
houses = house_data[house_data[:, 0] > 4]

avg = np.mean(houses[:, 2])

print("Average sale price:", avg)
```

input;

Average sale price: 400000

expp3 dsa.py - C:/Users/Jashw/expp3 dsa.py (3.13.14)

File Edit Format Run Options Window Help

```
import numpy as np

# Columns: Bedrooms, Square Footage, Sale Price
house_data = np.array([
     [3, 1200, 200000],
     [5, 1800, 350000],
     [4, 1500, 250000],
     [6, 2200, 450000],
     [5, 2000, 400000]
])

# Select houses with more than 4 bedrooms
houses = house_data[house_data[:, 0] > 4]

# Calculate average sale price
avg = np.mean(houses[:, 2])

print("Average sale price:", avg)
```