

```

function Question1
xx2 = [0.1:0.001:15]; %#ok<NBRAK2>
for i = 1:length(xx2)
    yy(i)=gx(xx2(i));
end
%plot(xx2, yy)
%ylim([-5,5])

options=optimset('Display', 'off');
sol1_range=[4.19,4.21];
x2_sol1=fzero(@gx, sol1_range, options);
sol2_range=[4.275,4.28];
x2_sol2=fzero(@gx, sol2_range, options);
sol3_range=[4.3268,4.327];
x2_sol3=fzero(@gx, sol3_range, options);
sol4_range=[4.356,4.358];
x2_sol4=fzero(@gx, sol4_range, options);
sol5_range=[4.378,4.38];
x2_sol5=fzero(@gx, sol5_range, options);

xx2 = x2_sol1;
[x13_sol1,~]=fsolve(@fx,[1,1],options);
fprintf('Solution 1: x1 = %2.3f, x2 = %2.3f, x3 = %2.3f\n\n', x2_sol1, x13_sol1(1),
x13_sol1(2))

xx2 = x2_sol2;
[x13_sol2,~]=fsolve(@fx,[1,1],options);
fprintf('Solution 2: x1 = %2.3f, x2 = %2.3f, x3 = %2.3f\n\n', x2_sol2, x13_sol2(1),
x13_sol2(2))

xx2 = x2_sol3;
[x13_sol3,~]=fsolve(@fx,[1,1],options);
fprintf('Solution 3: x1 = %2.3f, x2 = %2.3f, x3 = %2.3f\n\n', x2_sol3, x13_sol3(1),
x13_sol3(2))

xx2 = x2_sol4;
[x13_sol4,~]=fsolve(@fx,[1,1],options);
fprintf('Solution 4: x1 = %2.3f, x2 = %2.3f, x3 = %2.3f\n\n', x2_sol4, x13_sol4(1),
x13_sol4(2))

xx2 = x2_sol5;
[x13_sol5,~]=fsolve(@fx,[1,1],options);
fprintf('Solution 5: x1 = %2.3f, x2 = %2.3f, x3 = %2.3f\n\n', x2_sol5, x13_sol5(1),
x13_sol5(2))

function ff=fx(z)
    % z(1) is x1, z(2) is x3
    x1 = z(1); x3 = z(2);
    % These need to be equal to zero
    ff(1,1)=6*x1+x3*log(xx2)+xx2*x3-6;
    ff(2,1)=x1+xx2+x3-5;
end

function f2=gx(x2)
    options=optimset('Display', 'off');

```

```

[x_sol,~] = fsolve(@fx,[0,0], options);
xx1 = x_sol(1); xx3 = x_sol(2);
f2=exp(xx1)*sin(xx3)-5*exp(-x2)-10;

function ff=fx(z)
    % z(1) is x1, z(2) is x3
    x1 = z(1); x3 = z(2);
    % These need to be equal to zero
    ff(1,1)=6*x1+x3*log(x2)+x2*x3-6;
    ff(2,1)=x1+x2+x3-5;
end
end
end

```

Solution 1: x1 = 4.201, x2 = 4.107, x3 = -3.308

Solution 2: x1 = 4.279, x2 = 6.995, x3 = -6.274

Solution 3: x1 = 4.327, x2 = 10.098, x3 = -9.425

Solution 4: x1 = 4.357, x2 = 13.209, x3 = -12.566

Solution 5: x1 = 4.379, x2 = 16.329, x3 = -15.708

```

function Question2
K1=1.93e-4;
K2=5.528;

% e1 is going to heavily favor reactants and be less than 2
e1_guess=0.1;

% e2 will be less than e2, but the reaction will moderately favor products
e2_guess=0.08;

options=optimset('Display', 'off');
[e_sol,~]=fsolve(@get_eqs,[e1_guess, e2_guess],options);
ee1=e_sol(1);
ee2=e_sol(2);

fprintf('Carbon Monoxide Fraction: %1.4f\n', (ee1-ee2)/(10+2*ee1))
fprintf('Hydrogen Fraction: %1.4f\n', (3*ee1+ee2)/(10+2*ee1))
fprintf('Water Fraction: %1.4f\n', (8-ee1-ee2)/(10+2*ee1))
fprintf('Carbon Dioxide Fraction: %1.4f\n', (ee2)/(10+2*ee1))
fprintf('Methane Fraction: %1.4f\n', (2-ee1)/(10+2*ee1))

```

```

function rxn_eqs=get_eqs(x)
    % x(1) is e1, x(2) is e2
    e1 = x(1); e2 = x(2);
    % These need to be equal to zero
    rxn_eqs(1,1)=(e1-e2)*(3*e1+e2)^3-K1*(2-e1)*(8-e1-e2)*(10+2*e1)^2;
    rxn_eqs(2,1)=e2*(3*e1+e2)-K2*(e1-e2)*(8-e1-e2);
end
end

```

Carbon Monoxide Fraction: 0.0024

Hydrogen Fraction: 0.1881

Water Fraction: 0.6309

Carbon Dioxide Fraction: 0.0452

Methane Fraction: 0.1333