

# JS Briefing

總分 45/50



part- 1

電子郵件 \*

stellachiuau@gmail.com

✓ How would you properly refactor this code block using the ternary operator? \*5/5

```
if (walkSignal === 'Walk') {  
  console.log('You may walk!');  
} else {  
  console.log('Do not walk!');  
}
```

- ☐ walkSignal ? console.log('You may walk!') : console.log('Do not walk!');
- ☐ walkSignal === 'Walk' ? ('You may walk!') : ('Do not walk!');
- ☒ walkSignal === 'Walk' ? console.log('You may walk!') : console.log('Do not walk!'); ✓
- ☐ walkSignal === 'Walk' : console.log('You may walk!') : console.log('Do not walk!');

建議



Correct!



✓ What will the code block log to the console? \*

5/5

```
let groceryItem = "apple";

switch (groceryItem) {
  case "tomato":
    console.log("Tomatoes are $0.49");
    break;
  case "lime":
    console.log("Limes are $1.49");
    break;
  case "papaya":
    console.log("Papayas are $1.29");
    break;
  default:
    console.log("Invalid item");
    break;
}
```

- ☐ Tomatoes are \$0.49
- ☐ Papayas are \$1.29
- ☒ Invalid item
- ☐ Limes are \$1.49



建議



Correct! Since `groceryItem = "apple"`, it does not match any of the cases, so the default block will run.



✓ If **isHungry** equals **true**, which of the following expressions evaluates to **true**? \*5/5

- ☐ !isHungry === true
- ☐ !isHungry
- ☐ isHungry === false
- ☒ isHungry !== false



建議



Correct!

✗ What will the following code log to the console? \* .../5

```
let needTacos = true;
```

```
if (needTacos) {  
  console.log("Finding tacos");  
} else {  
  console.log("Keep on keeping on!");  
}
```

- ☐ Keep on keeping on!
- ☒ Finding tacos



無正確答案



✓ What is the correct way to call the **random** method on the **Math** global object? \*5/5

- ☐ Math(random)
- ☒ Math.random()
- ☐ random.Math()
- ☐ math.random()



建議



Nice work! This is the correct syntax.

✓ What will the following code print to the console? \* 5/5

```
let num = 10;  
num *= 3;  
console.log(num);
```

- ☐ 'num'
- ☒ 30
- ☐ 3
- ☐ 10



建議



Correct! \*= will multiply the num by 3 and then reassign the value of num to that result.



✓ What will the code block log to the console? \*

5/5

```
let runTime = 35;
```

```
let runDistance = 3.5;
```

```
if (runTime <= 30 && runDistance > 3.5) {  
  console.log("You're super fast!");  
} else if (runTime >= 30 && runDistance <= 3) {  
  console.log("You're not making your pace!");  
} else if (runTime > 30 || runDistance > 3) {  
  console.log("Nice workout!");  
} else {  
  console.log("Keep on running!");  
}
```

- ☒ Nice workout! ✓
- ☐ You're not making your pace!
- ☐ You're super fast!
- ☐ isHungry !== false

建議



Correct!



✓ What is the outcome of this statement? \*

5/5

```
console.log('hi!'.length);
```

- ☒ 3 is printed to the console.
- ☐ 'hi!'.length will be printed to the console.
- ☐ 1 is printed to the console.
- ☐ hi! is printed to the console.



建議



*Nice work! .length will access the length property of hi! which is 3 characters long.*

✓ What is string interpolation? \*

5/5

- ☐ Changing the value of a variable.
- ☒ Using template literals to embed variables into strings.
- ☐ Joining multiple strings together using operators like +
- ☐ Printing a string to the console.



建議



*Correct! String interpolation is when we insert, or interpolate, variables into strings using template literals.*



✓ What is the correct way to call a string's built-in method? \*

5/5

- ☐ toUpperCase.'codecademy'();
- ☐ 'codecademy'.toUpperCase;
- ☒ 'codecademy'.toUpperCase();
- ☐ toUpperCase('codecademy');



建議



*Nice work! .toUpperCase() is appended to the string to call it.*

這份表單是在 Mr. & Mrs. Cloud 中建立。

Google 表單



