

Discrete Mathematics and Its Applications

Lecture 2: Basic Structures: Set Theory

MING GAO

DaSE@ ECNU

(for course related communications)

mgao@dase.ecnu.edu.cn

Sep. 27, 2018

Outline

- 1 Set Concepts
- 2 Set Operations
- 3 Application
- 4 Take-aways

Set

Definition

Set A is a collection of objects (or elements).

- $a \in A$: “ a is an element of A ” or “ a is a member of A ”;
- $a \notin A$: “ a is not an element of A ”;
- $A = \{a_1, a_2, \dots, a_n\}$: A contains a_1, a_2, \dots, a_n ;
- Order of elements is meaningless;
- It does not matter how often the same element is listed.

Set

Definition

Set A is a collection of objects (or elements).

- $a \in A$: “ a is an element of A ” or “ a is a member of A ”;
- $a \notin A$: “ a is not an element of A ”;
- $A = \{a_1, a_2, \dots, a_n\}$: A contains a_1, a_2, \dots, a_n ;
- Order of elements is meaningless;
- It does not matter how often the same element is listed.

Set equality

Sets A and B are equal if and only if they contain exactly the same elements.

- If $A = \{9, 2, 7, -3\}$ and $B = \{7, 9, 2, -3\}$, then $A = B$.
- If $A = \{9, 2, 7\}$ and $B = \{7, 9, 2, -3\}$, then $A \neq B$;
- If $A = \{9, 2, -3, 9, 7, -3\}$ and $B = \{7, 9, 2, -3\}$, then $A = B$.

Applications

Examples

- Bag of words model: documents, reviews, tweets, news, etc;
- Transactions: shopping list, app downloading, book reading, video watching, music listening, etc;
- Records in a DB, data item in a data streaming, etc;
- Neighbors of a vertex in a graph;

Applications

Examples

- Bag of words model: documents, reviews, tweets, news, etc;
- Transactions: shopping list, app downloading, book reading, video watching, music listening, etc;
- Records in a DB, data item in a data streaming, etc;
- Neighbors of a vertex in a graph;

“Standard” sets

- Natural numbers: $N = \{0, 1, 2, 3, \dots\}$
- Integers: $Z = \{\dots, -2, -1, 0, 1, 2, \dots\}$
- Positive integers: $Z^+ = \{1, 2, 3, 4, \dots\}$
- Real Numbers: $R = \{47.3, -12, -0.3, \dots\}$
- Rational Numbers: $Q = \{1.5, 2.6, -3.8, 15, \dots\}$

Representation of sets

Tabular form

- $A = \{1, 2, 3, 4, 5\};$
- $B = \{-2, 0, 2\};$

Representation of sets

Tabular form

- $A = \{1, 2, 3, 4, 5\};$
- $B = \{-2, 0, 2\};$

Descriptive form

- $A =$ set of first five natural numbers;
- $B =$ set of positive odd integers;

Representation of sets

Tabular form

- $A = \{1, 2, 3, 4, 5\};$
- $B = \{-2, 0, 2\};$

Descriptive form

- $A =$ set of first five natural numbers;
- $B =$ set of positive odd integers;

Set builder form

- $Q = \{a/b : a \in Z \wedge b \in Z \wedge b \neq 0\};$
- $B = \{y : P(y)\},$ where $P(Y) : y \in E \wedge 0 < y \leq 50;$

Representation of sets

Remarks


- $A = \emptyset$: empty set, or null set;
- Universal set U : contains all the objects under consideration.
- $A = \{\{a, b\}, \{b, c, d\}\}$;

Representation of sets

Remarks

- $A = \emptyset$: empty set, or null set;
- Universal set U : contains all the objects under consideration.
- $A = \{\{a, b\}, \{b, c, d\}\}$;

Venn diagrams



In general, a universal set is represented by a rectangle.

Subsets

Definition

Set A is a subset of B iff every element of A is also an element of B , denoted as $A \subseteq B$.

Subsets

Definition

Set A is a subset of B iff every element of A is also an element of B , denoted as $A \subseteq B$.

- $A \subseteq B = \forall x(x \in A \rightarrow x \in B);$

Subsets

Definition

Set A is a subset of B iff every element of A is also an element of B , denoted as $A \subseteq B$.

- $A \subseteq B = \forall x(x \in A \rightarrow x \in B)$;
- For every set S , we have: (1) $\emptyset \subseteq S$; and (2) $S \subseteq S$;

Subsets

Definition

Set A is a subset of B iff every element of A is also an element of B , denoted as $A \subseteq B$.

- $A \subseteq B = \forall x(x \in A \rightarrow x \in B)$;
- For every set S , we have: (1) $\emptyset \subseteq S$; and (2) $S \subseteq S$;
- When we wish to emphasize that set A is a subset of set B but that $A \neq B$, we write $A \subset B$ and say that A is a proper subset of B , i.e., $\forall x(x \in A \rightarrow x \in B) \wedge \exists(x \in B \wedge x \notin A)$;

Subsets

Definition

Set A is a subset of B iff every element of A is also an element of B , denoted as $A \subseteq B$.

- $A \subseteq B = \forall x(x \in A \rightarrow x \in B)$;
- For every set S , we have: (1) $\emptyset \subseteq S$; and (2) $S \subseteq S$;
- When we wish to emphasize that set A is a subset of set B but that $A \neq B$, we write $A \subset B$ and say that A is a proper subset of B , i.e., $\forall x(x \in A \rightarrow x \in B) \wedge \exists(x \in B \wedge x \notin A)$;
- Two useful rules: (1) $A = B \Leftrightarrow (A \subseteq B) \wedge (B \subseteq A)$;
(2) $(A \subseteq B) \wedge (B \subseteq C) \Rightarrow (A \subseteq C)$;

Subsets

Definition

Set A is a subset of B iff every element of A is also an element of B , denoted as $A \subseteq B$.

- $A \subseteq B = \forall x(x \in A \rightarrow x \in B)$;
- For every set S , we have: (1) $\emptyset \subseteq S$; and (2) $S \subseteq S$;
- When we wish to emphasize that set A is a subset of set B but that $A \neq B$, we write $A \subset B$ and say that A is a proper subset of B , i.e., $\forall x(x \in A \rightarrow x \in B) \wedge \exists(x \in B \wedge x \notin A)$;
- Two useful rules: (1) $A = B \Leftrightarrow (A \subseteq B) \wedge (B \subseteq A)$;
(2) $(A \subseteq B) \wedge (B \subseteq C) \Rightarrow (A \subseteq C)$;

Subsets

Definition

Set A is a subset of B iff every element of A is also an element of B , denoted as $A \subseteq B$.

- $A \subseteq B = \forall x(x \in A \rightarrow x \in B)$;
- For every set S , we have: (1) $\emptyset \subseteq S$; and (2) $S \subseteq S$;
- When we wish to emphasize that set A is a subset of set B but that $A \neq B$, we write $A \subset B$ and say that A is a proper subset of B , i.e., $\forall x(x \in A \rightarrow x \in B) \wedge \exists(x \in B \wedge x \notin A)$;
- Two useful rules: (1) $A = B \Leftrightarrow (A \subseteq B) \wedge (B \subseteq A)$;
(2) $(A \subseteq B) \wedge (B \subseteq C) \Rightarrow (A \subseteq C)$;
- Given a set S , the power set of S is the set of all subsets of S , denoted as $\mathcal{P}(S)$. The size of $2^{|S|}$, where $|S|$ is the size of S .

Cartesian product

Definition

Let A and B be sets. The Cartesian product of A and B , denoted by $A \times B$, is set $A \times B = \{(a, b) : a \in A \wedge b \in B\}$, where (a, b) is an ordered 2-tuple, called ordered pairs.

Cartesian product

Definition

Let A and B be sets. The Cartesian product of A and B , denoted by $A \times B$, is set $A \times B = \{(a, b) : a \in A \wedge b \in B\}$, where (a, b) is a ordered 2-tuples, called ordered pairs.

- Let $A = \{1, 2\}$ and $B = \{a, b, c\}$, the Cartesian product

$$A \times B = \{(1, a), (1, b), (1, c), (2, a), (2, b), (2, c)\};$$

Cartesian product

Definition

Let A and B be sets. The Cartesian product of A and B , denoted by $A \times B$, is set $A \times B = \{(a, b) : a \in A \wedge b \in B\}$, where (a, b) is a ordered 2-tuples, called ordered pairs.

- Let $A = \{1, 2\}$ and $B = \{a, b, c\}$, the Cartesian product

$$A \times B = \{(1, a), (1, b), (1, c), (2, a), (2, b), (2, c)\};$$

- The Cartesian product of A_1, A_2, \dots, A_n is denoted as $A_1 \times A_2 \times \dots \times A_n$

$$A_1 \times A_2 \times \dots \times A_n = \{(a_1, a_2, \dots, a_n) : \forall i \ a_i \in A_i\};$$

Cartesian product

Definition

Let A and B be sets. The Cartesian product of A and B , denoted by $A \times B$, is set $A \times B = \{(a, b) : a \in A \wedge b \in B\}$, where (a, b) is a ordered 2-tuples, called ordered pairs.

- Let $A = \{1, 2\}$ and $B = \{a, b, c\}$, the Cartesian product

$$A \times B = \{(1, a), (1, b), (1, c), (2, a), (2, b), (2, c)\};$$

- The Cartesian product of A_1, A_2, \dots, A_n is denoted as $A_1 \times A_2 \times \dots \times A_n$

$$A_1 \times A_2 \times \dots \times A_n = \{(a_1, a_2, \dots, a_n) : \forall i \ a_i \in A_i\};$$

- A subset R of the Cartesian product $A \times B$ is called a relation from A to B .

Cartesian product Cont'd

Remarks

Let A and B be sets. The Cartesian product of A and B , denoted by $A \times B$, is set $A \times B = \{(a, b) : a \in A \wedge b \in B\}$, where (a, b) is an ordered 2-tuple, called ordered pairs.

Cartesian product Cont'd

Remarks

Let A and B be sets. The Cartesian product of A and B , denoted by $A \times B$, is set $A \times B = \{(a, b) : a \in A \wedge b \in B\}$, where (a, b) is a ordered 2-tuples, called ordered pairs.

- Let $A = \{1, 2\}$ and $B = \{a, b, c\}$, the Cartesian product

$$A \times B = \{(1, a), (1, b), (1, c), (2, a), (2, b), (2, c)\};$$

Cartesian product Cont'd

Remarks

Let A and B be sets. The Cartesian product of A and B , denoted by $A \times B$, is set $A \times B = \{(a, b) : a \in A \wedge b \in B\}$, where (a, b) is a ordered 2-tuples, called ordered pairs.

- Let $A = \{1, 2\}$ and $B = \{a, b, c\}$, the Cartesian product

$$A \times B = \{(1, a), (1, b), (1, c), (2, a), (2, b), (2, c)\};$$

- The Cartesian product of A_1, A_2, \dots, A_n is denoted as $A_1 \times A_2 \times \dots \times A_n$

$$A_1 \times A_2 \times \dots \times A_n = \{(a_1, a_2, \dots, a_n) : \forall i \ a_i \in A_i\};$$

Cartesian product Cont'd

Remarks

Let A and B be sets. The Cartesian product of A and B , denoted by $A \times B$, is set $A \times B = \{(a, b) : a \in A \wedge b \in B\}$, where (a, b) is a ordered 2-tuples, called ordered pairs.

- Let $A = \{1, 2\}$ and $B = \{a, b, c\}$, the Cartesian product

$$A \times B = \{(1, a), (1, b), (1, c), (2, a), (2, b), (2, c)\};$$

- The Cartesian product of A_1, A_2, \dots, A_n is denoted as $A_1 \times A_2 \times \dots \times A_n$

$$A_1 \times A_2 \times \dots \times A_n = \{(a_1, a_2, \dots, a_n) : \forall i \ a_i \in A_i\};$$

- A subset R of the Cartesian product $A \times B$ is called a relation from A to B .

Set operations

Operators

Let A and B be two sets, and U be the universal set

Set operations

Operators

Let A and B be two sets, and U be the universal set


- Union: $A \cup B = \{x : x \in A \vee x \in B\};$
- Intersection: $A \cap B = \{x : x \in A \wedge x \in B\};$
- Difference: $A - B = \{x : x \in A \wedge x \notin B\}$ (sometimes denoted as $A \setminus B$);
- Complement: $\bar{A} = U - A = \{x \in U : x \notin A\};$

Set operations

Operators

Let A and B be two sets, and U be the universal set

- Union: $A \cup B = \{x : x \in A \vee x \in B\};$
- Intersection: $A \cap B = \{x : x \in A \wedge x \in B\};$
- Difference: $A - B = \{x : x \in A \wedge x \notin B\}$ (sometimes denoted as $A \setminus B$);
- Complement: $\bar{A} = U - A = \{x \in U : x \notin A\};$




Set operations

Operators

Let A and B be two sets, and U be the universal set

- Union: $A \cup B = \{x : x \in A \vee x \in B\}$;
- Intersection: $A \cap B = \{x : x \in A \wedge x \in B\}$;
- Difference: $A - B = \{x : x \in A \wedge x \notin B\}$ (sometimes denoted as $A \setminus B$);
- Complement: $\bar{A} = U - A = \{x \in U : x \notin A\}$;



- $A - B = A \cap \bar{B}$;
- $|A \cup B| = |A| + |B| - |A \cap B|$.

Set identities

Table of logical equivalence

equivalence	name
$A \cap U = A$ $A \cup \emptyset = A$	Identity laws
$A \cap A = A$ $A \cup A = A$	Idempotent laws
$(A \cap B) \cap C = A \cap (B \cap C)$ $(A \cup B) \cup C = A \cup (B \cup C)$	Associative laws
$A \cup (A \cap B) = A$ $A \cap (A \cup B) = A$	Absorption laws
$A \cap \bar{A} = \emptyset$ $A \cup \bar{A} = U$	Complement laws

Logical equivalence Cont'd

Table of logical equivalence

equivalence	name
$A \cup U = U$ $A \cap \emptyset = \emptyset$	Domination laws
$A \cap B = B \cap A$ $A \cup B = B \cup A$	Commutative laws
$(A \cap B) \cup C = (A \cup C) \cap (B \cup C)$ $(A \cup B) \cap C = (A \cap C) \cup (B \cap C)$	Distributive laws
$\overline{(A \cap B)} = \overline{A} \cup \overline{B}$ $\overline{(A \cup B)} = \overline{A} \cap \overline{B}$	De Morgan's laws

Proof of De Morgan law

Proof

Use set builder notation and logical equivalences to establish the first De Morgan law

Steps	Reasons
$A \cap B$	prmise

Proof of De Morgan law

Proof

Use set builder notation and logical equivalences to establish the first De Morgan law

Steps

$$\overline{A \cap B} \\ = \{x : x \notin A \cap B\}$$

Reasons

premise

definition of complement

Proof of De Morgan law

Proof

Use set builder notation and logical equivalences to establish the first De Morgan law

Steps

$$\begin{aligned} & \overline{A \cap B} \\ &= \{x : x \notin A \cap B\} \\ &= \{x : \neg(x \in A \cap B)\} \end{aligned}$$

Reasons

premise
definition of complement
definition of does not belong symbol

Proof of De Morgan law

Proof

Use set builder notation and logical equivalences to establish the first De Morgan law

Steps

$$\begin{aligned} & \overline{A \cap B} \\ &= \{x : x \notin A \cap B\} \\ &= \{x : \neg(x \in A \cap B)\} \\ &= \{x : \neg(x \in A \wedge x \in B)\} \end{aligned}$$

Reasons

premise
definition of complement
definition of does not belong symbol
definition of intersection

Proof of De Morgan law

Proof

Use set builder notation and logical equivalences to establish the first De Morgan law

Steps	Reasons
$A \cap B$	premise
$= \{x : x \notin A \cap B\}$	definition of complement
$= \{x : \neg(x \in A \cap B)\}$	definition of does not belong symbol
$= \{x : \neg(x \in A \wedge x \in B)\}$	definition of intersection
$= \{x : \neg(x \in A) \vee \neg(x \in B)\}$	De Morgan law for logic

Proof of De Morgan law

Proof

Use set builder notation and logical equivalences to establish the first De Morgan law

Steps

Reasons

$A \cap B$	prmise
$= \{x : x \notin A \cap B\}$	definition of complement
$= \{x : \neg(x \in A \cap B)\}$	definition of does not belong symbol
$= \{x : \neg(x \in A \wedge x \in B)\}$	definition of intersection
$= \{x : \neg(x \in A) \vee \neg(x \in B)\}$	De Morgan law for logic
$= \{x : (x \notin A) \vee (x \notin B)\}$	definition of does not belong symbol

Proof of De Morgan law

Proof

Use set builder notation and logical equivalences to establish the first De Morgan law

Steps

Reasons

$\overline{A \cap B}$	prmise
$= \{x : x \notin A \cap B\}$	definition of complement
$= \{x : \neg(x \in A \cap B)\}$	definition of does not belong symbol
$= \{x : \neg(x \in A \wedge x \in B)\}$	definition of intersection
$= \{x : \neg(x \in A) \vee \neg(x \in B)\}$	De Morgan law for logic
$= \{x : (x \notin A) \vee (x \notin B)\}$	definition of does not belong symbol
$= \{x : (x \in \overline{A}) \vee (x \in \overline{B})\}$	definition of complement

Proof of De Morgan law

Proof

Use set builder notation and logical equivalences to establish the first De Morgan law

Steps

Reasons

$\overline{A \cap B}$	prmise
$= \{x : x \notin A \cap B\}$	definition of complement
$= \{x : \neg(x \in A \cap B)\}$	definition of does not belong symbol
$= \{x : \neg(x \in A \wedge x \in B)\}$	definition of intersection
$= \{x : \neg(x \in A) \vee \neg(x \in B)\}$	De Morgan law for logic
$= \{x : (x \notin A) \vee (x \notin B)\}$	definition of does not belong symbol
$= \{x : (x \in \overline{A}) \vee (x \in \overline{B})\}$	definition of complement
$= \{x : x \in (\overline{A} \cup \overline{B})\}$	definition of union

Proof of De Morgan law

Proof

Use set builder notation and logical equivalences to establish the first De Morgan law

Steps

Reasons

$\overline{A \cap B}$	promise
$= \{x : x \notin A \cap B\}$	definition of complement
$= \{x : \neg(x \in A \cap B)\}$	definition of does not belong symbol
$= \{x : \neg(x \in A \wedge x \in B)\}$	definition of intersection
$= \{x : \neg(x \in A) \vee \neg(x \in B)\}$	De Morgan law for logic
$= \{x : (x \notin A) \vee (x \notin B)\}$	definition of does not belong symbol
$= \{x : (x \in \overline{A}) \vee (x \in \overline{B})\}$	definition of complement
$= \{x : x \in (\overline{A} \cup \overline{B})\}$	definition of union
$= \overline{A} \cup \overline{B}$	meaning of set builder notation

Generalized unions and intersections

Union

- $A_1 \cup A_2 \cup \cdots \cup A_n = \bigcup_{i=1}^n A_i;$
- $A_1 \cup A_2 \cup \cdots \cup A_n \cup \cdots = \bigcup_{i=1}^{\infty} A_i;$

Generalized unions and intersections

Union

- $A_1 \cup A_2 \cup \cdots \cup A_n = \bigcup_{i=1}^n A_i;$
- $A_1 \cup A_2 \cup \cdots \cup A_n \cup \cdots = \bigcup_{i=1}^{\infty} A_i;$

Intersection

- $A_1 \cap A_2 \cap \cdots \cap A_n = \bigcap_{i=1}^n A_i;$
- $A_1 \cap A_2 \cap \cdots \cap A_n \cap \cdots = \bigcap_{i=1}^{\infty} A_i;$

Set covering problem

Input

Universal set $U = \{u_1, u_2, \dots, u_n\}$

Subsets $S_1, S_2, \dots, S_m \subseteq U$

Cost c_1, c_2, \dots, c_m

Set covering problem

Input

Universal set $U = \{u_1, u_2, \dots, u_n\}$

Subsets $S_1, S_2, \dots, S_m \subseteq U$

Cost c_1, c_2, \dots, c_m

Goal

Find a set $I \subseteq \{1, 2, \dots, m\}$ that minimizes $\sum_{i \in I} c_i$,
such that $\bigcup_{i \in I} S_i = U$

Set covering problem

Input

Universal set $U = \{u_1, u_2, \dots, u_n\}$

Subsets $S_1, S_2, \dots, S_m \subseteq U$

Cost c_1, c_2, \dots, c_m

Goal

Find a set $I \subseteq \{1, 2, \dots, m\}$ that minimizes $\sum_{i \in I} c_i$,
such that $\bigcup_{i \in I} S_i = U$

Applications

- Document summarization
- Natural language generation
- Information cascade

Take-aways

- Set Concepts;
- Set Operations;
- Applications.