Computation with Absolutely No Space Overhead

Lane A. Hemaspaandra*
Department of Computer Science
University of Rochester
Rochester, NY 14627, USA
lane@cs.rochester.edu

Proshanto Mukherji
Department of Computer Science
University of Rochester
Rochester, NY 14627, USA
mukherji@cs.rochester.edu

Till Tantau[†]
International Computer Science Institute
1947 Center Street
Berkeley, CA, USA
tantau@icsi.berkeley.edu

September 23, 2003

Abstract

We study Turing machines that are allowed absolutely no space overhead. The only work space the machines have, beyond the fixed amount of memory implicit in their finite-state control, is that which they can create by cannibalizing the input bits' own space. This model more closely reflects the fixed-sized memory of real computers than does the standard complexity-theoretic model of linear space. Though some context-sensitive languages cannot be accepted by such machines, we show that all deterministic context-free languages can be accepted deterministically in polynomial time with absolutely no space overhead. Similarly, all context-free languages can be accepted nondeterministically without space overhead.

Keywords. Space overhead, space reuse, overhead-free computation, context-sensitive languages, context-free languages, linear space, in-place algorithms.

1 Introduction

Complexity theory studies which problems can be solved realistically using a computer. Since it depends on context what resources are deemed "realistic," different resource bounds on various models have been studied. For example, deterministic linear space is a possible formalization of the limited memory of computers. Unfortunately, the standard complexity-theoretic formalizations may be too "rough" in realistic contexts, as most have hidden constants tucked away inside their definitions. Polynomial-time algorithms with a time bound of n^{100} and linear-space algorithms that need one megabyte of extra memory per input bit will typically be unhelpful from a practical point of view.

. . .

^{*}Supported in part by grants NSF-CCR-9322513 and NSF-INT-9815095 / DAAD-315-PPP-gü-ab.

[†]Supported in part by an Erwin-Stephan-Prize grant of the Technical University of Berlin and a postdoc research fellowship grant of the German Academic Exchange Service (DAAD). Work done in part while working at the Technical University of Berlin and while visiting the University of Rochester.




Figure 1: The outline.



Figure 2: A jump back.