

# Outline

---

## Outline

## Contents

<b>I</b>	<b>Main Talk</b>	<b>1</b>
<b>1</b>	<b>Models</b>	<b>2</b>
1.1	Standard Model . . . . .	2
1.2	Our Model . . . . .	4
<b>2</b>	<b>Power of the Model</b>	<b>6</b>
2.1	Palindromes . . . . .	6
2.2	Linear Languages . . . . .	7
2.3	Forbidden Subword . . . . .	8
2.4	Complete Languages . . . . .	10
<b>3</b>	<b>Limitations of the Model</b>	<b>11</b>
3.1	Strict Inclusion . . . . .	11
<b>A</b>	<b>Appendix</b>	<b>13</b>
A.1	Complete Languages . . . . .	13
A.2	Improvements for Context-Free Languages . . . . .	13
A.3	Abbreviations . . . . .	13

---

## Part I


# Main Talk

## 1 The Model of Overhead-Free Computation

### 1.1 The Standard Model of Linear Space

---

The Standard Model of Linear Space



#### Characteristics

- Input fills *fixed-size tape*
  - Input may be *modified*
  - Tape alphabet *is larger than* input alphabet
-

---

# Linear Space is a Powerful Model

PSPACE-hard

PSPACE

NLinspace = CSL

DLinspace


CFL

---

## 1.2 Our Model of Absolutely No Space Overhead

---

### Our Model of “Absolutely No Space Overhead”



**Turing machine**

#### Characteristics

- Input fills *fixed-size tape*
- Input may be *modified*
- Tape alphabet *equals* input alphabet

#### *Intuition*

- Tape is used like a RAM module.

---

#### Definition of Overhead-Free Computations

##### **Definition**

A Turing machine is *overhead-free* if

- it has only a single tape,
  - writes only on input cells,
  - writes only symbols drawn from the input alphabet.
-

---

## Overhead-Free Computation Complexity Classes

### Definition

A language  $L \subseteq \Sigma^*$  is in

**DOF** if  $L$  is accepted by a deterministic overhead-free machine with input alphabet  $\Sigma$ ,

**DOF<sub>poly</sub>** if  $L$  is accepted by a deterministic overhead-free machine with input alphabet  $\Sigma$  in polynomial time.


**NOF** is the nondeterministic version of DOF,

**NOF<sub>poly</sub>** is the nondeterministic version of DOF<sub>poly</sub>.

---

---

## Simple Relationships among Overhead-Free Computation Classes




## 2 The Power of Overhead-Free Computation

### 2.1 Palindromes

---

Palindromes Can be Accepted in an Overhead-Free Way



#### Algorithm

*Phase 1:*

*Compare first and last bit*

*Place left end marker*

*Place right end marker*

*Phase 2:*

*Compare bits next to end markers*

*Find left end marker*

*Advance left end marker*


*Find right end marker*

*Advance right end marker*

---

---

## Relationships among Overhead-Free Computation Classes



## 2.2 Linear Languages

---

### A Review of Linear Grammars

#### Definition

A grammar is *linear* if it is context-free and there is only one nonterminal per right-hand side.

#### Example

$G_1: S \rightarrow 00S0 \mid 1$  and  $G_2: S \rightarrow 0S10 \mid 0$ .

#### Definition

A grammar is *deterministic* if “there is always only one rule that can be applied.”

#### Example

$G_1: S \rightarrow 00S0 \mid 1$  is deterministic.

$G_2: S \rightarrow 0S10 \mid 0$  is *not* deterministic.

---

### Deterministic Linear Languages Can Be Accepted in an Overhead-Free Way

#### Theorem

Every deterministic linear language is in  $\text{DOF}_{\text{poly}}$ .

---

---

## Metalinear Languages Can Be Accepted in an Overhead-Free Way

### Definition

A language is *metalinear* if it is the concatenation of linear languages.

### Example

TRIPLE-PALINDROME =  $\{uvw \mid u, v, \text{ and } w \text{ are palindromes}\}$ .

### Theorem


Every metalinear language is in  $\text{NOF}_{\text{poly}}$ .

---



---

## Relationships among Overhead-Free Computation Classes



## 2.3 Context-Free Languages with a Forbidden Subword

---

### Definition of Almost-Overhead-Free Computations

#### Definition

A Turing machine is *almost-overhead-free* if

- it has only a single tape,
  - writes only on input cells,
  - writes only symbols drawn from the input alphabet  
*plus one special symbol.*
-



---

## Context-Free Languages with a Forbidden Subword Can Be Accepted in an Overhead-Free Way

### Theorem

Let  $L$  be a context-free language with a forbidden word.  
Then  $L \in \text{NOF}_{\text{poly}}$ .

Skip proof


### Proof.

Every context-free language can be accepted by a nondeterministic almost-overhead-free machine in polynomial time.

---

---

## Relationships among Overhead-Free Computation Classes



## 2.4 Languages Complete for Polynomial Space

---

### Overhead-Free Languages can be PSPACE-Complete

#### Theorem

DOF contains languages that are complete for PSPACE.

pspacecomplete;2;Proof details


#### Proof.

- Let  $A \in \text{DLINSPACE}$  be PSPACE-complete.  
Such languages are known to exist.
- Let  $M$  be a linear space machine that accepts  $A \subseteq \{0, 1\}^*$  with tape alphabet  $\Gamma$ .
- Let  $h: \Gamma \rightarrow \{0, 1\}^*$  be an isometric, injective homomorphism.
- Then  $h(L)$  is in DOF and it is PSPACE-complete.

pspacecomplete;1;Return

---

### Relationships among Overhead-Free Computation Classes



## 3 Limitations of Overhead-Free Computation

### 3.1 Linear Space is Strictly More Powerful

---

**Some Context-Sensitive Languages  
Cannot be Accepted in an Overhead-Free Way**

**Theorem**  
 $\text{DOF} \subsetneq \text{DLINSPACE}$ .


**Theorem**  
 $\text{NOF} \subsetneq \text{NLINSPACE}$ .

The proofs are based on old diagonalisations due to Feldman, Owings, and Seiferas.

---

---

#### Relationships among Overhead-Free Computation Classes



---

**Candidates for Languages that  
Cannot be Accepted in an Overhead-Free Way**

**Conjecture**  
 $\text{DOUBLE-PALINDROMES} \notin \text{DOF}$ .

**Conjecture**  
 $\{ww \mid w \in \{0,1\}^*\} \notin \text{NOF}$ .

Proving the first conjecture would show  $\text{DOF} \subsetneq \text{NOF}$ .

---

## Summary

### Summary

---

#### Summary

- Overhead-free computation is a more faithful *model of fixed-size memory*.
  - Overhead-free computation is *less powerful* than linear space.
  - *Many* context-free languages can be accepted by overhead-free machines.
  - We conjecture that *all* context-free languages are in  $\text{NOF}_{\text{poly}}$ .
  - Our results can be seen as new results on the power of *linear bounded automata with fixed alphabet size*.
- 

## Further Reading

---

### For Further Reading

## References

- [1] A. Salomaa. *Formal Languages*. Academic Press, 1973.
  - [2] E. Dijkstra. Smoothsort, an alternative for sorting in situ. *Science of Computer Programming*, 1(3):223–233, 1982.
  - [3] E. Feldman and J. Owings, Jr. A class of universal linear bounded automata. *Information Sciences*, 6:187–190, 1973.
  - [4] P. Jančar, F. Mráz, M. Plátek, and J. Vogel. Restarting automata. *FCT Conference 1995*, LNCS 985, pages 282–292. 1995.
-

## A Appendix

---

### Appendix Outline

### Contents

---

#### A.1 Complete Languages

#### A.2 Improvements for Context-Free Languages

---

##### Improvements

##### Theorem

1.  $\text{DCFL} \subseteq \text{DOF}_{\text{poly}}$ .
  2.  $\text{CFL} \subseteq \text{NOF}_{\text{poly}}$ .
- 

#### A.3 Abbreviations

---

##### Explanation of Different Abbreviations

---