

# Computation with Absolutely No Space Overhead

Lane Hemaspaandra<sup>1</sup>   Proshanto Mukherji<sup>1</sup>   Till Tantau<sup>2</sup>

<sup>1</sup>Department of Computer Science  
University of Rochester

<sup>2</sup>Fakultät für Elektrotechnik und Informatik  
Technical University of Berlin

Developments in Language Theory Conference, 2003



# Outline

- 1 The Model of Overhead-Free Computation
  - The Standard Model of Linear Space
  - Our Model of Absolutely No Space Overhead
- 2 The Power of Overhead-Free Computation
  - Palindromes
  - Linear Languages
  - Context-Free Languages with a Forbidden Subword
  - Languages Complete for Polynomial Space
- 3 Limitations of Overhead-Free Computation
  - Linear Space is Strictly More Powerful



# Outline

- 1 The Model of Overhead-Free Computation
  - The Standard Model of Linear Space
  - Our Model of Absolutely No Space Overhead
- 2 The Power of Overhead-Free Computation
  - Palindromes
  - Linear Languages
  - Context-Free Languages with a Forbidden Subword
  - Languages Complete for Polynomial Space
- 3 Limitations of Overhead-Free Computation
  - Linear Space is Strictly More Powerful



# Outline

- 1 The Model of Overhead-Free Computation
  - The Standard Model of Linear Space
  - Our Model of Absolutely No Space Overhead
- 2 The Power of Overhead-Free Computation
  - Palindromes
  - Linear Languages
  - Context-Free Languages with a Forbidden Subword
  - Languages Complete for Polynomial Space
- 3 Limitations of Overhead-Free Computation
  - Linear Space is Strictly More Powerful



# Outline


- 1 The Model of Overhead-Free Computation
  - The Standard Model of Linear Space
  - Our Model of Absolutely No Space Overhead
- 2 The Power of Overhead-Free Computation
  - Palindromes
  - Linear Languages
  - Context-Free Languages with a Forbidden Subword
  - Languages Complete for Polynomial Space
- 3 Limitations of Overhead-Free Computation
  - Linear Space is Strictly More Powerful



# The Standard Model of Linear Space

tape

0	0	1	0	0	1	0	0
---	---	---	---	---	---	---	---



Turing machine


## Characteristics

- Input fills **fixed-size** tape
- Input may be **modified**
- Tape alphabet **is larger than** input alphabet

# The Standard Model of Linear Space

tape

\$	0	1	0	0	1	0	0
----	---	---	---	---	---	---	---



Turing machine


## Characteristics

- Input fills **fixed-size** tape
- Input may be **modified**
- Tape alphabet **is larger than** input alphabet

# The Standard Model of Linear Space

tape

\$	0	1	0	0	1	0	0
----	---	---	---	---	---	---	---



Turing machine

## Characteristics

- Input fills **fixed-size** tape
- Input may be **modified**
- Tape alphabet **is larger than** input alphabet



# The Standard Model of Linear Space

tape

\$	0	1	0	0	1	0	\$
----	---	---	---	---	---	---	----



Turing machine

## Characteristics

- Input fills **fixed-size** tape
- Input may be **modified**
- Tape alphabet **is larger than** input alphabet

# The Standard Model of Linear Space

tape

\$	0	1	0	0	1	0	\$
----	---	---	---	---	---	---	----



Turing machine

## Characteristics

- Input fills **fixed-size** tape
- Input may be **modified**
- Tape alphabet **is larger than** input alphabet

# The Standard Model of Linear Space

tape

\$	\$	1	0	0	1	0	\$
----	----	---	---	---	---	---	----



Turing machine

## Characteristics

- Input fills **fixed-size** tape
- Input may be **modified**
- Tape alphabet **is larger than** input alphabet

# The Standard Model of Linear Space

tape

\$	\$	1	0	0	1	0	\$
----	----	---	---	---	---	---	----



Turing machine

## Characteristics

- Input fills **fixed-size** tape
- Input may be **modified**
- Tape alphabet **is larger than** input alphabet

# The Standard Model of Linear Space

tape

\$	\$	1	0	0	1	\$	\$
----	----	---	---	---	---	----	----




Turing machine

## Characteristics

- Input fills **fixed-size** tape
- Input may be **modified**
- Tape alphabet **is larger than** input alphabet

# The Standard Model of Linear Space

tape





Turing machine

## Characteristics

- Input fills **fixed-size** tape
- Input may be **modified**
- Tape alphabet **is larger than** input alphabet

# The Standard Model of Linear Space

tape




Turing machine

## Characteristics

- Input fills **fixed-size** tape
- Input may be **modified**
- Tape alphabet **is larger than** input alphabet

# Linear Space is a Powerful Model





# Outline

- 1 The Model of Overhead-Free Computation
  - The Standard Model of Linear Space
  - Our Model of Absolutely No Space Overhead
- 2 The Power of Overhead-Free Computation
  - Palindromes
  - Linear Languages
  - Context-Free Languages with a Forbidden Subword
  - Languages Complete for Polynomial Space
- 3 Limitations of Overhead-Free Computation
  - Linear Space is Strictly More Powerful



# Our Model of “Absolutely No Space Overhead”

tape

0	0	1	0	0	1	0	0
---	---	---	---	---	---	---	---



Turing machine

## Characteristics

- Input fills **fixed-size** tape
- Input may be **modified**
- Tape alphabet **equals** input alphabet

# Our Model of “Absolutely No Space Overhead”

tape

1	0	1	0	0	1	0	0
---	---	---	---	---	---	---	---



Turing machine

## Characteristics

- Input fills **fixed-size** tape
- Input may be **modified**
- Tape alphabet **equals** input alphabet

# Our Model of “Absolutely No Space Overhead”

tape

1	0	1	0	0	1	0	0
---	---	---	---	---	---	---	---



Turing machine

## Characteristics

- Input fills **fixed-size** tape
- Input may be **modified**
- Tape alphabet **equals** input alphabet

# Our Model of “Absolutely No Space Overhead”

tape

1	0	1	0	0	1	0	1
---	---	---	---	---	---	---	---



Turing machine

## Characteristics

- Input fills **fixed-size** tape
- Input may be **modified**
- Tape alphabet **equals** input alphabet

# Our Model of “Absolutely No Space Overhead”

tape

1	0	1	0	0	1	0	1
---	---	---	---	---	---	---	---



Turing machine

## Characteristics

- Input fills **fixed-size** tape
- Input may be **modified**
- Tape alphabet **equals** input alphabet

# Our Model of “Absolutely No Space Overhead”

tape

1	1	1	0	0	1	0	1
---	---	---	---	---	---	---	---



Turing machine

## Characteristics

- Input fills **fixed-size** tape
- Input may be **modified**
- Tape alphabet **equals** input alphabet

# Our Model of “Absolutely No Space Overhead”



Turing machine

## Intuition

- Tape is used like a RAM module.



# Definition of Overhead-Free Computations

## Definition

A Turing machine is **overhead-free** if

- it has only a single tape,
- writes only on input cells,
- writes only symbols drawn from the input alphabet.

# Overhead-Free Computation Complexity Classes

## Definition

A language  $L \subseteq \Sigma^*$  is in

**DOF** if  $L$  is accepted by a deterministic overhead-free machine with input alphabet  $\Sigma$ ,

**DOF<sub>poly</sub>** if  $L$  is accepted by a deterministic overhead-free machine with input alphabet  $\Sigma$  in polynomial time.

**NOF** is the nondeterministic version of DOF,

**NOF<sub>poly</sub>** is the nondeterministic version of DOF<sub>poly</sub>.



# Overhead-Free Computation Complexity Classes

## Definition

A language  $L \subseteq \Sigma^*$  is in

**DOF** if  $L$  is accepted by a deterministic overhead-free machine with input alphabet  $\Sigma$ ,

**DOF<sub>poly</sub>** if  $L$  is accepted by a deterministic overhead-free machine with input alphabet  $\Sigma$  in polynomial time.

**NOF** is the nondeterministic version of DOF,

**NOF<sub>poly</sub>** is the nondeterministic version of DOF<sub>poly</sub>.



# Overhead-Free Computation Complexity Classes

## Definition

A language  $L \subseteq \Sigma^*$  is in

**DOF** if  $L$  is accepted by a deterministic overhead-free machine with input alphabet  $\Sigma$ ,

**DOF<sub>poly</sub>** if  $L$  is accepted by a deterministic overhead-free machine with input alphabet  $\Sigma$  in polynomial time.

**NOF** is the nondeterministic version of DOF,

**NOF<sub>poly</sub>** is the nondeterministic version of DOF<sub>poly</sub>.



# Overhead-Free Computation Complexity Classes

## Definition

A language  $L \subseteq \Sigma^*$  is in

**DOF** if  $L$  is accepted by a deterministic overhead-free machine with input alphabet  $\Sigma$ ,


**DOF<sub>poly</sub>** if  $L$  is accepted by a deterministic overhead-free machine with input alphabet  $\Sigma$  in polynomial time.

**NOF** is the nondeterministic version of DOF,

**NOF<sub>poly</sub>** is the nondeterministic version of DOF<sub>poly</sub>.



# Simple Relationships among Overhead-Free Computation Classes



# Outline

- 1 The Model of Overhead-Free Computation
  - The Standard Model of Linear Space
  - Our Model of Absolutely No Space Overhead
- 2 The Power of Overhead-Free Computation
  - Palindromes
  - Linear Languages
  - Context-Free Languages with a Forbidden Subword
  - Languages Complete for Polynomial Space
- 3 Limitations of Overhead-Free Computation
  - Linear Space is Strictly More Powerful



# Palindromes Can be Accepted in an Overhead-Free Way

tape

0	0	1	0	0	1	0	0
---	---	---	---	---	---	---	---



overhead-free machine

## Algorithm

Phase 1:

Compare first and last bit

Place left end marker

Place right end marker

Phase 2:

Compare bits next to end markers

Find left end marker

Advance left end marker

Find right end marker

Advance right end marker





# Palindromes Can be Accepted in an Overhead-Free Way

tape

1	0	1	0	0	1	0	0
---	---	---	---	---	---	---	---



overhead-free machine

## Algorithm

Phase 1:

Compare first and last bit

Place left end marker

Place right end marker

Phase 2:

Compare bits next to end markers

Find left end marker

Advance left end marker

Find right end marker

Advance right end marker

# Palindromes Can be Accepted in an Overhead-Free Way

tape

1	0	1	0	0	1	0	0
---	---	---	---	---	---	---	---



overhead-free machine

## Algorithm

Phase 1:

Compare first and last bit

Place left end marker

Place right end marker

Phase 2:

Compare bits next to end markers

Find left end marker

Advance left end marker

Find right end marker

Advance right end marker

# Palindromes Can be Accepted in an Overhead-Free Way

tape

1	0	1	0	0	1	0	1
---	---	---	---	---	---	---	---



overhead-free machine

## Algorithm

Phase 1:

Compare first and last bit

Place left end marker

Place right end marker

Phase 2:

Compare bits next to end markers

Find left end marker

Advance left end marker

Find right end marker

Advance right end marker

# Palindromes Can be Accepted in an Overhead-Free Way

tape

1	0	1	0	0	1	0	1
---	---	---	---	---	---	---	---



overhead-free machine

## Algorithm

Phase 1:

Compare first and last bit

Place left end marker

Place right end marker

Phase 2:

Compare bits next to end markers

Find left end marker

Advance left end marker

Find right end marker

Advance right end marker



# Palindromes Can be Accepted in an Overhead-Free Way

tape

0	1	1	0	0	1	0	1
---	---	---	---	---	---	---	---



overhead-free machine

## Algorithm

Phase 1:

Compare first and last bit

Place left end marker

Place right end marker

Phase 2:

Compare bits next to end markers

Find left end marker

Advance left end marker

Find right end marker

Advance right end marker

# Palindromes Can be Accepted in an Overhead-Free Way

tape

0	1	1	0	0	1	0	1
---	---	---	---	---	---	---	---



overhead-free machine

## Algorithm

Phase 1:

Compare first and last bit

Place left end marker

Place right end marker

Phase 2:

Compare bits next to end markers

Find left end marker

Advance left end marker

Find right end marker

Advance right end marker

# Palindromes Can be Accepted in an Overhead-Free Way

tape

0	1	1	0	0	1	1	0
---	---	---	---	---	---	---	---



overhead-free machine

## Algorithm

Phase 1:

Compare first and last bit

Place left end marker

Place right end marker

Phase 2:

Compare bits next to end markers

Find left end marker

Advance left end marker

Find right end marker

Advance right end marker

# Palindromes Can be Accepted in an Overhead-Free Way

tape

0	1	1	0	0	1	1	0
---	---	---	---	---	---	---	---



overhead-free machine

## Algorithm

Phase 1:

Compare first and last bit

Place left end marker

Place right end marker

Phase 2:

Compare bits next to end markers

Find left end marker

Advance left end marker

Find right end marker

Advance right end marker





# Palindromes Can be Accepted in an Overhead-Free Way

tape

0	0	1	0	0	1	1	0
---	---	---	---	---	---	---	---



overhead-free machine

## Algorithm

Phase 1:

Compare first and last bit

Place left end marker

Place right end marker

Phase 2:

Compare bits next to end markers

Find left end marker

Advance left end marker

Find right end marker

Advance right end marker



# Palindromes Can be Accepted in an Overhead-Free Way

tape

0	0	1	0	0	1	1	0
---	---	---	---	---	---	---	---



overhead-free machine

## Algorithm

Phase 1:

Compare first and last bit

Place left end marker

Place right end marker

Phase 2:

Compare bits next to end markers

Find left end marker

Advance left end marker

Find right end marker

Advance right end marker

# Palindromes Can be Accepted in an Overhead-Free Way

tape

0	0	1	0	0	1	0	0
---	---	---	---	---	---	---	---



overhead-free machine

## Algorithm

Phase 1:

Compare first and last bit

Place left end marker

Place right end marker

Phase 2:

Compare bits next to end markers

Find left end marker

Advance left end marker

Find right end marker

Advance right end marker



# Palindromes Can be Accepted in an Overhead-Free Way

tape

0	0	1	0	0	1	0	0
---	---	---	---	---	---	---	---



overhead-free machine

## Algorithm

Phase 1:

Compare first and last bit

Place left end marker

Place right end marker

Phase 2:

Compare bits next to end markers

Find left end marker

Advance left end marker

Find right end marker

Advance right end marker

# Palindromes Can be Accepted in an Overhead-Free Way

tape

0	0	0	1	0	1	0	0
---	---	---	---	---	---	---	---



overhead-free machine

## Algorithm

Phase 1:

Compare first and last bit

Place left end marker

Place right end marker

Phase 2:

Compare bits next to end markers

Find left end marker

Advance left end marker

Find right end marker

Advance right end marker

# Palindromes Can be Accepted in an Overhead-Free Way

tape

0	0	0	1	0	1	0	0
---	---	---	---	---	---	---	---



overhead-free machine

## Algorithm

Phase 1:

Compare first and last bit

Place left end marker

Place right end marker

Phase 2:

Compare bits next to end markers

Find left end marker


Advance left end marker

Find right end marker

Advance right end marker

# Palindromes Can be Accepted in an Overhead-Free Way

tape



overhead-free machine

## Algorithm

Phase 1:

Compare first and last bit

Place left end marker

Place right end marker

Phase 2:

Compare bits next to end markers

Find left end marker


Advance left end marker

Find right end marker

Advance right end marker



# Relationships among Overhead-Free Computation Classes





# Outline

- 1 The Model of Overhead-Free Computation
  - The Standard Model of Linear Space
  - Our Model of Absolutely No Space Overhead
- 2 The Power of Overhead-Free Computation
  - Palindromes
  - Linear Languages
  - Context-Free Languages with a Forbidden Subword
  - Languages Complete for Polynomial Space
- 3 Limitations of Overhead-Free Computation
  - Linear Space is Strictly More Powerful



# A Review of Linear Grammars

## Definition

A grammar is **linear** if it is context-free and there is only one nonterminal per right-hand side.

## Example

$G_1: S \rightarrow 00S0 \mid 1$  and  $G_2: S \rightarrow 0S10 \mid 0$ .

## Definition

A grammar is **deterministic** if  
“there is always only one rule that can be applied.”

## Example

$G_1: S \rightarrow 00S0 \mid 1$  is deterministic.  
 $G_2: S \rightarrow 0S10 \mid 0$  is **not** deterministic.

# A Review of Linear Grammars

## Definition

A grammar is **linear** if it is context-free and there is only one nonterminal per right-hand side.

## Example

$G_1: S \rightarrow 00S0 \mid 1$  and  $G_2: S \rightarrow 0S10 \mid 0$ .

## Definition

A grammar is **deterministic** if “there is always only one rule that can be applied.”

## Example

$G_1: S \rightarrow 00S0 \mid 1$  is deterministic.  
 $G_2: S \rightarrow 0S10 \mid 0$  is **not** deterministic.



# Deterministic Linear Languages Can Be Accepted in an Overhead-Free Way

## Theorem

Every deterministic linear language is in  $\text{DOF}_{\text{poly}}$ .



# Metalinear Languages

## Can Be Accepted in an Overhead-Free Way

### Definition

A language is **metalinear** if it is the concatenation of linear languages.

### Example

$\text{TRIPLE-PALINDROME} = \{uvw \mid u, v, \text{ and } w \text{ are palindromes}\}.$

### Theorem

Every metalinear language is in  $\text{NOF}_{\text{poly}}$ .

# Metalinear Languages Can Be Accepted in an Overhead-Free Way

## Definition

A language is **metalinear** if it is the concatenation of linear languages.

## Example

TRIPLE-PALINDROME =  $\{uvw \mid u, v, \text{ and } w \text{ are palindromes}\}$ .

## Theorem

Every metalinear language is in  $\text{NOF}_{\text{poly}}$ .



# Metalinear Languages

## Can Be Accepted in an Overhead-Free Way

### Definition

A language is **metalinear** if it is the concatenation of linear languages.


### Example

TRIPLE-PALINDROME =  $\{uvw \mid u, v, \text{ and } w \text{ are palindromes}\}$ .

### Theorem

Every metalinear language is in  $\text{NOF}_{\text{poly}}$ .

# Relationships among Overhead-Free Computation Classes





# Outline

- 1 The Model of Overhead-Free Computation
  - The Standard Model of Linear Space
  - Our Model of Absolutely No Space Overhead
- 2 The Power of Overhead-Free Computation
  - Palindromes
  - Linear Languages
  - Context-Free Languages with a Forbidden Subword
  - Languages Complete for Polynomial Space
- 3 Limitations of Overhead-Free Computation
  - Linear Space is Strictly More Powerful



# Definition of Almost-Overhead-Free Computations

## Definition

A Turing machine is **almost-overhead-free** if

- it has only a single tape,
- writes only on input cells,
- writes only symbols drawn from the input alphabet  
plus one special symbol.

# Definition of Almost-Overhead-Free Computations

## Definition

A Turing machine is **almost-overhead-free** if

- it has only a single tape,
- writes only on input cells,
- writes only symbols drawn from the input alphabet  
plus one special symbol.

# Definition of Almost-Overhead-Free Computations

## Definition

A Turing machine is **almost-overhead-free** if

- it has only a single tape,
- writes only on input cells,
- writes only symbols drawn from the input alphabet **plus one special symbol**.

# Context-Free Languages with a Forbidden Subword Can Be Accepted in an Overhead-Free Way

## Theorem

Let  $L$  be a context-free language with a forbidden word.  
Then  $L \in \text{NOF}_{\text{poly}}$ .

► Skip proof



# Context-Free Languages with a Forbidden Subword Can Be Accepted in an Overhead-Free Way


## Theorem

Let  $L$  be a context-free language with a forbidden word.  
Then  $L \in \text{NOF}_{\text{poly}}$ .

## Proof.

Every context-free language can be accepted by a nondeterministic almost-overhead-free machine in polynomial time.

# Relationships among Overhead-Free Computation Classes



# Outline

- 1 The Model of Overhead-Free Computation
  - The Standard Model of Linear Space
  - Our Model of Absolutely No Space Overhead
- 2 The Power of Overhead-Free Computation
  - Palindromes
  - Linear Languages
  - Context-Free Languages with a Forbidden Subword
  - Languages Complete for Polynomial Space
- 3 Limitations of Overhead-Free Computation
  - Linear Space is Strictly More Powerful






# Some PSPACE-complete Languages Can Be Accepted in an Overhead-Free Way

## Theorem

DOF contains languages that are complete for PSPACE.

▶ Proof details

# Relationships among Overhead-Free Computation Classes



# Outline

- 1 The Model of Overhead-Free Computation
  - The Standard Model of Linear Space
  - Our Model of Absolutely No Space Overhead
- 2 The Power of Overhead-Free Computation
  - Palindromes
  - Linear Languages
  - Context-Free Languages with a Forbidden Subword
  - Languages Complete for Polynomial Space
- 3 Limitations of Overhead-Free Computation
  - Linear Space is Strictly More Powerful



# Some Context-Sensitive Languages Cannot be Accepted in an Overhead-Free Way

## Theorem

$\text{DOF} \subsetneq \text{DLINSPACE}$ .


## Theorem

$\text{NOF} \subsetneq \text{NLINSPACE}$ .

The proofs are based on old diagonalisations due to Feldman, Owings, and Seiferas.



# Relationships among Overhead-Free Computation Classes



# Candidates for Languages that Cannot be Accepted in an Overhead-Free Way

## Conjecture

DOUBLE-PALINDROMES  $\notin$  DOF.

## Conjecture

$\{ww \mid w \in \{0,1\}^*\} \notin$  NOF.

Proving the first conjecture would show  $\text{DOF} \subsetneq \text{NOF}$ .



# Candidates for Languages that Cannot be Accepted in an Overhead-Free Way

## Theorem

$\text{DOUBLE-PALINDROMES} \in \text{DOF}$ .

## Conjecture

$\{ww \mid w \in \{0,1\}^*\} \notin \text{NOF}$ .

Proving the first conjecture would show  $\text{DOF} \subsetneq \text{NOF}$ .



# Summary

- Overhead-free computation is a more faithful **model of fixed-size memory**.
- Overhead-free computation is **less powerful** than linear space.
- **Many** context-free languages can be accepted by overhead-free machines.
- We conjecture that **all** context-free languages are in  $\text{NOF}_{\text{poly}}$ .
- Our results can be seen as new results on the power of **linear bounded automata with fixed alphabet** size.





# For Further Reading



A. Salomaa.

*Formal Languages.*

Academic Press, 1973.



E. Dijkstra.

Smoothsort, an alternative for sorting in situ.

*Science of Computer Programming*, 1(3):223–233, 1982.



E. Feldman and J. Owings, Jr.

A class of universal linear bounded automata.

*Information Sciences*, 6:187–190, 1973.



P. Jančar, F. Mráz, M. Plátek, and J. Vogel.

Restarting automata.

*FCT Conference 1995*, LNCS 985, pages 282–292. 1995.

# For Further Reading



A. Salomaa.

*Formal Languages.*

Academic Press, 1973.



E. Dijkstra.

Smoothsort, an alternative for sorting in situ.

*Science of Computer Programming*, 1(3):223–233, 1982.



E. Feldman and J. Owings, Jr.

A class of universal linear bounded automata.

*Information Sciences*, 6:187–190, 1973.



P. Jančar, F. Mráz, M. Plátek, and J. Vogel.

Restarting automata.

*FCT Conference 1995*, LNCS 985, pages 282–292. 1995.

# For Further Reading



A. Salomaa.

*Formal Languages.*

Academic Press, 1973.



E. Dijkstra.

Smoothsort, an alternative for sorting in situ.

*Science of Computer Programming*, 1(3):223–233, 1982.



E. Feldman and J. Owings, Jr.

A class of universal linear bounded automata.

*Information Sciences*, 6:187–190, 1973.



P. Jančar, F. Mráz, M. Plátek, and J. Vogel.

Restarting automata.

*FCT Conference 1995*, LNCS 985, pages 282–292. 1995.

## For Further Reading



A. Salomaa.

*Formal Languages.*

Academic Press, 1973.



E. Dijkstra.

Smoothsort, an alternative for sorting in situ.

*Science of Computer Programming*, 1(3):223–233, 1982.



E. Feldman and J. Owings, Jr.

A class of universal linear bounded automata.

*Information Sciences*, 6:187–190, 1973.



P. Jančar, F. Mráz, M. Plátek, and J. Vogel.

Restarting automata.

*FCT Conference 1995*, LNCS 985, pages 282–292. 1995.

# Appendix Outline

## 4 Appendix

- Overhead Freeness and Completeness
- Improvements for Context-Free Languages
- Abbreviations



# Overhead-Free Languages can be PSPACE-Complete

## Theorem

DOF contains languages that are complete for PSPACE.

## Proof.

- Let  $A \in \text{DLINSPACE}$  be PSPACE-complete.  
Such languages are known to exist.
- Let  $M$  be a linear space machine that accepts  $A \subseteq \{0, 1\}^*$  with tape alphabet  $\Gamma$ .
- Let  $h: \Gamma \rightarrow \{0, 1\}^*$  be an isometric, injective homomorphism.
- Then  $h(L)$  is in DOF and it is PSPACE-complete.

[Return](#)

# Improvements

## Theorem

1.  $\text{DCFL} \subseteq \text{DOF}_{\text{poly}}$ .
2.  $\text{CFL} \subseteq \text{NOF}_{\text{poly}}$ .

# Explanation of Different Abbreviations

DOF	Deterministic Overhead-Free.
NOF	Nondeterministic Overhead-Free.
$\text{DOF}_{\text{poly}}$	Deterministic Overhead-Free, polynomial time.
$\text{DOF}_{\text{poly}}$	Nondeterministic Overhead-Free, polynomial time.

Table: Explanation of what different abbreviations mean.

