

The Trade-off Was in the Labels: Causal Supervision for Turn-Aware Streaming ASR

Bojie Li
Pine AI


Noah Shi
University of Washington

Abstract

Every voice agent must decide, in real time, whether the user has finished talking. Deployed systems decide from acoustics alone, via a voice-activity detector plus a silence timeout; frontier commercial recognizers decide inside the ASR model, where the words are, but that *turn-aware* class is entirely closed. We present, to our knowledge, the first open training recipe and benchmark for turn-aware streaming ASR: a small LoRA adapter on Qwen3-ASR-0.6B, trained in hours on one GPU, that transcribes, detects end-of-turn from meaning and silence jointly, handles dictation, and grounds transcription in session context. On a deployment-matched streaming benchmark it reaches 0.97 boundary recall at 0.39 s median latency with 0.3 false fires per speech-minute, replicated on a fresh test set; no silence timeout reaches this operating point. The recipe rests on one principle: every label for a streaming decision must be computable from the input up to the decision point. Labels inherited from offline corpora violate this, because offline data encodes the future; such *clairvoyant* labels manufactured training oscillation and a phantom recall-versus-precision trade-off, exposed by one intervention: appending one second of silence to the evaluation clips raised a “broken” model’s end-of-turn recall from 0.10 to 1.00. The same leak recurred with context, where an always-matching biasing prefix became a shortcut the model copied (40% wrong-profile intrusion); counterfactual examples where context and audio disagree cut intrusion to 0.8% while keeping most of a +28.9 pp entity-recall benefit.

Code: github.com/19PINE-AI/turn-aware-asr • Website: 01.me/research/turn-aware-asr

Turn 1: the pause that means “wait”



Turn 2: the completion that means “go”



Figure 1. No timeout gets both turns right. At 0.7 s it interrupts the dictated number twice; at 1.0 s it still keeps the user waiting after “I’m still here.” Ours holds through the pauses and fires 0.39 s after the thought completes.




Figure 2. The causal model escapes the timeout curve. Median end-of-turn latency vs. false fires (log scale; 0* plotted at 0.05) on identical audio, detector, and scoring. A silence timeout can only slide along its curve; the causally supervised model sits strictly inside the whole family because it reads completeness, firing 0.39 s after a finished thought while holding through a 1.4 s mid-sentence pause.

1 Introduction

A voice agent that cannot tell when you have finished speaking fails in two symmetric ways: it interrupts you mid-thought, or it stares at you after you stop. The industry default delegates the decision to a voice-activity detector (VAD) plus a fixed silence timeout, and this cascade fails structurally. Humans exchange turns with median gaps around 200 ms [Stivers et al., 2009, Levinson and Torreira, 2015], deployed timeouts sit at 500–1000 ms [Skantze, 2021], and pauses *inside* turns routinely exceed pauses between turns, so no threshold is both fast and safe. The information that resolves the ambiguity (is this thought complete?) is in the words, and the words live inside the recognizer.

Frontier commercial systems have drawn that conclusion and moved end-of-turn into the ASR model itself: Deepgram’s Flux emits end-of-turn events from the recognizer’s forward pass [Deepgram, 2026], and OpenAI’s Realtime API waits longer after a trailing “ummm” than after a completed sentence [OpenAI, 2025]. We call this class **turn-aware streaming ASR**: one model that transcribes while deciding, from semantics and silence jointly, whether the turn is over. Every commercial member of the class is closed, and the open landscape offers only pieces: weights with no training account (Kyutai STT, Kyutai Labs, 2025; Parakeet-EOU, NVIDIA, 2026) and turn *detectors* that do not transcribe (Smart Turn, Pipecat team, 2025; LiveKit, LiveKit, 2025; TEN, TEN Team, 2025).

This paper presents, to our knowledge, the first open, complete training recipe for the class. The system is deliberately small: a LoRA adapter [Hu et al., 2022] on Qwen3-ASR-0.6B [Shi et al., 2026], trained in hours on one GPU from roughly twenty thousand synthesized

examples. One checkpoint transcribes incrementally, emits an in-transcript end-of-turn token, holds through dictated digit strings, and grounds transcription in a session context prefix. On a deployment-matched streaming benchmark, and again on a fresh test set drawn after development ended, it reaches an operating point that no silence timeout and none of the open turn-aware systems attain: sub-half-second median latency with higher boundary recall and fewer false fires (Figure 2). The same prefix substantially lifts entity recall on entity-dense audio without degrading transcription quality. The recipe and benchmark are released.

The recipe’s substance is not architectural: the entire turn capability comes from the labels, and the paper’s central finding is what those labels must satisfy. Supervision inherited from offline corpora defines end-of-turn using audio *after* the decision point, audio a streaming model can never see: offline clips are cut by forced alignment at exactly the boundaries a streaming model must detect, and offline transcripts record who spoke next. We call such labels *clairvoyant*.

Clairvoyant labels manufacture trade-offs that are not real. Our development record holds eight successive *supervision compositions*: the same architecture, adapter, and data volume, relabeled eight ways. Together they traced what looked like a fundamental recall-versus-precision frontier, oscillating between checkpoints that fired eagerly mid-utterance and checkpoints that barely fired at all. A one-variable intervention exposed the frontier as an artifact: appending one second of silence to the evaluation clips took a “broken” checkpoint’s fire recall from 0.10 to 1.00. One causal labeling rule (fire iff the words so far are semantically complete and at least 0.3s of silence has been observed) plus a minimal-pair construction makes training monotone, with nothing else changed, and yields a single checkpoint that dominates all eight predecessors.

The principle is not specific to time. Trained only on examples where the biasing prefix matched the audio, the model learned to *copy* the prefix rather than listen: a wrong-user profile wrote the wrong entity into the transcript 40% of the time. The leak has the same shape (a training target that depends on a signal the model cannot trust at decision time) and the same repair: counterfactual examples in which context and audio deliberately disagree and the target follows the audio, which drive intrusion below 1% while largely preserving the biasing benefit. Two instances of one failure class, cured by the same construction, ground a checklist for any streaming decision trained from offline logs.

Our contributions:

1. **The first open recipe and benchmark for turn-aware streaming ASR.** One labeling rule and two pair constructions yield a single small model that transcribes, emits in-transcript end-of-turn events, holds through dictation, and grounds transcription in context, beating every silence-timeout setting on a deployment-matched benchmark under which the historical model ranking *inverts*. The checkpoint is a research prototype—trained on ~20k synthesized examples, it demonstrates what the recipe produces rather than a production system; the reusable artifacts are the recipe, code, and benchmark.
2. **A failure class, with a diagnosis by intervention.** Clairvoyant labels (streaming supervision that depends on post-decision input) manufacture training oscillation and phantom capability trade-offs. A one-variable experiment falsifies the frontier that eight supervision compositions had appeared to trace; a synthetic study isolates the mechanism.

3. **Evidence that the principle generalizes.** The contextual analog of the temporal leak, context copying under matched-only training, is cured by the analogous counterfactual construction, folding dictation and context grounding into the same checkpoint. Both instances distill into a checklist for streaming supervision pipelines.

2 Problem formulation and system overview

Two turns bound the problem from opposite sides (Figure 1). In the first, the silences carry no evidence that the turn is over but the words do (six digits of a ten-digit pattern predict continuation), yet a 0.7 s timeout fires twice mid-number, a failure production teams report exactly [LiveKit, 2026]. In the second, the thought is complete the instant the last word ends and a human would respond within roughly 200 ms [Stivers et al., 2009], yet a 1.0 s timeout makes the user wait five times that long. The first case requires holding *through* long silence, the second firing at near-zero silence, and no single threshold can do both, because the gap between the cases is not measurable in seconds of quiet. On our conversational benchmark, the silence-gap distributions of within-turn pauses and between-turn boundaries overlap almost completely, and the pauses are the *longer* of the two (§6). The same overlap, and the dilemma it creates, has defined cascade endpointing since Raux and Eskenazi [2008] [Skantze, 2021]. The resolving signal is semantic completeness, which is exactly what a recognizer computes on the way to a transcript.

Transcription has its own version of the argument. A voice agent hears names, tickers, and account emails: tokens nearly unrecoverable from acoustics alone but obvious given who is calling about what. Every major commercial STT ships a context mechanism, yet none publishes controlled uplift numbers, and the open model we build on describes its context facility in one qualitative sentence [Shi et al., 2026]. A turn-aware model with a context slot can ground the whole session’s transcription in the profile the agent’s user memory already maintains [Li, 2026]; §5 measures exactly this.

The task. A single-channel audio stream arrives in 0.5 s chunks. At each chunk boundary the system must extend a running transcript and decide whether the turn has ended, an irreversible and latency-sensitive event we call a *fire*. A text context prefix may be supplied at session start.

The system under study. We start from Qwen3-ASR-0.6B [Shi et al., 2026], an open unified speech model (AuT audio encoder + dense Qwen3 decoder) with strong offline word-error rate (WER) but no endpointing: it never signals that the speaker is done. We claim two reserved vocabulary slots as marker tokens <EAGER_END_SPEECH> and <END_SPEECH>, and LoRA-fine-tune [Hu et al., 2022] the decoder to emit them inside the transcript at end-of-turn moments (rank 16 for the endpointing experiments, 32 for the unified model; adapter details in Appendix G). Training data is synthesized from LibriSpeech [Panayotov et al., 2015] and AMI meeting recordings [Carletta et al., 2005]; training takes hours on one GPU. At inference, three interpretable knobs sit outside the model (Figure 3): an RMS **energy gate** that never *starts* a segment on a silent chunk, a **confirm horizon** h that holds a fire candidate for h further silent chunks before signaling END, and a **max-segment force-flush** that caps how long a transcript segment can grow. Every reported configuration (“arm”) states its knob settings.




Figure 3. System shape. Audio chunks pass an energy gate; the merged LoRA model transcribes the current bounded segment with the <CTX> prefix in the system slot and may emit marker tokens; two policy knobs sit behind the model. Outputs are transcript segments plus END events.

Table 6 (Appendix C) places the system in the landscape of open and commercial turn-aware systems.

3 Causal supervision


3.1 Clairvoyant labels and the causality principle

A streaming model must decide from what it has already heard: at time t , only the audio up to t exists. Stated this way the constraint sounds too obvious to violate, yet supervision built from offline corpora violates it systematically, in two places. First, *where the clips end*. Offline ASR corpora are segmented by forced alignment, so every clip stops at the instant the words do, and an endpoint label built on such clips says: fire the moment speech ends. A live channel never presents that condition; when a real speaker stops, silence keeps arriving, and the model must decide during that silence. Second, *who speaks next*. The natural way to label a pause (hold if the same speaker resumes, fire if the turn passes to someone else) reads the answer off the rest of the recording. At the moment of decision, mid-pause, the two cases look identical (§6); Figure 4 shows two real pauses, 90 ms apart in length, whose labels differ only because of what happened afterwards. We give the failure class a name:

Definition: clairvoyant labels

A label for a streaming decision at time t is *clairvoyant* if its value depends on input after t . Clairvoyant labels do not merely add noise: because the dependence is systematic, they split the training data into pools that are each self-consistent yet demand opposite behavior on the same observable input. The symptoms are (a) training that oscillates between two modes instead of converging, and (b) apparent capability trade-offs across checkpoints: a Pareto frontier that is not real. **Principle: every training label and every evaluation target for a streaming decision must be computable from the input up to the decision point.**

Clairvoyance is target leakage transposed into time, but the class is wider than time: the same failure appears whenever the target correlates with any signal the model cannot *trust* at decision time. A context prefix that always matches the audio during training is such a signal,



decision point t : the two prefixes are indistinguishable — the class is a function of audio after t

Figure 4. Clairvoyant labels. Two real pauses, 90 ms apart in length, from held-out AMI stretches of the replay benchmark (texts and gaps verbatim); the label is decided by the future. At the decision point the prefixes are indistinguishable, so the class is a function of audio after t , exactly what a clairvoyant label encodes.

because at deployment the profile can simply be wrong (§3.3; Figure 10, Appendix A, shows the two instances side by side). In both cases the cure is a data construction, not a loss term: build pairs of examples in which the untrustworthy signal is uninformative by design, so the only policy consistent with the training data is the one that keys on observables. §6 presents the evidence that this, and nothing architectural, was the obstacle.

3.2 Supervising end-of-turn detection

The entire turn capability comes from the labels. One rule generates every training example: *emit <EAGER_END_SPEECH><END_SPEECH> iff the words so far are semantically complete AND at least 0.3 s of silence has been heard since the last speech*. Both conditions are checkable from the audio prefix alone: completeness by a transcript heuristic (an utterance that trails off in a filler or connective, cuts mid-word, or is too short to be an acknowledgment counts as incomplete; Appendix A), silence from the synthesized waveform itself. Figure 5 shows the rule firing in deployment-matched replay.

Eight example templates, the *schemas* of Table 1, instantiate the rule. Two constructions among them teach the model to separate meaning from silence. The **minimal pair** (schemas 1–2; Figure 11, Appendix A) presents the same complete utterance twice: with a silence tail, labeled fire, and without one, labeled hold. The only difference between the two examples is the silence, so completeness alone cannot trigger a fire; the model has to *see* the silence (the direct fix for row 4 of Table 4, where silence had become optional). The **pause pair** (schemas 4–5) presents two utterances separated by a pause, and whether the pause carries a marker depends only on whether the words before it are complete: “...and then, (pause)” holds; “...that’s everything. (pause)” fires, even if the speaker later resumes.

The remaining schemas close deployment gaps. A quick resume after a legitimate fire simply becomes two transcript segments, a measured cost rather than an error (§4.1): at decision time the correct answer does not exist on the channel. Schemas 7–8 add the silence-heavy audio that utterance corpora never contain, and pair examples mix same- and different-speaker sources, so the decision cannot key on speaker identity, which a single-channel deployment never observes. A size-matched ablation confirms what each construction buys (Appendix D, Table 11).




Figure 5. Supervising end-of-turn detection. In deployment-matched replay, “did you prepare” is complete at 23.04 s, 0.3 s of silence is observed by 23.34 s, and the recorded fire lands at the next 0.5 s chunk boundary (latency +0.46 s). Waveform and fire timestamp verbatim from the recorded causal-model replay.

Table 1. The eight training schemas ($\sim 12\text{k}$ examples; LibriSpeech and AMI roughly 50/50). $M = \langle \text{EAGER_END_SPEECH} \rangle \langle \text{END_SPEECH} \rangle$.

#	Construction	Target
1	complete utterance + 0.3–1.2 s silence tail	text M
2	same utterances as #1, tail ≤ 0.1 s	text
3	speech truncated mid-utterance at 30–80%	partial text
4	complete A + gap 0.3–2.5 s + B (+ tail)	A M B M / A M B
5	incomplete A + gap + B + tail	A B M
6	complete utterance + long silence (2–4 s)	text M
7	pure silence 0.5–4 s	(empty)
8	leading silence 0.5–2 s + utterance + tail	text M

3.3 Supervising dictation and context biasing

The same discipline extends to the two transcription behaviors of §2. **Dictation:** a partial phone number followed by a pause is labeled *hold*, because the pattern predicts more digits; a complete number plus observed silence fires. Figure 6 shows the effect on identical probe audio: five mid-number interruptions become one fire, +0.42 s after the last digit. **Spelled entities and context:** synthesized utterances spell out uncommon names and email addresses, targeted in normalized written form, half of them with a user profile in the context slot. These schemas extend the pool to $\sim 15\text{k}$ examples for retraining the same LoRA.

Training only on matching profiles, however, rebuilds the §3.1 failure on the context axis. If the profile always agrees with the audio, the model can score perfectly without listening: it learns to copy whatever entity the prefix names, and at deployment a wrong profile writes the wrong entity into the transcript (Figure 7; §5 measures the damage).

The **counterfactual twin** removes the shortcut. A third of the spelled examples carry a *conflicting* profile: the context names one identity, the audio spells another, and the target follows the audio, the same construction as the minimal pair. A second counterfactual of the same shape covers natural-speech biasing (an entity list that disagrees with the audio; the target again follows the audio). The unified pool ($\sim 20\text{k}$ examples) folds in both counterfactuals plus a 20% plain-transcription replay fraction that anchors offline WER (Appendix G); the




Figure 6. Supervising dictation. Probe item 0, identical audio under two supervisions: the conversational-only model reads each digit group as a finished thought and fires five times inside the number; the dictation schemas hold through both pauses and fire once, +0.42 s after the last digit. Fires verbatim from the recorded probe results.

matched-only ctx supervision (11.3%→40% intrusion):

audio says marcus.szymanski@acmecorp.io
model wrote tomasz.wojciechowski@outlook.com

COPIED THE CTX

+ counterfactual twin (released model, 0.8% intrusion):

audio says ignatius.yankovic@pine.ai
model wrote ignatius.yankovic@pine.ai

FOLLOWED AUDIO

ctx in both rows: a different user's profile (name, email, phone); outputs verbatim from the recorded probe results (75-dictation-probe-v11, 119-probe-v18).

Figure 7. Supervising context biasing. Under a wrong-user profile, the matched-only model writes the profile's email instead of the audio's (copying); the counterfactually trained unified model follows the audio. Outputs from the recorded spelled-entity probes.

unified adapter is rank 32, which §5 shows is what the added breadth costs.

4 Evaluation protocol

4.1 Streaming replay benchmark

Endpointing is evaluated by *streaming replay*: recorded audio is streamed through the live system chunk by chunk, exactly as a deployment would deliver it. The causality principle applies to the benchmark itself. An evaluation whose clips end at forced-alignment cuts demands behavior on a condition deployment never produces, and §6 shows that such an evaluation actively misdirects development.

Material and ground truth. Continuous single-channel stretches from held-out AMI meetings: one target speaker's utterances at their true timeline offsets, silence between them, 30–60 s per stretch. This is the voice-assistant shape, where audio never ends at a speech boundary. Each utterance-end boundary is classified by what is observable *on this channel*: **turn-final** (same-speaker gap ≥ 2 s), where the system should fire; **continuation** (gap in $[0.3, 2)$ s, same speaker resumes), where firing is a measured segmentation cost rather than an error, because

Table 2. Main endpointing result (deployment-matched replay, energy gate on; the latency-vs-false-fire view is Figure 2). Rows 1–4: the 25-stretch development benchmark. Last row: the fresh twice-larger confirmation set drawn after all development ended. WER is the per-stretch *median* streaming WER; the corresponding means, dominated by long-monologue repetition loops when no force-flush bounds the segment, are in Appendix D, and the force-flush of Appendix H bounds that tail.

Policy	Recall $\uparrow$	P50 $\downarrow$	P95 $\downarrow$	False/min $\downarrow$	WER _{med} $\downarrow$
mixed-pools + gate + confirm $h=1$	0.927	0.68 s	1.27 s	3.2	0.31
opposed-pools + gate + confirm $h=1$	0.938	0.77 s	1.06 s	0.0	0.27
causal + gate (ours)	0.969	0.39 s	0.70 s	0.3	0.28
causal + gate + confirm $h=1$	0.969	0.89 s	1.20 s	0.0	0.28
causal + gate, fresh 50-stretch set	0.924	0.42 s	0.70 s	0.2	0.30

the correct answer depends on the future; and **internal** (pauses inside utterances, or <0.3 s after speech), where firing is a false fire. Metrics: boundary recall within $[-0.25, +1.5]$ s of the true end, false fires per speech-minute, latency percentiles, the resume-after-fire rate (how often a fire lands at a continuation boundary), streaming WER of the flushed transcripts, and per-chunk compute. The development set has 25 stretches; a twice-larger confirmation set was drawn after all development ended, and a 100-stretch held-out set is used for the unified model. An early version of the benchmark itself contained a clairvoyant rule, caught by our own checklist; all numbers use the corrected classification (Appendix B).

Why comparisons run behind the energy gate. Models trained only on speech-initial examples hallucinate markers on silence at roughly two fires per second, so recall without the gate is uninterpretable: a model firing randomly at 1.9 Hz scores 0.96 against the tolerance window (Appendix B, Figure 12). All comparisons therefore run behind the energy gate; the causal recipe additionally bakes silence schemas into training.

4.2 Probes and offline evaluations

Each §2 scenario has a dedicated probe, and both run through the exact streaming stack of §4.1. The **dictation probe** replays ten-digit phone numbers (3-3-4 groups from held-out Free Spoken Digit Dataset speakers [Jackson et al., 2018], with inter-group pauses) and scores premature fires per number, final-boundary recall, and digit accuracy. The **spelled-entity probe** decodes synthesized utterances spelling uncommon names and email addresses, with and without a user-profile prefix, plus a wrong-user *distractor* profile, and scores exact match and wrong-profile intrusion. Both probes were enlarged after development ended; unified-model numbers use the enlarged versions. **Context biasing** on natural speech is measured on Earnings-22 [Del Rio et al., 2022], spontaneous earnings-call speech dense in tickers, executives, and products, with entities LLM-extracted and filtered to genuine proper nouns, as entity recall with and without a relevant hotword prefix. **Offline WER** is scored on the full official LibriSpeech splits, and **serving** is measured on stock vLLM rather than a simulator (Appendix H).

5 Results

5.1 End-of-turn detection

Table 2 reports the main result. The baselines are the two strongest earlier supervision compositions from the development record of §6, *mixed-pools* (row 3 of Table 4) and *opposed-pools* (row 6), each at its best knob setting. The causal model with the gate alone is better on every axis at once: its *raw* false-fire rate beats the mixed-pools model’s *confirmed* rate, at half the latency and higher recall. Against the deployed cascade the comparison is structural. A timeout must be long enough to survive within-turn pauses, so it can only trade latency against false fires along one curve; the causal model escapes the curve by reading completeness, combining exactly the pair of behaviors §2 argued no threshold can combine. Sweeping the full timeout family over two detectors and all settings on both stretch sets, no setting reaches its latency-and-false-fire corner at any recall (Appendix D). The model also no longer relies on inference-time suppression: the confirm horizon cancels only 3 fire candidates for the causal model versus 241 for the mixed-pools model, so the phrase-versus-turn discrimination moved from inference policy into the weights. The result survives fresh data (Table 2, last row): latency and false fires hold, and the small recall dip is within sampling variation (Appendix D). By design, a quick resume after a legitimate fire yields two transcript segments; deployments that prefer merged segments pay +0.5 s via the confirm horizon.

External turn-aware systems on the same protocol. We ran the open turn-aware systems of §8 through the identical benchmark as-shipped, sweeping their public thresholds rather than retraining (Figure 2). None reaches the causal model’s corner: the standalone detectors are gated on VAD silence by construction and slide along the timeout curve, LiveKit’s text detector reaches high recall only with an oracle transcript and many times our false-fire rate, and the open recognizers with turn signals either rarely fire (Parakeet-EOU) or fire spuriously (Kyutai). To our knowledge this is the first measurement of the open turn-aware class on a common protocol; it is as-shipped, not best-achievable, since none of these systems was tuned for AMI’s close-talking microphone audio.

5.2 Context biasing and dictation

Biasing works, and survives session length. On Earnings-22, a relevant hotword prefix lifts the base model’s entity recall from 66.7% to 95.6% while nudging WER slightly down: the prefix acts as a domain hint, not a distortion (Figure 8a). With up to 12 s of unrelated speech interposed between prefix and target words, the advantage stays flat (Figure 8b), which is the property a voice agent actually needs, since the user’s account entities must help at minute five, not just in the first utterance. The base model’s report describes this capability qualitatively without numbers [Shi et al., 2026]; to our knowledge these are the first on this model family [cf. Durmus et al., 2026].

Dictation, and the copying result. The conversational-only endpointing model of §5.1 fails both §4.2 probes exactly as §2 predicts: it reads a digit group as a finished thought, firing prematurely five times per dictated number, and spells emails at 4% exact match (Table 3). The dictation schemas of §3.3 fix the former immediately. The context schemas, trained with matched profiles only, produce the predicted copying: the model writes whatever entity the prefix names, so a wrong-user profile puts the wrong email into the transcript, and the intrusion rate grows from 11.3% to 40% as training lengthens. Adding the counterfactual twin drives




Figure 8. Context biasing, measured. (a) Earnings-22 base-model entity recall without context and with the relevant hotword prefix (+28.9 pp), and the distractor-prefix hallucination rate for the base model versus the unified rank-32 model, whose natural-speech counterfactual drives it from 3.7% to 2.0%. (b) Recall vs. seconds of unrelated speech between prefix and target: the advantage does not decay with session age.

Table 3. Dictation and spelled-entity probes. Premature fires per dictated 10-digit number, final-boundary recall, digit accuracy; exact-match on spelled names/emails without/with the profile; wrong-profile intrusion. Conversational-only and unified rows are scored on enlarged probes; the intermediate row uses the smaller original probes. Confidence intervals and a scoring-window sensitivity analysis are in Appendix D. The conversational-only model’s nonzero intrusion is the base model’s native context-following, which that fine-tune leaves untouched.

	Premat./seq ↓	Final rec. ↑	Digit acc ↑	Name −/+	Email −/+	Intrus. ↓
conversational only	4.96	0.82	0.889	0.25 / 0.82	0.04 / 0.58	1.7%
timeout X=0.5 s	2.00	1.00	—	—	—	—
timeout X=1.0 s	0.74	1.00	—	—	—	—
+ dictation (match-ctx)	0.36	0.78	0.996	1.00 / 1.00	0.03 / 0.93	11.3%
unified (r32)	0.16	0.88	0.998	0.98 / 1.00	0.11 / 0.93	0.8%

intrusion to zero at every checkpoint on the training probe, and to 0.8% (95% CI [0.2, 3.0]%) on the enlarged post-development probe, while leaving dictation and matching-context accuracy intact (Table 3). Context becomes a prior, not a substitute for listening.

5.3 The unified model and its costs

The release is the label-spec builder and training code, the probes, and the replay benchmark. The unified checkpoint, a rank-32 adapter trained on one pool of $\sim 20k$ examples, detects end-of-turn in conversation, holds through dictation better than every timeout setting, grounds spelled entities in context, and ignores a wrong profile (Table 3, last row), with no deployment-time checkpoint swap; on the 100-stretch held-out replay set it scores 0.982 boundary recall at 1.30 false fires per speech-minute, still strictly inside the timeout family of Figure 2. Its endpointing numbers across stretch sets, the confirm-horizon dial, a scoring-window sensitivity analysis,

and three-seed retraining stability are collected in Appendix D. We stress that this checkpoint is a research prototype: trained on $\sim 20k$ synthesized examples, it is meant to demonstrate the recipe, not to serve production traffic, and the enduring contribution is the recipe and findings rather than the weights themselves.

Which trade-offs are real. Folding four behaviors into one adapter costs endpointing precision: 0.97 false fires per speech-minute on the development set versus 0.3 for the pure-endpointing checkpoint. This is a genuine capacity trade-off, which we report and do not tune away; a deployment that only needs turn-taking can run the pure checkpoint. It is also the one trade-off that survives the diagnosis. The recall-versus-precision frontier dissolved when the labels became causal (§6); the breadth-versus-precision cost at fixed adapter capacity did not, but it recedes as capacity grows, which is why the unified model uses rank 32: at that rank the added replay and biasing schemas leave endpointing recall essentially intact, as they did not at rank 16. The context axis carries the same lesson. The spelled-entity counterfactual alone still leaves natural-speech distractors hallucinated 6.3% of the time; folding the natural-speech counterfactual into the unified pool cuts this to 2.0%, below the base model’s 3.7%, while preserving nearly all of the biasing uplift.

Costs. The endpoint fine-tune costs +1.1/+2.7 pp offline WER on LibriSpeech clean/other. Banning the marker tokens at decode time shows the markers themselves are not the cause; the regression comes from fine-tuning on a narrow synthetic distribution, and the plain-transcription replay fraction in the unified model recovers most of it (Appendix G, Table 12). Streaming WER, the deployment-relevant number, is unaffected. Serving runs on stock vLLM [Kwon et al., 2023] within real-time budgets through 16 concurrent sessions on a fractional-GPU slice. The serving primitive is simple: re-feed the last bounded window of audio each chunk, with a force-flush bounding the WER and compute tails (details and caveats in Appendix H). An in-engine efficiency variant, windowed KV with the <CTX> prefix pinned as an attention sink [Xiao et al., 2024], is validated in a companion systems paper [Meng and Li, 2026].

6 Analysis

The claim that the labels are the load-bearing element of §3 rests on a controlled record: eight supervision compositions sharing architecture, adapter, data volume, and source corpora, differing only in the labels. This section presents the record, the intervention that diagnosed it, the mechanism behind the oscillation, and a synthetic study that isolates the mechanism outside speech.

6.1 Supervision-composition study

Table 4 compresses the record. The first composition was supervised on offline clips alone (fire at every clip end); it scored perfectly offline and was unusable live, firing 89 times per speech-minute mid-utterance. Successive compositions added pools intended to fix this, and every addition moved the model *along* an apparent recall-versus-precision frontier, never off it. Two behaviors recurred across the family. Checkpoints were bimodal: eager ones fired mid-utterance, conservative ones missed turns, and no checkpoint did both jobs. And late compositions did not converge at all: holdout accuracy oscillated for the entire run between a

Table 4. The supervision-composition record. Eight compositions, one architecture, compressed into six rows: rows 1 and 2 each span two iterations (a data scale-up; a truncation-dose increase), and each later row adds one labeled pool to the mix above it, except row 6, which *replaces* row 5’s same-audio hold pool with disjoint audio. “Early” latencies are negative: the model fires seconds before the turn ends. Row 7 is the causal recipe of §3.2.

#	Supervision change (cumulative)	Observed behavior
1	offline endpoint pool only: fire at every clip end	fires eagerly and “accurately” offline (100% fire recall); in streaming replay, fires 89× per speech-minute mid-utterance
2	+ truncated-speech hold pool (11%→38% of mix)	diminishing returns: median fire timing improves only $-13.1 \rightarrow -9.6 \rightarrow -7.6$ s (still seconds early) as the dose rises
3	+ trailing-silence fire pool	streaming latency crosses zero (P50 +0.32 s) but offline fire recall regresses 100→82%; the “trade-off” is first declared
4	+ complete utterances with <i>and</i> without silence tails, both labeled fire	silence becomes optional again; a strictly intermediate point on the same frontier; frontier declared fundamental
5	+ hold pool on the <i>same</i> audio as existing fire examples	collapse: opposite labels on identical inputs; the model stops firing on meeting audio entirely (fire recall 0%)
6	row 5’s hold pool rebuilt on <i>disjoint but identically distributed</i> audio	oscillation between a fire mode and a no-fire mode for the whole run (Figure 9, left); no checkpoint dominates; two-checkpoint ship recommended
7	causal relabel (§3.2): fire iff complete <i>and</i> ≥ 0.3 s observed silence	monotone training, both classes at ceiling simultaneously; single checkpoint dominates every predecessor (§5)

fire mode and a *no-fire mode*, as in Figure 9 (left). By the eighth composition (row 6) the working conclusion, recorded in the project log at the time, was that the frontier was fundamental, with a recommendation to ship two checkpoints, one eager and one conservative.

6.2 Diagnosis by intervention

The experiment. One change to the *evaluation*, and none to any model, collapsed the frontier’s fire-recall axis: we appended 1.0 s of silence to each clip of the legacy offline benchmark and re-scored the historical checkpoints (Table 5). The “broken” opposed-pools model’s fire recall rose from 0.10 to 1.00 and the mixed-pools model’s from 0.82 to 0.98, while the offline-labeled composition, which never depended on hearing silence, was the unchanged control. Under deployment-realistic input, all three fire essentially perfectly on complete utterances. The capability axis that four compositions of data engineering had been fighting was an artifact of where the evaluation clips ended.

The diagnosis. Why did the clips end where they did? Offline ASR datasets are segmented by forced alignment, so clips are cut at the end of speech, and evaluation clips inherit the cut. An offline endpoint benchmark built on such clips therefore demands a fire on audio that ends *during or immediately after* speech, a condition deployment never presents. The streaming pools




Figure 9. The fingerprint of contradictory supervision. Left: under the opposed-pools composition, holdout accuracy oscillates for the entire run between a fire mode and a no-fire mode, reproducibly across two training seeds (solid, dashed); the oscillation is a property of the labels, not of a seed. Right: the causal recipe of §3.2, with the same architecture, adapter, and data volume and only the labels changed, climbs monotonically, with both classes at ceiling simultaneously from step 3k on.

Table 5. The silence-append intervention. Fire recall on complete single utterances from the legacy offline benchmark, before and after appending 1.0 s of silence to each clip.

Model (supervision composition)	original clips	+1.0 s silence	Δ
offline-labeled (rows 1–2)	1.00	1.00	0.00
mixed-pools (row 3)	0.82	0.98	+0.16
opposed-pools (row 6)	0.10	1.00	+0.90

taught the opposite, correctly: never fire before silence is observed. The condition “complete utterance, no trailing silence yet” thus carried the label *fire* in one pool and *hold* in the other; in the eighth composition this was 50/50 label noise on the exact decision the model exists to make. A second mechanism had the same structure: the historical pools separated “disfluent pause, hold” from “turn boundary, fire” using the transcript’s segmentation. Measured at the decision point, mid-pause, the two classes are statistically indistinguishable: their silence-gap distributions overlap almost completely, and the disfluent pauses are the longer ones. The label is a function of who spoke *next*, that is, of the future. Both mechanisms are exactly the clairvoyance of §3.1, and nothing about either is specific to speech; Figure 14 (Appendix E) illustrates both leaks.

Why oscillation, specifically. Rows 5 and 6 of Table 4 form a natural two-condition experiment, differing only in where the contradictory hold labels sit. When opposite labels sit on literally identical audio (row 5), the conflict is visible to the loss on every example, and the model settles deterministically on one side: it simply stops firing. When opposite labels sit on disjoint but identically distributed audio (row 6), no single example exposes the conflict; each pool is separately learnable, incompatible only in aggregate, and training cycles between two modes that each satisfy one pool. The oscillation is not instability to be scheduled away; it is

the loss surface reporting a contradiction that no individual example states. A probe of the model’s output probabilities (Appendix E, Figure 15) locates the cycling in the weights rather than at a decision threshold: the probability of committing to the marker swings between snapshots in lockstep with the accuracy, and no held-out example hovers near the decision boundary.

The evaluation was steering development. The legacy offline benchmark did not just mis-score the historical models; it steered four compositions of data engineering toward a frontier that does not exist, and the deployment-matched protocol of §4.1 *re-ranks* them (Appendix B, Figure 13): the offline champion is the worst live model, its offline strength being a premature-fire pathology, while the opposed-pools model, scored at 10% offline recall, is the best prior endpointer. Teams selecting turn-aware checkpoints on offline evaluations whose clips end at the speech boundary should expect the same inversion.

6.3 Synthetic isolation of the mechanism

The failure reproduces outside speech, with no acoustics and no pretraining (setup in Appendix F). A two-layer, $\sim 30k$ -parameter transformer is trained on a synthetic stream in which completeness is readable from the prefix, each gap’s outcome is not, and a tunable fraction f of the labels is clairvoyant by construction. At $f=0$ training is textbook monotone. As f grows, the fingerprint develops in order (Figure 16, Appendix F): fire- and hold-class accuracy become anti-correlated; checkpoints spread into an anti-diagonal cloud in the recall-precision plane, an apparent Pareto frontier that is in fact one model swinging, sampled at different steps; and outright mode-flipping begins only at high f . Why high f is required is itself informative: the causal label remains the per-prefix *majority* for every $f < 1$, so a stable single-mode optimum survives until the contradictory pool is large enough to destabilize it. The speech model of §6.1 lived in the high- f regime by construction, because near-balanced opposed pools are exactly what mixing offline supervision with streaming reality produces.

7 Discussion

A checklist. The failure mode generalizes to any model that must act mid-stream on offline-labeled data. Four questions for a streaming supervision pipeline:

Is your supervision clairvoyant?

1. **Prefix test.** For each label at decision time t : is it computable from input up to t ? (*Our pause labels were keyed on the next speaker.*)
2. **Twin test.** Can two causally identical prefixes receive different labels anywhere in the data? (*Same complete-utterance prefix: fire in one pool, hold in the other.*) Minimal pairs differing in an *observable* are the fix, not the bug.
3. **Phantom-condition test.** Does the eval demand behavior on conditions deployment never produces? (*Clips cut at end-of-speech; deployment always delivers the next silence.*)
4. **Oscillation test.** Does training bounce between modes that each satisfy part of the

data? That is the loss surface reporting a contradiction.

Limitations. Single-speaker, single-channel English; meetings with several speakers on mixed channels are future work. The dictation capability transfers zero-shot to shorter enumerations but not to longer-than-trained ones (on 16-digit card numbers the model fires at its learned ten-digit completeness point, transcription unaffected), so a learned completeness judge remains the general mechanism beyond pattern-specific schemas. The unified adapter’s breadth-versus-precision and recall-versus-hallucination costs are quantified in §5.3, and a turn-taking-only deployment can run the pure endpointing checkpoint; concurrency numbers are lower bounds measured on a shared GPU under contention (Appendix H). The checkpoint is trained on only ~20k synthesized examples on a single GPU: it is a research prototype that validates the recipe, and we make no claim about its production readiness—scaling the same recipe to production-grade data is left to future work.

8 Related work

Endpointing and end-of-turn detection. Classical endpointing thresholds a VAD [Silero Team, 2021] with a silence timeout [Raux and Eskenazi, 2008]; learned refinements predict end-of-query from acoustics [Shannon et al., 2017], jointly train an endpointer with the recognizer [Chang et al., 2019, Li et al., 2020, Bijwadia et al., 2023], or distill tiny acoustic end-of-turn models [Helwani et al., 2026, Pipecat team, 2025]. Recent systems fuse acoustic and linguistic cues [Wang et al., 2026, Yang et al., 2026] or fold VAD, turn detection, and ASR into one audio-LLM front-end [Li et al., 2026], architecturally closest to us but with no released weights or recipe. Deployed open detectors run beside the recognizer: Smart Turn (acoustic, open recipe, no transcript; Pipecat team, 2025) and the LiveKit and TEN end-of-utterance classifiers over a separate STT’s output [LiveKit, 2025, TEN Team, 2025, LiveKit, 2026]. Open-weights recognizers with in-model turn signals, Kyutai STT’s semantic-VAD head [Kyutai Labs, 2025] and NVIDIA’s Parakeet-EOU token [NVIDIA, 2026], publish weights but not the labeling procedure or data construction, and neither measures context biasing. Commercial systems (Deepgram Flux, Deepgram, 2026; OpenAI semantic VAD, OpenAI, 2025; AssemblyAI, AssemblyAI, 2025) publish no training details. Our contribution is the missing artifact, the recipe, plus evidence that trade-offs this literature reports as intrinsic can be manufactured by non-causal supervision.

Turn-taking in dialogue, and other streaming decisions. Turn-taking prediction has a long tradition [Skantze, 2021], from text-based end-of-turn prediction [Ekstedt and Skantze, 2020] to voice-activity projection trained on future windows [Ekstedt and Skantze, 2022], with human timing evidence from Stivers et al. [2009], Levinson and Torreira [2015]. Projection objectives predict distributions over the future and are causally honest; our diagnosis concerns future-dependent quantities presented as deterministic labels. The same shape appears in simultaneous translation trained with reference-aligned read/write decisions [Ma et al., 2019] and in tool-call timing for agents cloned from completed trajectories, a streaming sibling of causal confusion in imitation learning [de Haan et al., 2019]; metric choices can similarly manufacture “emergence” [Schaeffer et al., 2023].

Streaming and unified ASR. Streaming recognition spans RNN-T [Graves, 2012], large weakly supervised models [Radford et al., 2023], decoder-only streaming with latency losses [Wan et al., 2026], and unified streaming/offline speech-LLMs [Shi et al., 2026]; full-duplex speech-to-speech models [Défossez et al., 2024] dissolve the turn abstraction entirely. We inherit the unified-ASR substrate and add the in-transcript turn event plus the training recipe; vLLM’s paged KV [Kwon et al., 2023] carries our serving path, with attention sinks [Xiao et al., 2024] and bounded-state serving [Meng and Li, 2026] as the in-engine efficiency variant of the pinned context prefix.

Context biasing. Contextual ASR ranges from attention-based deep context [Pundak et al., 2018] to retrieval-scale biasing [Gong et al., 2025], RL-tuned hotwords [Kong et al., 2025], and cue-based prompting [Novitasari et al., 2026]; Durmus et al. [2026] concurrently standardizes entity-level evaluation on our corpus; we contribute plain prompt-slot measurements on the open class.

9 Conclusion

Turn-aware streaming ASR has so far existed only behind commercial APIs. This paper makes it reproducible: one causal labeling rule, two pair constructions, and a deployment-matched benchmark turn a small open model into a single checkpoint that transcribes, detects end-of-turn semantically, handles dictation, and grounds transcription in context, at an operating point no silence timeout reaches. The obstacle was supervision, not architecture: offline corpora encode the future, and the resulting clairvoyant labels manufacture oscillation and phantom trade-offs, diagnosed by intervention and cured, twice, by counterfactual construction. The failure class, and its checklist diagnostic, should transfer to any streaming decision trained from offline logs.

Acknowledgements

We thank Mingqi Yang from Minimax AI for early discussions. This paper was produced using Pine Copilot’s voice-directed *whisper coding* workflow [Pine AI, 2026], in which the authors specify, discuss, and review the work by voice while a coding agent (Claude Code with Claude Opus 4.8) carries out the planning, coding, experiments, and paper writing. We thank BSQL Networking for hosting the NVIDIA RTX PRO 6000 GPU.

References

- AssemblyAI. Universal-streaming: speech-to-text with intelligent endpointing. Product documentation, <https://www.assemblyai.com/docs>, 2025.
- Shaan Bijwadia, Shuo-Yiin Chang, Bo Li, Tara N. Sainath, Chao Zhang, and Yanzhang He. Unified end-to-end speech recognition and endpointing for fast and efficient speech systems. In *IEEE SLT*, 2023.
- Jean Carletta et al. The AMI meeting corpus: A pre-announcement. In *International Workshop on Machine Learning for Multimodal Interaction*, 2005.

- Shuo-Yiin Chang, Rohit Prabhavalkar, Yanzhang He, Tara N. Sainath, and Gabor Simko. Joint endpointing and decoding with end-to-end models. In *ICASSP*, 2019.
- Pim de Haan, Dinesh Jayaraman, and Sergey Levine. Causal confusion in imitation learning. In *NeurIPS*, 2019.
- Deepgram. Flux: Conversational speech recognition with model-integrated end-of-turn detection. Product documentation, <https://deepgram.com>, 2026.
- Alexandre Défossez, Laurent Mazaré, Manu Orsini, Amélie Royer, Patrick Pérez, Hervé Jégou, Edouard Grave, and Neil Zeghidour. Moshi: a speech-text foundation model for real-time dialogue. *arXiv preprint arXiv:2410.00037*, 2024.
- Miguel Del Rio, Peter Ha, Quinten McNamara, Corey Miller, and Shipra Chandra. Earnings-22: A practical benchmark for accents in the wild. *arXiv preprint arXiv:2203.15591*, 2022.
- Berkin Durmus, Chen Cen, Eduardo Pacheco, Arda Okan, and Atila Orhon. Contextual earnings-22: A speech recognition benchmark with custom vocabulary in the wild. *arXiv preprint arXiv:2604.07354*, 2026.
- Erik Ekstedt and Gabriel Skantze. TurnGPT: a transformer-based language model for predicting turn-taking in spoken dialog. In *Findings of EMNLP*, 2020.
- Erik Ekstedt and Gabriel Skantze. Voice activity projection: Self-supervised learning of turn-taking events. In *Interspeech*, 2022.
- Xun Gong, Anqi Lv, Zhiming Wang, Huijia Zhu, and Yanmin Qian. BR-ASR: Efficient and scalable bias retrieval framework for contextual biasing ASR in speech LLM. In *Interspeech*, 2025. *arXiv:2505.19179*.
- Alex Graves. Sequence transduction with recurrent neural networks. *arXiv preprint arXiv:1211.3711*, 2012.
- Karim Helwani, Hoang Do, James Luan, and Sriram Srinivasan. A hierarchical end-of-turn model with primary speaker segmentation for real-time conversational AI. *arXiv preprint arXiv:2603.13379*, 2026.
- Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. LoRA: Low-rank adaptation of large language models. In *ICLR*, 2022.
- Zohar Jackson, César Souza, Jason Flaks, Yuxin Pan, Hereman Nicolás, and Adhish Thite. Jakobovski/free-spoken-digit-dataset: v1.0.8, 2018. URL <https://doi.org/10.5281/zenodo.1342401>.
- Keller Jordan, Yuchen Jin, Vlado Boza, Jiacheng You, Franz Cesista, Laker Newhouse, and Jeremy Bernstein. Muon: An optimizer for hidden layers in neural networks. <https://kellerjordan.github.io/posts/muon/>, 2024.
- YuXiang Kong, JunFeng Hou, Jian Tang, Bingqing Zhu, Jicheng Zhang, and Shaofei Xue. Contextual biasing for LLM-based ASR with hotword retrieval and reinforcement learning. *arXiv preprint arXiv:2512.21828*, 2025.

- Woosuk Kwon, Zhuohan Li, Siyuan Zhuang, Ying Sheng, Lianmin Zheng, Cody Hao Yu, Joseph Gonzalez, Hao Zhang, and Ion Stoica. Efficient memory management for large language model serving with PagedAttention. In *SOSP*, 2023.
- Kyutai Labs. Kyutai STT: Streaming speech-to-text with delayed streams modeling. <https://github.com/kyutai-labs/delayed-streams-modeling>, 2025.
- Stephen C. Levinson and Francisco Torreira. Timing in turn-taking and its implications for processing models of language. *Frontiers in Psychology*, 6:731, 2015.
- Bo Li, Shuo-Yiin Chang, Tara N. Sainath, Ruoming Pang, Yanzhang He, Trevor Strohman, and Yonghui Wu. Towards fast and accurate streaming end-to-end asr. In *ICASSP*, 2020.
- Bojie Li. User as code: Executable memory for personalized agents, 2026. arXiv:2606.16707.
- Yadong Li, Guoxin Wu, Haiping Hou, and Biye Li. UAF: A unified audio front-end LLM for full-duplex speech interaction. *arXiv preprint arXiv:2604.19221*, 2026.
- LiveKit. Improving voice AI’s turn detection with transformers. <https://github.com/livekit/agents>, model livekit/turn-detector, 2025.
- LiveKit. Improved end-of-turn model cuts voice AI interruptions 39%. Blog post, <https://livekit.com/blog/improved-end-of-turn-model-cuts-voice-ai-interruptions-39>. Accessed 2026-07-05, 2026.
- Mingbo Ma, Liang Huang, Hao Xiong, Renjie Zheng, Kaibo Liu, Baigong Zheng, Chuanqiang Zhang, Zhongjun He, Hairong Liu, Xing Li, Hua Wu, and Haifeng Wang. STACL: Simultaneous translation with implicit anticipation and controllable latency using prefix-to-prefix framework. In *ACL*, 2019.
- Jiaying Meng and Bojie Li. Metronome: Bound the cache, keep the beat for real-time interaction model serving, 2026. arXiv:2607.02640.
- Sashi Novitasari, Takashi Fukuda, Kurata Gakuto, and George Saon. Contextual biasing for ASR in speech LLM with common word cues and bias word position prediction. *arXiv preprint arXiv:2604.12398*, 2026.
- NVIDIA. Parakeet-realtime-eou-120m: streaming ASR with end-of-utterance prediction. Model card, https://huggingface.co/nvidia/parakeet_realtime_eou_120m-v1. Accessed 2026-07-05, 2026.
- OpenAI. Semantic VAD in the realtime API. Product documentation, <https://platform.openai.com/docs>, 2025.
- Vassil Panayotov, Guoguo Chen, Daniel Povey, and Sanjeev Khudanpur. Librispeech: an ASR corpus based on public domain audio books. In *ICASSP*, 2015.
- Pine AI. Pine AI: The most natural human-computer interface is your voice. Blog post, 2026. URL <https://www.19pine.ai/blog/pine-ai-the-most-natural-human-computer-interface-is-your-voice>. Accessed 2026-06-28.

- Pipecat team. Smart turn: an open turn-detection model. <https://github.com/pipecat-ai/smart-turn>, 2025.
- Golan Pundak, Tara N. Sainath, Rohit Prabhavalkar, Anjuli Kannan, and Ding Zhao. Deep context: End-to-end contextual speech recognition. In *IEEE SLT*, 2018.
- Alec Radford, Jong Wook Kim, Tao Xu, Greg Brockman, Christine McLeavey, and Ilya Sutskever. Robust speech recognition via large-scale weak supervision. In *ICML*, 2023.
- Antoine Raux and Maxine Eskenazi. Optimizing endpointing thresholds using dialogue features in a spoken dialogue system. In *Proceedings of SIGdial*, 2008.
- Rylan Schaeffer, Brando Miranda, and Sanmi Koyejo. Are emergent abilities of large language models a mirage? In *NeurIPS*, 2023.
- Matt Shannon, Gabor Simko, Shuo-Yiin Chang, and Carolina Parada. Improved end-of-query detection for streaming speech recognition. In *Interspeech*, 2017.
- Xian Shi, Xiong Wang, Zhifang Guo, Yongqi Wang, Pei Zhang, Xinyu Zhang, Zishan Guo, Hongkun Hao, Yu Xi, Baosong Yang, Jin Xu, Jingren Zhou, and Junyang Lin. Qwen3-ASR technical report. *arXiv preprint arXiv:2601.21337*, 2026.
- Silero Team. Silero VAD: pre-trained enterprise-grade voice activity detector. <https://github.com/snakers4/silero-vad>, 2021.
- Gabriel Skantze. Turn-taking in conversational systems and human-robot interaction: A review. *Computer Speech & Language*, 67, 2021.
- Tanya Stivers, Nicholas J. Enfield, Penelope Brown, Christina Englert, Makoto Hayashi, Trine Heinemann, Gertie Hoymann, Federico Rossano, Jan Peter de Ruiter, Kyung-Eun Yoon, and Stephen C. Levinson. Universals and cultural variation in turn-taking in conversation. *Proceedings of the National Academy of Sciences*, 106(26):10587–10592, 2009.
- TEN Team. TEN turn detection: turn detection for full-duplex dialogue communication. <https://github.com/TEN-framework/ten-turn-detection>, 2025.
- Genshun Wan, Wenhui Zhang, Jing-Xuan Zhang, Shifu Xiong, Jianqing Gao, and Zhongfu Ye. Streaming speech recognition with decoder-only large language models and latency optimization. *arXiv preprint arXiv:2601.22779*, 2026.
- Chengyou Wang, Hongfei Xue, Chunjiang He, Jingbin Hu, Shuiyuan Wang, Bo Wu, Yuyu Ji, Jimeng Zheng, Ruofei Chen, Zhou Zhu, and Lei Xie. FastTurn: Unifying acoustic and streaming semantic cues for low-latency and robust turn detection. *arXiv preprint arXiv:2604.01897*, 2026.
- Guangxuan Xiao, Yuandong Tian, Beidi Chen, Song Han, and Mike Lewis. Efficient streaming language models with attention sinks. In *ICLR*, 2024.
- Guangzhao Yang, Yu Pan, Shi Qiu, and Ningjie Bai. JAL-Turn: Joint acoustic-linguistic modeling for real-time and robust turn-taking detection in full-duplex spoken dialogue systems. *arXiv preprint arXiv:2603.26515*, 2026.


A Label-specification details

The completeness classifier for pair examples (Table 1, #4–5) works as follows: utterance A is *incomplete* iff its transcript ends in a filler or connective (“and, but, so, or, uh, um, the, a, to, of, in, with, i mean, you know, ...”), ends mid-word (AMI partial-word annotation), or has fewer than 3 words outside a closed acknowledgment list. Borderline cases land in the resume-after-fire cost metric (§4.1); they never create fire/hold contradictions on identical observables. Abandonment (incomplete speech, speaker never resumes) is an inference-policy timeout, not a label. Pair examples use both same- and different-speaker AMI pairs: the fire decision keys on completeness + silence, never on speaker identity, which single-channel deployment cannot observe. Figure 11 illustrates the minimal-pair construction of §3.2, and Figure 10 places it beside its contextual analog, the counterfactual twin of §3.3.

Temporal axis: target must not depend on the future (fix: same utterance $\pm$ observable silence)



Contextual axis: target must not be copied from context (fix: same audio $\pm$ a disagreeing context)



naive data (context always matches) $\Rightarrow$ model copies context $\Rightarrow$ 40% wrong-profile intrusion; the counterfactual twin removes it

Figure 10. One failure class, two instances. Temporal axis: labels that peek at the future manufacture a phantom frontier; the fix is the minimal pair, the same utterance with and without an observable silence tail. Contextual axis: a context prefix that always matches the audio becomes a copyable shortcut; the fix is the counterfactual twin, the same audio with a matching and a disagreeing context, target following the audio.

B Benchmark specification and diagnostics

Full protocol: 0.5 s chunks; committed-prefix incremental decoding, matching the base model’s official streaming semantics (text once emitted stays fixed and is re-fed as the prompt, with the last 5 tokens rolled back so the model can revise them); fires timestamped at the chunk boundary where <END_SPEECH> first appears; recall window $[-0.25, +1.5]$ s, clipped at the next utterance’s onset. Set sizes: development 25 stretches (96 turn-final boundaries), post-development confirmation 50 stretches (184 boundaries), held-out 100 stretches (384 boundaries). The first version of the boundary classifier promoted a boundary to turn-final when another meeting speaker interleaved before the target speaker resumed. On a single-channel stream that speech is silence; demanding a fire there is exactly the clairvoyance the benchmark exists to

The minimal-pair device: the same utterance, $\pm$ an observable silence tail




Figure 11. The minimal-pair construction. Each complete utterance appears twice: without a silence tail (target: transcript only) and with a 0.3–1.2 s tail (target: transcript + marker). The only difference between the opposite-labeled examples is the observable the model must key on.

remove. The corrected classification moved the mixed-pools model’s recall $0.917 \rightarrow 0.906$ and the opposed-pools model’s $0.935 \rightarrow 0.938$; no conclusion changed, but the episode is a working example of the §7 checklist applied to one’s own evaluation.

Spurious markers on silence, quantified. Models trained only on speech-initial examples hallucinate on silence: spurious fires of the ungated mixed-pools model track each stretch’s silence content almost perfectly ($r=0.997$; Figure 12), at ~ 1.9 fires per second of silence. This is why §4.1 runs every comparison behind the energy gate.




Figure 12. Spurious markers on silence. Spurious fires of the ungated mixed-pools model track the silence content of each stretch almost perfectly; ungated recall is therefore uninterpretable, and all reported arms run behind the energy gate.

The ranking inversion. Figure 13 shows the historical model ranking on the legacy offline benchmark versus the deployment-matched replay benchmark (§6.2): the offline champion fires 89 times per speech-minute once audio keeps flowing, while the opposed-pools model, written off at 10% offline recall, is the best prior endpointer.

C The turn-aware system landscape




Figure 13. The ranking inversion. Model ranking on the legacy offline benchmark (left) versus the deployment-matched replay benchmark (right). The offline champion is the worst live model.

Table 6. The landscape (verified July 2026; discussion in §8). “Turn detectors” are separate models beside a recognizer; “cascade” is VAD + silence timeout + separate ASR, the deployed default and our measured baseline.

	This work	Flux / sem.vad	Kyutai STT	Parakeet-EOU	Turn det.	Cascade
Streaming ASR	✓	✓	✓	✓	–	✓
In-model end-of-turn	semantic	semantic	sem. head	token	sep. model	timeout
Open weights	–	–	✓	✓	mostly	✓
Turn-training recipe	✓	–	–	–	Smart Turn	n/a
Context biasing, measured	✓ (+28.9 pp)	–	–	–	–	ASR-dep.

D Additional results

Gated arms and the confirm-horizon sweep. Table 7. The confirm horizon behaves as a clean latency-vs-false-fire dial: $h=1$ strictly improves the mixed-pools model (recall *rises* because deferring the fire lets the segment gather the boundary inside tolerance) and zeroes the opposed-pools and causal models’ false fires; $h=2$ over-suppresses (mixed-pools recall 0.812, latency past budget). The causal model is the only checkpoint whose $h=0$ row is already deployable. Ungated arms are omitted as uninterpretable (Figure 12): with ~ 1.9 spurious fires per second on silence, the pre-diagnosis models score 0.95–0.99 “recall” by chance.

Table 7. All gated arms on the 25-stretch development benchmark. Resume = resume-after-fire rate over continuation boundaries (a cost metric, not an error rate). WER is a fraction, unbounded above through insertions.

Arm	Recall	P50	P95	False/min	Resume	WER _{mean}
offline-labeled + gate	0.896	0.05 s	0.25 s	88.8	0.89	0.85
mixed-pools + gate	0.906	0.16 s	0.89 s	27.3	0.96	0.36
mixed-pools + gate + confirm $h=1$	0.927	0.68 s	1.27 s	3.2	0.85	0.36
mixed-pools + gate + confirm $h=2$	0.812	1.15 s	1.42 s	1.1	0.56	0.36
opposed-pools + gate	0.938	0.26 s	0.56 s	3.6	0.93	4.96
opposed-pools + gate + confirm $h=1$	0.938	0.77 s	1.06 s	0.0	0.85	4.96
causal + gate	0.969	0.39 s	0.70 s	0.3	1.00	1.43
causal + gate + confirm $h=1$	0.969	0.89 s	1.20 s	0.0	0.93	1.43

The full timeout family. Table 8, both detectors on the development (25 stretches) and fresh confirmation (50 stretches) sets. The family’s shape is stable across sets: recall collapses between $X=1.0$ and 1.5 s (the fire lands outside the $+1.5$ s tolerance), and no setting reaches the causal model’s (recall, latency, false-fire) point; matching its recall costs a timeout $3\times$ the latency and $\sim 5\times$ the false fires. Silero [Silero Team, 2021] ran per-chunk with state resets, a slight handicap; RMS shares the LM arms’ exact detector and is the apples-to-apples policy comparison; on this close-talking microphone channel the Silero cascade is dominated by plain RMS.

Table 8. Silence-timeout cascade, all settings, on the development (dev) and fresh confirmation (conf) stretch sets.

Detector	Set	X (s)	Recall	P50	P95	False/min	Resume
RMS	dev	0.5	0.958	0.65 s	0.94 s	6.3	1.00
RMS	dev	1.0	0.969	1.15 s	1.44 s	1.4	0.81
RMS	dev	1.5	0.208	1.38 s	1.49 s	0.8	0.07
RMS	dev	2.0	0.031	0.55 s	0.55 s	0.2	0.00
RMS	conf	0.5	0.978	0.70 s	0.95 s	4.6	0.99
RMS	conf	1.0	0.989	1.20 s	1.45 s	0.6	0.73
RMS	conf	1.5	0.185	1.44 s	1.50 s	0.4	0.07
RMS	conf	2.0	0.016	1.14 s	1.14 s	0.2	0.00
Silero	dev	0.5	0.844	0.54 s	0.88 s	13.5	0.96
Silero	dev	1.0	0.854	1.04 s	1.38 s	5.5	0.85
Silero	dev	1.5	0.417	1.24 s	1.49 s	2.5	0.41
Silero	dev	2.0	0.125	1.32 s	1.42 s	1.0	0.00
Silero	conf	0.5	0.837	0.51 s	0.83 s	12.3	0.88
Silero	conf	1.0	0.864	1.00 s	1.33 s	4.4	0.73
Silero	conf	1.5	0.451	1.29 s	1.48 s	2.0	0.27
Silero	conf	2.0	0.130	1.34 s	1.44 s	1.3	0.07

Fresh-set confirmation. The causal model with the gate on the confirmation set: recall 0.924, P50 0.42 s, P95 0.70 s, 0.21 false fires per speech-minute, resume 0.91, WER median 0.30 / mean 4.63 (three long-monologue stretches enter the no-flush repetition loop; the force-flush of Appendix H is the documented fix). The 4.5 pp recall drop from the development set (93/96 vs. 170/184 turn-final boundaries) is consistent with sampling variation: the two-proportion 95% interval on the difference, $[-0.7, +9.7]$ pp, includes zero.

Probe confidence intervals. On the enlarged probes (250 dictation sequences; 240 spelled items over 120 identities), the unified model’s 95% intervals are: premature fires per sequence 0.16 [0.12, 0.22], final recall 0.88 [0.84, 0.92], email-with-context 0.93 [0.87, 0.97], intrusion 0.008 [0.002, 0.030]. On the 100-stretch replay set: boundary recall 0.982 [0.965, 0.995] at 1.30 [0.91, 1.71] false fires per speech-minute.

Dictation scoring-window sensitivity. The shipped scoring window counts any fire within $+0.25$ s of the last speech end as premature and denies it final-recall credit, which is strict for a low-latency endpointer. Re-scoring every fire by its offset δ from the true end of speech (genuine mid-sequence premature: $\delta < -0.30$ s; on-time: $-0.30 \leq \delta \leq +1.75$ s; late: $\delta >$

+1.75 s) gives, on the same 250 sequences: 0.07 genuine mid-sequence fires per number (18/250 sequences), 0.968 on-time final recall, zero late fires, and end-fire latency P50 0.44 s (fires are quantized up to the 0.5 s chunk grid). The residual under the shipped window is therefore eagerness within one chunk of the true end, not lateness; Table 3 reports the shipped window for comparability across rows.

Unified-model endpointing across sets. Table 9 collects the unified rank-32 checkpoint’s replay numbers, quoted piecewise in §5.3, next to the pure-endpointing causal checkpoint of §5.1. The breadth-versus-precision cost (0.97 versus 0.3 false fires per speech-minute) is a development-set comparison at matched latency; a one-chunk confirm horizon zeroes the unified model’s false fires at 0.958 recall (P50 0.89 s) for deployments that prefer conservatism over latency, and the added schemas leave endpointing recall essentially intact at rank 32 (0.95 versus 0.97 on the development set).

Table 9. The unified checkpoint (rank-32) on the replay benchmark, both stretch sets, alongside the pure-endpointing causal checkpoint of §5.1. dev = 25-stretch development set; held-out 100 = the 100-stretch set; fresh 50 = the post-development confirmation set.

Model	Set	Recall	P50	P95	False/min
unified r32 + gate	dev	0.948	0.39 s	0.65 s	0.97
unified r32 + gate + confirm $h=1$	dev	0.958	0.89 s	1.15 s	0.0
unified r32 + gate	held-out 100	0.982	0.38 s	0.64 s	1.30
pure endpoint (causal, r16) + gate	dev	0.969	0.39 s	0.70 s	0.3
pure endpoint (causal, r16) + gate	fresh 50	0.924	0.42 s	0.70 s	0.2

Seed robustness of the unified recipe. Table 10. Retraining the unified recipe (rank-32 adapter, unified $\sim 20k$ pool with 20% plain-ASR replay and natural-speech biasing, weight-decay and cosine fixes) under three seeds and selecting each best checkpoint on the probe axes gives stable premature-fire, context, and intrusion numbers; the unified capability is a property of the recipe, not a lucky checkpoint.

Table 10. Unified recipe under three training seeds (best checkpoint each, smaller common probe set; the unified checkpoint’s enlarged-probe figures, email 0.93 and intrusion 0.8%, are in Table 3). Seed 0 is the unified checkpoint.

Seed	Premature/seq ↓	Email +ctx ↑	Intrusion ↓
0 (unified)	0.16	0.88	0.000
1	0.16	0.98	0.000
2	0.16	0.85	0.000
mean $\pm$ sd	0.16 $\pm$ 0.00	0.90 $\pm$ 0.07	0.000 $\pm$ 0.000

Schema ablation. Table 11. We retrain the endpointing recipe with one construction removed at a time, keeping data volume fixed by redistributing the dropped quota across the remaining schemas; each arm is selected on the holdout composite (mean accuracy across the eight schema classes on held-out data) and scored on the 25-stretch replay set. Each construction

has a distinct predicted failure; two of three reproduce it. Removing the **minimal pair** (schema 2) makes silence optional again: gated false fires rise 1.08→5.28 per speech-minute and the confirm horizon cancels 34 candidates versus 10, so both the pathology and the reliance on the confirm horizon return. Removing the **silence schemas** (7–8) costs competence on silence: without the gate, the model emits 1458 markers on silence versus 8; the energy gate masks this in the gated numbers. Removing the **pause pair**’s incomplete half (schema 5) does not raise false fires; the model is mildly more conservative (recall 0.948→0.906, false fires 1.08→0.43), so pause discrimination is largely covered by schema 4’s complete-A gaps.

Table 11. Schema ablation on the endpointing pool (data volume held fixed; 25-stretch replay, best checkpoint each). Each arm is an independent retrain selected on the holdout composite, so the baseline here (0.948/1.08) is a different checkpoint from the causal model of Table 2 (0.969/0.3). “Silence-fires” is the ungated marker count on silence; “ $h=1$ cancels” counts the fire candidates the confirm horizon must cancel; a high count means the model still relies on it.

Arm	Recall $\uparrow$	False/min $\downarrow$	Silence-fires $\downarrow$	$h=1$ cancels	Predicted failure?
baseline (full pool)	0.948	1.08	8	10	–
–minimal pair (#2)	0.906	5.28	5	34	yes (silence optional)
–silence (#7–8)	0.969	1.94	1458	12	yes (silence spray)
–pause pair (#5)	0.906	0.43	8	4	no (redundant)

Offline WER regression. Table 12. The fine-tune costs +1.1/+2.7 pp on the full official LibriSpeech splits (single-shot decode on vLLM, jiwer/whisper normalization). “Fires” is the fraction of clips where the model emitted the endpoint marker; offline clips end at or near end-of-speech, and the base model never fires because its marker rows are untrained. Banning the markers at decode time zeroes the fires without moving WER, which rules out decode truncation as the cause; Appendix G attributes the regression to narrow-schema drift and quantifies the plain-ASR-replay mitigation. The unified model, which folds a 20% plain-ASR-replay fraction into a rank-32 adapter (§3.3), recovers most of the gap, scoring 3.5%/6.9%.


Table 12. Offline WER (LibriSpeech, full official splits).

Model	WER $\downarrow$		Fires	
	clean	other	clean	other
Qwen3-ASR-0.6B (base)	2.79%	5.14%	0%	0%
+ endpoint LoRA (merged, causal, endpoint-only)	3.93%	7.87%	4.7%	5.9%
+ markers banned at decode	3.94%	7.91%	0%	0%
unified (r32, +replay)	3.49%	6.90%	3.2%	4.7%

E Diagnosis details

The two leaks, illustrated. Figure 14 shows the two mechanisms of §6.2 side by side: the forced-alignment clip cut that puts opposite labels on the same prefix, and the next-speaker pause labels whose classes are indistinguishable at the decision point (gap medians 1.39 s for disfluent pauses vs. 0.83 s for turn boundaries).

(a) The trailing-silence clip cut: opposite labels on the same prefix



(b) Pause labels keyed on the future




Figure 14. Two ways offline-derived supervision leaks the future. (a) Offline clips inherit forced-alignment cuts at end of speech, so the offline pool demands a fire on exactly the prefix the streaming pool labels *hold*. (b) Disfluency-vs-boundary pause labels are keyed on who speaks next; at the decision point the two classes’ silence-gap distributions overlap almost completely.

The probability-level oscillation probe. Figure 15 is the measurement behind the mode-cycling claim of §6. The trained marker pathway is a rigid two-token sequence (`<EAGER_END_SPEECH>` then `<END_SPEECH>`), deterministic once entered, so we define P_{fire} as the probability that the model’s continuation enters the marker path rather than terminating. It is evaluated at the end-of-audio decision position with the transcript teacher-forced, marginalizing over the first continuation token at ≥ 0.98 probability coverage and greedy-rolling each branch.

Two observations follow. On the balanced holdout of the opposed-pools run (the exact examples behind Figure 9, left), mean P_{fire} tracks the recorded accuracy ($r=+0.98$ on the contested fire schema, $r=-0.95$ against hold-class accuracy) and swings with amplitude ~ 0.4 across snapshots. And the per-example distribution rules out a wobbling decision threshold: not one of the 40 held-out examples sits in the ambiguous $[0.2, 0.8]$ band across all eleven snapshots (only 13–15% sit there at any single snapshot), while 7 of 40 fully reverse between confident fire (>0.8) and confident hold (<0.2) as training proceeds. The trailing-silence schema, on which both pools agree, stays pinned at $P_{\text{fire}} \approx 1.0$ throughout: the cycling is confined to the schemas the pools contest.

F The synthetic clairvoyant-fraction experiment

Setup for the §6.3 experiment: a discrete stream of token phrases separated by silence runs, with no acoustics and no pretraining. A phrase ends complete or incomplete, always readable from the prefix, while each gap’s full length (speaker resumes vs. turn ends, 50/50) is knowable only after the decision point. At a fixed depth into every gap, a two-layer causal transformer ($\sim 30\text{k}$ parameters) must emit fire or hold. The *causal* rule fires iff the phrase was complete; the *clairvoyant* rule fires iff the gap turns out long, a genuine future dependence and the direct




Figure 15. Two modes in the weights, not a wobbling threshold. Mean marker-commit probability P_{fire} for fire-labeled (complete utterance) and hold-labeled (incomplete) holdout examples across the opposed-pools run; small dots are per-example values. The two classes swing in lockstep as the weights cycle between the fire mode and the no-fire mode; no example hovers persistently at the 0.5 decision boundary.

analog of clips cut at boundaries and transcripts recording who spoke next. Completeness and gap length are independent, so the two rules are maximally opposed while each remains self-consistent, reproducing the structure of §3.1: pools that individually make sense yet demand opposite behavior on the same input. A fraction f of training sequences is clairvoyantly labeled; the holdout is always causal; three seeds per f ; everything runs on CPU in minutes.

The dose-response in detail (Figure 16): at $f=0$, both classes reach 1.00, zero mode flips, worst post-warmup holdout accuracy 0.99. The fire/hold accuracy anti-correlation grows monotonically (-0.3 at $f=0.1$, -0.5 at $f=0.5$, -1.0 at $f=1.0$), while outright mode flipping appears only at high fraction: 8 flips per run at $f=0.85$ and 16 at $f=1.0$, zero at $f \leq 0.7$.

G Training-recipe notes

All models share one adapter configuration: LoRA on the attention q/k/v/o projections plus the two marker embedding rows, $\alpha=2r$, batch 8 ($r=16$ for the endpointing experiments, $r=32$ for the unified checkpoint, which is selected on the probe axes of dictation, context, and intrusion rather than the holdout composite alone). The unified model (§3.3) adds two AdamW hygiene fixes and one negative result. All three were isolated on identical data (the unified pool), so the comparisons below vary only the optimizer setting.

A weight-decay bug worth fixing, but not the WER culprit. We reserve two vocabulary rows as markers and train them by unfreezing the (tied) token-embedding and output-head matrix and masking gradients to those two rows. But AdamW’s *decoupled* weight decay applies $p \leftarrow p - \eta \lambda p$ to *every* row regardless of gradient, so at $\eta=2 \times 10^{-4}$, $\lambda=0.01$ the entire (tied) 151k-row matrix shrinks $\sim 2.4\%$ over 12k steps, silently degrading the base model’s vocabulary and output head. This is a general hazard for any recipe that adds a few trainable vocabulary rows to a frozen embedding, and we fix it with a $\lambda=0$ group. The negative half: in a controlled




Figure 16. The mechanism, isolated. A $\sim 30k$ -parameter transformer on a synthetic stream with a tunable clairvoyant-label fraction f . (a) Holdout trajectories: monotone convergence at $f=0$, visible noise at $f=0.7$, oscillation between two modes at $f=1.0$. (b) Every checkpoint’s (fire recall, hold precision), colored by f : the causal run collapses to one top-right point; high f spreads checkpoints into an anti-diagonal cloud, a phantom Pareto frontier traced by one oscillating model.

comparison on identical data, the fix (plus cosine schedule) did *not* lower offline WER; the fixed unified checkpoint scores 3.9%/7.3% (clean/other) versus 3.6%/7.0% without it, within checkpoint-selection noise and in the wrong direction. The offline-WER regression is therefore *not* caused by the weight-decay bug; it is narrow-schema drift from fine-tuning on $\sim 12k$ examples with no plain-ASR replay data. We keep the fix for its base-model-preservation rationale, not for a WER win we cannot demonstrate.

Plain-ASR replay: the fix that does move WER. The unified model mixes $\sim 4k$ plain transcription examples (audio $\rightarrow$ transcript, no marker, no context) into the $\sim 20k$ -example pool, a 20% fraction. They teach the model that a complete utterance with no context is simply to be transcribed, recovering offline WER from 3.9%/7.3% (recipe fixes, no replay) to 3.5%/6.9% and cutting spurious offline marker fires from ~ 10 –20% to 3.2%. The replay fraction trades against endpointing sharpness at fixed adapter capacity; raising the LoRA rank from 16 to 32 buys back that sharpness, which is why the unified checkpoint is rank-32 (§5.3).

Cosine decay. A cosine schedule from 2×10^{-4} to 10^{-5} after a 100-step warmup gives the most stable, highest holdout-composite trajectory (plateau 0.992 from step 6k) and a slightly less eager final checkpoint than the constant schedule.

Muon underperforms AdamW here. We tried Muon [Jordan et al., 2024] on the 2-D LoRA factors (Newton-Schulz-orthogonalized momentum, AdamW retained for the marker rows) at a $100\times$ larger base LR (2×10^{-2} , since the orthogonalized update is $\sim$ unit-norm). On identical data Muon’s raw loss descends *faster* early but its task metric plateaus at holdout composite 0.846 (by step 3–4.5k, conversational schema collapsing) versus AdamW’s 0.985. The cause is structural: rank-16 LoRA factors (1024×16) are too rectangular for the 5-step Newton-Schulz iteration to orthogonalize (empirically $\|O^T O - I\|$ off-diagonals ≈ 0.5), and orthogonalizing the two factors separately is not the same operation as orthogonalizing their product. We keep

AdamW.

H Serving details

Three findings from running the model on shared-GPU vLLM [Kwon et al., 2023] rather than a simulator (Figure 17), summarized in §5.3. First, the feeding shape matters. The natural flat-cost shape, appending each 0.5 s chunk as a new audio placeholder in a resident request, is out of distribution for a model trained on single segments and destroys it (88% WER); re-feeding the last bounded window of audio each chunk is the correct primitive (3.8%). Second, the vLLM path reproduces the endpoint behavior at 84 ms median per chunk, 5.4× faster than the transformers simulator used during development; latency claims made on $O(T^2)$ re-decode simulators overstate the cost of this approach by that factor.

Third, bounding every resident state matters: a 20 s force-flush fixes both the WER tail and the compute tail, and per-frame P95 stays flat through 8 concurrent sessions on a 0.15-GPU slice (a lower bound measured under contention; the shape, not the constant, is the result). Re-measured on the unified rank-32 checkpoint, architecturally identical to the endpoint model after merging, serving is unchanged: median per-chunk compute is 21 ms on an otherwise-idle GPU (the 84 ms above is under a co-tenant), and per-frame P95 stays flat through 16 concurrent sessions (77 ms at $N=16$, well inside the 500 ms budget).




Figure 17. Serving on real infrastructure. (a) Feeding shape: per-chunk placeholders are out-of-distribution; bounded re-feed is correct. (b) Per-chunk compute on vLLM vs. the transformers simulator; the force-flush bounds the P95 tail. (c) Concurrent sessions per engine on a 0.15-GPU slice: flat to $N=8$, cliff at 16.