

-- A. KPI's

-- 1. Total Revenue

```
SELECT SUM(total_price) AS total_revenue
FROM pizza_sales;
```

-- 2. Average Order Value

```
SELECT ROUND(SUM(total_price) / COUNT(DISTINCT order_id), 2) AS avg_order_value
FROM pizza_sales;
```

-- 3. Total Pizzas Sold

```
SELECT SUM(quantity) AS total_pizzas_sold
FROM pizza_sales;
```

-- 4. Total Orders

```
SELECT COUNT(DISTINCT order_id) AS total_orders
FROM pizza_sales;
```

-- 5. Average Pizzas Per Order

```
SELECT ROUND(SUM(quantity) / COUNT(DISTINCT order_id), 2) AS avg_pizzas_per_order
FROM pizza_sales;
```

-- B. Daily Trend for Total Orders

```
SELECT DAYNAME(order_date) AS order_day,
COUNT(DISTINCT order_id) AS total_orders
FROM pizza_sales
GROUP BY DAYNAME(order_date)
ORDER BY total_orders DESC;
```

-- C. Hourly Trend for Orders

```
SELECT HOUR(order_time) AS order_hour,
COUNT(DISTINCT order_id) AS total_orders
FROM pizza_sales
GROUP BY HOUR(order_time)
ORDER BY order_hour;
```

-- D. % of Sales by Pizza Category

```
SELECT pizza_category,  
ROUND(SUM(total_price), 2) AS total_revenue,  
ROUND(SUM(total_price) * 100 /  
(SELECT SUM(total_price) FROM pizza_sales), 2) AS pct_sales  
FROM pizza_sales  
GROUP BY pizza_category  
ORDER BY pct_sales DESC;
```

-- E. % of Sales by Pizza Size

```
SELECT pizza_size,  
ROUND(SUM(total_price), 2) AS total_revenue,  
ROUND(SUM(total_price) * 100 /  
(SELECT SUM(total_price) FROM pizza_sales), 2) AS pct_sales  
FROM pizza_sales  
GROUP BY pizza_size  
ORDER BY pct_sales DESC;
```

-- F. Total Pizzas Sold by Pizza Category

```
SELECT pizza_category,  
SUM(quantity) AS total_quantity_sold  
FROM pizza_sales  
WHERE MONTH(order_date) = 2  
GROUP BY pizza_category  
ORDER BY total_quantity_sold DESC;
```

-- G. Top 5 Best Sellers by Total Pizzas Sold

```
SELECT pizza_name,  
SUM(quantity) AS total_pizza_sold  
FROM pizza_sales  
GROUP BY pizza_name  
ORDER BY total_pizza_sold DESC  
LIMIT 5;
```

-- H. Bottom 5 Best Sellers by Total Pizzas Sold

```
SELECT pizza_name,  
SUM(quantity) AS total_pizza_sold  
FROM pizza_sales  
GROUP BY pizza_name  
ORDER BY total_pizza_sold ASC  
LIMIT 5;
```

-- Monthly Filter Example

```
SELECT DAYNAME(order_date) AS order_day,  
COUNT(DISTINCT order_id) AS total_orders  
FROM pizza_sales  
WHERE MONTH(order_date) = 1  
GROUP BY DAYNAME(order_date);
```

-- Quarterly Filter Example

```
SELECT DAYNAME(order_date) AS order_day,  
COUNT(DISTINCT order_id) AS total_orders  
FROM pizza_sales  
WHERE QUARTER(order_date) = 1  
GROUP BY DAYNAME(order_date);
```