LAB 12

Write a C program to simulate disk scheduling algorithms

a) FCFS

b) SCAN



Write a C program to simulate disk scheduling algorithms:
a) FCFS
b) SCAN
d) C-SCAN

```
#include <stdio.h>
#include <stdlib.h>
int disks;
void quicksort(int number[25], int first, int last)
{
    int i, j, pivot, temp
    if (first < last)
    {
        pivot = first;
        i = first;
        j = last;
        while (i<j)
        { while (number[i]<=number[pivot] && i<last)
            i++;
          while (number[j] > number[pivot])
            j--;
          if (i<j)
          {
            temp = number[i];
            number[i] = number[j];
            number[j] = temp;
          }
        }
        temp = number[pivot];
        number[pivot] = number[j]
        number[j] = temp;
        quicksort(number, first, j-1);
        quicksort(number, j+1, last);
    }
}
void fcfs(int arr[], int src, int n)
```

```
{ int sseq[20],i;
sseq[0] = abs(arr[0]-src);
for(i=1;i<n;i++)
sseq[i] = abs(arr[i]-arr[i-1]);
int sum=0;
for(i=0;i<n;i++)
sum += sseq[i];
printf("\nFCFS Total seek sequence : %d\n Seek
        sequence:\n", sum);
for(i=0;i<n;i++)
printf("%d", sseq[i]);
printf("\n");
}
void cscan(int arr[], int src, int n)
{
    int i,sum=0,j,sseq[20];
    quicksort(arr,0,n-1);
    int index;
    for(index=0;index<n;index++) {
        if(arr[index]==src) {
            break;
    }
    i=index+1;
    j=0;
    while(i<=n)
    {
        sseq[j]=abs(arr[i]-arr[i-1]);
        i++;
    } j++;
    sseq[j++]=abs(disks-arr[i-1]);
    i=0;
    sseq[j++]=abs(disks);
    while(i<index)
    {
```

```
        sseq [j++] = abs (arr[i] - arr[i-1]);
        i++;
    }
    for (i=0; i<(n+2); i++)
    sum += sseq [i];

printf ("\n C-SCAN \n Total seek sequence : %d \n
        seek sequence: \n", sum);
for (i=0; i<n+2; i++)
 printf ("%d", sseq [i]);
 printf ("\n");
}
void scan (int arr [], int src, int n)
{
    int i, sum=0, j, sseq [20];
    quicksort (arr, 0, n-1);
     int index;
    for (index=0; index<n; index++) {
        if (arr [index] == src) {
            break;
        }
    }
    i = index - 1;
    j = 0;
    while (i >= 0)
    {   sseq [j] = abs (arr [i] - arr [i+1]);
        i--;
        j++;
    }
    i = index + 1;
    sseq [j++] = abs (arr[i] - arr [0]);
    while (i<=n)
    {   sseq [j++] = abs (arr [i] - arr [i-1]);
        i++;
    }
```

```
for(i=0; i<n; i++)
    sum += sseq[i];
printf("\n SCAN \n Total seek sequence: %d \n Seek
    sequence: \n", sum);
for(i=0; i<n; i++)
printf("%d", sseq[i]);
printf("\n");
}

void main()
{
int source, arr[20], i, n, copy[20];
printf("Enter number of disks: ");
scanf("%d", &n);

printf("\n Enter %d values: ", n);
for(i=0; i<n; i++)
scanf("%d", &arr[i]);

printf("\n Enter source position: ");
scanf("%d", &source);

printf("\n Enter number of disks: ");
scanf("%d", &disks);

for(i=0; i<n; i++)
copy[i] = arr[i];
arr[n] = source;
copy[n] = arr[n];
fcfs(copy, source, n);
scan(copy, source, n);
cscan(arr, source, n);
}
```

Output:

Enter number of disks : 5

Enter 5 values: 10 25 30 45 12

Enter source position : 19

Enter number of disks : 50

FCFS

Total seek sequence : 77

seek sequence:

9 15 5 15 33

C-SCAN

Total seek sequence : 118

seek sequence

31 50 2 2 13 5 15

SCAN

Total seek sequence : 61

seek sequence :

26 15 5 13 2

OUTPUT:


"C:\Users\ysrmo\OneDrive - Base PU College\Desktop\4thsem\CN\CN_LAB\OS\bin\Debug\OS.exe"
Enter number of disks: 5
Enter 5 values: 10 25 30 45 12
Enter source position: 19
Enter number disks: 50
FCFS
Total seek sequenece: 77
Seek Sequence:
9 15 5 15 33
SCAN
Total seek sequenece: 81
Seek Sequence:
31 5 15 5 13 2 10
C-SCAN
Total seek sequenece: 116
Seek Sequence:
31 50 10 5 2 13 5