

WEEK 5

a) Write a C program to simulate the concept of Dining-Philosophers problem.

b) Write a C program to simulate producer-consumer problem using semaphores.

a) CODE:

```
#include <pthread.h>

#include <semaphore.h>

#include <stdio.h>

#define N 5

#define THINKING 2

#define HUNGRY 1

#define EATING 0

#define LEFT (phnum + 4) % N

#define RIGHT (phnum + 1) % N

int state[N];

int phil[N] = { 0, 1, 2, 3, 4 };

sem_t mutex;

sem_t S[N];

void test(int phnum)

{

    if (state[phnum] == HUNGRY

        && state[LEFT] != EATING
```

```
&& state[RIGHT] !=  
EATING) { state[phnum] =  
EATING;
```

```
sleep(2);
```

```
printf("Philosopher %d takes fork %d and %d\n", phnum  
+ 1, LEFT + 1, phnum + 1);
```

```
printf("Philosopher %d is Eating\n", phnum + 1);
```

```

        sem_post(&S[phnum]);
    }
}

void take_fork(int phnum)
{
    sem_wait(&mutex);
    state[phnum] = HUNGRY;
    printf("Philosopher %d is Hungry\n", phnum + 1);
    test(phnum);
    sem_post(&mutex);
    sem_wait(&S[phnum]);
    sleep(1);
}

void put_fork(int phnum)
{
    sem_wait(&mutex);
    state[phnum] = THINKING;
    printf("Philosopher %d putting fork %d and %d down\n",
           phnum + 1, LEFT + 1, phnum + 1);
    printf("Philosopher %d is thinking\n", phnum + 1);
    test(LEFT);
    test(RIGHT);
    sem_post(&mutex);
}

void* philosopher(void* num)

```

```

{
    while (1) {
        int* i = num;
        sleep(1);
        take_fork(*i);
        sleep(0);
        put_fork(*i);
    }
}

int main()
{
    int i;
    pthread_t thread_id[N];
    sem_init(&mutex, 0, 1);
    for (i = 0; i < N; i++)
        sem_init(&S[i], 0, 0);
    for (i = 0; i < N; i++) {
        //      create philosopher
        //      processes
        pthread_create(&thread_id[i],
            NULL,
                        philosopher, &phil[i]);

        printf("Philosopher %d is thinking\n", i + 1);
    }
    for (i = 0; i < N; i++)
        pthread_join(thread_id[i], NULL);
}

```

OUTPUT:

```
Philosopher 1 is thinking
Philosopher 2 is thinking
Philosopher 3 is thinking
Philosopher 4 is thinking
Philosopher 5 is thinking
Philosopher 3 is hungry
Philosopher 1 is hungry
Philosopher 5 is hungry
Philosopher 4 is hungry
Philosopher 4 takes fork 3 and 4
Philosopher 2 is hungry
Philosopher 4 is eating
Philosopher 2 takes fork 1 and 2
Philosopher 2 is eating
Philosopher 4 putting fork 3 and 4 down
Philosopher 4 is thinking
Philosopher 5 takes fork 4 and 5
Philosopher 5 is eating
Philosopher 2 putting fork 1 and 2 down
Philosopher 2 is thinking
Philosopher 3 takes fork 2 and 3
Philosopher 3 is eating
Philosopher 5 putting fork 4 and 5 down
Philosopher 5 is thinking
Philosopher 1 takes fork 5 and 1
Philosopher 1 is eating
Philosopher 4 is hungry
Philosopher 2 is hungry
Philosopher 3 putting fork 2 and 3 down
Philosopher 3 is thinking
Philosopher 4 takes fork 3 and 4
Philosopher 4 is eating
Philosopher 1 putting fork 5 and 1 down
Philosopher 1 is thinking
Philosopher 2 takes fork 1 and 2
Philosopher 2 is eating
Philosopher 5 is hungry
Philosopher 3 is hungry
Philosopher 4 putting fork 3 and 4 down
Philosopher 4 is thinking
Philosopher 5 takes fork 4 and 5
Philosopher 5 is eating
Philosopher 1 is hungry
Philosopher 2 putting fork 1 and 2 down
Philosopher 2 is thinking
Philosopher 3 takes fork 2 and 3
Philosopher 3 is eating
Philosopher 4 is hungry
Philosopher 5 putting fork 4 and 5 down
Philosopher 5 is thinking
Philosopher 1 takes fork 5 and 1
Philosopher 1 is eating
Philosopher 2 is hungry
Philosopher 3 putting fork 2 and 3 down
Philosopher 3 is thinking
Philosopher 4 takes fork 3 and 4
Philosopher 4 is eating
Philosopher 5 is hungry
Philosopher 1 putting fork 5 and 1 down
Philosopher 1 is thinking
Philosopher 2 takes fork 1 and 2
Philosopher 2 is eating
Philosopher 3 is hungry
```

else

```

        printf("Buffer is empty!!");
        break;
    case 3:
        exit(0);
        break;
    }
}
return 0;
}

int wait(int s)
{
    return (--s);
}

int signal(int s)
{
    return(++s);
}

void producer()
{
    mutex=wait(mutex);
    full=signal(full);
    empty=wait(empty);
    x++;
    printf("\nProducer produces the item %d",x);
    mutex=signal(mutex);
}

```

```
void consumer()
{
    mutex=wait(mutex);
    full=wait(full);
    empty=signal(empty);
    printf("\nConsumer consumes item %d",x);
    x--;
    mutex=signal(mutex);
}
```


OUTPUT:

```
1.Producer
2.Consumer
3.Exit
Enter your choice:1

Producer produces the item 1
Enter your choice:2

Consumer consumes item 1
Enter your choice:2
Buffer is empty!!
Enter your choice:█
```