

VISVESVARAYA TECHNOLOGICAL UNIVERSITY

“JnanaSangama”, Belgaum -590014, Karnataka.



LAB REPORT on

Analysis and Design of Algorithms

Submitted by

G SANJANA HEBBAR(1BM21CS062)

in partial fulfillment for the award of the degree of
BACHELOR OF ENGINEERING
in
COMPUTER SCIENCE AND ENGINEERING



B.M.S. COLLEGE OF ENGINEERING

BENGALURU-560019

June-2023 to Sep-2023

(Autonomous Institution under VTU)

B. M. S. College of Engineering,

Bull Temple Road, Bangalore 560019

(Affiliated To Visvesvaraya Technological University, Belgaum)

Department of Computer Science and Engineering



CERTIFICATE

This is to certify that the Lab work entitled “**Analysis and Design of Algorithms**” carried out by **G SANJANA HEBBAR(1BM21CS062)**, who is a bonafide student of **B.M.S. College of Engineering**. It is in partial fulfillment for the award of **Bachelor of Engineering in Computer Science and Engineering** of the Visvesvaraya Technological University, Belgaum during the academic semester June-2023 to Sep-2023. The Lab report has been approved as it satisfies the academic requirements in respect of a **Analysis and Design of Algorithms (22CS4PCADA)** work prescribed for the said degree.

Radhika A D

Assistant Professor

Department of CSE

BMSCE, Bengaluru

Dr. Jyothi S Nayak

Professor and Head

Department of CSE

BMSCE, Bengaluru

Index Sheet

Lab Program No.	Program Details	Page No.
1	Write program to do the following: a. Print all the nodes reachable from a given starting node in a digraph using BFS method. b. Check whether a given graph is connected or not using DFS method.	1-4
2	Write program to obtain the Topological ordering of vertices in a given digraph.	5-7
3	Implement Johnson Trotter algorithm to generate permutations.	8-12
4	Sort a given set of N integer elements using Merge Sort technique and compute its time taken. Run the program for different values of N and record the time taken to sort.	13-15
5	Sort a given set of N integer elements using Quick Sort technique and compute its time taken.	16-18
6	Sort a given set of N integer elements using Heap Sort technique and compute its time taken.	19-21
7	Implement 0/1 Knapsack problem using dynamic programming.	22-23
8	Implement All Pair Shortest paths problem using Floyd's algorithm.	24-25
9	Find Minimum Cost Spanning Tree of a given undirected graph using Prim's and Kruskal's algorithm.	26-31
10	From a given vertex in a weighted connected graph, find shortest paths to other vertices using Dijkstra's algorithm.	32-35

11	Implement “N-Queens Problem” using Backtracking.	36-38
----	--	-------

Course Outcome

CO1	Analyze time complexity of Recursive and Non-recursive algorithms using asymptotic notations.
CO2	Apply various design techniques for the given problem.
CO3	Apply the knowledge of complexity classes P, NP, and NP-Complete and prove certain problems are NP-Complete
CO4	Design efficient algorithms and conduct practical experiments to solve problems.

PROGRAM-1

Q) Write program to do the following:

- a. Print all the nodes reachable from a given starting node in a digraph using BFS method.**
- b. Check whether a given graph is connected or not using DFS method.**

CODE-

```
#include<stdio.h>

int q[20],top=-1,front=-1,rear=-1,a[20][20],vis[20],stack[20];
int delete();
void add(int item);
void bfs(int s,int n);
void dfs(int s,int n);
void push(int item);
int pop();

void main()
{
    int n,i,s,ch,j;
    char c,dummy;
    printf("ENTER THE NUMBER VERTICES ");
    scanf("%d",&n);
    for(i=1;i<=n;i++)
    {
        for(j=1;j<=n;j++)
        {
            printf("ENTER 1 IF %d HAS A NODE WITH %d ELSE 0 ",i,j);
            scanf("%d",&a[i][j]);
        }
    }
    printf("THE ADJACENCY MATRIX IS\n");
    for(i=1;i<=n;i++)
    {
        for(j=1;j<=n;j++)
        {
            printf(" %d",a[i][j]);
        }
        printf("\n");
    }

    do
    {
        for(i=1;i<=n;i++)
            vis[i]=0;
        printf("\nMENU");
        printf("\n1.B.F.S");
        printf("\n2.D.F.S");
        printf("\nENTER YOUR CHOICE");
        scanf("%d",&ch);
```

```

printf("ENTER THE SOURCE VERTEX :");
scanf("%d",&s);

switch(ch)
{
case 1:bfs(s,n);
break;
case 2:
dfs(s,n);
break;
}
printf("DO U WANT TO CONTINUE(Y/N) ? ");
scanf("%c",&dummy);
scanf("%c",&c);
}while((c=='y')||(c=='Y'));
}

//*****BFS(breadth-first search) code*****//
void bfs(int s,int n)
{
int p,i;
add(s);
vis[s]=1;
p=delete();
if(p!=0)
printf(" %d",p);
while(p!=0)
{
for(i=1;i<=n;i++)
if((a[p][i]!=0)&&(vis[i]==0))
{
add(i);
vis[i]=1;
}
p=delete();
if(p!=0)
printf(" %d ",p);
}
for(i=1;i<=n;i++)
if(vis[i]==0)
bfs(i,n);
}

void add(int item)
{
if(rear==19)
printf("QUEUE FULL");
else
{
if(rear== -1)
{
q[++rear]=item;
front++;
}
}
}

```

```

else
q[++rear]=item;
}
}
int delete()
{
int k;
if((front>rear)||front==-1)
return(0);
else
{
k=q[front++];
return(k);
}
}

```

```

//*****DFS(depth-first search) code*****//
void dfs(int s,int n)
{
int i,k;
push(s);
vis[s]=1;
k=pop();
if(k!=0)
printf(" %d ",k);
while(k!=0)
{
for(i=1;i<=n;i++)
if((a[k][i]!=0)&&(vis[i]==0))
{
push(i);
vis[i]=1;
}
k=pop();
if(k!=0)
printf(" %d ",k);
}
for(i=1;i<=n;i++)
if(vis[i]==0)
dfs(i,n);
}
void push(int item)
{
if(top==19)
printf("Stack overflow ");
else
stack[++top]=item;
}
int pop()
{
int k;
if(top==1)
return(0);
else
{

```



```
k=stack[top--];  
return(k);  
}  
}
```

OUTPUT-

```
Enter The Number of Vertices 4  
Enter 1 If 1 Has A Node With 1 Else 0 0  
Enter 1 If 1 Has A Node With 2 Else 0 1  
Enter 1 If 1 Has A Node With 3 Else 0 1  
Enter 1 If 1 Has A Node With 4 Else 0 1  
Enter 1 If 2 Has A Node With 1 Else 0 0  
Enter 1 If 2 Has A Node With 2 Else 0 0  
Enter 1 If 2 Has A Node With 3 Else 0 0  
Enter 1 If 2 Has A Node With 4 Else 0 1  
Enter 1 If 3 Has A Node With 1 Else 0 0  
Enter 1 If 3 Has A Node With 2 Else 0 0  
Enter 1 If 3 Has A Node With 3 Else 0 0  
Enter 1 If 3 Has A Node With 4 Else 0 0  
Enter 1 If 4 Has A Node With 1 Else 0 0  
Enter 1 If 4 Has A Node With 2 Else 0 0  
Enter 1 If 4 Has A Node With 3 Else 0 1  
Enter 1 If 4 Has A Node With 4 Else 0 0  
the adjacency matrix is  
0 1 1 1  
0 0 0 1  
0 0 0 0  
0 0 1 0  
  
MENU  
1.BFS  
2.DFS  
enter choice1  
Enter source vertex:1  
1 2 3 4  
MENU  
1.BFS  
2.DFS  
enter choice2  
Enter source vertex:1  
1 4 3 2  
MENU  
1.BFS  
2.DFS  
enter choice|
```

PROGRAM-2

Q) Write program to obtain the Topological ordering of vertices in a given digraph.

CODE-

```
#include <stdio.h>
#include <stdlib.h>

#define MAX_VERTICES 100

typedef struct {
    int vertices[MAX_VERTICES];
    int count;
} Stack;

void initialize(Stack* stack) {
    stack->count = 0;
}

int isEmpty(Stack* stack) {
    return (stack->count == 0);
}

void push(Stack* stack, int value) {
    stack->vertices[stack->count++] = value;
}

int pop(Stack* stack) {
    if (isEmpty(stack)) {
        printf("Error: Stack underflow\n");
        exit(0);
    }
    return stack->vertices[--stack->count];
}
```

```

void topologicalSortDFS(int vertex, int** graph, int* visited, Stack* stack, int numVertices) {
    visited[vertex] = 1;
    int i;

    for (i = 0; i < numVertices; i++) {        if
(graph[vertex][i] && !visited[i]) {
        topologicalSortDFS(i, graph, visited, stack, numVertices);
    }
}

```

```

    push(stack, vertex + 1);
}

```

```

void topologicalSort(int** graph, int numVertices) {
    Stack stack;
    int visited[MAX_VERTICES];
    int i;

    initialize(&stack);

    for (i = 0; i < numVertices; i++) {
        visited[i] = 0;
    }

    for (i = 0; i < numVertices; i++) {
        if (!visited[i]) {
            topologicalSortDFS(i, graph, visited, &stack, numVertices);
        }
    }
}

```

```

    printf("Topological Ordering of Vertices:\n");
    while (!isEmpty(&stack)) {
        printf("%d ", pop(&stack));
    }
    printf("\n");
}

```

```

int main() {
    int numVertices, i, j;

    printf("Enter the number of vertices in the graph: ");
    scanf("%d", &numVertices);
}

```

```

int** graph = (int**)malloc(numVertices * sizeof(int*));
for (i = 0; i < numVertices; i++) {
    graph[i] = (int*)malloc(numVertices * sizeof(int));
}

printf("Enter the adjacency matrix of the graph:\n");
for (i = 0; i < numVertices; i++) {
    for (j = 0; j < numVertices; j++) {
        scanf("%d", &graph[i][j]);
    }
}

topologicalSort(graph, numVertices);

return 0;
}

```

OUTPUT-

```

Enter the number of vertices in the graph: 4
Enter the adjacency matrix of the graph:
0
1
1
1
0
0
0
0
0
0
1
0
0
1
0
0
Topological Ordering of Vertices:
1 4 3 2

```

PROGRAM-3

Q) Implement Johnson Trotter algorithm to generate permutations.

CODE-

```
#include <stdio.h>
#include <stdlib.h>

int flag = 0;

int swap(int *a,int *b) {
    int t = *a; *a = *b;
    *b = t;
}

int search(int arr[],int num,int mobile)
{
    int g;
    for(g=0;g<num;g++) {
        if(arr[g] == mobile)
            return g+1;
        else flag++;
    }
    return -1;
}

int find_Moblie(int arr[],int d[],int num)
{
    int mobile = 0;
    int mobile_p = 0;
    int i;
    for(i=0;i<num;i++)
    {
        if((d[arr[i]-1] == 0) && i != 0)
        {
```

```

if(arr[i]>arr[i-1] && arr[i]>mobile_p)
{
mobile = arr[i];
mobile_p = mobile;
}
else flag++;
}
else if((d[arr[i]-1] == 1) & i != num-1)
{
if(arr[i]>arr[i+1] && arr[i]>mobile_p)
{
mobile = arr[i];
mobile_p = mobile;
}
else
flag++;
}
else flag++; }

if((mobile_p == 0) && (mobile == 0))
return 0; else return mobile;
}

void permutations(int arr[],int d[],int num)
{ int i;
int mobile = find_Moblie(arr,d,num);
int pos = search(arr,num,mobile);
if(d[arr[pos-1]-1]==0)
swap(&arr[pos-1],&arr[pos-2]);
else swap(&arr[pos-1],&arr[pos]);
for(int i=0;i<num;i++)

```

```

{
if(arr[i] > mobile)
{
if(d[arr[i]-1]==0) d[arr[i]-1] = 1;
else
d[arr[i]-1] = 0;
}
}
for(i=0;i<num;i++)
{
printf(" %d ",arr[i]);
} }
int factorial(int k)
{ int f = 1;
int i = 0;
for(i=1;i<k+1;i++)
f = f*i;
return f;
}
int main()
{

int num = 0;
int i; int j; int z = 0;
printf("Johnson trotter algorithm to find all permutations of given numbers\n");
printf("Enter the number\n");
scanf("%d",&num);
int arr[num],d[num];
z = factorial(num);

```

```
printf("total permutations = %d",z);  
printf("\nAll possible permutations are: \n");  
for(i=0;i<num;i++)  
{ d[i] = 0; arr[i] = i+1;  
printf(" %d ",arr[i]);  
} printf("\n");  
for(j=1;j<z;j++) {  
    permutations(arr,d,num);  
printf("\n");  
}  
return 0;  
}
```


OUTPUT-

```
Enter the number
4
total permutations = 24
All possible permutations are:
1 2 3 4
1 2 4 3
1 4 2 3
4 1 2 3
4 1 3 2
1 4 3 2
1 3 4 2
1 3 2 4
3 1 2 4
3 1 4 2
3 4 1 2
4 3 1 2
4 3 2 1
3 4 2 1
3 2 4 1
3 2 1 4
2 3 1 4
2 3 4 1
2 4 3 1
4 2 3 1
4 2 1 3
2 4 1 3
2 1 4 3
2 1 3 4

Process returned 0 (0x0)   execution time : 3.463 s
Press any key to continue.
```

PROGRAM-4

Q) Sort a given set of N integer elements using Merge Sort technique and compute its time taken. Run the program for different values of N and record the time taken to sort.

CODE-

```
#include <stdio.h>

#include <stdlib.h>

void merge(int low,int mid,int high,int array[20],int mer[20])
{
    int i = low;    int j = mid+1;
    int k = 0;
    while(i<=mid && j<=high)
    {
        if(array[i]<array[j])
        {
            mer[k] = array[i];
            i++;      k++;
        }    else
        {
            mer[k] = array[j];
            j++;      k++;
        }
    }
    while (i <= mid)
    {
        mer[k] = array[i];
        i++;
        k++;
    }
```

```

while (j <= high)
{
    mer[k] = array[j];
    j++;    k++;
}

for(int i=0;i<k;i++)
{
    array[low+i] = mer[i];
}
}

void merge_sort(int low,int high,int array[20],int merged[20])
{
    if(low<high)
    {
        int mid = (low+high)/2;
        merge_sort(low,mid,array,merged);
        merge_sort(mid+1,high,array,merged);
        merge(low,mid,high,array,merged);
    }
}

int main()
{
    int n,array[30];
    printf("Enter no of elements:");
    scanf("%d",&n);
    printf("Enter elements:");

```

```
for(int i=0;i<n;i++)
{
    scanf("%d",&array[i]);
}

int merged[30];
merge_sort(0,n-1,array,merged);
printf("Sorted array:");

for(int i=0;i<n;i++)
{
    printf("%d ",array[i]);
}
}
```

OUTPUT-

```
Enter no of elements:5
Enter elements:4 2 -6 10 3
Sorted array:-6 2 3 4 10
Process returned 0 (0x0)    execution time : 10.119 s
Press any key to continue.
|
```

PROGRAM-5

Q) Sort a given set of N integer elements using Quick Sort technique and compute its time taken

CODE-

```
#include <stdio.h>

void swap(int *a, int *b) {

    int t = *a;

    *a = *b;

    *b = t;

}

int partition(int a[], int l, int h) {

    int pivot = a[l];

    int i = l,

    j = h;

    while (i < j) {

        while (a[i] <= pivot && i <= h) {

            i++;    }

        while (a[j] > pivot) {

            j--;    }    if (i < j) {

            swap(&a[i], &a[j]);

        }

    }

    swap(&a[l], &a[j]);
```

```

    return j;
}

void quickSort(int a[], int l, int h) {
    if (l < h) {
        int pi = partition(a, l, h);
        quickSort(a, l, pi - 1);
        quickSort(a, pi + 1, h);
    }
}

int main() {
    int a[20], n, i;
    printf("Enter size of array\n");
    scanf("%d", &n);
    printf("Enter data elements: ");
    for (i = 0; i < n; i++) {
        scanf("%d", &a[i]);
    }
    printf("Unsorted Array\n");
    for (i = 0; i < n; i++) {
        printf("%d\t", a[i]);
    }
    quickSort(a, 0, n - 1);

    printf("\nSorted array in ascending order: \n");

```

```
for (i = 0; i < n; i++) {  
    printf("%d\t", a[i]);  
}  
  
return 0;  
}
```

OUTPUT

```
Enter size of array  
5  
Enter data elements: 88 -5 65 -10 0 25 18  
Unsorted Array  
88      -5      65      -10      0  
Sorted array in ascending order:  
-10      -5      0      65      88  
Process returned 0 (0x0)   execution time : 22.359 s  
Press any key to continue.  
|
```

PROGRAM-6

Q) Sort a given set of N integer elements using Heap Sort technique and compute its time taken

CODE-

```
#include <stdio.h>

void swap(int* a, int* b)
{
    int temp = *a;
    *a = *b;
    *b = temp;
}

void heapify(int arr[], int N, int i)
{
    int largest = i;
    int left = 2 * i + 1;
    int right = 2 * i + 2;
    if (left < N && arr[left] > arr[largest])
        largest = left;
    if (right < N && arr[right] > arr[largest])
        largest = right;
    if (largest != i) {
        swap(&arr[i], &arr[largest]);
        heapify(arr, N, largest);
    }
}

void heapSort(int arr[], int N)
{
    for (int i = N / 2 - 1; i >= 0; i--)
```



```

    heapify(arr, N, i);
    for (int i = N - 1; i >= 0; i--) {
        swap(&arr[0], &arr[i]);
        heapify(arr, i, 0);
    }
}

void printArray(int arr[], int N)
{
    for (int i = 0; i < N; i++)
        printf("%d ", arr[i]);
    printf("\n");
}

int main()
{
    int n;
    printf("Enter number of elements:");
    scanf("%d",&n);
    int arr[n];
    printf("Enter the elements:");
    for (int i=0;i<n;i++)
    {
        scanf("%d",&arr[i]);
    }
    heapSort(arr, n);
    printf("Sorted array is\n");
    printArray(arr, n);
}

```

OUTPUT

```
Enter number of elements:6
Enter the elements:-1 7 2 0 9 8
Sorted array is
-1 0 2 7 8 9

Process returned 0 (0x0)   execution time : 12.823 s
Press any key to continue.
|
```

PROGRAM-7

Q)Implement 0/1 Knapsack problem using dynamic programming.

CODE-

```
#include <stdio.h>

int knap(int w[], int p[], int n, int ww) {
    int v[n+1][ww+1];

    for (int i = 0; i < n + 1; i++) {
        for (int j = 0; j < ww + 1; j++) {
            if (i == 0 || j == 0) {
                v[i][j] = 0;
                continue;
            } else {
                if (w[i - 1] > j) {
                    v[i][j] = v[i - 1][j];
                } else {
                    if (v[i - 1][j] > (v[i - 1][j - w[i - 1]] + p[i - 1])) {
                        v[i][j] = v[i - 1][j];
                    } else {
                        v[i][j] = v[i - 1][j - w[i - 1]] + p[i - 1];
                    }
                }
            }
        }
    }

    int q = v[n][ww];

    return q;
}

int main() {
    int w[10], p[10], n, ww, ans;
```

```
printf("Enter the number of items: ");
scanf("%d", &n);
printf("Enter the weight and profit of each item:\n");
for (int i = 0; i < n; i++) {
    scanf("%d %d", &w[i], &p[i]);
}
printf("Enter the required weight limit: ");
scanf("%d", &ww);
ans = knap(w, p, n, ww);
printf("Maximum profit: %d\n", ans);
return 0;
}
```

OUTPUT-

```
Enter the number of items: 4
Enter the weight and profit of each item:
25 15
33 10
60 35
35 35
Enter the required weight limit: 60
Maximum profit: 50

Process returned 0 (0x0)   execution time : 23.528 s
Press any key to continue.
```

PROGRAM-8

Q) Implement All Pair Shortest paths problem using Floyd's algorithm.

CODE-

```
#include <stdio.h>

int min(int a, int b) {
    if (a < b)
        return a;
    else
        return b;
}

void printm(int n, int d[][10]) {
    printf("Distance matrix is:\n");
    for (int i = 0; i < n; i++) {
        for (int j = 0; j < n; j++) {
            printf("%d\t", d[i][j]);
        }
        printf("\n");
    }
}

void floyd(int n, int a[][10]) {
    int d[10][10], i, j, k;
    for (i = 0; i < n; i++) {
        for (j = 0; j < n; j++) {
            d[i][j] = a[i][j];
        }
    }

    for (k = 0; k < n; k++) {
        for (i = 0; i < n; i++) {
            for (j = 0; j < n; j++) {
```

```

d[i][j] = min(d[i][j], (d[i][k] + d[k][j]));
}
}
}
printm(n, d);
}

int main() {
int a[10][10], i, j, n;
printf("Enter the order of the matrix: ");
scanf("%d", &n);
printf("Enter the adjacency matrix:\n");
for (i = 0; i < n; i++) {
for (j = 0; j < n; j++) {
scanf("%d", &a[i][j]);
}
}
floyd(n, a);
return 0;
}

```

OUTPUT

```

Enter the order of the matrix: 4
Enter the adjacency matrix:
0 1 999 4
999 0 999 999
8 2 0 999
999 6 5 0
Distance matrix is:
0      1      9      4
999     0     999    999
8       2      0     12
13      6      5      0

Process returned 0 (0x0)   execution time : 24.721 s
Press any key to continue.

```

PROGRAM-9

Q) Find Minimum Cost Spanning Tree of a given undirected graph using Prim/Kruskal's algorithm.

CODE

Prim's Algorithm-

```
#include <limits.h>
#include <stdbool.h>
#include <stdio.h>

int V;

int minKey(int key[], bool mstSet[]) {
    int min = INT_MAX, min_index;
    for (int v = 0; v < V; v++) {
        if (mstSet[v] == false && key[v] < min) {
            min = key[v];
            min_index = v;
        }
    }
    return min_index;
}

int printMST(int parent[], int graph[V][V]) {
    int sum = 0;
    printf("Edge \tWeight\n");
    for (int i = 1; i < V; i++) {
        printf("%d - %d \t%d \n", parent[i], i, graph[i][parent[i]]);
        sum += graph[i][parent[i]];
    }
    printf("weight=%d\n", sum);
}

void primMST(int graph[V][V]) {
```

```

int parent[V];
int key[V];
bool mstSet[V];
for (int i = 0; i < V; i++) {
    key[i] = INT_MAX;
    mstSet[i] = false;
}
key[0] = 0;
parent[0] = -1;
for (int count = 0; count < V - 1; count++) {
    int u = minKey(key, mstSet);
    mstSet[u] = true;
    for (int v = 0; v < V; v++) {
        if (graph[u][v] && mstSet[v] == false && graph[u][v] < key[v]) {
            parent[v] = u;
            key[v] = graph[u][v];
        }
    }
}
printMST(parent, graph);
}

int main() {
    printf("Enter the number of vertices: ");
    scanf("%d", &V);
    int graph[V][V];
    printf("Enter the adjacency matrix:\n");
    for (int i = 0; i < V; i++) {
        for (int j = 0; j < V; j++) {
            scanf("%d", &graph[i][j]);

```



```

}
}
primMST(graph);
return 0;
}

```

Krushkal's Algorithm-

```

#include <stdio.h>

int find(int v, int parent[10])
{
    while (parent[v] != v)
    {
        v = parent[v];
    }
    return v;
}

void union1(int i, int j, int parent[10])
{
    if (i < j)
        parent[j] = i;
    else
        parent[i] = j;
}

void kruskal(int n, int a[10][10])
{
    int count, k, min, sum, i, j, t[10][10], u, v, parent[10];
    count = 0;
    k = 0;
    sum = 0;
    for (i = 0; i < n; i++)

```

```

parent[i] = i;
while (count != n - 1)
{
    min = 999;
    for (i = 0; i < n; i++)
    {
        for (j = 0; j < n; j++)
        {
            if (a[i][j] < min && a[i][j] != 0)
            {
                min = a[i][j];
                u = i;
                v = j;
            }
        }
    }
    i = find(u, parent);
    j = find(v, parent);
    if (i != j)
    {
        union1(i, j, parent);
        t[k][0] = u;
        t[k][1] = v;
        k++;
        count++;
        sum = sum + a[u][v];
    }
    a[u][v] = a[v][u] = 999;
}

```

```

if (count == n - 1)
{
printf("spanning tree\n");
for (i = 0; i < n - 1; i++)
{
printf("%d %d\n", t[i][0], t[i][1]);
}
printf("cost of spanning tree=%d\n", sum);
}
else
printf("spanning tree does not exist\n");
}
int main()
{
int n, i, j, a[10][10];
printf("enter the number of nodes\n");
scanf("%d", &n);
printf("enter the adjacency matrix\n");
for (i = 0; i < n; i++)
{
for (j = 0; j < n; j++)
scanf("%d", &a[i][j]);
}
kruskal(n, a);
return 0;
}

```

OUTPUT

Prim's Algorithm

```
Enter the number of vertices: 6
Enter the adjacency matrix:
0 3 999 999 6 5
3 0 1 999 999 4
999 1 0 6 999 4
999 999 6 0 8 5
6 999 999 8 0 2
5 4 4 5 2 6
Edge    Weight
0 - 1    3
1 - 2    1
5 - 3    5
5 - 4    2
1 - 5    4
weight=15

Process returned 0 (0x0)   execution time : 626.030 s
Press any key to continue.
|
```

Krushkal's Algorithm

```
enter the number of nodes
6
enter the adjacency matrix
0 3 999 999 6 5
3 0 1 999 999 4
999 1 0 6 999 4
999 999 6 0 8 5
6 999 999 8 0 2
5 4 4 5 2 0
spanning tree
1 2
4 5
0 1
1 5
3 5
cost of spanning tree=15

Process returned 0 (0x0)   execution time : 71.515 s
Press any key to continue.
|
```

PROGRAM-10

Q) From a given vertex in a weighted connected graph, find shortest paths to other vertices using Dijkstra's algorithm.

CODE

```
#include <stdio.h>
#include <conio.h>
void dijkstras();
int c[10][10], n, src;
void printPath(int parent[], int node);
void main()
{
    int i, j;
    printf("\nEnter the no of vertices:\t");
    scanf("%d", &n);
    printf("\nEnter the cost matrix:\n");
    for (i = 1; i <= n; i++)
    {
        for (j = 1; j <= n; j++)
        {
            scanf("%d", &c[i][j]);
        }
    }
    printf("\nEnter the source node:\t");
    scanf("%d", &src);
    dijkstras();
    getch();
}
void dijkstras()
{
    }
```

```

int vis[10], dist[10], parent[10], u, j, count, min;
for (j = 1; j <= n; j++)
{
    dist[j] = c[src][j];
    parent[j] = src;
}
for (j = 1; j <= n; j++)
{
    vis[j] = 0;
}
dist[src] = 0;
vis[src] = 1;
count = 1;
while (count != n)
{
    min = 9999;
    for (j = 1; j <= n; j++)
    {
        if (dist[j] < min && vis[j] != 1)
        {
            min = dist[j];
            u = j;
        }
    }
    vis[u] = 1;
    count++;
    for (j = 1; j <= n; j++)
    {
        if (min + c[u][j] < dist[j] && vis[j] != 1)

```

```

{
dist[j] = min + c[u][j];
parent[j] = u;
}
}
}
printf("\nThe shortest distance is:\n");
for (j = 1; j <= n; j++)
{
printf("\n%d-->%d=%d (Path: %d", src, j, dist[j], src);
printPath(parent, j);
printf(")");
}
}
void printPath(int parent[], int node)
{
if (parent[node] == src)
{
printf("->%d", node);
return;
}
printPath(parent, parent[node]);
printf("->%d", node);
}

```

OUTPUT

```
Enter the no of vertices:6
```

```
Enter the cost matrix:
```

```
0 25 35 999 100 999
999 0 27 14 999 999
999 999 0 29 999 999
999 999 999 0 999 21
999 999 50 999 0 999
999 999 999 999 48 0
```

```
Enter the source node: 1
```

```
The shortest distance is:
```

```
1-->1=0 (Path: 1->1)
1-->2=25 (Path: 1->2)
1-->3=35 (Path: 1->3)
1-->4=39 (Path: 1->2->4)
1-->5=100 (Path: 1->5)
1-->6=60 (Path: 1->2->4->6)|
```


PROGRAM-11

Q) Implement “N-Queens Problem” using Backtracking

CODE

```
#include <stdio.h>
#include <math.h>

int x[20]; // Solution array to store column index of queens
int count = 0;

int place(int k, int i) {
    for (int j = 1; j <= k - 1; j++) {
        if (x[j] == i || abs(x[j] - i) == abs(j - k)) {
            return 0;
        }
    }
    return 1;
}

void nqueens(int k, int n) {
    for (int i = 1; i <= n; i++) {
        if (place(k, i)) {
            x[k] = i;
            if (k == n) {
                count++;
                printf("Solution %d:\n", count);
                for (int j = 1; j <= n; j++) {
                    for (int l = 1; l <= n; l++) {
                        if (x[j] == l) {
                            printf("Q ");
                        } else {
                            printf("0 ");
                        }
                    }
                }
            }
        }
    }
}
```

```

    }
    printf("\n");
}
printf("\n");
} else {
nqueens(k + 1, n);
}
}
}
}

int main() {
int n;
printf("Enter the number of queens: ");
scanf("%d", &n);
if (n <= 0) {
printf("Invalid input.\n");
return 1;
}
nqueens(1, n);
if (count == 0) {
printf("No solutions found for %d queens.\n", n);
} else {
printf("Total solutions: %d\n", count);
}
return 0;
}

```

OUTPUT-

```
Enter the number of queens: 4
Solution 1:
0 Q 0 0
0 0 0 Q
Q 0 0 0
0 0 Q 0

Solution 2:
0 0 Q 0
Q 0 0 0
0 0 0 Q
0 Q 0 0

Total solutions: 2

Process returned 0 (0x0)   execution time : 4.678 s
Press any key to continue.
|
```