LAB 8

To construct a simple LAN and understand the concept and operationof Address Resolution Protocol (ARP).

OBSERVATION:



03/08/2023

LAB-08

AIM:- To construct single LAN and understand the concept and operation of Address Resolution Protocol (ARP)

Topology:-

PROCEDURE:-

- Create a topology of 3 PC's and a Server.
- Assign IP address to all PC's and Server.
- Connect them through the Switch.
- Use the inspect tool to click on a PC to see ARP table.
- Command in cold for the same is arp-a
- Initially ARP table is empty.
- Also in CLI of Switch, the command - show mac address table can be given an easy

transaction to see how the switch learns from transactions and build the address-table.

- Use the capture button in the simulation panel and go step by step so that the changes in ARP can be clearly noted!

PING OUTPUT:-

PC -> Ping 10.0.0.4

Pinging 10.0.0.4 with 32 bytes of data.
Reply from 10.0.0.4 with 32 bytes time=0ms TTL=128
Reply from 10.0.0.4 with 32 bytes time=0ms TTL=128
Reply from 10.0.0.4 with 32 bytes time=0ms TTL=128
Reply from 10.0.0.4 with 32 bytes time=0ms TTL=128

Ping Statistics for 10.0.0.4:
Packet: Sent=4 Received=4 Lost=0 (0% loss)
Approximate round trip time in milliseconds.
Minimum=0ms, Maximum=0ms Average=0ms

PC> arp-a

Internet address	Physical Address	Type
10.0.0.4	0060.2fa0.304d	dynamic

OBSERVATION:-

→ When we Ping PC and Server the address of server is known to PC & vice-versa.

→ when we Ping b/w other two PC's simultaneously the address of each other are known.

→ Every time a host requires a MAC address in order to send a packet to another host in the LAN, it checks its ARP cache to see if the IP to MAC address translation address already exists of the translation does not exists it performs ARP.

18/8

TOPOLOGY:



OUTPUT:




Logical
[Root]
New Cluster
Move Object
Set Tiled Background
Viewport
ARP Table for Server0
IP Address
Hardware Address
Interface
10.0.0.2
0060.D35A.5B4A
FastEthernet0
ARP Table for PC0
10.0.0.1
0001.C904.5457
ARP Table for PC2
10.0.0.3
0009.7C19.7260
ARP Table for PC1
10.0.0.4
0001.64A0.8ECB
Switch1
Physical
Config
CLI
IOS Command Line Interface
%LINK-5-CHANGED: Interface FastEthernet2/1, changed state to up
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet2/1, changed state to up
%LINK-5-CHANGED: Interface FastEthernet3/1, changed state to up
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet3/1, changed state to up
Switch>arp -a
Translating "arp-a"...domain server (255.255.255.255)
% Unknown command or computer name, or unable to find computer address
Switch>show mac address-table
Mac Address Table
Vlan Mac Address Type Ports
1 0001.64a0.8ecb DYNAMIC Fa2/1
1 0001.c904.5457 DYNAMIC Fa2/1
1 0009.7c19.7260 DYNAMIC Fa2/1
1 00d0.d35a.5b4a DYNAMIC Fa3/1
Switch>
Copy
Paste
PC-PT PC0
PC-PT PC1
PC-PT PC2
Server-PT Server0
Time: 00:12:46.033
Power Cycle Devices
PLAY CONTROLS:
Back
Auto Capture / Play
Capture / Forward
Event List
Simulation
Connections
Scenario 0
New
Delete
Toggle PDU List Window
Fire
Last Status
Source
Destination
Type
Color
Time(sec)
Periodic
Num
Edit
Delete
In Progress
PC0
Server0
ICMP
0.000
N
0
(edit)
(delete)
Successful
PC1
PC2
ICMP
0.004
N
1
(edit)
(delete)