


LAB PROGRAM-06

RIP(Using 3 routers and 2 pcs):-



```
PC2
Physical Config Desktop Custom Interface

Command Prompt

Packet Tracer PC Command Line 1.0
PC>ping 40.0.0.2

Pinging 40.0.0.2 with 32 bytes of data:

Request timed out.
Request timed out.
Request timed out.
Request timed out.

Ping statistics for 40.0.0.2:
    Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),

PC>ping 40.0.0.2

Pinging 40.0.0.2 with 32 bytes of data:

Request timed out.
Reply from 40.0.0.2: bytes=32 time=6ms TTL=125
Reply from 40.0.0.2: bytes=32 time=8ms TTL=125
Reply from 40.0.0.2: bytes=32 time=6ms TTL=125

Ping statistics for 40.0.0.2:
    Packets: Sent = 4, Received = 3, Lost = 1 (25% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 6ms, Maximum = 8ms, Average = 6ms

PC>ping 40.0.0.2

Pinging 40.0.0.2 with 32 bytes of data:

Reply from 40.0.0.2: bytes=32 time=10ms TTL=125
Reply from 40.0.0.2: bytes=32 time=7ms TTL=125
Reply from 40.0.0.2: bytes=32 time=7ms TTL=125
Reply from 40.0.0.2: bytes=32 time=10ms TTL=125

Ping statistics for 40.0.0.2:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 7ms, Maximum = 10ms, Average = 8ms

PC>ping 40.0.0.2

Pinging 40.0.0.2 with 32 bytes of data:

Reply from 40.0.0.2: bytes=32 time=7ms TTL=125
Reply from 40.0.0.2: bytes=32 time=4ms TTL=125
Reply from 40.0.0.2: bytes=32 time=6ms TTL=125
Reply from 40.0.0.2: bytes=32 time=13ms TTL=125

Ping statistics for 40.0.0.2:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 4ms, Maximum = 13ms, Average = 7ms

PC>|
```

Router3

Physical Config CLI

IOS Command Line Interface

```

Router(config)#interface Serial2/0
Router(config-if)#ip address 20.0.0.1 255.0.0.0
Router(config-if)#no shutdown

%LINK-5-CHANGED: Interface Serial2/0, changed state to down
Router(config-if)#
%LINK-5-CHANGED: Interface Serial2/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface Serial2/0, changed state to up

Router(config-if)#exit
Router(config)#interface Serial2/0
Router(config-if)#
Router(config-if)#exit
Router(config)#router rip
Router(config-router)#network 10.0.0.0 20.0.0.0
^
% Invalid input detected at '^' marker.

Router(config-router)#network 10.0.0.0
Router(config-router)#network 20.0.0.0
Router(config-router)#exit
Router(config)#
Router(config)#interface Serial2/0
Router(config-if)#encapsulation ppp
Router(config-if)#
%LINEPROTO-5-UPDOWN: Line protocol on Interface Serial2/0, changed state to down

%LINEPROTO-5-UPDOWN: Line protocol on Interface Serial2/0, changed state to up

```

Copy

Paste

Router4

Physical Config CLI

IOS Command Line Interface

```

%LINEPROTO-5-UPDOWN: Line protocol on Interface Serial2/0, changed state to up

Router(config-if)#exit
Router(config)#interface Serial2/0
Router(config-if)#clock rate 64000
Router(config-if)#exit
Router(config)#exit
Router#
%SYS-5-CONFIG_I: Configured from console by console

Router#show ip route
Codes: C - connected, S - static, I - IGRP, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2, E - EGP
       i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2, ia - IS-IS inter area
       * - candidate default, U - per-user static route, o - ODR
       P - periodic downloaded static route

Gateway of last resort is not set

R    10.0.0.0/8 [120/1] via 20.0.0.1, 00:00:18, Serial2/0
    20.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C    20.0.0.0/8 is directly connected, Serial2/0
C    20.0.0.1/32 is directly connected, Serial2/0
    30.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C    30.0.0.0/8 is directly connected, Serial3/0
C    30.0.0.2/32 is directly connected, Serial3/0
R    40.0.0.0/8 [120/1] via 30.0.0.2, 00:00:02, Serial3/0
Router#

```

Copy

Paste

IOS Command Line Interface

```
Router(config)#interface Serial2/0
Router(config-if)#encapsulation ppp
Router(config-if)#
%LINEPROTO-5-UPDOWN: Line protocol on Interface Serial2/0, changed state to down

%LINEPROTO-5-UPDOWN: Line protocol on Interface Serial2/0, changed state to up

Router(config-if)#exit
Router(config)#exit
Router#
%SYS-5-CONFIG_I: Configured from console by console

Router#show ip route
Codes: C - connected, S - static, I - IGRP, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2, E - EGP
       i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2, ia - IS-IS inter area
       * - candidate default, U - per-user static route, o - ODR
       P - periodic downloaded static route

Gateway of last resort is not set

C    10.0.0.0/8 is directly connected, FastEthernet0/0
    20.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C    20.0.0.0/8 is directly connected, Serial2/0
C    20.0.0.2/32 is directly connected, Serial2/0
R    30.0.0.0/8 [120/1] via 20.0.0.2, 00:00:11, Serial2/0
R    40.0.0.0/8 [120/2] via 20.0.0.2, 00:00:11, Serial2/0
Router#
```

Copy

Paste











