LAB 12

To understand the operation of TELNET by accessing the router in server room from a PC in IT office.

TOPOLOGY:



OUTPUT:


PC0
Physical
Config
Desktop
Custom Interface
Command Prompt
Packet Tracer PC Command Line 1.0
PC>ping 10.0.0.1
Pinging 10.0.0.1 with 32 bytes of data:
Reply from 10.0.0.1: bytes=32 time=1ms TTL=255
Reply from 10.0.0.1: bytes=32 time=0ms TTL=255
Reply from 10.0.0.1: bytes=32 time=0ms TTL=255
Reply from 10.0.0.1: bytes=32 time=0ms TTL=255
Ping statistics for 10.0.0.1:
Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 0ms, Maximum = 1ms, Average = 0ms
PC>telnet 10.0.0.1
Trying 10.0.0.1 ...Open
User Access Verification
Password:
% Password: timeout expired!
[Connection to 10.0.0.1 closed by foreign host]
PC>telnet 10.0.0.1
Trying 10.0.0.1 ...Open
User Access Verification
Password:
Password:
Password:
[Connection to 10.0.0.1 closed by foreign host]
PC>telnet 10.0.0.1
Trying 10.0.0.1 ...Open
User Access Verification
Password:
r1>enable
Password:
r1#show ip route
Codes: C - connected, S - static, I - IGRP, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2, E - EGP
i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2, ia - IS-IS inter area
* - candidate default, U - per-user static route, o - ODR
P - periodic downloaded static route
Gateway of last resort is not set
C 10.0.0.0/8 is directly connected, FastEthernet0/0
r1#