

# VISVESVARAYA TECHNOLOGICAL UNIVERSITY

“JnanaSangama”, Belgaum -590014, Karnataka.



## LAB RECORD

### Bio Inspired Systems (23CS5BSBIS)

*Submitted by*

Sneha S Bhairappa (1BM23CS333)

*in partial fulfillment for the award of the degree of*

**BACHELOR OF ENGINEERING**  
*in*  
**COMPUTER SCIENCE AND ENGINEERING**



**B.M.S. COLLEGE OF ENGINEERING**

(Autonomous Institution under VTU)

**BENGALURU-560019**

**Aug-2025 to Jan-2026**

**B.M.S. College of Engineering,**  
**Bull Temple Road, Bangalore 560019**  
(Affiliated To Visvesvaraya Technological University, Belgaum)  
**Department of Computer Science and Engineering**



**CERTIFICATE**

This is to certify that the Lab work entitled “ Bio Inspired Systems (23CS5BSBIS)” carried out by **Sneha S Bhairappa (1BM23CS333)**, who is a bonafide student of **B.M.S. College of Engineering**. It is in partial fulfillment for the award of **Bachelor of Engineering in Computer Science and Engineering** of the Visvesvaraya Technological University, Belgaum. The Lab report has been approved as it satisfies the academic requirements of the above mentioned subject and the work prescribed for the said degree.

Mayanka Assistant Professor Department of CSE, BMSCE	Dr. Kavitha Sooda Professor & HOD Department of CSE, BMSCE
--	--

## Index

Sl. No.	Date	Experiment Title	Page No.
1	29/8/25	Genetic Algorithm	4-8
2	29/8/25	Gene Expression Algorithm	9-13
3	12/9/25	Particle Swarm Optimisation	14-16
4	10/10/25	Ant Colony Optimisation	17-22
5	17/10/25	Cuckoo Search Optimisation	23-25
6	17/10/25	Grey Wolf Optimisation	26-28
7	7/11/25	Parallel Cellular Algorithm	29-30

Github Link:

<https://github.com/1BM23CS333/BIS-LAB.git>

## Program 1

### Genetic Algorithm for Optimization Problems

#### Algorithm:

Genetic Algorithm

Steps:

- ① Selecting encoding techniques : 0 to 31
- ② Select the initial populat<sup>n</sup> - "4"

String No.	Initial populat <sup>n</sup>	X value	fitness $f(x) = x^2$	Prob $f(x)/\sum f(x)$	% prob	Expected count $f(x)/\text{avg}(\sum f(x))$	Actual count (floor value)
1	01100	12	144	0.1247	12.47	0.49	1
2	11001	25	625	0.5411	54.11	2.164	2
3	00101	5	25	0.0210	2.10	0.086	0
4	10011	19	361	0.3125	31.25	1.25	1

Sum : 1155  
Avg : 288.75  
Max : 625  $\rightarrow$  729  $\rightarrow$  841

③ Select mating pool

String No.	Mating pool	Crossover point	Offspring after crossover	X value	fitness $f(x) = x^2$
1	01100	4	01101	13	169
2	11001		11000	24	576
3	11001	2	11011	27	729
4	10011		10001	17	289

④ Crossover : Random 4 & 2  
Max value = 729

⑤ Mutation

String No.	Offspring after crossover	mutat <sup>n</sup> chromosome for flipping	offspring after mutat <sup>n</sup>	X value	fitness $f(x) = x^2$
1	01101	10000	11101	29	841
2	11000	00000	11000	24	576
3	11011	00000	11011	27	729
4	10001	00101	10100	20	400

Sum : 2546  
Avg : 630.5  
Max : 841

#### Pseudocode

Initialize populat<sup>n</sup> with random 10-bit chromosomes

For each generat<sup>n</sup>:

- Decode chromosomes to integers (0 to 1023)
- Calculate fitness =  $x^2$  for each individual
- Keep track of best individual & fitness (elitism)
- Create new populat<sup>n</sup>:
  - Add best individual directly (elitism)
  - While new populat<sup>n</sup> not full:
    - Select two parents via roulette wheel select<sup>n</sup>
    - Perform crossover with probability CROSS-RATE
    - Mutate offspring with probability MUT-RATE per bit
    - Add offspring to new populat<sup>n</sup>
- Replace old populat<sup>n</sup> with new populat<sup>n</sup>
- Print best sol<sup>n</sup> found & fitness

Gen 1 :  $x = 993$   $f(x) = 986049$   
 Gen 2 :  $x = 1009$   $f(x) = 1008016$   
 Gen 3 :  $x = 1022$   $f(x) = 1044484$   
 Gen 4 :  $x = 1023$   $f(x) = 1046529$   
 ...  
 Gen 10 :

**Code:**

```
import random

def fitness_function(x):
    return x ** 2

def decode(chromosome):
    return int(chromosome, 2)

def evaluate_population(population):
    return [fitness_function(decode(individual)) for individual in population]

def select(population, fitnesses):
    total_fitness = sum(fitnesses)
    if total_fitness == 0:
        return random.choice(population)
    pick = random.uniform(0, total_fitness)
    current = 0
    for individual, fitness in zip(population, fitnesses):
        current += fitness
        if current > pick:
            return individual

def crossover(parent1, parent2):
    if random.random() < CROSSOVER_RATE:
        point = random.randint(1, CHROMOSOME_LENGTH - 1)
        return (parent1[:point] + parent2[point:], parent2[:point] + parent1[point:])
    return parent1, parent2

def mutate(chromosome):
    new_chromosome = ""
    for bit in chromosome:
        if random.random() < MUTATION_RATE:
            new_chromosome += '0' if bit == '1' else '1'
        else:
            new_chromosome += bit
    return new_chromosome

def get_initial_population(size, length):
    population = []
    print(f'Enter {size} chromosomes (each of {length} bits, e.g., '10101'):')
    while len(population) < size:
        chrom = input(f'Chromosome {len(population)+1}: ').strip()
        if len(chrom) == length and all(bit in '01' for bit in chrom):
            population.append(chrom)
        else:
            print(f'Invalid input. Please enter a {length}-bit binary string.')
```

```

    return population

def genetic_algorithm():
    population = get_initial_population(POPULATION_SIZE, CHROMOSOME_LENGTH)
    best_solution = None
    best_fitness = float('-inf')

    for generation in range(GENERATIONS):
        fitnesses = evaluate_population(population)

        for i, individual in enumerate(population):
            if fitnesses[i] > best_fitness:
                best_fitness = fitnesses[i]
                best_solution = individual

        print(f'Generation {generation + 1}: Best Fitness = {best_fitness}, Best x = {decode(best_solution)}')

        new_population = []
        while len(new_population) < POPULATION_SIZE:
            parent1 = select(population, fitnesses)
            parent2 = select(population, fitnesses)
            offspring1, offspring2 = crossover(parent1, parent2)
            offspring1 = mutate(offspring1)
            offspring2 = mutate(offspring2)
            new_population.extend([offspring1, offspring2])

        population = new_population[:POPULATION_SIZE]

    print("\nBest solution found:")
    print(f'Chromosome: {best_solution}')
    print(f'x = {decode(best_solution)}')
    print(f'f(x) = {fitness_function(decode(best_solution))}')

POPULATION_SIZE = 4
CHROMOSOME_LENGTH = 5
MUTATION_RATE = 0.01
CROSSOVER_RATE = 0.8
GENERATIONS = 20

if __name__ == "__main__":
    genetic_algorithm()

```

## Output:

Enter 4 chromosomes (each of 5 bits, e.g., '10101'):

Chromosome 1: 01100

Chromosome 2: 11001

Chromosome 3: 00101

Chromosome 4: 10011

Generation 1: Best Fitness = 625, Best x = 25

Generation 2: Best Fitness = 625, Best x = 25

Generation 3: Best Fitness = 625, Best x = 25

Generation 4: Best Fitness = 625, Best x = 25

Generation 5: Best Fitness = 625, Best x = 25

Generation 6: Best Fitness = 625, Best x = 25

Generation 7: Best Fitness = 625, Best x = 25

Generation 8: Best Fitness = 625, Best x = 25

Generation 9: Best Fitness = 625, Best x = 25

Generation 10: Best Fitness = 625, Best x = 25

Generation 11: Best Fitness = 625, Best x = 25

Generation 12: Best Fitness = 625, Best x = 25

Generation 13: Best Fitness = 625, Best x = 25

Generation 14: Best Fitness = 625, Best x = 25

Generation 15: Best Fitness = 625, Best x = 25

Generation 16: Best Fitness = 625, Best x = 25

Generation 17: Best Fitness = 625, Best x = 25

Generation 18: Best Fitness = 625, Best x = 25

Generation 19: Best Fitness = 625, Best x = 25

Generation 20: Best Fitness = 625, Best x = 25

Best solution found:

Chromosome: 11001

x = 25

f(x) = 625

## Program 2

### Optimization via Gene Expression Algorithms:

#### Algorithm:

05/09/2025

Optimization via Gene Expression Algorithms

Algorithm/Pseudocode:

Algorithm GeneExpressionAlgorithm

Initialize population with random genes in [lower, upper]

For each generation:

Evaluate fitness of each chromosome:

- Express chromosome as average of its genes
- Fitness = (expressed value)<sup>2</sup>

Create new-population:

Repeat POP\_SIZE times:

- Select two parents by tournament
- Apply crossover with probability  $P_c$
- Apply mutation with probability  $P_m$
- Add child to new-population

Replace population with new-population

Track best solution  $(x, f(x))$

Return best solution found

End Algorithm

Output:

Gen1: Best  $x = -4.3850$ ,  $f(x) = 19.2279$

Gen2: Best  $x = 3.4352$ ,  $f(x) = 11.8008$

Gen3: Best  $x = 3.0554$ ,  $f(x) = 9.3358$

Gen4: Best  $x = 3.6876$ ,  $f(x) = 13.5987$

Gen5: Best  $x = 5.4107$ ,  $f(x) = 29.2759$

⋮

Gen20: Best  $x = 6.6529$ ,  $f(x) = 44.2616$

Best solution found:  $x = 6.6529$ ,  $f(x) = 44.2616$



**Code:**

```
import random
import math

def fitness_function(x):
    return x * math.sin(10 * math.pi * x) + 2

POPULATION_SIZE = 6
GENE_LENGTH = 10
MUTATION_RATE = 0.05
CROSSOVER_RATE = 0.8
GENERATIONS = 20
DOMAIN = (-1, 2)

def random_gene():
    return random.uniform(DOMAIN[0], DOMAIN[1])

def create_chromosome():
    return [random_gene() for _ in range(GENE_LENGTH)]

def initialize_population(size):
    return [create_chromosome() for _ in range(size)]

def evaluate_population(population):
    return [fitness_function(express_gene(chrom)) for chrom in population]

def express_gene(chromosome):
    return sum(chromosome) / len(chromosome)

def select(population, fitnesses):
    total_fitness = sum(fitnesses)
    pick = random.uniform(0, total_fitness)
    current = 0
    for individual, fitness in zip(population, fitnesses):
        current += fitness
        if current > pick:
            return individual
    return random.choice(population)

def crossover(parent1, parent2):
    if random.random() < CROSSOVER_RATE:
        point = random.randint(1, GENE_LENGTH - 1)
        child1 = parent1[:point] + parent2[point:]
        child2 = parent2[:point] + parent1[point:]
        return child1, child2
    return parent1[:], parent2[:]
```

```

def mutate(chromosome):
    new_chromosome = []
    for gene in chromosome:
        if random.random() < MUTATION_RATE:
            new_chromosome.append(random_gene())
        else:
            new_chromosome.append(gene)
    return new_chromosome

def gene_expression_algorithm():
    population = initialize_population(POPULATION_SIZE)
    best_solution = None
    best_fitness = float("-inf")

    for generation in range(GENERATIONS):
        fitnesses = evaluate_population(population)

        for i, chrom in enumerate(population):
            if fitnesses[i] > best_fitness:
                best_fitness = fitnesses[i]
                best_solution = chrom[:]

        print(f'Generation {generation+1}: Best Fitness = {best_fitness:.4f}, Best x =
        {express_gene(best_solution):.4f}')

        new_population = []
        while len(new_population) < POPULATION_SIZE:
            parent1 = select(population, fitnesses)
            parent2 = select(population, fitnesses)
            offspring1, offspring2 = crossover(parent1, parent2)
            offspring1 = mutate(offspring1)
            offspring2 = mutate(offspring2)
            new_population.extend([offspring1, offspring2])

        population = new_population[:POPULATION_SIZE]

    print("\nBest solution found:")
    print(f'Genes: {best_solution}')
    x_value = express_gene(best_solution)
    print(f'x = {x_value:.4f}')
    print(f'f(x) = {fitness_function(x_value):.4f}')

if __name__ == "__main__":
    gene_expression_algorithm()

```

## Output:

```
Generation 1: Best Fitness = 2.3125, Best x = 0.4262
Generation 2: Best Fitness = 2.3125, Best x = 0.4262
Generation 3: Best Fitness = 2.3125, Best x = 0.4262
Generation 4: Best Fitness = 2.3125, Best x = 0.4262
Generation 5: Best Fitness = 2.3125, Best x = 0.4262
Generation 6: Best Fitness = 2.3125, Best x = 0.4262
Generation 7: Best Fitness = 2.3125, Best x = 0.4262
Generation 8: Best Fitness = 2.4233, Best x = 0.6237
Generation 9: Best Fitness = 2.4233, Best x = 0.6237
Generation 10: Best Fitness = 2.4233, Best x = 0.6237
Generation 11: Best Fitness = 2.4233, Best x = 0.6237
Generation 12: Best Fitness = 2.4233, Best x = 0.6237
Generation 13: Best Fitness = 2.4233, Best x = 0.6237
Generation 14: Best Fitness = 2.4233, Best x = 0.6237
Generation 15: Best Fitness = 2.4233, Best x = 0.6237
Generation 16: Best Fitness = 2.4233, Best x = 0.6237
Generation 17: Best Fitness = 2.4395, Best x = 0.4594
Generation 18: Best Fitness = 2.4395, Best x = 0.4594
Generation 19: Best Fitness = 2.4395, Best x = 0.4594
Generation 20: Best Fitness = 2.4395, Best x = 0.4594

Best solution found:
Genes: [0.6948405045559576, -0.647173288232043, -0.3013499383055478, 1.631627548910124, 0.9271637073163099, 0.0324867196364278, -0.3565755055362756, 1.5226396608397925, 1.0654293190513275]
x = 0.4594
f(x) = 2.4395
```

### Program 3

## Particle Swarm Optimization

### Algorithm:

Particle Swarm Optimization

Algorithm

- ① Create a 'population' of agents (particles) uniformly distributed over  $x$
- ② Evaluate each particle's position according to the objective function (say)  
$$y = f(x) = x^2 + 5x + 20$$
- ③ If a particle's current position is better than its previous best position, update it
- ④ Determine the best particle (according to the particle's previous best position)
- ⑤ Update particle's velocities:  
$$v_i^{t+1} = \underbrace{v_i^t}_{\text{inertia}} + \underbrace{c_1 U_1^t (p_{\text{best}}^t - p_i^t)}_{\text{personal influence}} + \underbrace{c_2 U_2^t (g_{\text{best}}^t - p_i^t)}_{\text{social influence}}$$
- ⑥ Move particles to their new positions:  $p_i^{t+1} = p_i^t + v_i^{t+1}$
- ⑦ Go to step 2 until stopping criteria are satisfied

Output:

Iteration 1150 | Best value: 0.786887 at  $[-0.442602479, -0.768758866]$

Iteration 50150 | Best value: 0.000 at  $[9.119794577206948e-09, -2.0957413670574333e-08]$

Optimal solution found:  
Best position:  $[9.119794577206948e-09, -2.0957413670574333e-08]$

Minimal value: 5.140408354217994e-16

Pseudocode

```
p = particle initialization()
for i = 1 to max
    for each particle p in p do
```

$f_1 = f(p)$

If  $f(p)$  is better than  $f(p_{\text{best}})$   
     $p_{\text{best}} = p$   
end  
end  
 $g_{\text{best}} = \text{best } p \text{ in } p$   
for each particle  $p$  in  $p$  do  
     $v_i^{t+1} = v_i^t + c_1 v_i^t (p_{\text{best}}^t - p_i^t) + c_2 v_i^t (g_{\text{best}}^t - p_i^t)$   
     $p_i^{t+1} = p_i^t + v_i^{t+1}$   
end  
end

Application:

## Code:

```
import numpy as np
import matplotlib.pyplot as plt

def objective_function(x):
    return x**2 - 4*x + 4

class Particle:
    def __init__(self, lower_bound, upper_bound):
        self.position = np.random.uniform(lower_bound, upper_bound)
        self.velocity = np.random.uniform(-1, 1)
        self.best_position = self.position
        self.best_value = objective_function(self.position)

    def update(self, global_best_position, w, c1, c2):
        r1 = np.random.rand()
        r2 = np.random.rand()

        self.velocity = w * self.velocity + c1 * r1 * (self.best_position - self.position) + c2 * r2 *
(global_best_position - self.position)
        self.position += self.velocity

        current_value = objective_function(self.position)

        if current_value < self.best_value:
            self.best_value = current_value
            self.best_position = self.position

# PSO parameters
num_particles = 30
num_iterations = 100
w = 0.7
c1 = 1.5
c2 = 1.5
lower_bound = -10
upper_bound = 10

particles = [Particle(lower_bound, upper_bound) for _ in range(num_particles)]

global_best_position = particles[0].best_position
global_best_value = particles[0].best_value
```

```

# PSO loop
for iteration in range(num_iterations):
    for particle in particles:
        particle.update(global_best_position, w, c1, c2)

    if particle.best_value < global_best_value:
        global_best_value = particle.best_value
        global_best_position = particle.best_position

    if iteration % 10 == 0:
        print(f"Iteration {iteration}: Global Best Position = {global_best_position}, Value = {global_best_value}")

print(f"\nOptimal Position: {global_best_position}")
print(f"Optimal Value: {global_best_value}")

x_values = np.linspace(lower_bound, upper_bound, 100)
y_values = objective_function(x_values)

plt.plot(x_values, y_values, label="Objective Function f(x)")
plt.scatter(global_best_position, global_best_value, color='red', label='Optimal Solution (PSO)', zorder=5)
plt.title("Particle Swarm Optimization for Minimizing f(x) = x^2 - 4x + 4")
plt.xlabel("x")
plt.ylabel("f(x)")
plt.legend()
plt.show()

```

### Output:

```

... Iteration 2:
      x      y      vx      vy  pbest_x  pbest_y  pbest_val
0  1.00  1.00 -0.75 -0.750      1.00      1.00      27.000
1 -1.00  1.00  1.25 -0.750     -1.00      1.00      27.000
2  0.50 -0.50  0.25  0.750      0.50     -0.50      25.500
3  1.00 -1.00  0.15  2.000      1.00     -1.00      27.000
4  0.85  0.25  0.00  0.125      0.85      0.25      25.785

Output:
Best position: (0.5, -0.5)
Best value: 25.500

```

## Program 4

### Ant Colony Optimization for Vehicle Routing Problem:

#### Algorithm:

10/10/25

Ant Colony Optimization Algorithm

Pseudocode

Initialize pheromone  $\tau$  on all edges  
Set parameters  $\alpha, \beta, \rho, Q$ , number\_of\_ants, max\_iterations

for  $i = 1$  to max\_iterations:

    for each ant:

        Build a tour by moving probabilistically using pheromone and heuristic info  
        Calculate tour length

    Evaporate pheromone on all edges:  $\tau = (1 - \rho) * \tau$

    for each ant:

        Deposit pheromone on edges used:  $\tau = Q / \text{tour\_length}$

    update best tour if found

return best tour;

Output: Shortest path:  $[(0, 2), (2, 3), (3, 1), (1, 0)]$   
Distance: 9.0

10/10/25

**Code:**

```
import random

import numpy as np

class VRP:

    def __init__(self, depot, customers, capacities):

        self.depot = depot

        self.customers = customers

        self.capacities = capacities

        self.num_customers = len(customers)

        self.num_vehicles = len(capacities)

        self.distance_matrix = self.create_distance_matrix()

    def create_distance_matrix(self):

        dist_matrix = np.zeros((self.num_customers + 1, self.num_customers + 1)) # +1 for depot

        for i in range(self.num_customers + 1):

            for j in range(i + 1, self.num_customers + 1):

                if i == 0:

                    dist = np.linalg.norm(np.array(self.depot) - np.array(self.customers[j-1]))

                elif j == 0:

                    dist = np.linalg.norm(np.array(self.depot) - np.array(self.customers[i-1]))

                else:

                    dist = np.linalg.norm(np.array(self.customers[i-1]) - np.array(self.customers[j-1]))

                dist_matrix[i][j] = dist_matrix[j][i] = dist

        return dist_matrix
```



```

class AntColony:

    def __init__(self, vrp, num_ants, alpha=1, beta=5, rho=0.5, q0=0.9, iterations=100):

        self.vrp = vrp

        self.num_ants = num_ants

        self.alpha = alpha

        self.beta = beta

        self.rho = rho

        self.q0 = q0

        self.iterations = iterations

        self.pheromone = np.ones((vrp.num_customers + 1, vrp.num_customers + 1))

        self.best_solution = None

        self.best_solution_length = float('inf')

    def construct_solution(self, ant_idx):

        unvisited = set(range(1, self.vrp.num_customers + 1))

        routes = {vehicle: [] for vehicle in range(self.vrp.num_vehicles)}

        demands = {vehicle: 0 for vehicle in range(self.vrp.num_vehicles)}

        current_city = 0

        while unvisited:

            vehicle = random.choice(range(self.vrp.num_vehicles))

            if demands[vehicle] < self.vrp.capacities[vehicle]:

                next_city = self.select_next_city(current_city, unvisited)

                routes[vehicle].append(next_city)

```

```

        unvisited.remove(next_city)

        demands[vehicle] += 1

        current_city = next_city

    else:

        continue

for vehicle in range(self.vrp.num_vehicles):

    routes[vehicle].append(0)

return routes

def calculate_probabilities(self, current_city, unvisited):

    probabilities = []

    for city in unvisited:

        pheromone = self.pheromone[current_city][city] ** self.alpha

        distance = self.vrp.distance_matrix[current_city][city]

        heuristic = (1 / distance) ** self.beta

        probabilities.append(pheromone * heuristic)

    total_prob = sum(probabilities)

    if total_prob == 0:

        return [1 / len(unvisited)] * len(unvisited)

    probabilities = [p / total_prob for p in probabilities]

    return probabilities

```

```

def select_next_city(self, current_city, unvisited):

    probabilities = self.calculate_probabilities(current_city, unvisited)

    return random.choices(list(unvisited), probabilities)[0]


def update_pheromones(self, solutions, lengths):

    self.pheromone *= (1 - self.rho)

    for idx, solution in enumerate(solutions):

        length = lengths[idx]

        for route in solution.values():

            for i in range(len(route) - 1):

                self.pheromone[route[i]][route[i + 1]] += 1 / length


def run(self):

    for iteration in range(self.iterations):

        all_solutions = []

        all_lengths = []

        for ant_idx in range(self.num_ants):

            solution = self.construct_solution(ant_idx)

            length = self.calculate_solution_length(solution)

            all_solutions.append(solution)

            all_lengths.append(length)

```

```

        if length < self.best_solution_length:

            self.best_solution = solution

            self.best_solution_length = length

    self.update_pheromones(all_solutions, all_lengths)

    print(f"Iteration {iteration + 1}/{self.iterations}: Best Length = {self.best_solution_length}")

    return self.best_solution, self.best_solution_length

def calculate_solution_length(self, solution):

    length = 0

    for vehicle in solution.values():

        for i in range(len(vehicle) - 1):

            length += self.vrp.distance_matrix[vehicle[i]][vehicle[i + 1]]

    return length

if __name__ == "__main__":

    depot = (0, 0)

    customers = [(2, 4), (3, 2), (6, 5), (8, 3), (7, 8), (5, 7)]

    capacities = [3, 3]

    vrp = VRP(depot, customers, capacities)

    aco = AntColony(vrp, num_ants=10, alpha=1, beta=2, rho=0.5, q0=0.9, iterations=50)

```

```

best_solution, best_solution_length = aco.run()

print("Best Solution (Routes):")

for vehicle, route in best_solution.items():

    print(f"Vehicle {vehicle + 1}: {route}")

print(f"\nBest Solution Length (Total Distance): {best_solution_length}")

```

### Output:

```

... Iteration 1/50: Best Length = 30.704096057970965
Iteration 2/50: Best Length = 25.85324233796014
Iteration 3/50: Best Length = 25.85324233796014
Iteration 4/50: Best Length = 25.85324233796014
Iteration 5/50: Best Length = 25.85324233796014
Iteration 6/50: Best Length = 25.85324233796014
Iteration 7/50: Best Length = 25.80789435080295
Iteration 8/50: Best Length = 25.80789435080295
Iteration 9/50: Best Length = 25.80789435080295
Iteration 10/50: Best Length = 25.80789435080295
Iteration 11/50: Best Length = 25.738177938973646
Iteration 12/50: Best Length = 25.738177938973646
Iteration 13/50: Best Length = 25.738177938973646
Iteration 14/50: Best Length = 22.65045276546171
Iteration 15/50: Best Length = 22.65045276546171
Iteration 16/50: Best Length = 22.65045276546171
Iteration 17/50: Best Length = 22.65045276546171
Iteration 18/50: Best Length = 22.65045276546171
Iteration 19/50: Best Length = 22.65045276546171
Iteration 20/50: Best Length = 22.65045276546171
Iteration 21/50: Best Length = 22.65045276546171
Iteration 22/50: Best Length = 22.65045276546171
Iteration 23/50: Best Length = 22.483842533421615
Iteration 24/50: Best Length = 22.483842533421615
Iteration 25/50: Best Length = 22.483842533421615
Iteration 26/50: Best Length = 22.483842533421615
Iteration 27/50: Best Length = 22.483842533421615
Iteration 28/50: Best Length = 22.483842533421615
Iteration 29/50: Best Length = 22.483842533421615
Iteration 30/50: Best Length = 22.483842533421615
Iteration 31/50: Best Length = 22.483842533421615
Iteration 32/50: Best Length = 22.483842533421615
Iteration 33/50: Best Length = 22.483842533421615
Iteration 34/50: Best Length = 22.483842533421615
Iteration 35/50: Best Length = 22.483842533421615

```

```

Iteration 36/50: Best Length = 22.483842533421615
Iteration 37/50: Best Length = 22.483842533421615
Iteration 38/50: Best Length = 22.483842533421615
Iteration 39/50: Best Length = 22.483842533421615
Iteration 40/50: Best Length = 22.483842533421615
Iteration 41/50: Best Length = 22.483842533421615
Iteration 42/50: Best Length = 22.483842533421615
Iteration 43/50: Best Length = 22.483842533421615
Iteration 44/50: Best Length = 22.483842533421615
Iteration 45/50: Best Length = 22.483842533421615
Iteration 46/50: Best Length = 22.483842533421615
Iteration 47/50: Best Length = 22.483842533421615
Iteration 48/50: Best Length = 22.483842533421615
Iteration 49/50: Best Length = 22.483842533421615
Iteration 50/50: Best Length = 22.483842533421615
Best Solution (Routes):
Vehicle 1: [5, 6, 1, 0]
Vehicle 2: [3, 4, 2, 0]

Best Solution Length (Total Distance): 22.483842533421615

```

## Program 5

### Cuckoo Search Algorithm for Task Scheduling Optimization:

#### Algorithm:

17/10/25

Cuckoo Search Algorithm

Pseudocode

Initialize population of  $n$  nests (solutions)  
Set discovery probability  $P_a$  and max iteration  
Repeat until stopping condition:  
    Generate a new soln by Levy flight  
    Evaluate its fitness  
    Randomly choose a nest  $j$   
    if new soln is better than nest  $j$ :  
        Replace nest  $j$  with new soln  
    Abandon a fraction  $P_a$  of worst nests  
    Create a new random solns for them  
    Keep the best soln found so far  
End repeat  
Return the best soln.

Output:

Best schedule: [6, 5, 4, 3, 2]  
Total time: 20

Application: Task scheduling optimization

**Code:**

```
import random

tasks = [2, 3, 4, 5, 6]
num_tasks = len(tasks)
num_nests = 5
Pa = 0.25
MaxGen = 50

def fitness(schedule):
    """Lower total duration = better fitness."""
    total_time = 0
    for t in schedule:
        total_time += t
    return -total_time

def random_schedule():
    """Create a random schedule (random order of tasks)."""
    s = tasks[:]
    random.shuffle(s)
    return s

def levy_flight(schedule):
    """Generate new schedule by small random changes."""
    new_s = schedule[:]
    i, j = random.sample(range(num_tasks), 2)
    new_s[i], new_s[j] = new_s[j], new_s[i]
    return new_s

nests = [random_schedule() for _ in range(num_nests)]
fitness_values = [fitness(s) for s in nests]

for gen in range(MaxGen):
    for i in range(num_nests):
        new_solution = levy_flight(nests[i])
        new_fitness = fitness(new_solution)

        j = random.randint(0, num_nests - 1)
        if new_fitness > fitness_values[j]:
            nests[j] = new_solution
            fitness_values[j] = new_fitness

    sorted_nests = sorted(zip(fitness_values, nests), reverse=True)
    num_abandon = int(Pa * num_nests)
    for k in range(num_abandon):
        sorted_nests[-(k+1)] = (fitness(random_schedule()), random_schedule())

    fitness_values, nests = zip(*sorted_nests)
```

```
fitness_values, nests = list(fitness_values), list(nests)

best_index = fitness_values.index(max(fitness_values))
print("Best Schedule:", nests[best_index])
print("Total Time:", -fitness_values[best_index])
```

**Output:**

```
... Best Schedule: [6, 5, 4, 3, 2]
    Total Time: 20
```



## Program 6

### Grey Wolf Optimizer (GWO):

#### Algorithm:

19/10/25

Grey Wolf Optimizer

Pseudocode

- ① Initialize parameters: no. of wolves (N), maximum (T)
- ② Initialize the position of each wolf randomly within the search space
- ③ Evaluate fitness of all wolves
- ④ Identify alpha (best), beta (second best), delta (third best) wolves
- ⑤ while ( $t < T$ ) do
  - or for each wolf i:
    - update coefficient vectors A & C
    - compute distances to alpha, beta, delta
    - update position using
$$x_i(t+1) = (x_i + x_p + x_g) / 3$$
  - or enforce search boundaries
  - or Evaluate fitness of updated positions
  - or Update  $\alpha, \beta, \delta$  wolves
  - or  $t = t + 1$
- ⑥ Return alpha wolf position as the best solution

Output:

Best Makespan = 21.60780380

Best Task Allocation (Task  $\rightarrow$  VM)

Task 1  $\rightarrow$  VM 2

Task 2  $\rightarrow$  VM 1

Task 3  $\rightarrow$  VM 4

Task 4  $\rightarrow$  VM 5

Task 5  $\rightarrow$  VM 3

Task 6  $\rightarrow$  VM 5

Task 7  $\rightarrow$  VM 4

Task 8  $\rightarrow$  VM 1

Task 9  $\rightarrow$  VM 1

Task 10  $\rightarrow$  VM 5

Task 11  $\rightarrow$  VM 4

Task 12  $\rightarrow$  VM 3

Task 13  $\rightarrow$  VM 4

Task 14  $\rightarrow$  VM 2

Task 15  $\rightarrow$  VM 3

Task 16  $\rightarrow$  VM 5

Task 17  $\rightarrow$  VM 4

Task 18  $\rightarrow$  VM 4

Task 19  $\rightarrow$  VM 1

Task 20  $\rightarrow$  VM 4

Application: Cloud Task Allocation

**Code:**

```
import numpy as np

num_tasks = 20
num_vms = 5
num_wolves = 15
max_iter = 50

task_load = np.random.randint(1000, 10000, num_tasks)

vm_speed = np.random.randint(500, 2000, num_vms)

def fitness(position):
    """
    position[i] = VM index assigned to task i
    Fitness = total makespan (time to finish all tasks)
    """
    loads = np.zeros(num_vms)
    for i, vm in enumerate(position.astype(int)):
        loads[vm] += task_load[i] / vm_speed[vm]
    return np.max(loads)

wolves = np.random.randint(0, num_vms, (num_wolves, num_tasks))
alpha, beta, delta = None, None, None
alpha_score, beta_score, delta_score = np.inf, np.inf, np.inf

for t in range(max_iter):
    a = 2 - 2 * t / max_iter

    for i in range(num_wolves):
        score = fitness(wolves[i])

        if score < alpha_score:
            alpha_score, alpha = score, wolves[i].copy()
        elif score < beta_score:
            beta_score, beta = score, wolves[i].copy()
        elif score < delta_score:
            delta_score, delta = score, wolves[i].copy()

    for i in range(num_wolves):
        for j in range(num_tasks):
            r1, r2 = np.random.rand(), np.random.rand()
            A1, C1 = 2*a*r1 - a, 2*r2
            D_alpha = abs(C1 * alpha[j] - wolves[i][j])
            X1 = alpha[j] - A1 * D_alpha

            r1, r2 = np.random.rand(), np.random.rand()
```

```

A2, C2 = 2*a*r1 - a, 2*r2
D_beta = abs(C2 * beta[j] - wolves[i][j])
X2 = beta[j] - A2 * D_beta

r1, r2 = np.random.rand(), np.random.rand()
A3, C3 = 2*a*r1 - a, 2*r2
D_delta = abs(C3 * delta[j] - wolves[i][j])
X3 = delta[j] - A3 * D_delta

new_pos = (X1 + X2 + X3) / 3
wolves[i][j] = np.clip(round(new_pos), 0, num_vms - 1)

best_allocation = alpha.astype(int)
best_makespan = alpha_score

print("Best Makespan:", best_makespan)
print("Best Task Allocation (task → VM):")
for i, vm in enumerate(best_allocation):
    print(f" Task {i+1} → VM {vm+1}")

```

### Output:

```

... Best Makespan: 21.60720720720721
Best Task Allocation (task → VM):
Task 1 → VM 2
Task 2 → VM 1
Task 3 → VM 4
Task 4 → VM 5
Task 5 → VM 3
Task 6 → VM 5
Task 7 → VM 4
Task 8 → VM 1
Task 9 → VM 1
Task 10 → VM 5
Task 11 → VM 4
Task 12 → VM 3
Task 13 → VM 4
Task 14 → VM 2
Task 15 → VM 3
Task 16 → VM 5
Task 17 → VM 4
Task 18 → VM 2
Task 19 → VM 1
Task 20 → VM 4

```

## Program 7

### Parallel Cellular Algorithm :

#### Algorithm:

Parallel Cellular Algorithm

Pseudocode

Input:

- Grid size (row, col)
- Neighborhood type: e.g., Moore (8 neighbors) or Von Neumann (4 neighbors)
- Initialize rule: how to set initial states
- Update rule: function  $f(\text{state}, \text{neighbors})$  defining local evolution
- Max steps: no. of iterations

Output:

- Final grid of cell states

1. Initialize:

for each cell  $(i, j)$  in the grid:

state  $[i][j] \leftarrow \text{Initialize\_rule}(i, j)$

2. Repeat for  $t = 1$  to Max steps (or until convergence):

parallel-for each cell  $(i, j)$  in the grid:

neighbors  $\leftarrow \text{get\_neighbors}(\text{state}, i, j, \text{Neighborhood\_type})$

newstate  $[i][j] \leftarrow \text{Update\_rule}(\text{state}[i][j], \text{neighbors})$

state  $\leftarrow \text{new\_state}$

3. Return Final grid state

Output:

Step 1:

```
[0 1 1 0]
[1 0 0 0]
[1 1 1 0]
[0 1 1 0]
```

Step 2:

```
[1 0 1 0]
[1 0 0 0]
[1 0 1 0]
[1 0 1 0]
```

Step 3:

```
[1 0 0 0]
[1 0 0 0]
[1 0 0 0]
[0 0 0 0]
```

Step 4:

```
[1 0 0 0]
[0 0 0 0]
[0 0 0 0]
[0 0 0 0]
```

Final grid state:

```
[1 0 0 0]
[0 0 0 0]
[0 0 0 0]
[0 0 0 0]
```

Application: Image Processing

11/11/25

**Code:**

```
import numpy as np

N = 20
infection_prob = 0.25
infection_duration = 5
steps = 10

grid = np.zeros((N, N), dtype=int)
infection_time = np.zeros((N, N), dtype=int)

for _ in range(5):
    x, y = np.random.randint(0, N, 2)
    grid[x, y] = 1

print("Step | Healthy | Infected | Recovered")
print("-----")

for step in range(steps):
    new_grid = grid.copy()

    for i in range(N):
        for j in range(N):
            if grid[i, j] == 0:
                for dx in [-1, 0, 1]:
                    for dy in [-1, 0, 1]:
                        if dx == 0 and dy == 0:
                            continue
                        ni, nj = (i + dx) % N, (j + dy) % N
                        if grid[ni, nj] == 1 and
np.random.rand() < infection_prob:
                            new_grid[i, j] = 1
                            break
                        elif grid[i, j] == 1:
                            infection_time[i, j] += 1
                            if infection_time[i, j] >
infection_duration:
                                new_grid[i, j] = 2

    grid = new_grid

healthy = np.count_nonzero(grid == 0)
infected = np.count_nonzero(grid == 1)
recovered = np.count_nonzero(grid == 2)
```

```
print(f'{step:>4} | {healthy:>7} |  
{infected:>8} | {recovered:>9}')
```

**Output:**

...	Step	Healthy	Infected	Recovered
	0	388	12	0
	1	371	29	0
	2	338	62	0
	3	301	99	0
	4	244	156	0
	5	200	195	5
	6	162	226	12
	7	106	265	29
	8	64	274	62
	9	30	271	99