



- Exporting the [[Serial peripheral interface](#)] SPI analyzer results into a CSV export will give us the flag. Going through the data you will need to spot it out or filter it.
- I just opened it with Vscide and CTRL + F, for the "H" character and scrolled till i found it and i did.

```
2341
2342 "SPI","result",2.49386454,0.0000019,"ÿ","H"
2343 "SPI","result",2.49386816,0.00000192,"ÿ","T"
2344 "SPI","result",2.4938718,0.0000019,"ÿ","B"
2345 "SPI","result",2.49387542,0.00000192,"ÿ","{"
2346 "SPI","result",2.49387906,0.0000019,"ÿ","u"
2347 "SPI","result",2.49388268,0.0000019,"ÿ","n"
2348 "SPI","result",2.49388632,0.0000019,"ÿ","p"
2349 "SPI","result",2.49388994,0.0000019,"ÿ","2"
2350 "SPI","result",2.49389356,0.00000192,"ÿ","0"
2351 "SPI","result",2.4938972,0.0000019,"ÿ","7"
2352 "SPI","result",2.49390082,0.00000192,"ÿ","3"
2353 "SPI","result",2.49390446,0.0000019,"ÿ","c"
2354 "SPI","result",2.49390808,0.0000019,"ÿ","7"
2355 "SPI","result",2.49391172,0.0000019,"ÿ","3"
2356 "SPI","result",2.49391534,0.0000019,"ÿ","d"
2357 "SPI","result",2.49391898,0.0000019,"ÿ","_"
2358 "SPI","result",2.4939226,0.0000019,"ÿ","5"
2359 "SPI","result",2.49392622,0.00000192,"ÿ","3"
2360 "SPI","result",2.49392986,0.0000019,"ÿ","2"
2361 "SPI","result",2.49393348,0.00000192,"ÿ","1"
2362 "SPI","result",2.49393712,0.0000019,"ÿ","4"
2363 "SPI","result",2.49394074,0.0000019,"ÿ","1"
2364 "SPI","result",2.49394438,0.0000019,"ÿ","_"
2365 "SPI","result",2.493948,0.0000019,"ÿ","n"
```

- The Flag hidden between the lines is
: HTB{unp2073c73d_532141_p2070c015_0n_53cu23_d3v1c35}