

Evidence-Monotone Audio Representation: Preventing Provenance Promotion Across Derived Audio Transformations

A. Urias^{a,*}

^a*Aurtech, C.P. 83220, Hermosillo, Sonora, Mexico*

Abstract

Derived audio can keep its exact waveform while silently strengthening what it says about its own origin. Under a minimal boundary-only inheritance policy (a constructed reference policy, not the behaviour of any named product), a clip assembled from captured and generated material, then trimmed, resampled and re-encoded, emerges described as captured-only: the derived asset inherits from its parent, summarised from the boundaries of the retained region rather than from every source interval the output actually represents. We treat this as a representation problem and specify an operator contract for derived audio: provenance is the union over the complete required source set, same-channel support is the minimum over it, applicability is intersected, lineage is the union, and an unverified source interval is absorbing. The underlying algebra is an instance of a known meet-semilattice construction and is not claimed as new; what is new is the executable temporal instantiation over sample-exact intervals with declared kernel footprints, a signed transport that carries interval evidence inside C2PA temporal regions of interest, and a measured demonstration. No model is trained and no acoustic feature is used. Across 787 443 contract checks over all 9 840 source words of length up to 8 over $\{C, G, \perp\}$, 10 000 frozen adversarial timelines at 5 composition depths, 600 mixed-origin clips transformed by stock FFmpeg through 8 transformations, and 10 860 cases of a two-language differential oracle, complete-source propagation produced 0 contract failures, 0 promotions and 0 lineage omissions, while boundary-only inheritance promoted on 94.5% of adversarial timelines and on 3 600 of 4 800 transformation runs. Decoded essence was identical before and after signing under both policies in 120 signed round-trips across 3 containers, with 0 mismatches; bookkeeping cost 0.95 ms per audio-minute, 0.151% of FFmpeg time, and the evidential cost of the footprints is measured rather than assumed: on the short mechanism corpus, single transformations dilute at most 44.92% of a clip's samples, in fixed-radius bands at ancestry boundaries; deep composition chains on such short assets can dilute most of the asset, while the same three-operator broadcast-style chain on a 30-second asset dilutes 2.40%. The cost of conservatism is quantified here, not hidden. The contract constrains what a derived representation may claim about its sources; it does not detect deepfakes, does not establish that speech is truthful, and a cryptographically valid signature proves only that an assertion was signed, not that it is true.

Keywords: digital evidence, media provenance, content credentials, C2PA, audio forensics, synthetic speech, chain of custody

*Corresponding author. ORCID: 0009-0007-3147-323X.

Email address: alex@aurtech.mx (A. Urias)

1. Introduction

Speech can now be generated convincingly enough that the question “is this recording real?” is answered less and less reliably by listening to it. Two different mechanisms have grown up in response. Detection asks whether a signal carries the traces of synthesis [1, 2]. Provenance asks what an asset’s own cryptographically signed history says about where it came from [3]. These answer different questions, and this work is about the second one, so nothing here is a detection result.

Provenance systems bind assertions to an asset. They do not, on their own, say what a derived asset is entitled to assert. That gap opens as soon as audio is edited, because editing is routine: a broadcast clip is trimmed, a podcast segment is spliced, a submitted exhibit is resampled and re-encoded before it reaches an examiner. Each of those steps produces a new asset whose manifest is written by whatever software performed the step. The C2PA specification describes the relationship such an asset has to its input with the ingredient relationship `parentOf`, whose meaning is given as “The current asset is a derived asset or asset rendition of this ingredient” [3, Table 10, §18.16.3]. The specification’s vocabulary is in fact rich enough to carry everything the problem needs: a composed asset records each component as a `componentOf` ingredient with its own manifest history, a generative origin can be marked with a `digitalSourceType`, and an assertion can be scoped to a temporal range. What the text does not prescribe, and we searched it for such a rule, is the *reduction*: the aggregate evidence state a derived interval should emit when the component histories it represents disagree. The specification can preserve the component histories; it does not define the conservative claim that must be computed over them. That distinction is the entire subject of this paper, and it means the contribution here is not a competing provenance system but a semantic aggregation contract that operates inside the standard’s own vocabulary.

The consequence is concrete. Consider five consecutive source intervals of a recording whose third interval is generated speech and whose other four are captured. A derived asset representing all five can be described from its retained boundaries, which are captured, and emerge labelled captured-only. The decoded audio is bit-identical either way. Only the evidential claim differs (Figure 1). In a forensic setting that difference is the whole point: an examiner reading a captured-only claim over an interval that contains generated speech is being told something stronger than the sources support, by a chain in which no signature was forged and no cryptographic primitive failed.

We call this *provenance promotion*: a derived representation acquiring a stronger evidential claim than the complete source material it represents, without any change to the decoded signal. The requirement that prevents it is what we call *evidence monotonicity*: along a chain of representation-only transformations, the emitted claim must be no stronger than the meet of every required source, ancestry accumulates rather than disappears, and the absence of verified evidence is absorbing.

An earlier instantiation of that requirement exists for spatial data, where derived terrain geometry can overstate the evidence of the source arc it replaces [4]. This work asks whether the requirement is usable in a temporal medium with a real signed transport and real processing software, and what it costs. It is not a re-presentation of that work: Table 1 states exactly what is inherited and what is new, no earlier result is reused, and the row-by-row transfer analysis is Supplementary Note S1. The short version is that the algebra transfers and almost nothing else does: temporal interval maps, the kernel-footprint problem and its monotonicity resolution, the guard-band validation against third-party processing, signal transparency on decoded PCM, and the signed transport have no spatial analogue.

We are equally explicit about what is *not* new. The algebra we use, a meet over a lattice of labels with union of ancestry and an absorbing bottom element, is an instance of constructions that


Table 1: Relation to the spatial predecessor [4]. Inherited elements are prior work and are cited, not claimed; every reported number in this paper is new.

Inherited from the spatial work	New in this work
Evidence record (P, S, A, L) ; provenance as an atom set with mixed by union	Temporal required-source sets over half-open sample intervals
Same-channel meet by minimum; scope intersection; lineage union	The captured/generated alphabet and the capture-support channel
Absorbing unverified state	Requirement (iv’): a $\perp$ source also withholds every numeric channel
Non-promotion in the spatial setting	Kernel footprints with declared guard bands, validated per clip against stock FFmpeg; footprint monotonicity (Proposition 4)
Conformance-test methodology (exhaustive enumeration, frozen fixtures, independent oracle)	Signal transparency on decoded PCM; signed C2PA transport with temporal regions; the claim-dilution cost metric

are decades old, in provenance annotation over absorptive semirings [5] and in label lattices for secure information flow [6, 7]. We therefore do not claim the non-amplification property as a new theorem. We state it as an instance, prove the parts that are specific to the temporal setting, and locate the contribution in what is executable and measured.

Contributions.. Each is traceable to a completed experiment.

1. An operator contract for derived media stated without reference to any modality, with its non-amplification property presented as an instance of a known meet-semilattice construction rather than as a new theorem (Section 4).
2. A temporal audio instantiation over sample-exact half-open intervals for eight representation operators, each with a declared conservative kernel footprint, together with a footprint-monotonicity result showing that over-approximating the required source set is always safe (Section 5, Proposition 4).
3. A signed transport in which interval-level evidence is carried inside C2PA temporal regions of interest and survives derivation and re-signing, demonstrated end-to-end on 3 audio containers with 120 round-trips, plus a C2PA-native heterogeneous composition in which signed captured and generated sources become `componentOf` ingredients with spec-conformant `c2pa.placed` references and the EM aggregate rides alongside (Sections 5.4, 7.5, 7.6).
4. A policy ablation showing that complete-source aggregation and declared kernel footprints are each necessary and neither sufficient: removing either one produces promotion on every timeline of the arm it fails (Section 7.3).
5. An executable conformance suite: 787 443 checks over every source word of length up to 8 over $\{C, G, \perp\}$, with 0 failures, and a two-language differential over 10 860 frozen cases with 0 disagreements (Sections 7.1, 7.8).
6. A measured demonstration on 600 mixed-origin clips processed entirely by stock FFmpeg, in which the interval model is validated against the behaviour of software we do not control and the guard bands are shown adequate (Section 7.4).



The waveform is identical under both policies. Only the evidential claim differs.

Figure 1: The minimal temporal counterexample. Five source intervals, of which the third is generated-derived. A boundary-only reading of the retained region sees captured evidence at both ends and may emit CAPTURED; the complete-source rule sees $C + C + G + C + C$ and emits MIXED $\{C, G\}$. The decoded audio is identical under both policies.

7. A cost measurement on both axes that matter: runtime, where bookkeeping is 0.151% of the processing time it accompanies and the assertion grows linearly in evidence intervals at 333 B per interval (Section 7.9); and *evidential* cost, a claim-dilution metric showing that the conservatism the footprints buy is priced in samples per ancestry boundary, not in fractions of the asset (Section 7.7).

Three framing sentences apply throughout. The contract does not infer authenticity from acoustic features; it prevents a provenance-aware processing chain from promoting a mixed or unverified source interval into a stronger captured-only class. An unsigned or provenance-stripped asset is classified as unverified, never as synthetic. The contract is orthogonal to passive deepfake detectors and to watermarking systems, and composes with either.

Transparency obligations for synthetic content under Article 50 of Regulation (EU) 2024/1689 became applicable on 2 August 2026 [8], which makes machine-readable origin claims about derived media operationally relevant. We make no legal claim about what any particular disclosure regime requires.

2. Related work

Detection of synthetic speech.. Anti-spoofing and deepfake-speech detection classify a signal by its acoustic traces, with challenge resources and surveys documenting both the progress and the generalisation gap when detectors meet unseen attacks or unseen codecs [2, 1]. What this line guarantees is a decision about a signal. What it does not do is constrain what a derived asset may assert about its own sources, and it needs no source evidence to exist. The two are complementary: a detector can be run on an asset whose evidence chain is intact, and the contract here says nothing about what the detector should conclude.

Watermarking and soft bindings.. Localised audio watermarking marks generated speech at synthesis time and detects the mark per region [9]; C2PA treats watermarking and fingerprinting as *soft bindings* used to recover a manifest that has been separated from its asset [3, §18.10]. These guarantee recoverability and, in the localised case, region-level presence of a mark. They do not define what the aggregate evidence claim of a derived asset should be when its sources differ, and a region that carries no mark is not thereby captured.

Cryptographic media provenance.. C2PA binds signed assertions and transformation history to an asset, defines ingredient relationships `parentOf`, `componentOf` and `inputTo`, and supports assertions scoped to part of an asset through regions of interest, including temporal ranges in normal play time [3, §18.2.2.3, §18.16.3]. Security analyses of the standard and its implementations report problems in the cryptographic and trust layers: timestamp disagreement, certificate revocation handling, and inconsistent validator behaviour [10]. Related work constructs assets whose manifest and whose watermark make contradictory claims that each pass their own verification, through ordinary editing workflows and without any cryptographic compromise [11]. Our concern is a different layer again, and it is orthogonal to both: assuming keys are intact, signatures verify, and no assertion is omitted in bad faith, is the assertion that a conforming derived asset emits conservative with respect to every source interval it represents? The distinction matters because the specification already preserves a great deal: a `componentOf` ingredient carries its own manifest, composition is required to record the placed components, and a generative component can carry a `digitalSourceType` [3, §18.16.3]. A consumer walking the full ingredient graph could in principle reconstruct everything. What the text does not define is the aggregate: when a five-second derived interval represents four captured components and one generated one, no normative rule states that the interval’s own evidence claim must be the conservative reduction over all five rather than an inheritance from its parent. We read the specification for a rule of that kind and did not find one; the specification governs how assertions are bound and validated, not how an aggregate evidence claim over heterogeneous sources must be computed.

Provenance for edited audio.. Two recent lines are the closest work in this medium. Chunk-localised speech provenance binds short time segments to an issuer-signed original through perceptual fingerprints and Merkle commitments, addressing exactly the fragility of hard bindings under re-encoding [12]. Zero-knowledge constructions prove that an edit was drawn from an allowed operation set while hiding the source, the edits and the device [13]. Both provide something this work does not: the first re-establishes the link between a time segment and a signed original after transport, the second proves edit correctness without disclosure. Neither states an aggregation rule for what the derived asset’s evidence claim may be when the sources it represents disagree, and neither proves a non-amplification property.

Table 2: Positioning. Each row names a guarantee the line already provides, then the evidence property it does not, by itself, enforce on a derived audio interval. The contribution here is the joint enforcement of the right-hand column through representation-only operators, not the reinvention of any left-hand guarantee.

Line of work	Guarantee it provides	Left unenforced on a derived interval
Synthetic-speech detection [2, 1]	A decision about a signal from its acoustic traces	What the derived asset may assert about its own sources
Localised watermarking and soft bindings [9, 3]	Region-level presence of a mark; recovery of a separated manifest	Aggregation of heterogeneous source evidence into one claim
Cryptographic provenance [3]	Signed assertions, ingredient relationships, temporal regions of interest	A rule requiring the derived claim to be conservative over all ingredients
C2PA security analysis and cross-layer attacks [10, 11]	Weaknesses in the trust, timestamp and validator layers; contradictions between layers	Behaviour of a chain in which every layer is intact and honest
Provenance for edited audio [12, 13]	Chunk-to-original binding after transport; zero-knowledge edit correctness	An aggregation rule when represented sources disagree
Provenance graphs and lineage [14]	A truthful record of derivation	Operator-level monotonicity as an executable contract
Provenance semirings and information-flow lattices [5, 6]	The algebra of conservative combination	A temporal media instantiation with a signed transport

Provenance models and information flow. W3C PROV records derivation as a graph [14]: a PROV record can state truthfully that a segment was derived from a source while a consumer still reads the segment’s evidence from its boundaries. Concretely, a PROV graph for the five-interval counterexample would contain `wasDerivedFrom` edges to all five source intervals, a complete and true derivation record, and still say nothing about which *claim* the derived segment may emit, because PROV constrains the shape of the history, not the aggregation of evidential authority over it. The algebraic machinery for constraining that reading is long established. Provenance semirings annotate derived data so that annotations combine associatively and idempotently [5]; lattice models of secure information flow classify objects and require that combination move only in the conservative direction [6, 7]. The property we need, that a combination is never stronger than any of its inputs, is the meet in such a structure, and we present it as such rather than as a discovery.

The gap. Table 2 places these lines side by side. Each row states what that line does guarantee before naming the property it leaves unenforced on a derived audio interval. No row provides an operator-level complete-source rule instantiated over media time and carried in a signed transport; that combination is what this work contributes, and the matrix behind the table, with search dates and query strings, is Supplementary Note S2.

3. Threat model

In scope. Provenance promotion and laundering through representation-only transformations, under four conditions: source evidence exists; the processing system holds the source-to-output mapping;

the operator is expected to conform to the contract; and cryptographic primitives and signing keys are intact.

Out of scope. Capture devices that lie about what they recorded; compromised signing keys; dishonest certificate authorities; unsigned media of unknown origin; speaker identity; the truthfulness of what is said; semantic misinformation; waveform-artefact deepfake detection; watermark removal; and full provenance stripping followed by construction of a fresh, dishonest trust chain. Attacks on the cryptographic and trust layers are the subject of separate analyses [10] and are assumed away here precisely so that the residual semantic question is isolated.

Required behaviour when evidence is absent or invalid. The state is UNVERIFIED or INVALID. It is never automatically “fake” and never automatically “captured”. An asset can lose its manifest for entirely benign reasons, and nothing in this work licenses reading a missing manifest as evidence of intent.

Malicious signer. Cryptographic validity proves that an assertion was signed, not that it is true. A signer willing to assert falsehoods can produce a valid manifest containing them, and no propagation rule inside the processing chain can prevent that. The contract constrains conforming operators; it is not a defence against a dishonest issuer. A threat-model matrix pairing attacker capability against contract behaviour and against what is explicitly not prevented is Supplementary Table S3.

4. Formal model

4.1. Evidence records

Let a source asset be partitioned into elements. Each element x carries an evidence record

$$e_x = (P_x, S_x, A_x, L_x), \quad (1)$$

where P_x is provenance, S_x is a partial map from a semantically typed support channel to $[0, 1]$, A_x records the scope over which each channel is declared applicable, and L_x is lineage.

Provenance is a set of ancestry atoms drawn from $\{C, G\}$, for captured-derived and generated-derived sources. Mixed ancestry is $\{C, G\}$ and is produced only by union; it is never a primitive. The absence of verified evidence is a distinct state $\perp$. It is not an atom, and it is never silently mapped onto C or G . The presentation labels CAPTURED, GENERATED, MIXED and UNVERIFIED are rendering choices; the normative fields are P , S , A and L . The word REAL is not used as a provenance state anywhere in the model, the implementation or the serialisation.

4.2. The claim order and its meet

Write $\widehat{\mathcal{C}} = \{\perp\} \cup (2^{\{C, G\}} \setminus \emptyset)$ for the set of provenance claims, ordered by

$$q_1 \sqsubseteq q_2 \iff q_1 = \perp \text{ or } (q_2 \neq \perp \text{ and } q_1 \supseteq q_2), \quad (2)$$

read “ q_1 is no stronger than q_2 ”. A larger atom set is a weaker, less specific claim, and $\perp$, which asserts nothing, is the bottom element. Under this order $\widehat{\mathcal{C}}$ is a meet-semilattice whose meet is

$$q_1 \sqcap q_2 = \begin{cases} \perp & \text{if } q_1 = \perp \text{ or } q_2 = \perp, \\ q_1 \cup q_2 & \text{otherwise.} \end{cases} \quad (3)$$

This is an instance of a standard construction: an idempotent, commutative, associative combination with an absorbing element, of the kind used to annotate derived data in provenance semirings [5] and to classify objects in information-flow lattices [6]. We record it explicitly rather than deriving it as a novelty.

4.3. The complete-source operator

Let a representation operator T produce output element y from the *complete required source set* $D_y = \{x_1, \dots, x_k\}$. Two notions of dependency must be distinguished here, because they diverge for some operators. The *representational* dependency of y is the source content y stands for: what a listener at y 's position is hearing a representation of. The *computational* dependency is the set of source samples that numerically influence y 's value. The contract governs the representational reading: D_y is every source element whose content y represents. The kernel footprint then reconciles the two where signal processing makes them bleed together. A resampling filter makes neighbouring content numerically influence y , and since the direction of that influence cannot be distinguished from representation at the contract's level of abstraction, the footprint conservatively enlarges D_y to cover it. The one v1 operator for which the two readings diverge completely is amplitude normalisation, whose scalar gain is computed from the whole signal while each output sample represents exactly one source sample; Section 9 states the choice made there and its tested alternative. Write $D_y^\mu = \{x \in D_y : \mu \in A_x\}$ for the sources that declare channel μ applicable. The contract requires:

- (i) **Provenance** $P_y = \bigcap_{x \in D_y} P_x$, that is, the exact union of the required source provenance sets, with $\perp$ absorbing and with no invented ancestry.
- (ii) **Support** if $P_y \neq \perp$, $D_y^\mu \neq \emptyset$ and every member of D_y^μ supplies a value, then $S_y(\mu) = \min_{x \in D_y^\mu} S_x(\mu)$; otherwise the channel is *unavailable*.
- (iii) **Applicability** $A_y(\mu) \subseteq \bigcap_{x \in D_y^\mu} A_x(\mu)$; an empty intersection makes the channel unavailable.
- (iv) **No partial subsets** a channel applicable to some required source but unreported by it is unavailable on the output; it is never computed from the remaining sources.
- (iv') **Unverified absorption for channels** if any required source is in state $\perp$, every numeric channel on the output is unavailable.
- (v) **Lineage** $L_y = \bigcup_{x \in D_y} L_x$, identifying the complete required source set directly or reproducibly.

Requirement (iv') is the one place where this model is strictly stronger than its spatial predecessor, and it needs a justification. An element in state $\perp$ carries no evidence record at all, so nothing is declared about any channel over the span it occupies. Computing a numeric channel from the remaining, verified sources would be exactly the partial-subset computation that (iv) forbids, applied to the represented span rather than to the channel. Making every channel unavailable is the conservative resolution, and it is tested separately in the conformance suite.

4.4. Properties

Proposition 1 (Exact union; no promotion). *Under (i), P_y contains every atom present on a required source and no other, and $P_y \subseteq P_x$ for every $x \in D_y$.*

Proof. Immediate from (3): if no source is $\perp$ then P_y is the union, which contains each P_x and hence is $\sqsubseteq P_x$ by (2); if some source is $\perp$ then $P_y = \perp \sqsubseteq q$ for every q . Membership of an atom in P_y requires membership in some P_x , so no ancestry is invented. $\square$

Proposition 2 (Unverified non-promotion). *If any $x \in D_y$ has $P_x = \perp$ then $P_y = \perp$, and no numeric channel is emitted.*

Proof. Absorption in (3) gives $P_y = \perp$; requirement (iv') then withholds every channel. $\square$

Proposition 3 (Typed support and scope non-promotion). *For every emitted channel μ , $S_y(\mu) \leq S_x(\mu)$ for every $x \in D_y^\mu$, and $A_y(\mu)$ is no broader than any $A_x(\mu)$.*

Proof. The minimum over a set is bounded above by each member; requirement (ii) refuses to emit unless every applicable source supplies a value, so the minimum is taken over the complete applicable set rather than a subset. Repeated intersection in (iii) cannot enlarge a set. $\square$

Theorem 1 (Closure under composition). *A finite composition of operators each satisfying (i)–(v) satisfies (i)–(v), and the composed claim is no stronger than the meet over the union of all ancestral required source sets.*

Proof. Associativity and commutativity of $\sqcap$ make the composed provenance the meet over the union of the ancestral sets, so no ancestor is dropped or invented; absorption of $\perp$ is preserved inductively because no later operator receives a verified element in place of an unverified ancestor. For a channel μ , each operator either refuses the channel or emits a value bounded by its applicable inputs, and transitivity of $\leq$ bounds the final value by every applicable ancestor. Repeated intersection cannot broaden a scope, and lineage composes by union of the per-operator source maps. $\square$

The property in Theorem 1 is the standard consequence of combining in a meet-semilattice and is stated here for completeness rather than as a new result. The next proposition is specific to the temporal setting and is what makes the contract implementable against real processing software.

Proposition 4 (Footprint monotonicity). *If $D_y \subseteq D'_y$ then the claim computed from D'_y is no stronger than the claim computed from D_y , and each emitted channel value is no greater.*

Proof. Enlarging the index set of a union can only add atoms, and by (2) a superset is a weaker claim; adding a source in state $\perp$ sends the claim to $\perp$, which is weaker still. For channels, enlarging D_y can only add members to D_y^μ , and the minimum over a larger set is no larger; if an added source declares μ applicable but reports no value, the channel becomes unavailable, which is weaker than any value. $\square$

Proposition 4 is the practical result of this section. It means an implementation does not need the exact dependency set of a filtered operator: a *conservative over-approximation* is always safe, and only under-approximation can promote. That converts an intractable requirement, knowing exactly which input samples every output sample depends on inside a third-party codec, into a tractable one: declare a bound, and test that the bound holds.




Figure 2: Where the contract sits. Stock FFmpeg performs the transformation; the interval map with its declared kernel footprint determines the complete required source set; the complete-source meet produces the emitted evidence; the result is serialised as C2PA temporal regions of interest and signed. The evidence path never touches the signal path, which is what signal transparency (P8) measures.

Signal transparency (P8).. Finally, the contract must not change the audio. We define the canonical essence of an asset as the SHA-256 of its decoded stream rendered to signed 16-bit little-endian PCM at the asset’s own rate and channel count, and require that essence be identical whether the EM assertion or the baseline assertion is attached. Whole-file hashes are unusable for this purpose, because embedding a manifest changes the file by construction; the distinction matters and is measured in Section 7.5.

5. Audio instantiation

5.1. Temporal intervals

All positions are sample indices on a named asset and all intervals are half-open $[a, b)$, matching the C2PA convention that “All start times are inclusive of that moment in time, and all end times are, by default, exclusive of it” [3, §18.2.2.3]. A source timeline is a gapless ordered partition of an asset into evidence-homogeneous intervals.

An operator emits a set of *map pieces*. A piece states that output range $[o_a, o_b)$ represents source range $[s_a, s_b)$ on a named asset, together with a footprint radius in source samples. Where pieces overlap, as in a mix or an overlay, the required source set of an output interval is the union over every piece covering it, so an overlapped region represents both sources. The emitted output partition is the pull-back of every source evidence boundary across every piece, which gives each emitted interval a stable complete source set.

5.2. The v1 operator set and its kernel footprints

Table 3 gives the eight operators in scope with their mapping and declared footprint. Pitch shifting is deliberately not a ninth primitive: its common implementations are compositions of operators already in scope, a rate change reinterpreted plus a compensating time stretch, so its contract behaviour follows from Theorem 1 applied to those two, with the composed footprint the composition of theirs; a phase-vocoder implementation would instead declare its own analysis-window footprint, exactly as time stretching does. A named regression test exercises the composite.

Table 3: The v1 operator set. Footprints are conservative bounds in source samples, quoted for the configurations used in the experiments; by Proposition 4 an over-declared bound can only weaken the emitted claim, while an under-declared bound is a conformance failure.

Operator	Source mapping	Footprint	Reason
trim / crop	1:1 on the retained range	0	exact
concatenate	1:1 per part	0	exact
resample	$n_{\text{out}} \cdot f_{\text{in}} / f_{\text{out}}$	33	polyphase FIR
transcode (MP3)	1:1	2304	MDCT window + encoder delay
transcode (FLAC)	1:1	0	lossless
amplitude normalisation	1:1	0 (strict: whole signal)	scalar gain
time stretch	$t_{\text{src}} = \tau t_{\text{out}}$	2577	overlap-add window
silence removal	explicit retained runs	2048	frame-granular selector
mix / overlay	1:1 from every covering source	0	sample-wise sum

Denoising, source separation, speech enhancement and generative editing are out of scope: they are not representation-only, and a generative edit legitimately introduces new ancestry rather than propagating existing ancestry.

The footprint entries deserve comment, because a reviewer will look for an off-by-one. For a polyphase resampler the radius follows from the pinned filter length and the rate ratio. For MPEG-1 Layer III the long window is 1152 samples with 50% overlap and the encoder introduces a further delay, so the declared value covers a full window plus that delay. For overlap-add time stretching it covers the analysis window scaled by the tempo factor. For a frame-granular selector such as silence removal, the exact retained-sample model and the implementation’s frame-aligned cut points differ, and the declared value covers that difference. In every case the declared value is a bound, not an estimate, and Proposition 4 makes an over-declared bound safe. The experiment in Section 7.4 measures, for every clip and every transformation, whether the bound actually holds against the output of software we do not control.

5.3. The baseline reference policy

The comparison policy throughout is *boundary-only, primary-parent inheritance*: the derived output inherits from its parent ingredient, evaluated at the first and last source elements of the retained region, ignoring kernel footprints. It is a **constructed reference policy**. It is not a description of the behaviour of any shipping product, and no claim is made here about what any named tool does. Its motivation is the specification text: a derived asset’s relationship to its input is **parentOf**, defined as “The current asset is a derived asset or asset rendition of this ingredient” [3, Table 10, §18.16.3], and the minimal way to inherit from a parent over a retained region is to read that region’s endpoints. The policy is minimal by design because the point of the comparison is to isolate one mechanism, not to caricature an opponent.

The baseline combines two independent shortcuts, boundary-only inheritance and blindness to the kernel footprint, so the experiments also evaluate the two intermediate policies that remove one shortcut each, and report all four (Section 7.3).

5.4. Signed transport

Evidence is carried as a namespaced C2PA assertion, `mx.aurtech.emaudio.evidence`, with one entry per output evidence interval. Each entry gives a temporal region of interest as an `npt` range [3, §18.2.2.3], the sample-exact bounds alongside it because `npt` strings are lossy at sample resolution, the provenance atom list (`null` for unverified, never an atom), the available support channels, their applicability scopes, and the lineage set. Derivation records the source as an ingredient with relationship `parentOf`; the specification requires a corresponding `c2pa.opened` action carrying a hashed-URI reference to that ingredient assertion [3, §15.11.3.2], which the claim generator inserts. Composition records each source as a `componentOf` ingredient carrying its full source manifest, with a `c2pa.placed` action referencing each component’s ingredient assertion [3, §18.16.3], so the transport exercises exactly the composition vocabulary whose missing aggregation rule motivates the paper (Section 7.6). The full schema, with a worked manifest, is Supplementary Note S4.

The transport is a bridge, not a re-implementation: signing and validation are performed by the official `c2patool`, so the transport guarantees are the tool’s. The choice of C2PA is not load-bearing for any claim in this paper. The contract is defined over source sets and typed evidence, and the same assertion can be carried in a detached signed sidecar; the experiments use C2PA because it is the deployed standard and because doing so tests the mapping against a real validator.

6. Methods

6.1. Study design

The experiments separate three questions that are easy to conflate: whether the implementation realises the stated guarantees (a mathematical question, answered by exhaustive enumeration and by differential testing); whether a competing metadata rule produces counterexamples on adversarial and on realistic input (a mechanism question, answered by frozen fixtures and a labelled corpus); and what the contract costs (an engineering question, answered by timed repetitions). Exact algebraic properties and finite-state classifications are reported as deterministic counts and are not assigned *p*-values. Fixture failure frequencies characterise the frozen fixture family and are a **mechanism stress rate**: they are not, and must not be read as, an estimate of how often any deployed system promotes provenance.

6.2. Deterministic fixtures

Experiment A enumerates every source word of length 1 to 8 over $\{C, G, \perp\}$, giving 9 840 words, and pushes each through up to ten operator configurations. Two configurations require a minimum word length: the inner trim needs at least three elements and silence removal at least two. So the 3 single-element words receive eight configurations, the 9 two-element words nine, and the remaining 9 828 words the full ten, giving 98 385 cases. Each case is checked against the full property suite and against an independent closed-form oracle that recomputes the expected state directly from the operator’s nominal source ranges without using the evidence algebra; for zero-footprint operators the states must match exactly, and for kernel operators the emitted claim may only be weaker.

Experiment B freezes 10 000 timelines of 64 source intervals each, generated from a fixed seed, in which the majority of intervals are captured and one to four *non-boundary* intervals are replaced by generated or unverified evidence. Each is pushed through composition chains of depth 1 to 5 and, separately, through each operator alone. Because the anomalies are deliberately placed away from the boundaries, the baseline’s failure rate on this family is high by construction; to make that

explicit the experiment includes a control arm in which anomaly positions are drawn uniformly over all positions, for which the baseline’s promotion probability has the closed form $\binom{n-2}{k}/\binom{n}{k}$ for k anomalies of a single type over n positions. Agreement between the measured rate and that closed form is an analytic check on the harness.

6.3. Mixed-origin audio corpus

600 clips are built deterministically, each of the form captured | generated | captured with sample-exact ground truth. Captured segments are crops of LibriSpeech **dev-clean** [15], licensed CC BY 4.0 with the licence text read from the file shipped inside the archive; generated segments are produced locally by eSpeak NG formant synthesis from phrases written for this study. No speaker is identified, no voice is cloned, and no speaker-identity claim is made. Segment durations are matched so that the generated region is a modest interior interval rather than a synthetic clip with captured fragments attached. Licences, versions, URLs, access dates and checksums are recorded in `DATA_LICENSES.md` in the repository.

Because the evidence algebra reads no acoustic feature, the result cannot in principle depend on signal character; a supplementary robustness arm demonstrates this empirically rather than leaving it to argument, rebuilding 50 clips with a modern neural TTS (Piper, a VITS-architecture engine, with a voice trained on the public-domain LJSpeech corpus) in place of formant synthesis, and overlaying 50 clips with locally generated pink noise at -18 dB so that every ancestry boundary is acoustically buried.

Concatenation and every subsequent transformation are performed by **stock FFmpeg through its command line, with no project code in the signal path**. This matters for the same reason a third-party generalizer mattered in the spatial setting: the artefact that either does or does not exhibit promotion is produced by software the author does not control, and only the evidence policies are under study.

6.4. Metrics

We report promotion counts and rates, lineage-omission counts, unverified-to- verified promotions, support promotions, conformance failures, decoded-essence mismatches, manifest validation outcomes, model-versus-implementation sample deviations, runtime and metadata size. We deliberately do not report accuracy, precision, recall, F_1 or AUC: no classifier is evaluated, and detector metrics would invite the wrong comparison. Timing is reported as medians with interquartile ranges over 30 repetitions with the machine declared.

6.5. Reproducibility and AI use

Every number in this manuscript is emitted by code into `results/machine_readable/`, converted into a $\text{\LaTeX}$ macro by a generator script, and used in the text through that macro; no result is typed by hand. Every figure is rendered from the same files. `run_all.sh` exits non-zero if any conformance check fails. Generative-AI tools were used as programming and review assistants during development of the verification tooling and in preparing the manuscript; all reported outcomes were produced by executing the committed deterministic code, and the author reviewed and verified every claim, calculation, code-derived number and reference.

7. Results

7.1. Exhaustive conformance

Over 9 840 source words and 98 385 operator cases, the property suite and the closed-form oracle together evaluated 787 443 checks with 0 failures, including 363 explicit composition cases. Every named regression test passes: 28 of 28, with 0 failures (Table 6).

The suite has teeth. During development it failed on the overlay operator, where the implementation evaluated overlapping map pieces independently and so emitted a captured claim and a generated claim over the same output interval instead of one mixed claim. That was a genuine defect in our own code, found by the test named for it, and fixed by making the output partition global across pieces. We report it because a conformance suite that has never failed is evidence of nothing.

7.2. Adversarial timelines

On 10 000 frozen timelines, boundary-only inheritance promoted the provenance claim on 9 455 timelines (94.5%) at composition depth 1 and on 9 455 at depth 5; complete-source propagation produced 0 promotions summed over every depth, 0 unverified-to-verified promotions, 0 lineage omissions and no support promotion. Boundary-only inheritance omitted required lineage on 10 000 timelines at depth 1 and reported 7 222 unverified spans as verified.

The rate does not rise with depth, and that is the finding rather than a flat line on a chart: the loss is established at the first derivation and is irreversible, because once the interior evidence has been discarded no downstream operator can recover it (Figure 3, left). Across the 9 operator configurations applied singly, baseline promotion ranged from 94.3% to 100.0%, and complete-source propagation produced 0 promotions in total (Figure 3, centre).

In the control arm, where anomaly positions are uniform over all positions rather than confined to the interior, measured baseline rates agreed with the closed-form prediction to within 0.0070 in absolute rate (0.70 percentage points) in every cell (Figure 3, right). This is the honest reading of the adversarial arm: its near-unity rate is a property of the deliberate construction, arithmetically predictable, and carries no information about deployed software. The informative quantity is the exact zero on the other side.

7.3. Which shortcut matters: a policy ablation

The baseline combines two shortcuts, and it is fair to ask which one does the damage. Removing them one at a time over 10 000 timelines per arm gives an unambiguous answer (Table 4). In the *interior* arm the anomaly lies inside the nominal represented range, so only the inheritance axis can see it: both boundary-only policies promoted on every timeline (10 000 and 10 000) and both complete-source policies on none. In the *footprint* arm the anomaly lies just outside the nominal range but inside the operator’s declared kernel footprint, so only the footprint axis can see it: both footprint-blind policies promoted on every timeline (10 000 and 10 000) and both footprint-aware policies on none.

Neither axis is redundant and neither is sufficient. Complete-source aggregation without a declared footprint fails exactly the case that filtered operators create, and a declared footprint without complete-source aggregation fails exactly the case that interior edits create. Only the full contract clears both arms, which is the argument for specifying them together rather than separately.



Figure 3: Boundary-only versus complete-source inheritance on 10 000 deterministic timelines. Left: promotion does not grow with composition depth because the loss is established at the first derivation and is irreversible. Centre: per-operator rates when each operator is applied alone. Right: control arm with anomaly positions uniform over all positions, measured against the closed form $\binom{n-2}{k}/\binom{n}{k}$. Percentages quantify mechanism stress on a frozen fixture family; they are not real-world prevalence.

Table 4: Policy ablation over 10 000 timelines per arm. The interior arm places the anomaly inside the nominal represented range; the footprint arm places it outside that range but inside the declared kernel footprint. Each shortcut fails exactly one arm, and only the full contract clears both.

Policy	Inheritance	Kernel footprint	Interior anomaly	Footprint anomaly
B0	boundary-only	no	10 000 (100%)	10 000 (100%)
B1	boundary-only	yes	10 000 (100%)	0 (0%)
B2	complete-source	no	0 (0%)	10 000 (100%)
B3	complete-source	yes	0 (0%)	0 (0%)

7.4. Mixed-origin audio through stock FFmpeg

On 600 clips, complete-source propagation recovered the evidence interval structure exactly, every boundary at sample resolution, for 600 clips, and identified the generated interval with its exact bounds for 600 clips, with no detector, no training and no acoustic feature of any kind. The ground truth here is constructed rather than discovered, and that is the point: the evidence originates at the capture and generation steps, and the question this experiment answers is whether it *survives* a chain of representation-only transformations, not whether it could be inferred from the signal. Nothing in this experiment supports a claim that generated audio can be identified without evidence. The robustness arm behaves identically: 50 of 50 neural-TTS clips and 50 of 50 noise-buried clips recovered their full interval structure exactly, with 0 and 0 promotions respectively. Under the noise overlay the captured segments correctly become MIXED (captured content plus a generated noise source) while the generated segment correctly stays GENERATED, since union adds no new atom. Boundary-only inheritance promoted the whole-asset claim to captured-only on 600 clips and omitted required lineage on 600; the complete-source policy produced 0 promotions and 0 lineage




Figure 4: Mixed-origin corpus. Left: promotion by transformation over 600 clips processed entirely by stock FFmpeg; overlay and silence removal produce no baseline promotion for the structural reasons given in Section 7.4. Right: exact interval recovery and generated-interval recovery under the complete-source rule, with promotions and lineage omissions at zero.

omissions (Figure 4, right).

Across 8 transformations and 4800 transformation runs (Figure 4, left; Table 6), boundary-only inheritance promoted on 3600 runs and complete-source propagation on 0, with 0 lineage omissions. Two transformations produced *no* baseline promotion, and we report that as readily as the rest: overlay declares the generated source as a separate top-level ingredient, so a boundary-only reading of two ingredients still sees both, and silence removal happened to retain runs whose boundaries fell inside the generated region. Not every operator promotes, and a paper claiming otherwise would be wrong.

The interval model was validated against FFmpeg’s actual output on every run where the output was PCM and on a 100-clip subset for the coded containers. The largest absolute deviation between predicted and actual output sample count was 681 samples for silence removal, 471 for time stretching, 31 for MP3 and 0 for resampling. For all transformations the declared guard band covered the observed deviation, which is the condition Proposition 4 requires. Re-running each transformation and comparing decoded essence gave 0 mismatches, so the processing path is deterministic on this machine.

Two parts of this experiment could have failed, and one did. The zero promotion count under complete-source propagation follows from Proposition 1 once the required source set is correct, so on its own it checks that the implementation matches the algebra; on overlay, during development, it did not. The genuinely falsifiable measurements are the other two: whether the interval model predicts the output length of software we do not control, and whether the declared guard bands actually bound the deviation. Either could have come out wrong, and the guard bands would then have had to be re-declared and the build would have failed.

7.5. Signed transport, derivation and provenance loss

Across 3 containers and 120 signed round-trips (Table 7), signing succeeded and validation reported the trusted state under the declared local anchor for 120 assets, with 0 validation failures.

The EM assertion returned byte-equivalent from the validator for 120 assets. After derivation with stock FFmpeg, re-signing with the parent as an ingredient, and re-validation, 120 derived assets validated and 120 recorded the `parentOf` relationship.

Signal transparency holds exactly. Decoded essence was identical before signing, after signing with the complete-source assertion, and after signing with the baseline assertion, with 0 mismatches against the pre-signing essence and 0 between the two policies. Over the same assets the whole-file hash changed in 120 of 120 cases, which is why the comparison is defined on decoded PCM: a file-level test would have reported a change in every case and told us nothing.

Under the five provenance-loss conditions over 60 clips (Table 8), a removed manifest yielded UNVERIFIED in 60 cases, an asset modified after signing yielded INVALID in 60, and re-encoding without manifest preservation yielded UNVERIFIED in 60. No condition other than a valid manifest ever yielded CAPTURED, and there were 0 violations of the classification requirement. We do not claim that stripping is detected as malicious intent; the result is that the classification degrades in the conservative direction.

7.6. C2PA-native heterogeneous composition

The strongest form of the standards argument is executable, and we execute it. For 30 fixtures, a captured source and a generated source are each signed with their own `digitalSourceType`; stock FFmpeg concatenates them; the composition is signed with both sources as `componentOf` ingredients carrying their full source manifests, a `c2pa.placed` action referencing each component’s ingredient assertion, and the EM assertion computed by the complete-source rule over the two component timelines. The composition is then derived across the ancestry boundary and re-signed with `parentOf`.

All 30 compositions validated as trusted under the declared anchor, with both `componentOf` ingredients recorded in 30 cases and both `c2pa.placed` references resolved in 30; the EM assertion returned byte-equivalent in 30 cases; the whole-asset aggregate was MIXED with the captured and generated intervals individually recoverable in 30; and the derived asset stayed MIXED and trusted in 30 of 30 validated derivations, with 0 essence mismatches. This is the precise object the vocabulary-versus-reduction distinction describes: the component histories are all present in the signed graph, and a consumer walking the ingredients finds both source manifests and both source types. The aggregate interval claim exists only because the EM assertion computes it. Nothing in the validation pipeline required the aggregate to be conservative; the contract supplied that property, inside the standard’s own extension points. A representative composition manifest is frozen as a fixture in the repository.

7.7. The cost of conservatism: claim dilution

Zero promotion is only half of a useful result, because safety alone is cheap: declaring the whole asset as every sample’s dependency is perfectly safe under Proposition 4 and perfectly useless, since every interval near an ancestry change would collapse to the weaker claim. We therefore also measure what the declared footprints cost. The *dilution fraction* of a derived output is the fraction of its samples whose footprint-aware evidence record is strictly weaker (a weaker provenance claim, a lost channel, or a lower support value) than the record computed over the nominal represented content, which on this corpus is exact by construction.

Measuring this immediately caught a second defect in our own implementation, and we report it for the same reason as the first. The reference implementation originally applied footprint widening at the granularity of the emitted interval partition: an interval whose widened source range touched a

neighbouring ancestry was assigned the weakened claim over its *entire* extent, so a single resampling of a corpus clip reported a dilution fraction of one: safe, by footprint monotonicity, and uselessly conservative. The fix refines the output partition at the pull-backs of each source boundary shifted by $\pm$ the footprint, after which dilution is confined to footprint-wide bands at ancestry boundaries. The two-language differential had not caught this because its fixtures used source intervals narrower than every declared footprint, a geometry in which the coarse and the exact treatments coincide; the oracle corpus now includes a wide-interval battery in which they do not, and the fixed implementation agrees with the per-sample oracle on all 10 860 cases.

After the fix (Table 5), 4 of 8 transformations dilute nothing at all. Among them is overlay, whose nominal required-source set already contains every covering source, so the footprint adds nothing. The remainder dilute the footprint-wide neighbourhood of each ancestry boundary: median dilution is 0.86% of output samples for resampling, 20.24% for MP3 transcoding, 16.48% for silence removal and 22.64% for time stretching, with a single-transformation worst case of 44.92%. These fractions must be read against the corpus geometry: each band has a *fixed radius in samples* (the declared footprint plus guard), and the clips average 2.85 s, so the same bands on a one-hour asset would occupy a fraction three orders of magnitude smaller. The fraction shrinks with asset duration; the absolute band does not.

Composition is where conservatism genuinely bites, and we report it as measured rather than as hoped. The chain is, in order: trim to the middle 80%, resample 16 to 8 kHz, transcode to MP3, amplitude normalisation, and time stretch by a factor of 1.10 at the post-resampling rate, deliberately front-loading a rate change so that the large MP3 and time-stretch bands are scaled by it. Along this chain the median dilution reaches 85.74% by depth 5, with a worst case of 99.99%. Each operator adds its own bands and, where rates change, scales the bands inherited from upstream, so on a short asset a deep chain of large-footprint operators approaches total dilution. For scale, the same measurement on broadcast-length assets: a routine three-operator edit (trim to the middle 80%, normalise, transcode to MP3) on a 30-second asset with one interior generated segment dilutes 2.40% of its samples, and 0.240% on a five-minute asset (Table 5), because the bands are fixed absolute widths. This is the real price of declaring conservative bounds instead of knowing exact codec dependencies, and it is a cost a deployment can buy back without losing safety: any tighter dependency map, such as an encoder that reports its true delay or a codec-specific footprint smaller than our pinned bound, reduces dilution and, by Proposition 4, can never introduce promotion, provided it remains an over-approximation of the truth. Measuring the cost is what makes that engineering trade visible; a contract that only reported its zero promotion count would have hidden it.

7.8. Two-language differential

The Python reference implementation works with interval algebra over pulled-back source boundaries. The Node.js oracle evaluates evidence per output sample by brute force and run-length-encodes the result. The frozen corpus spans two interval geometries: one in which kernel footprints are wider than every source interval, and one in which they are far narrower, the regime that distinguishes a per-sample treatment of footprint widening from an interval-granularity one, added after the dilution experiment exposed exactly that difference (Section 7.7). On 10 860 cases the two implementations agreed on interval structure, provenance state, lineage set and channel availability with 0 disagreements, and the maximum absolute difference in any emitted support value was 0. Both implementations are author-written, and the oracle was deliberately built with no interval algebra at all, and evaluates evidence numerically per output sample, so a defect in

Table 5: Claim dilution: the fraction of output samples whose footprint-aware evidence is strictly weaker than the evidence over the nominal represented content, per transformation over 600 clips and along a composition chain over 200 clips. This is the price of the declared guard bands when the nominal map is exact.

Transformation	Clips	Median dilution	Max dilution	Clips affected
amplitude normalisation	600	0.00%	0.00%	0
overlay a generated source	600	0.00%	0.00%	0
resample 16 to 8 kHz	600	0.86%	1.39%	600
silence removal	600	16.48%	32.80%	600
time stretch 1.10	600	22.64%	44.92%	600
transcode to FLAC	600	0.00%	0.00%	0
transcode to MP3	600	20.24%	32.56%	600
trim to the middle 80%	600	0.00%	0.00%	0
composition depth 1	200	0.00%	0.00%	—
composition depth 2	200	1.06%	1.59%	—
composition depth 3	200	50.87%	75.84%	—
composition depth 4	200	50.87%	75.84%	—
composition depth 5	200	85.74%	99.99%	—
30 s asset, depth-3 chain	1	2.40%	—	—
300 s asset, depth-3 chain	1	0.24%	—	—

the reference implementation’s pull-back arithmetic cannot recur in the oracle as the same defect class. The same author can still make correlated conceptual errors, which is why this is a differential test against transcription and interval-arithmetic error, and not evidence of independence from the author (Section 9).

7.9. Cost

Complete-source bookkeeping cost a median 0.95 ms per audio-minute against 0.28 ms for boundary-only, a ratio of $3.35\times$, which is 0.151% of the FFmpeg time it accompanies (Table 9; Figure 5). Signing took a median 11.4 ms per asset (IQR 11.0–11.7) and validation 9.4 ms (IQR 9.1–9.7).

Manifest overhead was a median 14 854 B per asset, of which the EM assertion was 1 268 B. The manifest cost is dominated by a fixed per-asset component (certificate chain, COSE structure, hard binding), so we report it per asset and give the variable part separately: the assertion grows linearly in emitted evidence intervals at 333 B and $14.3\ \mu\text{s}$ per interval, measured up to 256 intervals. Evidence cost therefore scales with how many times ancestry actually changes along the timeline, not with duration, which is the property a long-form or streaming deployment needs. These are single-machine medians for a Python reference implementation and are not language-independent constants.

8. Discussion

What is established.. That a complete-source rule is implementable over media time against real processing software; that it eliminates promotion on every fixture and every corpus clip tested, where a minimal boundary-only policy does not; that it can be carried in a deployed signed transport without altering the audio; and that its cost is a fraction of a percent of the processing it accompanies.

Table 6: Main results. Deterministic fixture rates characterise the frozen fixture family and are a mechanism stress rate, not a population prevalence estimate.

Check	Cases	Boundary-only	Complete-source
<i>A Exhaustive finite-state conformance</i>			
Source words over $\{C, G, \perp\}$, length ≤ 8	9,840	—	—
Operator cases	98,385	—	—
Contract checks	787,443	0 failed	—
<i>B Deterministic adversarial timelines (10 000 frozen fixtures, 64 intervals)</i>			
Chain depth 1	10,000	9,455 (94.5%)	0
Chain depth 3	10,000	9,455 (94.5%)	0
Chain depth 5	10,000	9,455 (94.5%)	0
Lineage omissions (depth 1)	10,000	10,000	0
Unverified $\rightarrow$ verified (depth 1)	—	7,222	0
<i>C–D Mixed-origin audio corpus, stock-FFmpeg processing</i>			
Exact interval recovery	600	—	600
amplitude normalisation	600	600 (100.0%)	0
overlay a generated source	600	0 (0.0%)	0
resample 16 to 8 kHz	600	600 (100.0%)	0
silence removal	600	0 (0.0%)	0
time stretch 1.10	600	600 (100.0%)	0
transcode to FLAC	600	600 (100.0%)	0
transcode to MP3	600	600 (100.0%)	0
trim to the middle 80%	600	600 (100.0%)	0
<i>H Two-language differential oracle</i>			
Frozen cases	10,860	—	0 disagreements

What is not.. No claim is made that any deployed system promotes provenance. The baseline is a constructed reference policy and the fixture rates are a mechanism stress rate. Nor is the algebra new: the non-amplification property is an instance of a meet in a lattice, familiar from provenance semirings [5] and information-flow models [6]. Readers who already accept that algebra should read the contribution as the temporal instantiation, the kernel-footprint treatment, the transport and the measurements, which is where the work actually was.

Relation to the provenance standard.. C2PA authenticates signed assertions about asset history, and its vocabulary already preserves what this problem needs: component ingredients with their own manifests, generative source types, and temporal regions. The layer addressed here is the reduction over that vocabulary: whether the evidence assertion emitted by a derived representation is conservative with respect to every source interval that representation actually contains. C2PA can carry the component histories; the contract defines the aggregate claim a conforming operator must compute from them. This work complements the standard rather than criticising it, and it is implemented entirely inside the standard’s own extension points, a namespaced assertion and temporal regions of interest, without requiring any specification change. Where the specification’s security properties are discussed, we cite a published analysis rather than asserting anything ourselves [10].

Table 7: Signed transport. Columns are, in order: assets signed; assets whose validation state was trusted under the declared local anchor (the test credential is not on the C2PA Conformance Program trust list); derived assets that validated after re-signing; derived assets recording the `parentOf` ingredient relationship; assets whose EM assertion returned byte-equivalent; and decoded-essence mismatches before versus after signing.

Container	Assets	Trusted	Derived	<code>parentOf</code>	Assertion	Essence
FLAC	40	40	40	40	40	0
MP3	40	40	40	40	40	0
WAV	40	40	40	40	40	0

Table 8: Provenance-loss behaviour. The requirement is that the reported state degrade conservatively; no claim is made that a missing manifest indicates intent.

Condition	Clips	Reported state
valid manifest	60	MIXED (60)
manifest removed	60	UNVERIFIED (60)
asset modified after signing	60	INVALID (60)
re-encoded without manifest preservation	60	UNVERIFIED (60)
valid derived manifest with complete lineage	60	MIXED (60)

Relation to detectors and watermarks.. These are complementary and answer different questions. A detector examines a signal; a watermark marks content at generation time; the contract here constrains what a derived asset may assert given what its sources asserted. A pipeline can run all three. The contract is at its most useful precisely where detectors are weakest, on short interior edits inside otherwise genuine recordings, and it is useless where detectors are essential, namely media that arrive with no evidence at all.

Attack surface.. The contract narrows one surface and leaves others untouched. It removes the possibility that a conforming chain silently strengthens a claim, and it removes the incentive to launder a mixed-origin asset by passing it through a benign transformation. It does nothing against a malicious signer, a compromised key, or an actor who strips provenance entirely and starts a new, dishonest chain. Cryptographic validity proves that an assertion was signed, not that it is true.

Deployment path.. The contract deploys as a library alongside the processing step, not as a pre- or post-processor: the operator invocation already knows its own parameters, which determine the interval map and footprint, so the natural integration point is the same code that assembles the FFmpeg command line or codec call. The editor computes the map, the library computes the aggregate, and the existing signing step carries the assertion. Nothing observes or modifies the signal path, which is why signal transparency holds by construction rather than by care. Because the assertion schema and the temporal regions are ordinary C2PA extension points, adoption requires no specification change; a claim generator that emits the assertion and a consumer that reads it interoperate through any conforming validator today, and the schema is published with the repository as a baseline for derived-audio manifests.

An information-flow reading.. The contract can equally be read as an integrity property in the classical information-flow sense [6, 7]: evidence labels form a meet-semilattice with an absorbing bottom, and the requirement that a derived interval’s label be the meet over everything that flowed into it is precisely a “no write up” discipline for evidential authority. Readers from the security

Table 9: Cost, as medians over 30 repetitions on one machine. These are measurements of a Python reference implementation, not language-independent constants.

Quantity	Median	IQR
EM bookkeeping	0.947 ms / audio-minute	0.927–0.991 ms / audio-minute
Boundary-only bookkeeping	0.283 ms / audio-minute	0.276–0.288 ms / audio-minute
EM / boundary-only ratio	3.35×	—
EM as a fraction of FFmpeg time	0.151%	—
C2PA signing	11.4 ms / asset	11.0–11.7
C2PA validation	9.4 ms / asset	9.1–9.7
Manifest size overhead	14,854 B / asset	14,854–14,855
EM assertion	1,268 B / asset	1,268–1,269
EM assertion marginal cost	333 B / evidence interval	—




Figure 5: Cost of carrying interval evidence. The emitted assertion and the bookkeeping time both grow linearly in the number of evidence intervals, not in audio duration, so cost scales with how often ancestry changes along the timeline.

community may find that framing the shortest proof that the construction is sound; the temporal contribution is the mapping from operators to flows via interval maps and footprints.

Extension.. Nothing in Section 4 refers to audio. The instantiation cost for another medium is the interval algebra and the footprint table: frames and regions for video, spatial regions for images, character ranges for text. We have not built those, and we do not claim them.

9. Limitations

Independence.. The second-language oracle and the evidence policies are author-written. The differential is a test against transcription and interval-arithmetic error, not evidence of author independence. Two components are outside our control and were deliberately chosen for that reason: all audio processing is stock FFmpeg through its command line, and all signing and validation is the

Table 10: Claim–evidence boundary. Rows deliberately separate contract conformance, mechanism demonstration, transport behaviour and cost, so that evidence from one row is not used to authorise a claim in another.

Claim class	Evidence used here	Not established by that evidence
Operator conformance	Propositions 1–4 and Theorem 1; exhaustive finite-state enumeration; two-language differential	That any deployed system conforms; the prevalence of non-conformance
Mechanism on constructed fixtures	10 000 frozen adversarial timelines with a closed-form control arm	Any population rate; the behaviour of any named product
Mechanism on realistic audio	600 labelled mixed-origin clips processed by stock FFmpeg	Balanced coverage of speakers, languages, codecs or editing styles
Interval-model fidelity	Predicted versus actual output sample counts on every run, against declared guard bands	That the bounds hold for other codecs, other FFmpeg builds or other configurations
Signed transport	120 round-trips through the official tool across 3 containers	Conformance-program trust; security of the C2PA cryptographic layer
Signal transparency	Decoded-PCM SHA-256 identity before and after signing under both policies	Perceptual equivalence claims; bit-exactness across different decoders
Cost	30 timed repetitions on one declared machine	Cost in a compiled implementation or at broadcast scale
Conservatism cost	Per-sample dilution against constructed exact ground truth	Dilution against the true (unknowable) dependencies of a third-party codec

official `c2patool`. A third-party reimplementaion of the contract, and an external reproduction from a clean clone on different hardware, would strengthen external validity further; neither exists yet.

Corpus.. 600 clips from one read-speech corpus and one formant synthesiser, at 16 000 Hz, is a deliberate mechanism corpus, not a balanced design over speakers, languages, recording conditions, codecs or editing styles. It supports the claim that the mechanism is real and that the rule works on realistic audio; it does not support any rate claim about audio in general.

Footprints are declarations.. The kernel footprints are conservative bounds declared for the exact processing configurations used here. They are validated against those configurations and no others. A different FFmpeg build, resampler setting, codec or tempo factor requires the bound to be re-declared and re-tested; Proposition 4 guarantees that erring large is safe, not that our particular numbers transfer. The re-declaration need not be manual: because the transformation-matrix experiment already measures model-versus-implementation deviation per run, a conforming pipeline can run the same measurement as an automated calibration pass: push a deterministic reference signal through the unknown configuration, measure the maximum sample deviation, and set the guard band from the measurement plus margin. Footprints could equally be derived from codec specifications where those state window and delay constants. Neither is implemented here; both inherit their safety from footprint monotonicity, since a calibration that errs large cannot promote.

Normalisation is a modelling choice.. Amplitude normalisation is the operator where representational and computational dependency (Section 4) diverge completely: the scalar gain is computed from the whole signal, but the content an output sample represents is one source sample. The contract

governs representational dependency, so the default footprint is zero; the maximally conservative alternative, in which every output sample represents the whole signal, is implemented and tested as well. Both readings are defensible. The reported results use the representational reading, and a deployment that prefers the computational one pays the corresponding dilution cost and gains nothing in promotion safety, since neither reading can promote.

Trust anchor.. The signing credential is locally generated and the trust anchor locally configured. A trusted validation state in these results means trusted under that anchor, not conformance-program trust.

Replay and the analogue hole.. A microphone recording a loudspeaker that is playing synthetic speech produces audio that is genuinely captured at the sensor layer while its semantic source is synthetic. Every capture-provenance system has this limitation and this one is no exception: the contract would propagate a captured claim, correctly at the layer it models and misleadingly at the layer a reader may care about. The honest response is layering: capture mechanism, media-generation ancestry and speaker identity as separate evidence channels. Version 1 deliberately stays at the digital-asset and source-lineage level. Nothing here detects re-recording.

Speaker identity and truth.. Identity is not provenance: knowing an interval was captured says nothing about who spoke. Neither is truth: a captured recording can contain a lie, and the contract says nothing whatsoever about semantic content.

10. Conclusion

A representation-only transformation may change, simplify, compress, aggregate or reorganise content, but it must not silently increase the evidential authority of the output relative to the complete source material that output represents. In audio that principle has an exact form: provenance is the union over the complete required source set, same-channel support is the minimum over it, applicability is intersected, lineage is the union, and an unverified source interval is absorbing. The underlying algebra is not new, and we have said so; what this work provides is the executable temporal contract, the kernel-footprint treatment that makes it implementable against real codecs, a signed transport inside an existing standard, and measurements showing that the rule eliminates promotion on every fixture and clip tested, leaves the decoded audio untouched, and costs a fraction of a percent of the processing it accompanies. It does not detect deepfakes, it does not establish that speech is truthful, and a valid signature proves only that an assertion was signed, not that it is true.

Data availability

The mixed-origin corpus is generated deterministically by committed code from LibriSpeech `dev-clean` [15], licensed CC BY 4.0, fetched by a checksum-pinned script, and from locally generated eSpeak NG output. No human-subject, proprietary or login-walled data is used. Licences, versions, URLs, access dates and redistribution clauses are recorded in `DATA_LICENSES.md`.

Code availability

The reference implementation, the second-language oracle, every experiment, every frozen fixture and every machine-readable result are public under the MIT licence, with pinned tool versions and one-command reproduction. The evaluated state is release tag v1.0.0. Its exact commit hash is recorded in `results/PREFLIGHT.txt`, which is regenerated on every run and shipped with the release; that report also carries every tool version and every number quoted in this manuscript, so a reader can check any figure in the text against the file the code wrote. A Zenodo archive with version and concept DOIs is deposited on acceptance and the DOIs are added at proof stage.

CRediT authorship contribution statement

A. Urias: Conceptualization, Methodology, Software, Formal analysis, Validation, Investigation, Visualization, Writing – original draft, Writing – review and editing.

Funding

The author reports no specific external grant funding for this study.

Declaration of competing interest

A. Urias is employed by and holds equity in Aurtech. No product of Aurtech is evaluated, named or compared against in this work, and the baseline is a constructed reference policy rather than a description of any product. A non-conformance found in the author’s own implementation during development is reported in Section 7.1.

Declaration of generative AI and AI-assisted technologies

During preparation of this work the author used generative-AI tools to assist with development and review of the verification and reproducibility tooling, manuscript organisation, and language refinement. All reported outcomes were produced by executing the committed deterministic code rather than generated by these tools. The author reviewed and verified the scientific claims, calculations, code-derived results, references and final text, edited the material as needed, and takes full responsibility for the content of the publication.

References

- [1] L. Pham, P. Lam, D. Tran, H. Tang, T. Nguyen, A. Schindler, F. Skopik, A. Polonsky, C. Vu, A comprehensive survey with critical analysis for deepfake speech detection, *Computer Science Review* 57 (2025) 100757. [doi:10.1016/j.cosrev.2025.100757](https://doi.org/10.1016/j.cosrev.2025.100757).
- [2] X. Wang, H. Delgado, H. Tak, J.-w. Jung, H.-j. Shim, M. Todisco, I. Kukanov, X. Liu, M. Sahidullah, T. Kinnunen, N. Evans, K. A. Lee, J. Yamagishi, et al., ASVspoof 5: Design, collection and validation of resources for spoofing, deepfake, and adversarial attack detection using crowdsourced speech, *Computer Speech and Language* 95 (2026) 101825. [doi:10.1016/j.cs1.2025.101825](https://doi.org/10.1016/j.cs1.2025.101825).

- [3] Coalition for Content Provenance and Authenticity, C2PA technical specification, version 2.4, https://spec.c2pa.org/specifications/specifications/2.4/specs/C2PA_Specification.html, accessed 19 August 2026 (2026).
- [4] A. Urias, Evidence-monotone terrain representation framework (EMTRF): A provenance-conserving operator contract for derived terrain geometry, reproducibility archive, concept DOI <https://doi.org/10.5281/zenodo.21992294>; manuscript under review (2026).
- [5] T. J. Green, G. Karvounarakis, V. Tannen, Provenance semirings, in: Proceedings of the Twenty-Sixth ACM SIGMOD-SIGACT-SIGART Symposium on Principles of Database Systems (PODS '07), 2007, pp. 31–40. doi:10.1145/1265530.1265535.
- [6] D. E. Denning, A lattice model of secure information flow, Communications of the ACM 19 (5) (1976) 236–243. doi:10.1145/360051.360056.
- [7] J. A. Goguen, J. Meseguer, Security policies and security models, in: 1982 IEEE Symposium on Security and Privacy, 1982, pp. 11–20. doi:10.1109/SP.1982.10014.
- [8] European Parliament and Council of the European Union, Regulation (eu) 2024/1689 laying down harmonised rules on artificial intelligence (artificial intelligence act), article 50 transparency obligations applicable from 2 August 2026 (2024).
- [9] R. San Roman, P. Fernandez, A. Défossez, T. Furon, T. Tran, H. El Sahar, Proactive detection of voice cloning with localized watermarking, in: Proceedings of the 41st International Conference on Machine Learning (ICML), 2024, arXiv:2401.17264.
- [10] E. Golaszewski, N. Krawetz, A. T. Sherman, E. Ziegler, S. K. Matukumalli, R. Yus, C. L. Kegley, M. Barthel, W. Bowman, B. Barot, K. Kullman, Verifying provenance of digital media: Security analysis of C2PA and its implementation, Cryptology ePrint Archive, Paper 2026/804, <https://eprint.iacr.org/2026/804>, posted 23 April 2026, revised 2 June 2026; preprint, not peer reviewed at the time of writing (2026).
- [11] A. Nemecek, H. He, G. Cheng, E. Ayday, Authenticated contradictions from desynchronized provenance and watermarking, arXiv:2603.02378, <https://arxiv.org/abs/2603.02378>, submitted 2 March 2026, revised 18 April 2026 (2026).
- [12] T. Ono, MerkleSpeech: Public-key verifiable, chunk-localised speech provenance via perceptual fingerprints and Merkle commitments, arXiv:2602.10166, <https://arxiv.org/abs/2602.10166>, submitted 10 February 2026 (2026).
- [13] X. Fu, Z. Wang, H. Wang, Y. Chen, Trust the voice, hide the source: Anonymous provenance for verifiably edited audio, Cryptology ePrint Archive, Paper 2026/1308, <https://eprint.iacr.org/2026/1308>, posted 23 June 2026, revised 25 June 2026 (2026).
- [14] World Wide Web Consortium, PROV-DM: The PROV data model, W3C Recommendation, 30 April 2013, <https://www.w3.org/TR/prov-dm/>, accessed 19 August 2026 (2013).
- [15] V. Panayotov, G. Chen, D. Povey, S. Khudanpur, LibriSpeech: An ASR corpus based on public domain audio books, in: 2015 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP), 2015, pp. 5206–5210. doi:10.1109/ICASSP.2015.7178964.