

Scala Object System

Mikhail Mutcianko, Alexey Otts

СПБГУ, СП

27 февраля 2020 г.

Recap: Syntax Differences from Kotlin

Kotlin \Leftrightarrow Scala

Kotlin \Leftrightarrow Scala

`List<Integer>` \Leftrightarrow `List[Int]`

Kotlin \Leftrightarrow Scala

`List<Integer> \Leftrightarrow List[Int]`

`fun foo(x: Integer): A { } \Leftrightarrow def foo(x: Int): A = { }`

Kotlin \Leftrightarrow Scala

`List<Integer> \Leftrightarrow List[Int]`

`fun foo(x: Integer): A { } \Leftrightarrow def foo(x: Int): A = { }`

`import foo.* \Leftrightarrow import foo._`

Kotlin \Leftrightarrow Scala

`List<Integer> \Leftrightarrow List[Int]`

`fun foo(x: Integer): A { } \Leftrightarrow def foo(x: Int): A = { }`

`import foo.* \Leftrightarrow import foo._`

`when(x) { } \Leftrightarrow x match { }`

Kotlin \Leftrightarrow Scala

`List<Integer> \Leftrightarrow List[Int]`

`fun foo(x: Integer): A { } \Leftrightarrow def foo(x: Int): A = { }`

`import foo.* \Leftrightarrow import foo._`

`when(x) { } \Leftrightarrow x match { }`

`class Foo : Bar \Leftrightarrow class Foo extends Bar`

Kotlin \Leftrightarrow Scala

`List<Integer> \Leftrightarrow List[Int]`

`fun foo(x: Integer): A { } \Leftrightarrow def foo(x: Int): A = { }`

`import foo.* \Leftrightarrow import foo._`

`when(x) { } \Leftrightarrow x match { }`

`class Foo : Bar \Leftrightarrow class Foo extends Bar`

`-> \Leftrightarrow =>`

Kotlin \Leftrightarrow Scala

`List<Integer> \Leftrightarrow List[Int]`

`fun foo(x: Integer): A { } \Leftrightarrow def foo(x: Int): A = { }`

`import foo.* \Leftrightarrow import foo._`

`when(x) { } \Leftrightarrow x match { }`


`class Foo : Bar \Leftrightarrow class Foo extends Bar`

`-> \Leftrightarrow =>`

`it \Leftrightarrow _`

Scala Type System

Everything is a type



Top types

- Any
 - The base type of all types
 - Methods: `==`, `!=`, `equals`, `hashCode`, `toString`

Top types

- Any
 - The base type of all types
 - Methods: `==`, `!=`, `equals`, `hashCode`, `toString`
- AnyRef
 - The base type of all reference types
 - Alias of `java.lang.Object`

Top types

- Any
 - The base type of all types
 - Methods: `==`, `!=`, `equals`, `hashCode`, `toString`
- AnyRef
 - The base type of all reference types
 - Alias of `java.lang.Object`
- AnyVal
 - The base type of all primitive types

Bottom type

`Nothing` is at the bottom of Scala's type hierarchy. It is a subtype of every other type. There is no value of type `Nothing`.

Why is that useful?

- To signal abnormal termination
- As an element type of empty collections

Classes, Objects, Traits . . .

Basic

```
1 class Useless
2
3 class Calculator {
4   val brand: String = "HP"
5   def add(m: Int, n: Int): Int = m + n
6 }
```

Class constructor

- In Scala, a class implicitly introduces a primary constructor
- Takes the parameters of the class
- Executes all statements in the class body
- Can introduce members if parameters are specified as `val` or `var`

Class constructor

Example

```
1 class Calculator(brand: String) {  
2     /* A constructor */  
3     val colour: String = if (brand == "TI") {  
4         "blue"  
5     } else if (brand == "HP") {  
6         "black"  
7     } else {  
8         "white"  
9     }  
10    def add(m: Int, n: Int): Int = m + n  
11 }
```

Auxiliary Constructors

Scala also allows the declaration of auxiliary constructors.

These are methods named `this`

```
1 class Calculator(brand: String) {  
2   val color: String = ???  
3  
4   def this(other: Cal) = ??? // <<<  
5  
6   // An instance method.  
7   def +(m: Int, n: Int): Int = m + n  
8 }
```

Objects

- Scala has no static classes / methods / fields
- Objects are used to hold single instances of a class
- Objects are lazy, and are not initialized until first reference

Objects

Example

```
1 object Constants {  
2   val e = 2.71828182846  
3   def **(num: Double) = num * e  
4 }  
5  
6 Constants ** Constants.e
```

Companion objects

A companion object in Scala is an object that's declared in the same file as a class, and has the same name as the class

```
1 class SomeClass {  
2     def printFilename() = {  
3         println(SomeClass.HiddenFilename)  
4     }  
5 }  
6  
7 object SomeClass {  
8     private val HiddenFilename = "/tmp/foo.bar"  
9 }
```


Traits are collections of fields and behaviors that you can extend or mixin to your classes

- In Scala, a class can only have one superclass, but many traits
- Can have methods and properties
- Can have member definitions
- Cannot have constructors

Traits

Example

```
1 trait Planar {  
2   def height: Int  
3   def width: Int  
4   def surface = height * width // <<<  
5   val denom: Double  
6   val coeff: Double = 3.74716565 // <<<  
7 }  
8  
9 class Square extends Shape with Planar with Movable
```

Mixins

```
1 trait A
2   { def foo: Int }
3 trait B extends A
4   { override def foo = 1 }
5 trait C extends A
6   { override def foo = 2 }
7
8 new (trait D extends C with B).foo == 1
```

Mixins

```
1 trait A
2   { def foo: Int }
3 trait B extends A
4   { def foo = 1 }
5 trait C extends A
6   { def foo = 2 }
7
8 trait D extends C with B // <<<
```

Mixins

```
1 trait A
2   { def foo: Int }
3 trait B extends A
4   { def foo = 1 }
5 trait C extends A
6   { def foo = 2 }
7
8 trait D extends C with B // <<<
```

error: trait D inherits conflicting members:

method foo in trait C of type => Int and

method foo in trait B of type => Int

(Note: this can be resolved by declaring an override in trait D.)

```
trait D extends C with B
```

Super calls

Problem

To keep your Scala code DRY (“Don't Repeat Yourself”), you want to invoke a method that's already defined in a parent class or trait.

Super calls

Example

```
1 class WelcomeActivity extends Activity {  
2     override def onCreate(bundle: Bundle) {  
3         super.onCreate(bundle)  
4         // more code here ...  
5     }  
6 }
```

Super calls

Controlling which trait you call a method from

```
1 class Child extends Human with Mother with Father {  
2     def printSuper = super.hello  
3     def printMother = super[Mother].hello  
4     def printFather = super[Father].hello  
5     def printHuman = super[Human].hello  
6 }
```


Members

- `def` - method
- `val` - immutable property
- `var` - mutable property
- `lazy val` - lazy immutable property

Properties

All properties **implicitly** generate a backing field, a setter and a getter
Except for private ones

Properties

```
1 class Person() {  
2     private var name = ""  
3     var age = 0  
4 }
```

Properties

```
1 class Person() {  
2   private var name = ""  
3   var age = 0  
4 }
```

```
1 class Person() {  
2   private var name = ""  
3   // Private age variable, renamed to _age  
4   private var _age = 0  
5  
6   // Getter  
7   def age = _age  
8  
9   // Setter  
10  def age_ = (value:Int):Unit = _age = value  
11 }
```

Concrete member overriding

- `val`: can only be overridden by `val`
- `lazy val`: can only be overridden by `lazy val`
- `var`: a concrete `var` cannot be overridden
- `def`: can be overridden by all kinds of members

	val	lazy	var	def
val	✓	✗	✗	✗
lazy	✓	✗	✗	✗
var	✗	✗	✗	✗
def	✓	✓	✓	✓

Abstract member overriding

- lazy val: cannot be abstract
- val: can be overridden by val and lazy val
- var: can be overridden by var, or a pair of read and write operations implemented by def, val, or lazy val
- def: can be overridden by all kinds of members

	val	var	def
val	✓	✗	✗
var	✓+	✓	✓+
def	✓	✓	✓

TODO

Access modifiers

Problem

Scala methods are public by default, and you want to control their scope in ways similar to Java.

Access modifiers

Problem

Scala methods are public by default, and you want to control their scope in ways similar to Java.

Scopes

- object-private scope
- private
- package
- protected

Access modifiers

Problem

Scala methods are public by default, and you want to control their scope in ways similar to Java.

Scopes

- object-private scope
- private
- package
- protected

Access modifiers

object-private

The most restrictive access is to mark a method as “object-private.” When you do this, the method is available only to the current instance of the current object. Other instances of the same class cannot access the method.

```
1 class Foo {  
2     private[this] def isFoo = true  
3     def doFoo(other: Foo) {  
4         if (other.isFoo) { // this line won't compile  
5             // ...  
6         }  
7     }  
8 }
```

Access modifiers

package scope

```
1 package com.acme.coolapp.model {  
2     class Foo {  
3         private[model] def doX {}  
4         private def doY {}  
5     }  
6     class Bar {  
7         val f = new Foo  
8         f.doX // compiles  
9         f.doY // won't compile  
10    }  
11 }
```

apply method

apply is a syntactic sugar for calling something

- construct new instances
- directly call anonymous functions
- mimic callable behaviour
- see also: update method

apply method

example

```
1 class SomeClass(val x: Int)
2
3 object SomeClass {
4     def apply(x: Int) = new SomeClass(x)
5 }
6
7 new SomeClass(42)
8 SomeClass(42)
```

Packages

- declare one or more package names at the top of a Scala file

```
1 package users  
2 class User
```

Packages

- declare one or more package names at the top of a Scala file

```
1 package users
2 class User
```

- declare packages by using braces

```
1 package users {
2   package administrators {
3     class NormalUser
4   }
5   package normalusers {
6     class NormalUser
7   }
8 }
```


Imports

- single name

```
1 import users.User
```

Imports

- single name

```
1 import users.User
```

- all from package

```
1 import users._
```

Imports

- single name

```
1 import users.User
```

- all from package

```
1 import users._
```

- only import selected names

```
1 import users.{User, UserPreferences}
```

Imports

- single name

```
1 import users.User
```

- all from package

```
1 import users._
```

- only import selected names

```
1 import users.{User, UserPreferences}
```

- rename imported member

```
1 import users.{UserPreferences => UPrefs}
```

Package objects

Scala provides package objects as a convenient container shared across an entire package

Package objects

Scala provides package objects as a convenient container shared across an entire package

- can contain arbitrary definitions

Package objects

Scala provides package objects as a convenient container shared across an entire package

- can contain arbitrary definitions
- can inherit from other classes and traits

Package objects

Scala provides package objects as a convenient container shared across an entire package

- can contain arbitrary definitions
- can inherit from other classes and traits
- one package object per package

Package objects

Scala provides package objects as a convenient container shared across an entire package

- can contain arbitrary definitions
- can inherit from other classes and traits
- one package object per package
- should be placed in `package.scala`

Package obejcts

```
1 package com.myapp
2 package object model {
3     val MAGIC_NUM = 42 // field
4     def echo(a: Any) { println(a) } // method
5 }
```

Package objects

```
1 package com.myapp
2 package object model {
3     val MAGIC_NUM = 42 // field
4     def echo(a: Any) { println(a) } // method
5 }
```

```
1 package com.myapp.model
2 class MainDriver {
3     echo(42)
4     echo(MAGIC_NUM)
5 }
```

Functional OOP

Extractor object

An extractor object is an object with an `unapply` method.

`apply`

takes arguments and creates an object

`unapply`

takes an object and tries to give back
the arguments

unapply method

Return type

- If it is just a test, return a `Boolean`
- If it returns a single sub-value of type `T`, return an `Option[T]`
- If you want to return several sub-values `T1, ..., Tn`, group them in an optional tuple `Option[(T1, ..., Tn)]`

Extractor object

Example

```
1 class Cat(val name: String, val age: Int)
2
3 object Cat {
4   def apply(name: String, age: Int): Cat = new Cat(name, age)
5   def unapply(cat: Cat): Option[(String, Int)] = Some(cat.name -> cat.age)
6 }
```

Sealed traits

- sealed traits can only be extended in the same file

Sealed traits

- sealed traits can only be extended in the same file
- this lets the compiler easily know all possible subtypes

Sealed traits

- sealed traits can only be extended in the same file
- this lets the compiler easily know all possible subtypes
- example: the compiler can emit warnings if a match/case expression is not exhaustive

Sealed traits

- sealed traits can only be extended in the same file
- this lets the compiler easily know all possible subtypes
- example: the compiler can emit warnings if a match/case expression is not exhaustive
- use sealed traits when the number of possibly subtypes is finite and known in advance

Sealed traits

- sealed traits can only be extended in the same file
- this lets the compiler easily know all possible subtypes
- example: the compiler can emit warnings if a match/case expression is not exhaustive
- use sealed traits when the number of possibly subtypes is finite and known in advance
- they can be a way of creating something like an enum in Java

Sealed traits

- sealed traits can only be extended in the same file
- this lets the compiler easily know all possible subtypes
- example: the compiler can emit warnings if a match/case expression is not exhaustive
- use sealed traits when the number of possibly subtypes is finite and known in advance
- they can be a way of creating something like an enum in Java
- they help you define algebraic data types, or ADTs

Sealed traits

Example

```
1 sealed trait Answer
2 case object Yes extends Answer
3 case object No extends Answer
4 case class Maybe(something: String)
```

Class classes

Case classes are used to conveniently store and match on the contents of a class.
You can construct them without using `new`

Class classes

Case classes are used to conveniently store and match on the contents of a class.
You can construct them without using `new`

Case classes auto generate:

Class classes

Case classes are used to conveniently store and match on the contents of a class.
You can construct them without using `new`

Case classes auto generate:

- properties based on constructor arguments

Case classes

Case classes are used to conveniently store and match on the contents of a class. You can construct them without using `new`

Case classes auto generate:

- properties based on constructor arguments
- `equals`, `canEqual`, `hashCode` and `toString` based on properties

Class classes

Case classes are used to conveniently store and match on the contents of a class. You can construct them without using `new`

Case classes auto generate:

- properties based on constructor arguments
- `equals`, `canEqual`, `hashCode` and `toString` based on properties
- companion object with `apply` and `unapply` methods

Class classes

Case classes are used to conveniently store and match on the contents of a class. You can construct them without using `new`

Case classes auto generate:

- properties based on constructor arguments
- `equals`, `canEqual`, `hashCode` and `toString` based on properties
- companion object with `apply` and `unapply` methods
- `copy` method with default values

Destructuring bindings

Initializing a value may be more than binding a name — it's a pattern.

Destructuring bindings

Initializing a value may be more than binding a name — it's a pattern.

```
1 val pi = 3.1415
2 val pi: Double = 3.1415 // equivalent to first definition
3 val c@Cat(name, age) = Cat("bobik", 42) // a pattern definition
4 val x :: xs = c :: name :: age :: Nil // an infix pattern definition
```

Pattern matching

Values

```
1 val times = 1
2
3 times match {
4   case 1 => "one"
5   case 2 => "two"
6   case _ => "some other number"
7 }
```

Pattern matching

Guards

```
1 val times = 1
2
3 times match {
4   case i if i == 1 => "one"
5   case i if i == 2 => "two"
6   case _ => "some other number"
7 }
```


Pattern matching

Types

```
1 val animal = Cat("eve", 10)
2
3 val owner = animal match {
4     case a: Cat if a.name == "eve" => "Bob"
5     case a: Dog if a.name == "dis" => "Mary"
6     case _ => "Unknown"
7 }
```

Pattern matching

Unapply

```
1 val animal = Cat("eve", 10)
2
3 val owner = animal match {
4     case Cat("eve", _) => "Bob"
5     case Dog("dis", _) => "Mary"
6     case _ => "Unknown"
7 }
```

Pattern matching

Binding

```
1 val animal = Cat("eve", 10)
2
3 val fullName = animal match {
4   case c@Cat("eve", _) => s"Bob's ${c.name}"
5   case d@Dog("dis", _) => s"Mary's ${d.name}"
6   case _ => "Unknown"
7 }
```

Practice Functional List