

Hands-on Lab - Querying with GraphQL using Python



Estimated Time: 60 minutes

In this lab, you will become familiar with using GraphQL to query the APIs served through a GraphQL service running on a server using Postman.

Learning Objectives:

After completing this exercise, you should be able to perform the following tasks:

- Use GraphQL with Postman to access GraphQL Service
- Structure queries to access APIs to get selective information that you need

Pre-requisites

- You must be familiar with Docker applications and commands.
- You must have a good understanding of API.
- You must be familiar with using Postman.

Task 1 - Sign-up for Postman

If you already have a Postman account, you can skip this task.

1. On your browser, go to www.postman.com



postman.com



Product ▾

Pricing

Enterprise ▾

Resources and Support ▾

E

Build APIs together

Over 20 million developers use Postman. Get started by signing up or downloading the desktop app.

[Sign Up for Free](#)

Download the desktop app



2. Click **Sign Up for Free**.

3. Enter your email and choose a password, confirm it, and create a free account. You can alternatively use your Google account to sign in too. You may notice that **Stay signed in for 30 days** is selected by default. It is highly recommended that you uncheck that option if you are not using a personal computer for this lab.



POSTMAN

Why sign up?

- Organize all your API development within Postman Workspaces
- Sync your Postman data across devices
- Backup your data to the Postman cloud
- It's free!



Create Postman Account

Email

Username

Password

☐ Sign up to get product updates and join the marketing community

☒ Stay signed in forever

By creating an account, you agree to our [Privacy Policy](#).



You have successfully created a Postman account.

Task 2 - Run a GraphQL service

1. Open a terminal window by using the top menu in the IDE: **Terminal > New Terminal**.
2. In the terminal, clone the repository which has the GraphQL service code ready by pasting the following command. The repository that you clone has code that will run a GraphQL service where we can query details on US cities and states.

```
git clone https://github.com/ibm-developer-skills-network/jmgdo-microservices.git
```

3. Change the working directory to **jmgdo-microservices/graphql_example** by running the following command.

```
cd jmgdo-microservices/graphql_example
```

4. Build the application by running the following command. This will build the docker application using the docker file in the current directory and tag it **graphqlservice**.

```
docker build . -t graphqlservice
```


5. Run the application that you just built on port 8080, by running the following command on the terminal.

```
docker run -dp 8080:4000 graphqlservice
```

You will get a hex code that indicates the application has started.

6. To confirm that the service is running, execute the following command.

```
curl localhost:8080
```

A terminal window with a dark background. The prompt is 'theia@theiadocker- [redacted] /home/project/jmgdo-microservices\$'. The command 'curl' has been entered. Below the command, the text 'Copy the URL from the address-bar, to paste in Postman to use Graph' is visible, likely part of a larger output or instruction.


```
theia@theiadocker- [redacted] /home/project/jmgdo-microservices$ curl
```

Copy the URL from the address-bar, to paste in Postman to use Graph

If the output is as seen in the image above, your service is up and running.

7. Click on the Skills Network button on the left, it will open the "Skills Network Toolbox". Then click Launch Application, from there you enter the port no. as 8080 and click Your Application button. This will open a browser window.


8. This will launch a browser page. Copy the URL that you see in the address bar.



Copy the URL from the address-bar, to paste in Postman to use GrpahQL

Task 3 - Run GraphQL queries on Postman

1. Go to www.postman.com and sign in to Postman. Please note that the home page may look different for every person depending on the day of the year and the region you are signing in from.
2. On the homepage, click **Create new**.



Postman works best with teams

Collaborate in real-time and establish a single source of truth for all API workflows.

Create Team

-
- Workspaces >
 - Integrations >
 - Reports >

Good mor

Pick up where yo

Recently visit



My Worksp


Get started w


Start with so

Create a new re
API in a worksp


Create New →

3. This brings up the set of options you can use with Postman. Choose **HttpRequest**.





4. In the space provided for the **GET** request URL paste the URL you copied from step 8 of the previous task and suffix it with **/graphql**.



5. Choose **Body** and **GraphQL** as shown in the image below to start entering your query. Method will change to **POST**.

https://lavanyas-8080.theiadocker-3-labs-prod-theiak8s-4-tor01.proxy.cognitiveclass.a

POST



https://lavanyas-8080.theiadocker-3-labs-prod-theiak8s-4-tor01.proxy

Params

Authorization

Headers (8)

Body ●

Pre-request Script

Tests

S

● none

● form-data

● x-www-form-urlencoded

● raw

● binary

● GraphQL

QUERY

1

6. You will first query for all the cities in the US. What you can get is the city name and the state they are in. Paste the following in the **Query** tab and click **Send**.

```
{
  cities {
    city
    state
  }
}
```

POST

▼

https://lavanyas-8080.theiadocker-3-labs-prod-theiak8s-4-tor01.prox

Params

Authorization

Headers (8)

Body ●

Pre-request Script

Tests

S

● none

● form-data

● x-www-form-urlencoded

● raw

● binary

● GraphQL

QUERY

```

1  {
2    cities {
3      city
4      state
5    }
6  }

```

Body

Cookies (1)

Headers (7)

Test Results

Pretty

Raw

Preview

Visualize

JSON ▼

↺

```

1  {
2    "data": {
3      "cities": [
4        {
5          "city": "Abbeville",
6          "state": "Louisiana"
7        },
8        {
9          "city": "Aberdeen",
10         "state": "Maryland"
11        },
12      ]

```


As you can see, it lists all the 5980 cities in the US in the output tab.

- You can now try to retrieve just the names of the cities in a particular state. To do this, you need to pass the state as a parameter. You will now request the state name in the return value as you are querying only for one state.

```

{
  cities(state:"Florida") {
    city
  }
}

```

 https://lavanyas-8080.theiadockernext-0-labs-prod-theiak8s-4-tor01.proxy.cognitiveclass.ai/graphql

GET

https://lavanyas-8080.theiadockernext-0-labs-prod-theiak8s-4-tor01.proxy.cognitiveclass.ai/graphql

ParamsAuthorizationHeaders (10)BodyScriptsSettings

☐ none

☐ form-data

☐ x-www-form-urlencoded

☐ raw

☐ binary

☒ GraphQL

Auto Fetch

QUERY

```
1 {
2   | cities(state:"Florida") {
3   |   | city
4   | }
5 }
```

GRAPHQL VARIABLES ⓘ

1

As you can see, only the names of the cities in Florida are returned.

Additional Task

1. Construct a query to return all the cities in the state of “Ohio”, along with the state name.
- [Click here for the solution](#)

Congratulations! You have learned to construct queries using GraphQL.

Tutorial details

Author: Lavanaya T S
Contributors: Pallavi Rai

© IBM Corporation. All rights reserved.