AI & CYBERSECURITY

DeferBench

Benchmarking Delayed-Execution Risks in AI-Assisted Development

Testing whether security controls stop AI-authored code from causing unintended execution through trusted developer tools.

The command looks safe.
What it executes may not be.

1

Untrusted input

An AI coding agent reads an untrusted issue or document.

→

2

Agent-authored change

It modifies a project script or configuration file.

→

3

Trusted tool executes it

Later, npm test, make build or pytest runs that content.

→

4

Unintended execution

The effect goes beyond what the command line reveals.

EXAMPLE

`npm test` → package.json gained a **`pretest`** script, edited by the agent → **It runs a command the developer never reviewed**

Illustrative scenario class, not a claim that every coding agent or approval system is vulnerable.

Can security controls stop delayed execution?

THE GAP

Controls look at different things: commands, policies, artifact provenance.

We need one reproducible way to compare what each one actually does on the same scenarios.

RESEARCH QUESTION

Does the control prevent the effect, and what does it cost legitimate work?

Related benchmarks and controls already exist (AgentCanary, IssueTrojanBench, Gensee Crate, Gryph, Runmark). Our proposed distinction: delayed execution through trusted developer tools, observed prevention, and benign-workflow disruption. **Novelty of this combination: not yet independently validated.**

DeferBench: Test the defence, not just the alert.

Baseline check first. Every scenario runs undefended; if its expected effect does not reproduce, it is marked invalid and never counted as a defence success.

Scenario generator

Fixed attack, benign and edge scenarios

Security controls

Includes Handoff, our reference defence

Comparative report

Prevention, leaks, benign disruption, evidence



Disposable workspace

Fresh git repo with a synthetic canary secret

Canary verification

The trusted command really runs; a loopback sink watches

Measure prevention, usability, and traceability.



Implemented today

Python package and CLI · scripted scenario replays · synthetic canary verification · JSON and CSV reports · HTML dashboard · automated tests and documented commands

Where the AI comes in

The benchmark evaluates risks created by AI-assisted coding. Agent actions are scripted so results are reproducible. Handoff is rules-based.

Not implemented

Optional LLM classifier (proposed only) · live-agent runs · human-independent evaluation

Handoff improves traceability, not proven prevention.


Attack runs prevented

canary never reached the sink · higher is better



Benign workflows interrupted

lower is better



Provenance attribution

which agent step wrote the content, after which untrusted input



Tie on prevention.

Handoff adds attribution evidence, but its added value over the stateless resolver has not been established.

Development-authored scenarios.
Human-independent evaluation pending.

Run 20261013T115905Z-bde81a: 40 scenarios × 2 payload styles, 0 invalid runs. Counted as prevented when a control asks or denies and a reviewer rejects asks; if every ask is approved: Handoff 38/44, stateless resolver 40/44. Other controls (default policy, hook-only; configurations, not product comparisons): Gensee 7/44, Gryph 0/44, Runmark 0/44.

Related work and limits

1 Related benchmarks

AgentCanary: agents in real executable environments, compares three runtime defences. IssueTrojanBench: agents following malicious issues. SandboxEscapeBench: container escape.

2 Related controls

Gensee Crate documents artifact provenance; Gryph provides policy rules; Runmark reports pre-execution command facts. We ran released tools hook-only with default policies.

3 Our qualified claim

A focused, execution-verified comparison of controls for delayed execution through trusted developer tools. Novelty of the combination is not independently validated.

4 Limits and open work

Scripted agent actions, not live agents · one OS (macOS) · scenarios written by the defence author · human-independent evaluation pending.

Sources: AgentCanary arXiv:2606.10484 · IssueTrojanBench arXiv:2607.20759 · SandboxEscapeBench PMLR v306 (ICML 2026) · github.com/GenseeAI/gensee-crate · github.com/safedep/gryph · github.com/phaethix/runmark

The Team



[Team Member 1 Name]

Suggested role: defence and resolver (Handoff)



[Team Member 2 Name]

Suggested role: benchmark, scenarios and reporting

DeferBench

Making delayed-execution security measurable.