KebSEND

REST API v1

Official Developer Integration Quickstart & Endpoint Reference

Environment: Production Live
Format: JSON / HTTPS
Support: Ghana & International SMS

1. Base URLs - Choose According to Your API Key

KebSEND operates two dedicated production API gateways. Check the prefix of your API key to determine which endpoint URL to target:

WEB PORTAL KEYS

`https://textora-bms-website.onrender.com`

For API keys starting with ksnd_live_...

BOT / EXT KEYS

`https://textora-bmsv2.onrender.com`

For API keys starting with txt_...

2. Request Headers & Authentication

Authenticate all requests by including your secret key in either header:

Header	Example Value	Usage & Notes
x-api-key	`x-api-key: YOUR_API_KEY`	Recommended standard custom header
Authorization	`Bearer YOUR_API_KEY`	RFC 6750 Bearer token authorization format
Content-Type	`application/json`	Required for all POST requests

3. Check Account Credit Balance

GET `/api/v1/balance`

Returns remaining SMS units and registered account email address.

```
# Terminal cURL Command
curl -X GET "https://textora-bms-website.onrender.com/api/v1/balance" \
  -H "x-api-key: YOUR_API_KEY"

# Response (200 OK)
{ "ok": true, "balance": 450, "user_email": "developer@company.com" }
```

4. Approved Sender IDs List

GET `/api/v1/sender-ids`

```
# Terminal cURL Command
curl -X GET "https://textora-bms-website.onrender.com/api/v1/sender-ids" \
  -H "x-api-key: YOUR_API_KEY"

# Response (200 OK)
{ "ok": true, "senderIds": ["TXTORA", "MYSHOP"] }
```

5. Send SMS (Single or Multi-Recipient)

POST `/api/v1/send-sms`

Dispatches SMS to Ghanaian and international mobile numbers. Debits credit units automatically.

Field	Type	Required	Description & Format
`to`	String | Array	YES	'0244123456' or ['0244123456', '0501122334']. Ghana & intl formats.
`message`	String	YES	SMS body. 160 GSM chars = 1 credit unit; 70 chars for Unicode.
`senderId`	String	Optional	Branded Sender ID (default: TXTORA). Must be approved on account.

```
# Dispatch Request Example
curl -X POST "https://textora-bms-website.onrender.com/api/v1/send-sms" \
  -H "Content-Type: application/json" \
  -H "x-api-key: YOUR_API_KEY" \
  -d '{
    "to": ["0244123456", "0501122334"],
    "message": "Your verification code is 482910. Do not share this code.",
    "senderId": "TXTORA"
  }'

# Success Response (200 OK)
{
  "ok": true,
  "total_units_debited": 2,
  "remaining_balance": 448,
  "data": { "status": "success", "recipients_count": 2 }
}
```

6. Production Code Snippets

Node.js (Modern Fetch):

```
const res = await fetch("https://textora-bms-website.onrender.com/api/v1/send-sms", {
  method: "POST",
  headers: { "Content-Type": "application/json", "x-api-key": process.env.KEBSEND_API_KEY },
  body: JSON.stringify({ to: "0244123456", message: "OTP: 918234", senderId: "TXTORA" })
});
const data = await res.json();
console.log("Delivery status:", data);
```

Python 3 (Requests):

```
import requests

url = "https://textora-bms-website.onrender.com/api/v1/send-sms"
headers = { "Content-Type": "application/json", "x-api-key": "YOUR_API_KEY" }
payload = { "to": ["0244123456"], "message": "Order #482 confirmed!", "senderId": "TXTORA" }

response = requests.post(url, json=payload, headers=headers)
print(response.json())
```

7. HTTP Status Codes & Error Reference

HTTP Code	API Response Message	Meaning / Recommended Action
200 OK	`"ok": true`	SMS dispatched to telco carriers; units successfully deducted.
400 Bad Req	`Missing "to" or "message"`	Payload validation failed; verify JSON keys and recipient phone formats.
401 Unauth	`Missing or invalid API key`	Key is absent, invalid, or being sent to the incorrect Base URL.
402 Payment	`Insufficient balance`	Developer wallet credits exhausted. Top up via dashboard or recharge API.
429 Too Many	`Rate limit exceeded`	Rate limit is 120 calls/minute. Throttle requests or batch numbers in arrays.