VORON



ORBITER CLOCKWORK ASSEMBLY MANUAL

We build space shuttles with gardening tools
so anyone can have a space shuttle of their own.

HARDWARE



SOCKET HEAD CAP SCREW (SHCS)

Metric fastener with a cylindrical headand hex drive.

M3x8 Quantity 1



SOCKET HEAD CAP SCREW (SHCS)

Metric fastener with a cylindrical head and hex drive.

M3x16 Quantity 1



SOCKET HEAD CAP SCREW (SHCS)

Metric fastener with a cylindrical head and hex drive.

M3x20 Quantity 2



TAPERED HEAT-SET INSERTS FOR PLASTIC

The tapered shape makes it easier to guide these inserts into a hole during installation. Use a drill bit to create a straight hole, then taper the top half. Heat inserts with a soldering tip so that they melt the plastic when installed. As the plastic cools, it solidifies around the knurls and ridges on the insert for excellent resistance to both torque and pull-out.

M3 Brass Heat-Set Insert Quantity: 9

HARDWARE CONT.



PTFE Tube

The PTFE tube is used between the Orbiter extruder and the Toolhead. Specific hot end lengths are listed below:

Pheatus Dragon Hot end
PTFE Tube Length 45mm

E3D V6 Hot end
PTFE Tube Length ??mm (Not Tested Yet)

Slice Engineering Mosquito Hot end
PTFE Tube Length ??mm (Not Tested Yet)

PRINTED PARTS

Clockwork Adaptor Front

Clockwork Adaptor Back

Chain Anchor

Connector Cover

Filament Release Lever

Assembly A. Heat-Set Inserts

1



2



3



4



Assembly B. Orbiter Clockwork Adapter

5



6



Assembly C. Connecter Cover and Chain Anchor

7



8



9



Assembly Tip
This screw isn't necessary, so save it for future projects.

10



11



Assembly Tip
This screw isn't necessary, so save it for future projects.

12



13



14

Assembly Tip
This screw needs to be angled to bypass the main body of the orbiter.



15



16



17



Assembly Tip
Thread these two screws into the motor and then directly into the Chain Anchor.

18



19



Assembly Tip
Thread this screw directly into the Chain Anchor.

Assembly D. Filament Quick Release Lever

20



21



Assembly Tip
Thread this screw into the slot on the Chain Anchor until its tight then loosen by a half-turn.

22



Assembly E. Final Assembly

23



24



25



Assembly Tip
Insert the new PTFE tube and replace the original if applicable.

26



27



28



Assembly Tip

These two screws are not part of the BOM for the Orbiter Clockwork module, because they are from the Afterburner X-Carriage.

29

Assembly Tip
These two screws are not part of the BOM for the Orbiter Clockwork module, because they are from the Afterburner Fan Assembly.



30



Assembly Complete



Get the Latest Version of this document:
https://github.com/spacelab2021/Orbiter-Clockwork-Module/blob/main/docs/Orbiter_Cockwork_Manual.pdf

Version: OC-1001