Property	Values	Example

Mermaid Flowchart Customization Guide

Deep dive into flowchart customization — shapes, colors, layout, styling, and advanced patterns.

Node Shapes

Every shape has semantic meaning. Choose based on the node's purpose.

```
flowchart TD
    A[Rectangle - Process]
    B([Rounded - Start/End])
    C[(Database)]
    D{{Hexagon - Prepare/Setup}}
    E[/Parallelogram - Input/]
    F[\Parallelogram - Output\]
    G((Circle - Connection Point))
    H>Flag - Legacy]
    I{Diamond - Decision}
    J{{Double Hexagon}}
    K[["Subroutine"]]
    L[[("Cylindrical DB")]]
    M(("Double Circle"))
    N>"Asymmetric - Choice"]
```

Shape Syntax Quick Reference:

Rectangle	`[text]`	Standard process
Rounded	`([text])`	Start/end points
Stadium	`([text])`	Same as rounded
Subroutine	`[[text]]`	Function call
Cylindrical	`[(text)]`	Database
Circle	`((text))`	Connection point

Property	Values	Example
Parallelogram (input)	`[/text/]`	Input data
Parallelogram (output)	`[\text\]`	Output data
Trapezoid	`[/text\]`	Manual operation
Inverted Trapezoid	`[\text/]`	-

Arrow Types and Line Styles

Arrows communicate relationships. Mix types to show different connection meanings.

```
flowchart LR
    A1[Solid Arrow] --> A2[Target]
    B1[Dotted Arrow] -.-> B2[Optional/Weak]
    C1[Thick Arrow] ==> C2[Important/Primary]
    D1[No Arrow] --- D2[Association]
    E1[Dotted No Arrow] -.- E2[Weak Association]
    F1[Thick No Arrow] === F2[Strong Association]
    G1[Crossed Arrow] --x G2[Blocked/Prevented]
    H1[Circle End] o--o H2[Bidirectional]
    I1[Multi-Arrow] <--> I2[Two-way]
```

Arrow Syntax:

Solid line, arrow	`-->`	Standard flow
Dotted line, arrow	`-.->`	Optional/fallback
Thick line, arrow	`==>`	Primary/critical path
Solid line, no arrow	`---`	Association
Dotted line, no arrow	`-.-`	Weak association
Crossed	`--x`	Blocked
Circle ends	`o--o`	Bidirectional
Double arrow	`<-->`	Two-way communication

Adding Labels:

Property	Values	Example

```
    A --> B
    C ---> D
    E -----> F
    G -------> H
```

Color and Styling with classDef

`classDef` creates reusable style classes. Apply to multiple nodes for consistency.

Basic classDef Pattern

```
flowchart TD
    Start[Start] --> Process1[Process Data]
    Process1 --> Decision{Valid?}
    Decision -->|Yes| Success[Complete]
    Decision -->|No| Error[Show Error]
    Error --> Process1

    classDef successStyle fill:#51cf66,stroke:#2b8a3e,color:#fff,stroke-width:2px
    classDef errorStyle fill:#ff6b6b,stroke:#c92a2a,color:#fff,stroke-width:2px
    classDef processStyle fill:#4dabf7,stroke:#1971c2,color:#fff

    class Success successStyle
    class Error errorStyle
    class Process1,Start,Decision processStyle
```

classDef Syntax:

```
classDef <className> <property>:<value>,<property>:<value>,...
class <nodeId> <className>
```

Common Properties:

`fill`	Color hex/rgb	`fill:#ff6b6b`
`stroke`	Border color	`stroke:#c92a2a`
`stroke-width`	Border thickness	`stroke-width:3px`
`color`	Text color	`color:#fff`

Property	Values	Example

```
    A[Important Process]

    classDef important fill:#ff6b6b,stroke:#c92a2a
    classDef highlighted stroke-width:4px,stroke-dasharray: 5 5

    class A important,highlighted
```

Inline Styling (Quick One-offs)

```
flowchart LR
    A[Normal]
    B[Red]:::redStyle
    C[Blue]:::blueStyle

    classDef redStyle fill:#ff6b6b,color:#fff
    classDef blueStyle fill:#4dabf7,color:#fff
```

Theme Customization

Apply global themes to entire diagrams.

Pre-built Themes

```
%%{init: {'theme':'dark'}}%%
flowchart TD
    A[Dark Theme] --> B[High Contrast]
```

Available themes: `default`, `dark`, `forest`, `neutral`, `base`

Custom Theme Variables

```
%%{init: {
  'theme': 'base',
  'themeVariables': {
    'primaryColor': '#4dabf7',
    'primaryTextColor': '#fff',
    'primaryBorderColor': '#1971c2',
    'lineColor': '#364fc7',
    'secondaryColor': '#51cf66',
    'tertiaryColor': '#ff6b6b',
```

Property	Values	Example

Common Theme Variables:

```
{
  'primaryColor': '#color',        // Main nodes
  'primaryTextColor': '#color',    // Text on primary
  'primaryBorderColor': '#color',  // Border on primary
  'secondaryColor': '#color',      // Secondary nodes
  'tertiaryColor': '#color',       // Tertiary nodes
  'lineColor': '#color',           // Connector lines
  'fontSize': '16px',              // Base font size
  'fontFamily': 'sans-serif',      // Font family
  'background': '#color',          // Diagram background
  'mainBkg': '#color',             // Node background
  'textColor': '#color',           // Default text color
  'edgeLabelBackground': '#color'  // Label background
}
```

Layout and Direction

Control diagram orientation and flow.

```
flowchart TD
    A[Top to Bottom - TD]
    B[Same as TB]
```

```
flowchart LR
    A[Left to Right - LR]
```

```
flowchart RL
    A[Right to Left - RL]
```

```
flowchart BT
    A[Bottom to Top - BT]
```

Direction Codes:

- `TD` or `TB` — Top Down / Top to Bottom (default)
- `LR` — Left to Right
- `RL` — Right to Left

Property	Values	Example

```
flowchart TD
    A[Start]

    subgraph Processing
        B[Step 1]
        C[Step 2]
        D[Step 3]
    end

    subgraph Output
        E[Format]
        F[Send]
    end

    A --> B
    D --> E
    F --> G[End]
```

Named Subgraphs with Custom Direction

```
flowchart TB
    A[Input]

    subgraph Frontend ["Frontend Layer"]
        direction LR
        B[UI]
        C[State]
        B --> C
    end

    subgraph Backend ["Backend Services"]
        direction TB
        D[API Gateway]
        E[Auth Service]
        F[Data Service]
        D --> E
        D --> F
    end

    A --> Frontend
    Frontend --> Backend
```

Nested Subgraphs

Property	Values	Example

```
        end

        subgraph API ["API Layer"]
            D[Routes]
            E[Controllers]
        end

        UI --> API
    end

    A --> System
```

Styled Subgraphs

```
flowchart TD
    subgraph S1 ["Production Environment"]
        A[Load Balancer]
        B[App Server 1]
        C[App Server 2]
    end

    subgraph S2 ["Database Cluster"]
        D[(Primary)]
        E[(Replica 1)]
        F[(Replica 2)]
    end

    A --> B
    A --> C
    B --> D
    C --> D
    D -.-> E
    D -.-> F

    style S1 fill:#e3f2fd,stroke:#1976d2,stroke-width:2px
    style S2 fill:#f3e5f5,stroke:#7b1fa2,stroke-width:2px
```

Advanced Styling Patterns

Individual Node Styling

Property	Values	Example

```
flowchart LR
    A --> B
    B --> C
    C --> D
    D --> E

    linkStyle 0 stroke:#ff6b6b,stroke-width:4px
    linkStyle 1 stroke:#51cf66,stroke-width:2px
    linkStyle 2 stroke:#4dabf7,stroke-width:2px,stroke-dasharray: 5 5
    linkStyle 3 stroke:#ffd43b,stroke-width:3px
```

Link Styling Properties:

```
linkStyle <index> stroke:<color>,stroke-width:<width>,stroke-dasharray:<pattern>
```

Default Styles for All Nodes/Links

```
%%{init: {
  'flowchart': {
    'defaultRenderer': 'elk',
    'nodeSpacing': 50,
    'rankSpacing': 50,
    'curve': 'basis'
  }
}}%%
flowchart TD
    A --> B --> C --> D
```

Curve Options:

- `basis` — Smooth curves
- `linear` — Straight lines
- `step` — Step-like connections
- `stepBefore` — Step before
- `stepAfter` — Step after

Practical Styling Patterns

Status Indicators

```
flowchart TD
```

Property	Values	Example

```
    F --> J[Queue]

    classDef running fill:#ffd43b,stroke:#f59f00,color:#000
    classDef success fill:#51cf66,stroke:#2b8a3e,color:#fff
    classDef error fill:#ff6b6b,stroke:#c92a2a,color:#fff
    classDef pending fill:#adb5bd,stroke:#495057,color:#fff

    class C,G running
    class D,H success
    class E,I error
    class F,J pending
```

Priority Levels

```
flowchart LR
    A[Backlog] --> B{Prioritize}

    B --> C[P0 - Critical]
    B --> D[P1 - High]
    B --> E[P2 - Medium]
    B --> F[P3 - Low]

    classDef p0 fill:#fa5252,stroke:#c92a2a,color:#fff,stroke-width:3px
    classDef p1 fill:#ff922b,stroke:#e8590c,color:#fff,stroke-width:2px
    classDef p2 fill:#ffd43b,stroke:#fab005,color:#000
    classDef p3 fill:#adb5bd,stroke:#868e96,color:#fff

    class C p0
    class D p1
    class E p2
    class F p3
```

Environment Layers

```
flowchart TB
    subgraph DEV ["Development"]
        D1[Local]
        D2[Dev Server]
    end

    subgraph STAGING ["Staging"]
        S1[Staging API]
        S2[Test DB]
```

Property	Values	Example

```
    style DEV fill:#e3f2fd,stroke:#1976d2,stroke-width:2px,stroke-dasharray: 5 5
    style STAGING fill:#fff3e0,stroke:#f57c00,stroke-width:2px
    style PROD fill:#ffebee,stroke:#c62828,stroke-width:3px
```

Data Flow with Emphasis

```
flowchart LR
    User[User Input] ==> Validate{Validate}
    Validate ==>|Valid| Process["Process Data"]
    Validate -.->|Invalid| Error[Show Error]

    Process ==> Save[(Save to DB)]
    Process ==> Cache[(Update Cache)]

    Save ==> Success[Return Success]
    Cache -.-> Success

    Error -.-> User

    classDef criticalPath fill:#4dabf7,stroke:#1971c2,color:#fff,stroke-width:3px
    classDef errorPath fill:#ff6b6b,stroke:#c92a2a,color:#fff

    class Validate,Process,Save,Success criticalPath
    class Error errorPath

    linkStyle 0,1,3,4,5 stroke:#1971c2,stroke-width:3px
    linkStyle 2,6 stroke:#c92a2a,stroke-width:2px,stroke-dasharray: 5 5
```

Interactive Features

Clickable Nodes

```
flowchart LR
    A[Documentation] --> B[API Reference]
    C[Source Code] --> D[Tests]

    click A "https://docs.example.com" "Open Documentation" _blank
    click B href "https://api.example.com" "View API Docs"
    click C callback "viewSource()" "View Source Code"
```

Property	Values	Example

```
flowchart TD
    A[Hover for Info]

    style A title:"This node has a tooltip"
```

Layout Optimization

Managing Complex Layouts

Problem: Messy crossing lines

```
flowchart TD
    A --> B
    A --> C
    A --> D
    B --> E
    C --> E
    D --> E
    E --> F
```

Solution: Use invisible nodes for routing

```
flowchart TD
    A --> B
    A --> C
    A --> D
    B --> E
    C --> E
    D --> E
    E --> F

    %% Invisible routing nodes
    A ~~~ X1[ ]
    X1 ~~~ X2[ ]

    style X1 opacity:0
    style X2 opacity:0
```

Rank Separation Control

Property	Values	Example

```
    B ~~~ C ~~~ D
```

Real-World Examples

CI/CD Pipeline

```
flowchart LR
    Start([Code Push]) --> Lint[Lint Code]
    Lint --> Test[Run Tests]
    Test --> Build[Build Docker Image]
    Build --> Security[Security Scan]
    Security --> Push[Push to Registry]
    Push --> Deploy{Deploy?}

    Deploy -->|Staging| DeployStaging[Deploy to Staging]
    Deploy -->|Production| DeployProd[Deploy to Production]

    Test -.->|Fail| Notify1[Notify Team]
    Security -.->|Vulnerabilities| Notify2[Block & Notify]

    DeployStaging --> Verify1[Run E2E Tests]
    Verify1 -->|Pass| Success1([Staging Ready])
    Verify1 -.->|Fail| Rollback1[Auto Rollback]

    DeployProd --> Verify2[Health Check]
    Verify2 -->|Pass| Success2([Live])
    Verify2 -.->|Fail| Rollback2[Emergency Rollback]

    classDef buildStep fill:#4dabf7,stroke:#1971c2,color:#fff
    classDef testStep fill:#51cf66,stroke:#2b8a3e,color:#fff
    classDef deployStep fill:#ffd43b,stroke:#f59f00,color:#000
    classDef errorStep fill:#ff6b6b,stroke:#c92a2a,color:#fff
    classDef successStep fill:#51cf66,stroke:#2b8a3e,color:#fff,stroke-width:3px

    class Lint,Build,Push buildStep
    class Test,Security,Verify1,Verify2 testStep
    class DeployStaging,DeployProd deployStep
    class Notify1,Notify2,Rollback1,Rollback2 errorStep
    class Success1,Success2 successStep

    linkStyle 8,9,12,14 stroke:#ff6b6b,stroke-width:2px,stroke-dasharray: 5 5
```

Property	Values	Example

```
    ValidateToken -->|Yes| Dashboard[Load Dashboard]
    ValidateToken -->|No| Refresh{Can Refresh?}

    Refresh -->|Yes| RefreshToken[Refresh Token]
    Refresh -->|No| LoginForm

    RefreshToken --> Dashboard

    LoginForm --> Submit[User Submits]
    Submit --> Validate{Credentials Valid?}

    Validate -->|Yes| CreateSession[Create Session]
    Validate -->|No| RateLimit{Rate Limited?}

    RateLimit -->|Yes| Block[Block & Show Captcha]
    RateLimit -->|No| Error[Show Error]

    Error --> LoginForm
    Block --> LoginForm
    CreateSession --> Dashboard

    Dashboard --> End([User Active])

    classDef authStep fill:#4dabf7,stroke:#1971c2,color:#fff
    classDef successStep fill:#51cf66,stroke:#2b8a3e,color:#fff
    classDef errorStep fill:#ff6b6b,stroke:#c92a2a,color:#fff
    classDef decisionStep fill:#ffd43b,stroke:#f59f00,color:#000

    class LoginForm,Submit,CreateSession,RefreshToken authStep
    class Dashboard,End successStep
    class Error,Block errorStep
    class CheckSession,ValidateToken,Validate,Refresh,RateLimit decisionStep
```

Debugging Tips

1. **Test incrementally** — Add nodes/styling one at a time
2. **Use mermaid.live** for real-time preview
3. **Comment out sections** to isolate issues:

```
flowchart TD
    A --> B
    %% B --> C
    %% C --> D
```

Property	Values	Example

Named: `red`, `blue`, `green`

Sizes: - Pixels: `2px`, `10px` - Percent: `50%` - Em: `1.5em`

Stroke Patterns: - Solid: `stroke-width:2px` - Dashed: `stroke-dasharray: 5 5` - Dotted: `stroke-dasharray: 1 3` - Long dash: `stroke-dasharray: 10 5`

Font Families: - `monospace` - `sans-serif` - `serif` - `'Inter', system-ui, sans-serif`

Common Color Palettes

Status Colors (Friendly)

```
Success: fill:#51cf66,stroke:#2b8a3e,color:#fff
Warning: fill:#ffd43b,stroke:#f59f00,color:#000
Error: fill:#ff6b6b,stroke:#c92a2a,color:#fff
Info: fill:#4dabf7,stroke:#1971c2,color:#fff
Neutral: fill:#adb5bd,stroke:#495057,color:#fff
```

Priority Levels

```
P0 Critical: fill:#fa5252,stroke:#c92a2a,color:#fff
P1 High: fill:#ff922b,stroke:#e8590c,color:#fff
P2 Medium: fill:#ffd43b,stroke:#fab005,color:#000
P3 Low: fill:#94d82d,stroke:#5c940d,color:#000
```

Environment Tiers

```
Dev: fill:#e3f2fd,stroke:#1976d2,color:#000
Staging: fill:#fff3e0,stroke:#f57c00,color:#000
Production: fill:#ffebee,stroke:#c62828,color:#000
```

Quick Customization Workflow

1. **Build structure** (nodes + arrows)
2. **Define classDef** for common styles
3. **Apply classes** to nodes
4. **Style links** if needed

Property	Values	Example

```
    A[Start] --> B[Process]
    B --> C{Decision}
    C -->|Yes| D[Success]
    C -->|No| E[Error]

    %% 2. Define styles
    classDef successStyle fill:#51cf66,stroke:#2b8a3e,color:#fff
    classDef errorStyle fill:#ff6b6b,stroke:#c92a2a,color:#fff

    %% 3. Apply styles
    class D successStyle
    class E errorStyle

    %% 4. Style links (optional)
    linkStyle 2 stroke:#51cf66,stroke-width:2px
    linkStyle 3 stroke:#ff6b6b,stroke-width:2px
```