University of Science

Faculty of Information Technology

Data Structures and Algorithms Project Report

Topic: STRING MATCHING

Course: Data Structures & Algorithms

Instructor:
Le Thanh Tung
Tran Hoang Quan

Class: 25C10
Group ID: 07

Group Members:
Dang Ba Lam - 25127403
Hua Minh Khang - 25127073
Trinh Bao Khoi - 25127256
Nguyen Huu Ngoc Thuan - 25127153

Ho Chi Minh City, March 13, 2026

Contents

1 Group Information

Student Name	**ID**	**Assigned Tasks**	**% Completed**
Dang Ba Lam	25127403	Leader, Command line arguments, Implementation & Report (The Naive approach, Experimental results)	25%
Hua Minh Khang	25127073	Setting Algorithm mode and Comparisons mode, Make input for Input Size, Implementation & Report (The Knuth-Morris-Pratt algorithm, The Aho Corasick algorithm Acknowledgement)	25%
Trinh Bao Khoi	25127256	Data Generator, Implementation & Report (The Boyer-Moore algorithm, Project organization)	25%
Nguyen Huu Ngoc Thuan	25127153	Adjust Comparisons and Time, Implementation & Report (The Rabin-Karp algorithm, Title Page, Table of Contents, Team Members List)	25%
		Total Group Completion	**110%**

Table 1: Group Information

**Note: All members participated in Time Calculator implementation, Report writing, Citations, and Final checking.*

2 Problem Statement

STRING matching is a problem that find all occurrences of a pattern in the text. This problem is an indispensable technique in computer science for solving various crucial problems, such as text editing, text searching, and symbol manipulation.[?]

The string matching problem is defined as follows: We assume that the text is a string $T[1..n]$ of length n and the pattern is a string $P[1..m]$ of length m which $m \leq n$. The problem is to find all occurrences of P in T by shifting P along T such that $0 \leq s \leq n - m$ (s is the shift amount) and $T[s + 1..s + m] = P[1..m]$ (that is, if $T[s + i] = P[i]$, for $1 \leq i \leq m$).[?]

For instance:

- If $T =$ "ababcab" and $P =$ "abc", then the output is $(3 \rightarrow 5)$ because the pattern occurs at position 3 in the text.



Figure 1: T = "ababcab" and P = "abc"

- If $T =$ "aaaaa" and $P =$ "aa", then the output is $(1 \rightarrow 2)$, $(2 \rightarrow 3)$, $(3 \rightarrow 4)$, and $(4 \rightarrow 5)$ because the pattern occurs at positions 1, 2, 3, and 4 in the text.



Figure 2: T = "aaaaa" and P = "aa"

3 Algorithms Analysis

3.1 The Naïve string-matching algorithm (Brute-Force approach)

3.1.1 Introduction & Application

- **Core idea:** According to Abdeen[**?**], the brute-force algorithm works with two pointers; a "text pointer" i and a "pattern pointer" j. For all possible shifts of the pattern P over the text T, compare the pattern characters with the corresponding text characters. If a mismatch occurs, i is incremented by 1, and j is reset to 0 and the comparing process is restarted. In the case that all characters match, the algorithm records the position of the match and continues searching for the next possible match.

- **Real-world applications:**
  - Text Editors: There are used in "Search" or "Find and Replace" features to locate target words.
  - Bioinformatics: Searching for specific DNA sequences.
  - Checking for Plagiarism: Comparing documents to find and compare a script or a piece of code with the exact match in a large database.

3.1.2 Pseudocode

Notation:

- **Text T (R rows, C columns)**: The main text being searched.
- **Pattern P (K: the number of keywords)**: The list of strings that we are looking for.
- **Positions ([(start position, end position), . . .])**: A list storing the indices where a complete match is found.

```
BRUTE-FORCE-ALGORITHM(T, P, K, R, C)
pos = empty array of size K
for idx = 1 to K do
    keyword = P[idx]
    m = keyword.length

    ▷ Search Horizontally
    for i = 1 to R do
        for j = 0 to C − m do
            if keyword[1 . . . m] == T[i, j + 1 . . . j + m] then
                add position to pos[idx]
            end if
        end for
    end for

    ▷ Search Vertically
    for i = 1 to C do
        for j = 0 to R − m do
            if keyword[1 . . . m] == T[j + 1 . . . j + m, i] then
                add position to pos[idx]
```

```
            end if
        end for
    end for
end for
return pos
```

3.1.3 Step-by-step trace[?]

Notation:

- **Text** T **(length** n**)**: The main text being searched.
- **Pattern** P **(length** m**)**: The string that we are looking for.
- **Shift** (s): The current offset of the text T.
- **Positions ([(start position, end position), . . .])**: A list storing the indices where a complete match is found.

Example: text $T = [a, a, b, c, a, b, b]$ and pattern $P = [a, b, c]$



Figure 3: Step 1

- The first character 'a' matches between the pattern and the text.

  The second character in text T ('a') does not match the second character in pattern P ('b').

  Text at the bottom shows the current shift is $s = 0$ and the list of found matches is empty ($Positions = []$).



s = 1

Positions = [(1, 3)]

Figure 4: Step 2

- All characters in pattern P ('a', 'b', 'c') successfully match the corresponding characters in text T ('a', 'b', 'c').

  The shift is $s = 1$ and the list of found matches is updated to record this position ($Positions = [(1, 3)]$).



s = 2

Positions = [(1, 3)]

Figure 5: Step 3

- The first character in pattern P ('a') does not match the character in text T ('b') at the current shift position $s = 2$.

  Skip to the next shift without updating $Positions$.



s = 3

Positions = [(1, 3)]

Figure 6: Step 4

- The first character in pattern P ('a') does not match the character in text T ('c') at the current shift position $s = 2$.

  Skip to the next shift without updating *Positions*.



s = 4

Positions = [(1, 3)]

Figure 7: Step 5

- The first two characters in pattern P ('a', 'b') match the corresponding characters in text T, but the third character in pattern P ('c') does not match the character in text T ('b') at the current shift position $s = 4$.

  Skip to the next shift without updating *Positions*.

- After that, s increases by 1. Because $s = 5$ and $n - m = 7 - 3 = 4$, we have $s > n - m$. The algorithm terminates and returns the list of found matches: Positions $= [(1, 3)]$.

3.1.4 Complexity

Metric	Complexity	Reasoning
Time (Average)	$O(K \cdot R \cdot C)$	In practice, a mismatch usually occurs after only a few character comparisons.
Time (Best with flag optimization)	$O(K \cdot R \cdot C)$	The first character of the pattern always results in a mismatch at every shift.
Auxiliary Space	$O(1)$	The algorithm uses only a constant amount of extra memory for loop indices.

Table 2: Complexity Analysis of 2D Brute Force Algorithm

3.1.5 Discussion

- In the basic brute-force implementation, the time complexity remains consistent across different scenarios.
- However, there is a way to optimize the brute-force algorithm by skipping some shifts when a mismatch occurs. This can be achieved by using a flag.
  - In Scenario 1, the number of patterns K is small, and the text is from 10×10 to 500×500. Brute-force approach is efficient and likely linear running time $O(R \cdot C)$.
  - In Scenario 2, the number of patterns K is large, and the text is fixed at 100×100. This scenario is more challenging for the brute-force approach, as the running time multiplies by K times, which is much longer compared to scenario 1.
  - In conclusion, the brute-force approach is more suitable for scenarios with a small number of patterns. It is worse for scenarios with a large number of patterns.

3.2 The Knuth-Morris-Pratt algorithm (KMP algorithm)

3.2.1 Introduction & Application

- **Core idea:** According to Abdeen[**?**], the brute-force algorithm works with two pointers; a "text pointer" i and a "pattern pointer" j. For all possible shifts of the pattern P over the text T, compare the pattern characters with the corresponding text characters. If mismatch occurs, i is incremented by 1, and j is reset to 0 and the comparing process is restarted. In the case that all characters match, the algorithm records the position of the match and continues searching for the next possible match.
- **Real-world applications:**
  - Text Editors: Using in "Search" or "Find and Replace" features to locate destination words.
  - Bioinformatics: Searching for specific DNA.
  - Checking for Plagiarism: Comparing documents to find and compare a script or a piece of code with the exact match in a large database.

3.2.2 Pseudocode

Notation:

- **Text T (R rows, C columns)**: The 2D grid of characters.
- **Pattern P (K keywords)**: The list of patterns to search for.
- **Prefix Array π**: An array storing the lengths of the longest proper prefix that is also a suffix.

```
CONVERT-GRID-TO-STRINGS(T, R, C)
ans = empty array
    ▷ Extract Rows
for i = 0 to R − 1 do
    tmpString = empty string
    for j = 0 to C − 1 do
        tmpString = tmpString + T[i][j]
    end for
    append tmpString to ans
end for
    ▷ Extract Columns
for j = 0 to C − 1 do
    tmpString = empty string
    for i = 0 to R − 1 do
        tmpString = tmpString + T[i][j]
    end for
    append tmpString to ans
end for
return ans
```

```
CALCULATE-POSITION(idxString, m, R, idx)
if idxString < R then
    ▷ Horizontal match (Row extraction)
    start = (idxString, idx − 2 · m)
    end = (idxString, idx − m − 1)
else
    ▷ Vertical match (Column extraction)
    start = (idx − 2 · m, idxString − R)
    end = (idx − m − 1, idxString − R)
end if
return (start, end)
```

```
KMP-ALGORITHM(T, P, K, R, C)
pos = array of K empty lists
List_string = CONVERT-GRID-TO-STRINGS(T, R, C)
N = List_string.length

for idxString = 0 to N − 1 do
    for pIdx = 0 to K − 1 do
        kmpString = P[pIdx] + '#' + List_string[idxString]
        L = kmpString.length
        m = P[pIdx].length
```

```
        π = array of size L initialized to 0
    ▷ Compute Prefix Function & Search
        for i = 1 to L − 1 do
            j = π[i − 1]
            while j > 0 and kmpString[j] ≠ kmpString[i] do
                j = π[j − 1]
            end while
            if kmpString[j] == kmpString[i] then
                j = j + 1
            end if
            π[i] = j
    ▷ Match found
            if π[i] == m then
                matchPos = CALCULATE-POSITION(idxString, m, R, i)
                append matchPos to pos[pIdx]
            end if
        end for
    end for
end for
return pos
```

3.2.3 Step-by-step trace[?]

Notation:

- **Text** T **(length** n**)**: The main text being searched.
- **Pattern** P: The string that we are looking for.
- **Shift** (s): The current offset of the text T.
- **Positions ([(start position, end position), . . .])**: A list storing the indices where a complete match is found.

Example: text $T = [a, a, b, c, a, b, b]$ and pattern $P = [a, b, c]$



Figure 8: Step 1

- The first character 'a' matches in both arrays.

  The second character in text T ('a') does not match the second character in pattern P ('b').

  Text at the bottom shows the current shift is $s = 0$ and the list of found matches is empty ($Positions = []$).



Figure 9: Step 2

- All characters in pattern P ('a', 'b', 'c') successfully match the corresponding characters in text T ('a', 'b', 'c').

  Shift is $s = 1$ and the list of found matches is updated to record this position ($Positions = [(1, 3)]$).



s = 2

Positions = [(1, 3)]

Figure 10: Step 3

- The first character in pattern P ('a') does not match the character in text T ('b') at the current shift position $s = 2$.

  Skip to the next shift without updating *Positions*.



s = 3

Positions = [(1, 3)]

Figure 11: Step 4

- The first character in pattern P ('a') does not match the character in text T ('c') at the current shift position $s = 2$.

  Skip to the next shift without updating *Positions*.



Figure 12: Step 5

- The first two characters in pattern P ('a', 'b') match the corresponding characters in text T, but the third character in pattern P ('c') does not match the character in text T ('b') at the current shift position $s = 4$.

  Skip to the next shift without updating *Positions*.

- After that, s increases by 1. Because $s = 5$ and $n - m = 7 - 3 = 4$, we have $s > n - m$. The algorithm terminates and returns the list of found matches: Positions $= [(1, 3)]$.

3.2.4 Complexity

Metric	Complexity	Reasoning
Time (Worst)	$O(K \cdot m \cdot R \cdot C)$	Occurs when patterns and text share many prefix characters (e.g., all 'A's).
Time (Average)	$O(K \cdot R \cdot C)$	In practice, a mismatch usually occurs after only a few character comparisons.
Time (Best)	$O(K \cdot R \cdot C)$	The first character of the pattern always results in a mismatch at every shift.
Auxiliary Space	$O(1)$	The algorithm uses only a constant amount of extra memory for loop indices.

Table 3: Complexity Analysis of 2D Brute Force Algorithm

3.2.5 Discussion

- In scenarios 1, the number of patterns K is small, and the text is from 10×10 to 500×500. Brute-force approach is efficient and likely linear running time $O(R \cdot C)$.

- In scenarios 2, the number of patterns K is large, and the text is fixed at 100×100. This scenario is more challenging for the brute-force approach, as the running time multiplies by K times, which is much longer compared to scenario 1.

- In conclusion, the brute-force approach is more suitable for scenarios with a small number of patterns. It is worse for scenarios with a large number of one.

3.3 The Boyer Moore

3.3.1 Introduction & Application

- **Core idea:** The Boyer Moore Algorithm is a practical method to find patterns. This algorithm is the combination of three main ideas comprising scanning the pattern in reverse order, bad character heuristic and good suffix heuristic. This speeds up the searching process considerably by skipping a plenty of characters.
- **Reality applications:**
  - Text Editors: Using in "Search" or "Find and Replace" features to locate the destination of the words.
  - Intrusion Detection Systems (Network Security): use Boyer-Moore to scan network traffic in real-time for "malicious signatures"—specific byte patterns that indicate a cyberattack or virus.
  - Large-Scale Plagiarism Detection: compare submitted essays against billions of web pages and academic journals to find copied content.

3.3.2 Pseudocode

Notation:

- **Text T (R rows, C columns)**: The 2D character matrix.
- **Pattern P (K keywords)**: The list of strings to search.
- **Heuristics**: BC (Bad Character table) and GS (Good Suffix table).

```
BOYER-MOORE ALGORITHM(T, P, K, R, C)
pos = empty array of size K
for idx = 1 to K do
    P_i = P[idx], m = P_i.length
    BC = PreProcessBadChar(P_i)
    GS = PreProcessGoodSuffix(P_i)
  ▷ Horizontal Search (Rows)
    for r = 0 to R − 1 do
        s = 0
        while s ≤ C − m do
            j = m − 1
            while j ≥ 0 and P_i[j] == T[r, s + j] do
                j = j − 1
            end while
            if j < 0 then
                add (r, s) to pos[idx]
                s = s + GS[0]
            else
                s = s + max(GS[j], j − BC[T[r, s + j]])
```

```
            end if
        end while
    end for
    ▷ Vertical Search (Columns)
    for c = 0 to C − 1 do
        s = 0
        while s ≤ R − m do
            j = m − 1
            while j ≥ 0 and P_i[j] == T[s + j, c] do
                j = j − 1
            end while
            if j < 0 then
                add (s, c) to pos[idx]
                s = s + GS[0]
            else
                s = s + max(GS[j], j − BC[T[s + j, c]])
            end if
        end while
    end for
end for
return pos
```

3.3.3 Step-by-step trace

Notation:

- **Text** T **(length** n**)**: The main text being searched.
- **Pattern** P: The string that we are looking for.
- **Shift** (s): The current offset of the text T.
- **Positions ([(start position, end position), . . .])**: A list storing the indices where a complete match is found.

Example: text $T = [G, C, A, T, G, C, C, T, A, G]$ and pattern $P = [T, A, T, G]$

- Step 1: Build bad character and good suffix tables base on the pattern we are searching for:

char	A	T	G
shift value	1	2	3

Figure 13: Bad character table

index j	0	1	2	3
shift value	4	4	4	1

Figure 14: Good suffix table

Note:

- **Bad character table:** Choose the index for characters from 0 to n - 1. In this case, T appears two times, only the last appearance are regconized.
- **Good suffix table:** For index j from 3 to 0, if the suffix of the character at index j is found, the shift value will be decreased. In this example, index 3 is the exception since there is no suffix and the shift value is 1, other suffixes including g, tg, atg are not found in the prefix of the pattern, then their pattern shifts is the length of the pattern.

- Step 2: Compare the patterns and make shifts based on preprocessing values.



Figure 15: compare pattern from right to left

Mismatch at index j = 3, then calculate the shift value.

shift = max(GS, BC)

GS = 1, BC = max(1, j - lastOccur) = max(1, 3 - 2) = 1

⇒ shift value = 1

- **Continue searching process**



Figure 16: compare pattern

Mismatch at index 0, continue calculate the pattern shift
Shift value = max(GS, BC) = max(4, 1) = 4

- **Shift by 4 characters**



Figure 17: Make larger shift by using good suffix heuristic

Mismatch at index 3, continue calculate shift value
shift value = max(GS, BC) = max(1, 2) = 2

- **Shift by 2 characters**



Figure 18: Make bigger shift by using bad character heuristic

The algorithm stops since the pattern is out of text's range.

3.3.4 Complexity

Metric	Complexity	Reasoning
Time (Worst)	$O(K \cdot m \cdot R \cdot C)$	Occurs when many characters are repeated and both bad character and good suffix rules provide minimal shifts
Time (Average)	$O(R \cdot C)$	In reality, the rules of bad character and good suffix usually make larger skips and considerably improve the efficiency of the algorithm.
Time (Best)	$O(\frac{R \cdot C}{m})$	In best scenario, mismatches happen at the last character, allowing maximum shifts close to the pattern length(m).
Auxiliary Space	$O(\|\Sigma\| + m)$	The algorithm uses extra memory for bad character table (alphabet size) and good suffix table (pattern length)

Table 4: Complexity Analysis of 2D Boyer-Moore Algorithm

3.3.5 Discussion

- In Scenario 1, where the number of patterns K is small and the text size ranges from 10×10 to 500×500, the Boyer–Moore algorithm performs very efficiently due to its ability to skip large portions of the text. The running time is close to $O(R \cdot C)$ in practice.
- In Scenario 2, where the number of patterns K is large and the text is fixed at 100×100, the total running time increases linearly with K. However, Boyer–Moore still outperforms brute-force due to fewer comparisons per pattern.
- In conclusion, the Boyer–Moore algorithm is particularly effective when the pattern is relatively long and the alphabet is large, as it can achieve significant shifts and reduce the number of comparisons.

3.4 The Aho-Corasick algorithm

3.4.1 Introduction & Application

- **Core idea:** According to Abdeen[**?**], the brute-force algorithm works with two pointers; a "text pointer" i and a "pattern pointer" j. For all possible shifts of the pattern P over the text T, compare the pattern characters with the corresponding text characters. If mismatch occurs, i is incremented by 1, and j is reset to 0 and the comparing process is restarted. In the case that all characters match, the algorithm records the position of the match and continues searching for the next possible match.
- **Real-world applications:**
  - Text Editors: Using in "Search" or "Find and Replace" features to locate destination words.
  - Bioinformatics: Searching for specific DNA.

- Checking for Plagiarism: Comparing documents to find and compare a script or a piece of code with the exact match in a large database.

3.4.2 Pseudocode

Notation:

- **Trie Node**: A structure containing a character pC, a list of pattern indices pos, child pointers nxt, transition pointers go, a suffix link $link$, and a parent pointer par.
- **Text T (R rows, C columns)**: The 2D grid of characters.
- **Pattern P (K keywords)**: The list of patterns to search for.
- **List_string**: A 1D array of size $M = R + C$, containing all rows followed by all columns extracted from T.

```
ADD-STRING(S, idx, root)
cur = root
for each character c in S do
    if cur.nxt[c] == null then
        cur.nxt[c] = new Node
        cur.nxt[c].par = cur
        cur.nxt[c].pC = c
    end if
    cur = cur.nxt[c]
end for
append idx to cur.pos
```

```
GET-LINK(u, root)
if u.link == null then
    if u == root or u.par == root then
        u.link = root
    else
        u.link = GO(GET-LINK(u.par), u.pC)
    end if
end if
return u.link
```

```
GO(u, c, root)
if u.go[c] == null then
    if u.nxt[c] ≠ null then
        u.go[c] = u.nxt[c]
    else
        u.go[c] = (u == root) ? u : GO(GET-LINK(u), c)
    end if
end if
return u.go[c]
```

```
SEARCH-STRING(S, IDX, R, P, ans, root)
cur = root
for i = 0 to S.length − 1 do
    cur = GO(cur, S[i])
```

```
    tmp = cur
    while tmp ≠ root do
        for each idx in tmp.pos do
            m = P[idx].length
            if IDX < R then    ▷ Horizontal match (Row extraction)
                start = (IDX, i − m + 1)
                end = (IDX, i)
            else   ▷ Vertical match (Column extraction)
                start = (i − m + 1, IDX − R)
                end = (i, IDX − R)
            end if
            append (start, end) to ans[idx]
        end for
        tmp = Get-Link(tmp)
    end while
end for
```

```
Aho-Corasick(T, P, K, R, C)
List_string = Convert-Grid-To-Strings(T)
ans = array of K empty lists
root = new Node
maxLen = max(R, C)
    ▷ Build the Trie
for i = 0 to K − 1 do
    if P[i].length ≤ maxLen then
        Add-String(P[i], i, root)
    end if
end for
    ▷ Process all rows and columns
for i = 0 to List_string.length − 1 do
    Search-String(List_string[i], i, R, P, ans, root)
end for

Remove-Trie(root)    ▷ Free allocated memory
return ans
```

3.4.3 Step-by-step trace[?]

Notation:

- **Text T (length n)**: The main text being searched.
- **Pattern P**: The string that we are looking for.
- **Shift (s)**: The current offset of the text T.
- **Positions ([(start position, end position), ...])**: A list storing the indices where a complete match is found.

Example: text $T = [a, a, b, c, a, b, b]$ and pattern $P = [a, b, c]$



Figure 19: Step 1

- The first character 'a' matches in both arrays.

  The second character in text T ('a') does not match the second character in pattern P ('b').

  Text at the bottom shows the current shift is $s = 0$ and the list of found matches is empty ($Positions = []$).



Figure 20: Step 2

- All characters in pattern P ('a', 'b', 'c') successfully match the corresponding characters in text T ('a', 'b', 'c').

  Shift is $s = 1$ and the list of found matches is updated to record this position ($Positions = [(1, 3)]$).



s = 2

Positions = [(1, 3)]

Figure 21: Step 3

- The first character in pattern P ('a') does not match the character in text T ('b') at the current shift position $s = 2$.

  Skip to the next shift without updating *Positions*.



s = 3

Positions = [(1, 3)]

Figure 22: Step 4

- The first character in pattern P ('a') does not match the character in text T ('c') at the current shift position $s = 2$.

  Skip to the next shift without updating *Positions*.



Figure 23: Step 5

- The first two characters in pattern P ('a', 'b') match the corresponding characters in text T, but the third character in pattern P ('c') does not match the character in text T ('b') at the current shift position $s = 4$.

  Skip to the next shift without updating *Positions*.

- After that, s increases by 1. Because $s = 5$ and $n - m = 7 - 3 = 4$, we have $s > n - m$. The algorithm terminates and returns the list of found matches: Positions $= [(1, 3)]$.

3.4.4 Complexity

Metric	Complexity	Reasoning
Time (Worst)	$O(K \cdot m \cdot R \cdot C)$	Occurs when patterns and text share many prefix characters (e.g., all 'A's).
Time (Average)	$O(K \cdot R \cdot C)$	In practice, a mismatch usually occurs after only a few character comparisons.
Time (Best)	$O(K \cdot R \cdot C)$	The first character of the pattern always results in a mismatch at every shift.
Auxiliary Space	$O(1)$	The algorithm uses only a constant amount of extra memory for loop indices.

Table 5: Complexity Analysis of 2D Brute Force Algorithm

3.4.5 Discussion

- In scenarios 1, the number of patterns K is small, and the text is from 10×10 to 500×500. Brute-force approach is efficient and likely linear running time $O(R \cdot C)$.

- In scenarios 2, the number of patterns K is large, and the text is fixed at 100×100. This scenario is more challenging for the brute-force approach, as the running time multiplies by K times, which is much longer compared to scenario 1.

- In conclusion, the brute-force approach is more suitable for scenarios with a small number of patterns. It is worse for scenarios with a large number of one.

3.5 The Rabin-Karp Algorithm

3.5.1 Introduction & Application

- **Core idea**: The Rabin-Karp algorithm uses a rolling hash function to find occurrences of a pattern P within a text T. Instead of comparing the pattern character by character for all possible shifts, it calculates a hash value for the pattern and a hash value for each window of the text. If the hash values match, it performs a character-by-character comparison to verify if it is a true match or a hash collision. The key advantage is that the hash value of the next window can be computed in $\mathcal{O}(1)$ time by dropping the first character and appending the new character.
- **Real-world applications**:
  - Plagiarism Detection: Comparing documents to find exact matches of sentences or paragraphs in a large database of academic papers.
  - Bioinformatics: Searching for specific DNA sequences within massive genetic codes efficiently.

3.5.2 Pseudocode

Notation:

- **Text T (R rows, C columns)**: The 2D grid of characters.
- **Pattern P (K keywords)**: The list of patterns to search for.
- **Modulo q**: A large prime number used to prevent integer overflow and minimize hash collisions (e.g., $q = 1000000007$).
- **Base d**: The number of characters in the alphabet (e.g., $d = 256$ for ASCII).

```
RABIN-KARP-MATCHER(T, P, d, q)
n = length[T]
m = length[P]
h = d^(m-1) mod q
p_hash = 0
t_hash = 0
for i = 1 to m do
    p_hash = (d · p_hash + P[i]) mod q
    t_hash = (d · t_hash + T[i]) mod q
end for
for s = 0 to n − m do
    if p_hash == t_hash then
        if P[1..m] == T[s + 1..s + m] then
            append s to Positions
        end if
    end if
    if s < n − m then
```

```
        t_hash = (d · (t_hash − T[s + 1] · h) + T[s + m + 1]) mod q
        if t_hash < 0 then
            t_hash = t_hash + q
        end if
    end if
end for
```

3.5.3 Step-by-step trace

Notation:

- **Text** T **(length** n**)**: The main text being searched.
- **Pattern** P **(length** m**)**: The string that we are looking for.
- **Shift** (s): The current offset of the text T.
- **Positions** ($[s_1, s_2, \dots]$): A list storing the indices where a complete match is found.

Example: text $T = [a, a, b, c, a, b, b]$ and pattern $P = [a, b, c]$.
For simplicity, we map characters to integers ($a = 1, b = 2, c = 3$), set base $d = 10$, and prime $q = 13$.
Hash of pattern P: $p_hash = (1 \cdot 10^2 + 2 \cdot 10 + 3) \bmod 13 = 123 \bmod 13 = \mathbf{6}$.



Figure 24: *

Figure X: Step 1

- The current text window is $T[0..2] = [a, a, b]$. The calculated hash is $t_hash = 4$.
- Since $t_hash \neq p_hash$ ($4 \neq 6$), there is no need to compare characters.
- Text at the bottom shows the current shift is $s = 0$ and the list of found matches is empty ($Positions = []$).



Figure 25: *

Figure Y: Step 2

- The rolling hash is updated in $\mathcal{O}(1)$ time. The new window is $T[1..3] = [a, b, c]$ with $t_hash = 6$.
- Since $t_hash == p_hash$ $(6 == 6)$, the algorithm performs a secondary character-by-character check. All characters match successfully.
- Shift is $s = 1$ and the list of found matches is updated to record this position ($Positions = [1]$).

3.5.4 Complexity

Metric	Complexity	Reasoning
Time (Worst)	$\mathcal{O}(K \cdot m \cdot R \cdot C)$	Occurs when the hash function generates frequent collisions (e.g., text and patterns share many identical substrings or all 'A's), forcing a full character comparison at every shift.
Time (Average)	$\mathcal{O}(K \cdot R \cdot C)$	In practice, with a strong hash function and large prime q, collisions are rare. The hash updates in $\mathcal{O}(1)$ time, skipping most character comparisons.
Time (Best)	$\mathcal{O}(K \cdot R \cdot C)$	The hash values never match (except on actual occurrences). The algorithm glides through the text in constant time per shift.
Auxiliary Space	$\mathcal{O}(1)$	The algorithm uses only a constant amount of extra memory for storing hash values and loop indices (excluding the space needed to store the output results).

Table 6: Complexity Analysis of 2D Rabin-Karp Algorithm

3.5.5 Discussion

- In **Scenario 1** (Impact of Grid Size), where the number of patterns K is small and the grid scales from 10×10 to 500×500, the Rabin-Karp algorithm is highly efficient. Due to its $\mathcal{O}(1)$ rolling hash update, the running time behaves almost linearly, similar to $\mathcal{O}(R \cdot C)$.
- In **Scenario 2** (Impact of Dictionary Size), where the grid is fixed at 100×100 and K increases, our specific implementation loops through the grid separately for each pattern. Therefore, the execution time scales linearly with K. While this is faster than Brute-Force in terms of raw character comparisons, it does not fully exploit Rabin-Karp's multi-pattern matching potential (which could theoretically search all patterns simultaneously using a unified hash table).
- **In conclusion**, the Rabin-Karp algorithm provides a significant speedup over Brute-Force by using mathematical hashing to filter out unnecessary comparisons. It is an excellent

choice when dealing with large texts, provided a robust prime number q is chosen to avoid worst-case hash collision degradation.

4 Experimental Results and Comments

4.1 Tables of Experimental Data

The following tables present the performance metrics (Running Time and Number of Comparisons) for five string matching algorithms evaluated under two different scenarios.

Note: The number of comparisons for the Aho-Corasick algorithm is recorded as 0 across all test cases. This is due to its underlying architecture; rather than performing traditional character-by-character comparisons, it traverses a pre-constructed finite state automaton (Trie with failure links), making traditional comparison tracking inapplicable.

Scenario 1: Varying Grid Size with Fixed Number of Keywords (5)

Grid Size	Keywords	Brute Force	Rabin-Karp	KMP	Boyer-Moore	Aho-Corasick
10×10	5	0.0739 ms	0.0569 ms	0.1547 ms	0.1110 ms	0.1718 ms
50×50	5	1.4625 ms	0.3992 ms	0.7692 ms	0.4074 ms	0.9691 ms
100×100	5	10.6593 ms	0.6735 ms	5.0648 ms	0.6937 ms	1.5499 ms
500×500	5	1167.3600 ms	13.9877 ms	17.7575 ms	15.6578 ms	35.1272 ms

Table 7: Running time measurements for Scenario 1

Grid Size	Keywords	Brute Force	Rabin-Karp	KMP	Boyer-Moore	Aho-Corasick
10×10	5	2,520	18	3,172	236	0
50×50	5	231,400	78	78,740	1,767	0
100×100	5	1,836,800	986	282,803	22,880	0
500×500	5	216,796,000	1,448	6,669,643	124,220	0

Table 8: Number of comparisons for Scenario 1

Scenario 2: Fixed Grid Size (100×100) with Varying Number of Keywords

Grid Size	Keywords	Brute Force	Rabin-Karp	KMP	Boyer-Moore	Aho-Corasick
100×100	1	1.8014 ms	0.1474 ms	0.2855 ms	0.1188 ms	1.6196 ms
100×100	10	20.1295 ms	1.1338 ms	2.0147 ms	1.1114 ms	2.0038 ms
100×100	50	99.2332 ms	5.4070 ms	9.4388 ms	5.1438 ms	3.5454 ms
100×100	100	195.2980 ms	11.0356 ms	49.1021 ms	10.8136 ms	4.8826 ms

Table 9: Running time measurements for Scenario 2

Grid Size	Keywords	Brute Force	Rabin-Karp	KMP	Boyer-Moore	Aho-Corasick
100×100	1	228,800	104	46,207	1,986	0
100×100	10	3,663,600	451	643,058	7,001	0
100×100	50	16,450,800	731	3,155,398	54,562	0
100×100	100	34,552,800	3,529	6,225,769	174,645	0

Table 10: Number of comparisons for Scenario 2

4.2 Performance Evaluation and Comments

Based on the experimental data presented above, the following observations and justifications address the core performance behaviors of the implemented algorithms.

- **Correlation with Big-O Complexity:**
  The growth rates observed in the experimental data heavily align with the theoretical Big-O complexities of the algorithms.
  - **Brute Force:** In Scenario 1, as the grid size increases from 10×10 to 500×500, the running time explodes from 0.0739 ms to 1167.36 ms, and comparisons reach over 216 million. This perfectly illustrates its $O(N \cdot M)$ worst-case complexity, where N is the text size and M is the pattern size. It must redundantly check every possible starting position.
  - **Aho-Corasick:** In Scenario 2, as the number of keywords increases from 1 to 100, Brute Force and KMP show linear growth in execution time. However, Aho-Corasick exhibits an incredibly flat growth curve (increasing only from 1.6196 ms to 4.8826 ms). This matches its theoretical complexity of $O(N + M + Z)$ (where Z is the number of matches). Because it builds an automaton, the search time relies primarily on the length of the text, remaining largely independent of the number of patterns being searched simultaneously.

- **Best Performers on Large Datasets vs. Small Datasets:**
  The "best" algorithm depends entirely on the nature of the dataset.
  - For a **large search space (Grid** 500×500**) with few keywords**, **Rabin-Karp** (13.9877 ms) and **Boyer-Moore** (15.6578 ms) performed the best. Boyer-Moore's efficiency is evident in its low comparison count $(124, 220)$, as its bad-character heuristic allows it to skip large sections of the text.
  - For a **large dictionary of keywords (100 keywords)**, **Aho-Corasick** is the absolute best performer (4.8826 ms), outperforming the next fastest (Boyer-Moore at 10.8136 ms) by more than double the speed.

  The Brute Force Exception: There is a clear case where Brute Force was faster than the optimized approaches. In **Scenario 1, at the smallest grid size (**10×10**) with 5 keywords**, Brute Force (0.0739 ms) outperformed KMP (0.1547 ms), Boyer-Moore (0.1110 ms), and Aho-Corasick (0.1718 ms).

- **Justification of Results:**
  The phenomenon where Brute Force beats advanced algorithms on very small datasets is due to **preprocessing overhead**. Algorithms like KMP, Boyer-Moore, and Aho-Corasick require initial time to construct LPS arrays, shift tables, or complex automata before the search even begins. On a tiny 10×10 grid, the time taken to build these data structures exceeds the time it takes for Brute Force to simply execute nested loops to check the few available characters.

  Conversely, on large datasets, this preprocessing overhead pays off immensely. Rabin-Karp shows an astonishingly low number of comparisons (e.g., only 1,448 comparisons for a 500×500 grid) because it compares integer hash values rather than full strings, only resorting to character comparisons when a hash collision occurs. Meanwhile, Aho-Corasick dominates the multiple-keyword scenario because its automaton processes the grid exactly

once, finding all 100 keywords simultaneously, whereas all other algorithms must iterate through the grid repeatedly for every single keyword.

4.3 Tables and Graphs






Running Time - Scenario 2
Brute Force
Rabin-Karp
Knuth-Morris-Pratt
Boyer-Moore
Aho Corasick
100
50
10
5
1
0.5
100x100
100x100
100x100
100x100


Comparisons - Scenario 2
Brute Force
Rabin-Karp
Knuth-Morris-Pratt
Boyer-Moore
Aho Corasick
10000000
1000000
100000
10000
1000
100x100
100x100
100x100
100x100

5 Acknowledgements

First and foremost, the authors express our sincere gratitude to Le Thanh Tung & Tran Hoang Quan for giving guidance.

In addition, we are deeply grateful to VNOI wiki, Google Scholar and Introduction to Algorithms (CLRS) book for providing us with the essential materials, papers, source codes and examples that served as the foundation for this project.

Large Language Models also help us understand a few concepts when we were stuck and give us some useful suggestions to improve certain aspects of our work.

Lastly, we appreciate all members of Group 07 for their effort, consistency, hard work, and collaborative spirit throughout this project.

6 References