



derek.zhu



View New Content

Sign Out

OSx86 Project

Hardware Components and Drivers

Sound

VoodooHDA



## VoodooHDA - common problems

Started by oldnapalm, Sep 14 2011 04:06 AM

Page 1 of 7

oldnapalm

Posted 14 September 2011 - 04:06 AM

### Download:

<http://code.google.com/p/voodooohda/downloads/list>

### Official thread:

<http://www.projectosx.com/forum/index.php?showtopic=355>

**Problem:** kernel panic.

**Solution 1:** remove AppleHDA and restart the system before installing VoodooHDA.

**Solution 2:** edit Info.plist, replace the key **IOPCIClassMatch** by **IOPCIPrimaryMatch** and put the PCI ID of your audio card in string.  
Before

**ClassMatch**</key>

<string>0x04030000&0xffff0000</string> \_linenums:0'<key>IOPCIClassMatch</key><string>0x04030000&0xffff0000</string>

After

**PrimaryMatch**</key>

<string>0x3b568086</string> \_linenums:0'<key>IOPCIPrimaryMatch</key><string>0x3b568086</string>

oxDeviceIDVendorID

How to find device and vendor ID


<http://www.insanelymac.com/forum/index.php?showtopic=219584>

**Problem:** kext doesn't work (usually when there's more than one audio card or the video card has HDMI audio).


**Solution:** use solution 2 for kernel panic problem above. If you want to use both cards, create one entry for each card in IOKitPersonalities.

**Problem:** sound crackles.

**Solution 1:** change output format in **Applications - Utilities - Audio MIDI Setup**



**Solution 2:** check "Use SSE2" in VoodooHDA prefPane



You can also enable **Vectorize** in Info.plist

```
true/> _linenums:o'><key>Vectorize</key><true/>
```

**Problem:** volume control (slider) doesn't work.

**Solution:** enable **VoodooHDAEnableVolumeChangeFix** in Info.plist

```
true/> _linenums:o'><key>VoodooHDAEnableVolumeChangeFix</key><true/>
```

**Problem:** volume too low.  
**Solution:** enable **VoodooHDAEnableHalfVolumeFix** in Info.plist

```
true/> _linenums:o'><key>VoodooHDAEnableHalfVolumeFix</key><true/>
```

**Problem:** audio feedback (Larsen effect), sound loop between input (microphone) and output (speakers).  
**Solution:** mute **iGain** and increase **iMix** or **Mic** if microphone doesn't work

```
o</string> _linenums:o'><key>iGain</key><string>o</string>
```

It can also be done in the prefPane. In some cases you may need to mute **Monitor** instead of iGain.

**Problem:** audio delay. If you change volume, for example, it takes 1 or 2 seconds to play the test sound.  
**Solution 1:** delete com.apple.audio.DeviceSettings.plist and com.apple.audio.SystemSettings.plist from /Library/Preferences/Audio and reboot.  
**Solution 2:** use [SoundFlower](http://code.google.com/p/soundflower/downloads/list) (<http://code.google.com/p/soundflower/downloads/list>).

**Problem:** inputs or outputs don't show in sound preferences.  
**Solution 1:** look for a kext patched for your codec.

For VT1708S  
<http://www.insanelym...howtopic=231508> (<http://www.insanelymac.com/forum/index.php?showtopic=231508>)  
For AD1988B  
<http://www.insanelym...howtopic=267898> (<http://www.insanelymac.com/forum/index.php?showtopic=267898>)

**Solution 2:** add **NodesToPatch** based on **getDump** output (download in official thread).  
Example

```
<key>NodesToPatch</key>
<array>
  <dict>
    <key>Codec</key>
    <integer>2</integer>
    <key>Config</key>
    <string>0x90a70120</string>
    <key>Node</key>
    <integer>12</integer>
  </dict>
</array>
```

Config (PinDefault) is made up of the last 2 digits of each codec verb, but in the opposite order

```
01014410 = 21471c10 21471d44 21471e01 21471f01
|||||+- Sequence
|||||+- Default Association
||||+--- Misc
|||+---- Color
|||+---- Connection Type
||+----- Default Device
|+----- Location
+----- Port Connectivity _linenums:o'>0x01014410 = 21471c10 21471d44 21471e01 21471f01 ||||||+- Sequence ||||||+- Default Association ||||||+-
- Misc |||+---- Color |||+---- Connection Type ||+----- Default Device |+----- Location +----- Port Connectivity
```

**More detailed example**  
<http://olarila.com/f...php?f=18&t=604> (<http://olarila.com/forum/viewtopic.php?f=18&t=604>)

**Info about codec verbs**  
Source: <http://www.projectos...p?showtopic=465> (<http://www.projectosx.com/forum/index.php?showtopic=465>)

For each input/output there is a sequence of 4 verbs.

Jack	Color	Description	Node	PinDefault	Original Verbs
1/8	Green	Line Out at Ext Rear	20	0x14	0x01014410 21471c10 21471d44 21471e01 21471f01

Its about NodeID(NID) 0x14 in hex, 20 in decimal.

The default verbs for it: 21471c10 21471d44 21471e01 21471f01

CAAd (Codec Adress) NID (NodeID) Verb Command Verb Data

71cXY X=Default Association Y=Sequence

**Default Association and Sequence** are used together by software to group Pin Complexes (and therefore jacks) together into functional blocks to support multichannel operation. Software may assume that all jacks with the same association number are intended to be grouped together, for instance to provide six channel analog output. The Default Association can also be used by software to prioritize resource allocation in constrained situations. Lower Default Association values would be higher in priority for resources such as processing nodes or Input and Output Converters. Note that this is the default association only, and software can override this value if required, in particular if the user provides additional information about the particular system configuration. A value of 0000b is reserved and should not be used. Software may interpret this value to indicate that the Pin Configuration data has not been properly initialized. A value of 1111b is a special value indicating that the Association has the lowest priority. Multiple different Pin Complexes may share this value, and each is intended to be exposed as independent devices.

**Sequence** indicates the order of the jacks in the association group. The lowest numbered jack in the association group should be assigned the lowest numbered channels in the stream, etc. The numbers need not be sequential within the group, only the order matters. Sequence numbers within a set of Default Associations must be unique.

\*My notes for this, if you look on the vanilla codec verb(no matter what codec) you will see that **Sequence** is always 0. Why that, and why for us on our codec verbs is different? Simple **b/c Apple doesn't have multichannel analog out!** so you must change it to 0.

\*About **Default Association**, Keep the default one, in order, and on those that are the same replace them with new one that doesn't exist already in the dump... the values you can use are: 1, 2, 3, 4, 5, 6, 7, 8, 9, a, b, c, d and f.(see what does **verbit** if you still don't understand)

71dXY X=Color Y=Misc

**Color** indicates the color of the physical jack for use by software.

Unknown	0
Black	1
Grey	2
Blue	3
Green	4
Red	5
Orange	6
Yellow	7
Purple	8
Pink	9
Reserved	A-D
White	E

**Misc** is a bit field used to indicate other information about the jack. Currently, only bit 0 is defined. If bit 0 is set, it indicates that the jack has no presence detect capability, so even if a Pin Complex indicates that the codec hardware supports the presence detect functionality on the jack, the external circuitry is not capable of supporting the functionality.

Reserved 3  
Reserved 2  
Reserved 1  
Jack Detect Override 0

\*Use 0 for Jack Detect - External Device(e.g. Headphones Mic etc)  
Use 1 for Jack Detect Disabled - Internal Device(e.g. Internal speakers, Internal mic)

71eXY X=Default Device Y=Connection Type

**Default Device** indicates the intended use of the jack or device. This can indicate either the label on the jack or the device that is hardwired to the port, as with integrated speakers and the like.

Line Out	0
Speaker	1
HP Out	2
CD	3
SPDIF Out	4
Digital Other Out	5
Modem Line Side	6
Modem Handset Side	7
Line In	8
AUX	9
Mic In	A
Telephony	B

**Connection Type** indicates the type of physical connection, such as a 1/8-inch stereo jack or an optical digital connector, etc. Software can use this information to provide helpful user interface descriptions to the user or to modify reported codec capabilities based on the capabilities of the physical transport external to the codec.

**Unknown** 0  
 1/8" stereo/mono 1  
 1/4" stereo/mono 2  
 ATAPI **internal** 3  
 RCA 4  
**Optical** 5  
**Other Digital** 6  
**Other Analog** 7  
**Multichannel Analog (DIN)** 8  
 XLR/**Professional** 9  
 RJ-11 (**Modem**) A  
**Combination** B

71fXY X=Port Connectivity Y=Location

**Port Connectivity** indicates the external connectivity of the Pin Complex. Software can use this value to know what Pin Complexes are connected to jacks, internal devices, or not connected at all.

00b - The Port Complex is connected to a jack (1/8", ATAPI, etc.).

01b - No physical connection for Port.

10b - A fixed function device (integrated speaker, integrated mic, etc.) is attached.

11b - Both a jack and an internal device are attached. The Information provided in all other fields refers to the integrated device. The PD pin will reflect the status of the jack; the user will need to be queried to figure out what it is.

**Location** indicates the physical location of the jack or device to which the pin complex is connected. This allows software to indicate, for instance, that the device is the "Front Panel Headphone Jack" as opposed to rear panel connections.

\*Details:

Convert the 2 digit hex number to binary.

Pad the front with zero's to make it 8 dgits.

Example:

0x02 = binary 10 = 00000010 8 digit binary

**Reading** the bits **from** left to right:

**Port Connectivity** bits 7:6


00 - **Port is** connected to a **Jack**

01 - **No External Port -or- No** physical connection **for Port**

10 - **Fixed Function/Built In Device** (integrated speaker, mic, etc)

11 - **Jack and Internal** device are attached

**Location Part 1** - bits 5:4



Thanks so much for this! I'll try some of these.

BTW, some of the lingo probably passed over my head, but do you know how to get surround sound working?

oldnapalm

Posted 13 October 2011 - 03:31 AM

Usually (at least in the codecs I tested) all line-out have the same **default association**, only the **sequence** changes. You have to set a different default association for each line-out and set sequence as zero.

Once you have 3 or 4 line-out working, create an aggregate device, configure the speakers and select it in sound output.

Check this example  
<http://www.insanelymac.com/forum/index.php?showtopic=267898> (<http://www.insanelymac.com/forum/index.php?showtopic=267898>)

Quote

\*About Default Association, Keep the default one, in order, and on those that are the same replace them with new one that doesn't exist already in the dump... the values you can use are: 1, 2, 3, 4, 5, 6, 7, 8, 9, a, b, c, d and f.(see what does verbit if you still don't understand)

buoo

Posted 14 October 2011 - 05:01 AM

Thanks Crox86 😊  
Thanks to this guide the audio works, but not perfectly. I hear a little background noise (like crackling noises).  
I got my codec\_dump (http://www.insanelymac.com/forum/index.php?app=core&module=attach&section=attach&attach\_id=103537)  
**codec\_dump.txt** (http://www.insanelymac.com/forum/index.php?app=core&module=attach&section=attach&attach\_id=103537) 15.35KB  
52 downloads  
and that's what I get with verbit:

[codebox]Verbs from Linux Codec Dump File: codec#0

Codec: Realtek ALC887 Address: 0 DevID: 283904135 (0x10ec0887)

Jack Color Description Node PinDefault Original Verbs

1/8 Black Speaker at Ext Rear 17 0x11 0x411111f0 01171cf0 01171d11 01171e11 01171f41  
1/8 Black Speaker at Ext Rear 18 0x12 0x411111f0 01271cf0 01271d11 01271e11 01271f41  
1/8 Green Line Out at Ext Rear 20 0x14 0x01014010 01471c10 01471d40 01471e01 01471f01  
1/8 Black Speaker at Ext Rear 21 0x15 0x411111f0 01571cf0 01571d11 01571e11 01571f41  
1/8 Black Speaker at Ext Rear 22 0x16 0x411111f0 01671cf0 01671d11 01671e11 01671f41  
1/8 Black Speaker at Ext Rear 23 0x17 0x411111f0 01771cf0 01771d11 01771e11 01771f41  
Mic at Ext Rear 0x18 0x18 27367488 01871c40 01871d98 01871ea1 01871f01  
Mic at Ext Front 0x19 0x19 44145744 01971c50 01971d9c 01971ea1 01971f02  
1/8 Blue Line In at Ext Rear 26 0x1a 0x0181304f 01a71c4f 01a71d30 01a71e81 01a71f01  
HP Out at Ext Front 0x1b 0x1b 35736608 01b71c20 01b71d4c 01b71e21 01b71f02  
1/8 Black Speaker at Ext Rear 28 0x1c 0x411111f0 01c71cf0 01c71d11 01c71e11 01c71f41  
RCA UNKNOWN Line Out at Ext N/A 29 0x1d 0x4004c601 01d71c01 01d71dc6 01d71e04 01d71f40  
Optical Orange SPDIF Out at Ext Rear 30 0x1e 0x01456130 01e71c30 01e71d61 01e71e45 01e71f01  
1/8 Black Speaker at Ext Rear 31 0x1f 0x411111f0 01f71cf0 01f71d11 01f71e11 01f71f41

Jack Color Description Node PinDefault Modified Verbs

1/8 Green Line Out at Ext Rear 20 0x14 0x01014010 01471c10 01471d40 01471e01 01471f01  
Mic at Ext Rear 0x18 0x18 27367488 01871c40 01871d90 01871ea1 01871f01  
Mic at Ext Front 0x19 0x19 44145744 01971c50 01971d90 01971ea1 01971f01  
1/8 Blue Line In at Ext Rear 26 0x1a 0x0181304f 01a71c60 01a71d30 01a71e81 01a71f01  
HP Out at Ext Front 0x1b 0x1b 35736608 01b71c20 01b71d40 01b71e21 01b71f01  
RCA UNKNOWN Line Out at Ext N/A 29 0x1d 0x4004c601 01d71c70 01d71dc0 01d71e04 01d71f40  
Optical Orange SPDIF Out at Ext Rear 30 0x1e 0x01456130 01e71c30 01e71d60 01e71e45 01e71f01

I've tried replacing the default nodes with mine

From:  
[codebox]<key>NodesToPatch</key>  
<array>  
<dict>  
<key>Codec</key>

```
<integer>2</integer>
<key>Config</key>
<string>0x90a70120</string>
<key>Node</key>
<integer>12</integer>
</dict>
<dict>
<key>Codec</key>
<integer>2</integer>
<key>Config</key>
<string>0x02a1102f</string>
<key>Node</key>
<integer>14</integer>
</dict>
<dict>
<key>Codec</key>
<integer>2</integer>
<key>Config</key>
<string>0x90a6e140</string>
<key>Node</key>
<integer>19</integer>
</dict>
<dict>
<key>Codec</key>
<integer>2</integer>
<key>Config</key>
<string>0x02011030</string>
<key>Node</key>
<integer>15</integer>
</dict>
<dict>
<key>Codec</key>
<integer>2</integer>
<key>Config</key>
<string>0x02211050</string>
<key>DAC</key>
<string>3</string>
<key>Node</key>
<integer>10</integer>
</dict>
</array>[/codebox]
```

To:

```
[codebox]<key>NodesToPatch</key>
<array>
<dict>
<key>Node</key>
<integer>20</integer>
<key>Config</key>
<string>0x01014010</string>
</dict>
<dict>
<key>Node</key>
<integer>26</integer>
<key>Config</key>
<string>0x01813060</string>
</dict>
<dict>
<key>Node</key>
<integer>29</integer>
<key>Config</key>
<string>0x4004c070</string>
</dict>
<dict>
<key>Node</key>
<integer>30</integer>
<key>Config</key>
<string>0x01456030</string>
</dict>
</dict>
</array>[/codebox]
```

Magically the audio doesn't work anymore. 🤔

Help 🙏

Croxx86

Posted 14 October 2011 - 06:11 AM

@buoo

the problem in this edition of the nodes, I think.simple patch your dsdt and install the voodooHDA 2.7.2.pkg and edit the info.plist of the kext:

```
<key>IOMatchCategory</key>
    <string>VoodooHDADevice</string>
    <key>IOPCIPrimaryMatch</key>
    <string>0x27d88086</string>
    <key>IOProviderClass</key>
    <string>IOPCIDevice</string>
```

you're right the sound still works perfectly, more now.works best.with codec dump I did not succeed, controls lit up, but without sound.

oldnapalm

Posted 14 October 2011 - 06:15 AM

You have to specify the **Codec** key in each node patch.

Where did you get the "default" NodesToPatch?

Post your VoodooHDA getDump.

About the crackling sound, see here  
<http://www.insanelym...howtopic=267905> (<http://www.insanelymac.com/forum/index.php?showtopic=267905>)

buoo

Posted 14 October 2011 - 07:57 AM

*oldnapalm, on Oct 13 2011, 10:15 PM, said:*

You have to specify the **Codec** key in each node patch.

Where did you get the "default" NodesToPatch?

Post your VoodooHDA getDump.

About the crackling sound, see here  
<http://www.insanelym...howtopic=267905> (<http://www.insanelymac.com/forum/index.php?showtopic=267905>)

Thanks guys 😊


I'm using voodooohda 2.7.2, I only added my PCI ID.

```
<key>IOPCIPrimaryMatch</key>
<string>0x27d88086</string>
```

With "default" I mean the nodes that I found in the unpatched 2.7.2's plist.

Oldnapalm, Should be these the right nodes to use?

- 20 0x01014010
- 26 0x0181304f
- 29 0x4004c601
- 30 0x01456130

This is the getdump  
 ([http://www.insanelymac.com/forum/index.php?app=core&module=attach&section=attach&attach\\_id=103549](http://www.insanelymac.com/forum/index.php?app=core&module=attach&section=attach&attach_id=103549)) **getdump.rtf**  
([http://www.insanelymac.com/forum/index.php?app=core&module=attach&section=attach&attach\\_id=103549](http://www.insanelymac.com/forum/index.php?app=core&module=attach&section=attach&attach_id=103549)) 45.26KB 56 downloads

oldnapalm

Posted 14 October 2011 - 08:23 AM

Unpatched plist should have no nodes to patch



```
<key>NodesToPatch</key>
<array/>
```

I think you just need

```
<dict>
  <key>Codec</key>
  <integer>0</integer>
  <key>Config</key>
  <string>0x01813060</string>
  <key>Node</key>
  <integer>26</integer>
</dict>
```

You can try this to get headphones auto-detect

```
<dict>
  <key>Codec</key>
  <integer>0</integer>
  <key>Config</key>
  <string>0x02214c1f</string>
  <key>Node</key>
  <integer>27</integer>
</dict>
```

buoo

Posted 14 October 2011 - 07:30 PM

~~The audio works, but there are 2 problems:~~

~~the audio delay~~

~~the voodoo prefpane reset at the reboot~~

**Mission Complete!** 🎉🎉🎉

The audio works very god LoL using VoodooHDA**2.2** + my PCI ID

```
<key>IOPCIPrimaryMatch</key>
<string>0x27d88086</string>
```

buoo

Posted 24 October 2011 - 03:31 AM

~~Hi man, I don't understand the portuguese but I want to try it xD~~

~~1 minute...~~

Wow! This is the first VoodooHDA **2.7.2** that doesn't give me noice.  
But It gives me too much audio delay and the mic doesn't work.


Crosx86, do you know how to eliminate the audio delay?

Crosx86

Posted 24 October 2011 - 04:02 AM

@buoo

Hey buoo,for me works perfect...you can check in prefpane:



([http://www.insanelymac.com/forum/uploads/monthly\\_10\\_2011/post-711330-1319396502.png](http://www.insanelymac.com/forum/uploads/monthly_10_2011/post-711330-1319396502.png))

Your get dump is the same as mine?  
put your device id and your vendor ID in the plist text if it is already there, delete all nodes and run voodoo get dump and compare.

buoo

Posted 24 October 2011 - 04:09 AM

Our chips are different :\


I was looking your codec\_dump, however ...do you know how to eliminate the audio delay?

Thanks 😊


Edit: It is the same 0x27d88086

but the nodes are different

Could you take a look here?

 ([http://www.insanelymac.com/forum/index.php?app=core&module=attach&section=attach&attach\\_id=104162](http://www.insanelymac.com/forum/index.php?app=core&module=attach&section=attach&attach_id=104162)) **codec.txt.zip**

([http://www.insanelymac.com/forum/index.php?app=core&module=attach&section=attach&attach\\_id=104162](http://www.insanelymac.com/forum/index.php?app=core&module=attach&section=attach&attach_id=104162)) **1.9KB** 26 downloads

 ([http://www.insanelymac.com/forum/index.php?app=core&module=attach&section=attach&attach\\_id=104163](http://www.insanelymac.com/forum/index.php?app=core&module=attach&section=attach&attach_id=104163)) **getdump.zip**

([http://www.insanelymac.com/forum/index.php?app=core&module=attach&section=attach&attach\\_id=104163](http://www.insanelymac.com/forum/index.php?app=core&module=attach&section=attach&attach_id=104163)) **5.15KB** 55 downloads

..If you could help me, this audio chip is killing me.

Crosx86

Posted 24 October 2011 - 04:15 AM

EDIT: the get dump with this voodoo with nodes, remove all repair permissions reboot and run get dump

#### Quote

put your device id and your vendor ID in the plist text if it is already there, delete all nodes and run voodoo get dump and compare.

this part of your dump:

```
Probing codec #0...
HDA Codec #0: Realtek ALC887
HDA Codec ID: 0x10ec0887
Vendor: 0x10ec
Device: 0x0887
Revision: 0x02
Stepping: 0x02
PCI Subvendor: 0x83bc1043
startNode=1 endNode=2
Found audio FG nid=1 startNode=2 endNode=39 total=37
```

AND

post it.

buoo

Posted 24 October 2011 - 09:22 PM

Ok!  
I've deleted all nodes from your VoodooHDA

```
<key>MixerValues</key>      <dict>      <key>Mic</key>      <string>0</string>      <key>PCM</key>
>      <string>100</string>      <key>iGain</key>      <string>100</string>      <key>iMix</key>
      <string>30</string>      </dict>      <key>NodesToPatch</key>      </array>      <key>Noise</key>
      <integer>2</integer>      <key>Vectorize</key>      <true/>
```

Now this is the new getdump:

```
Probing codec #0...
HDA Codec #0: Realtek ALC887
HDA Codec ID: 0x10ec0887
  Vendor: 0x10ec
  Device: 0x0887
  Revision: 0x02
  Stepping: 0x02
PCI Subvendor: 0x84271043
startNode=1 endNode=2
Found audio FG nid=1 startNode=2 endNode=39 total=37

Processing audio FG cad=0 nid=1...
```

Is this the right configuration? The mic doesn't work and I got audio delay (2 seconds)

```
<key>NodesToPatch</key>      <array>      <dict>      <key>Codec</key>      <integer>0</integ
er>      <key>Config</key>      <string>0x01014010</string>      <key>Node</key>
      <integer>20</integer>      </dict>      <dict>      <key>Codec</key>      <integer>
0</integer>      <key>Config</key>      <string>0x01a19840</string>      <key>Node</key>
      <integer>24</integer>      </dict>      <dict>      <key>Codec</key>
      <integer>0</integer>      <key>Config</key>      <string>0x02a19c50</string>      <key>
Node</key>      <integer>25</integer>      </dict>      <dict>      <key>Codec</key>
      <integer>0</integer>      <key>Config</key>      <string>0x01813040</string>
      <key>Node</key>      <integer>26</integer>      </dict>      <dict>      <key>Code
c</key>      <integer>0</integer>      <key>Config</key>      <string>0x02214c20</string>
      <key>Node</key>      <integer>27</integer>      </dict>      <dict>
      <key>Codec</key>      <integer>0</integer>      <key>Config</key>      <string>0x0145613
```

oldnapalm

Posted 24 October 2011 - 11:04 PM

Just install SoundFlower and the delay should be gone.

<http://code.google.com/p/soundflower/downloads/list>

You just need to add in NodesToPatch the nodes you want to patch, the ones that are fine with the default **Config** you don't need to add.

You just need

```
nid 26 0x01813060
```

If you want to turn pink and blue rear into line-out (for 5.1 audio)

```
nid 24 0x01019840
nid 26 0x01013060
```

Crosx86

Posted 24 October 2011 - 11:57 PM

@buuo

Hey buuo,the error in node 26,you repeat the end of the strings.

your nodes to patch:

```
<key>NodesToPatch</key>
  <array>
    <dict>
      <key>Codec</key>
      <integer>0</integer>
      <key>Config</key>
      <string>0x01014010</string>
      <key>Node</key>
      <integer>20</integer>
    </dict>
  </array>
</dict>
<dict>
  <key>Codec</key>
```

The correct patching:

```
<key>NodesToPatch</key>
  <array>
    <dict>
      <key>Codec</key>
      <integer>0</integer>
      <key>Config</key>
      <string>0x01014010</string>
      <key>Node</key>
      <integer>20</integer>
    </dict>
  </array>
</dict>
<dict>
  <key>Codec</key>
```

You need put it line-out,use this string:0x01013060 in node 26

oldnapalm

Posted 25 October 2011 - 03:14 AM

Please see my post above

*Quote*

You just need to add in NodesToPatch the nodes you want to patch, the ones that are fine with the default Config you don't need to add.

The error is using default association 4 for node 26, it's already used in node 24.

buoo

Posted 25 October 2011 - 04:38 AM

The mic works but I hear it in the speakers and I'm not able to decrease the volume(of the mic).

oldnapalm

Posted 25 October 2011 - 05:03 AM

*buoo, on Oct 24 2011, 05:38 PM, said:*

The mic works but I hear it in the speakers

*Quote*

**Problem:** audio feedback (Larsen effect), sound loop between input (microphone) and output (speakers).

**Solution:** mute **iGain** and increase **iMix** or **Mic** if microphone doesn't work

```
o</string> _linenums:0'><key>iGain</key><string>0</string>
```

It can also be done in the prefPane. In some cases you may need to mute **Monitor** instead of iGain.

*Quote*

I'm not able to decrease the volume(of the mic)

Try to do it in VoodooHDA prefPane, once you find a good value you can set in Info.plist (MixerValues), but the value set in prefPane will be restored after reboot if you use **voodoohdahelper** (installed by the pkg).

**oldnapalm**

Posted 27 October 2011 - 04:07 AM

I found another solution to the delay problem (worked for me): delete com.apple.audio.DeviceSettings.plist and com.apple.audio.SystemSettings.plist from /Library/Preferences/Audio and reboot.