

VISVESVARAYA TECHNOLOGICAL UNIVERSITY

“JnanaSangama”, Belgaum -590014, Karnataka.



LAB REPORT
on

AI Lab Report

Submitted by

DHRUVA S(1BM21CS057)

in partial fulfillment for the award of the degree of
BACHELOR OF ENGINEERING
in
COMPUTER SCIENCE AND ENGINEERING



B.M.S. COLLEGE OF ENGINEERING

(Autonomous Institution under VTU)

BENGALURU-560019

NOV-2023 to FEB-2024

B. M. S. College of Engineering,
Bull Temple Road, Bangalore 560019
(Affiliated To Visvesvaraya Technological University, Belgaum)
Department of Computer Science and Engineering



CERTIFICATE

This is to certify that the Lab work entitled “Internet of things lab” carried out by **DHRUVA S(1BM21CS057)**, who is bonafide student of **B. M. S. College of Engineering**. It is in partial fulfillment for the award of **Bachelor of Engineering in Computer Science and Engineering** of the Visvesvaraya Technological University, Belgaum during the year 2023. The Lab report has been approved as it satisfies the academic requirements in respect of a **Artificial Intelligence lab - (22CS5PCAIN)** work prescribed for the said degree.

Dr. Saritha A N
Assistant professor
Department of CSE
BMSCE, Bengaluru

Dr. Jyothi S Nayak
Professor and Head
Department of CSE
BMSCE, Bengaluru

Table of Contents

Sl. No.	Title	Page No.
1.	Tic Tac Toe	3 11
2.	8 Puzzle Breadth First Search Algorithm	11-15
3.	8 Puzzle Iterative Deepening Search Algorithm	16-20
4.	8 Puzzle A* Search Algorithm	21 27
5.	Vacuum Cleaner	28 33
6.	Knowledge Base Entailment	34 36
7.	Knowledge Base Resolution	37 40
8.	Simulated Annealing	
9.	Unification	41 46
10.	FOL to CNF	47 52
11.	Forward reasoning	53 58

Program 1 : Tic Tac Toe

Code:

```
tic=[]
import random
def board(tic):
    for i in range(0,9,3):
        print("+"+"-"*29+"+")
        print("|"+" "*9+"|"+" "*9+"|"+" "*9+"|")
        print("|"+" "*3,tic[0+i]," "*3+"|"+" "*3,tic[1+i]," "*3+"|"+"
"*3,tic[2+i]," "*3+"|")
        print("|"+" "*9+"|"+" "*9+"|"+" "*9+"|")
    print("+"+"-"*29+"+")

def update_comp():
    global tic,num
    for i in range(9):
        if tic[i]==i+1:
            num=i+1
            tic[num-1]='X'
            if winner(num-1)==False:
                #reverse the change
                tic[num-1]=num
            else:
                return
    for i in range(9):
        if tic[i]==i+1:
            num=i+1
            tic[num-1]='O'
            if winner(num-1)==True:
                tic[num-1]='X'
                return
            else:
                tic[num-1]=num
    num=random.randint(1,9)
    while num not in tic:
        num=random.randint(1,9)
    else:
        tic[num-1]='X'
```

```

def update_user():
    global tic,num
    num=int(input("enter a number on the board :"))
    while num not in tic:
        num=int(input("enter a number on the board :"))
    else:
        tic[num-1]='O'

def winner(num):
    if tic[0]==tic[4] and tic[4]==tic[8] or tic[2]==tic[4] and tic[4]==tic[6]:
        return True
    if tic[num]==tic[num-3] and tic[num-3]==tic[num-6]:
        return True
    if tic[num//3*3]==tic[num//3*3+1] and
tic[num//3*3+1]==tic[num//3*3+2]:
        return True
    return False

try:
    for i in range(1,10):
        tic.append(i)
    count=0
    #print(tic)
    board(tic)
    while count!=9:
        if count%2==0:
            print("computer's turn :")
            update_comp()
            board(tic)
            count+=1
        else:
            print("Your turn :")
            update_user()
            board(tic)
            count+=1
    if count>=5:

```

```
        if winner(num-1):
            print("winner is ",tic[num-1])
            break
        else:
            continue
    except:
        print("\nerror\n")
```

Observation:

Output:

[1, 2, 3, 4, 5, 6, 7, 8, 9]

1	2	3
4	5	6
7	8	9

computer's turn :

1	2	3
4	5	6
X	8	9

Your turn :

enter a number on the board :2

1	0	3
4	5	6
X	8	9

computer's turn :

1	0	3
4	5	X
X	8	9

Your turn :

enter a number on the board :5

1	0	3
4	0	X
X	8	9

Program 2 : 8 Puzzle Breadth First Search Algorithm

Code:

```
def bfs(src,target):
    queue=[]
    queue.append(src)
    exp=[]
    while len(queue)>0:
        source=queue.pop(0)
        #print("queue",queue)
        exp.append(source)

        print(source[0],'|',source[1],'|',source[2])
        print(source[3],'|',source[4],'|',source[5])
        print(source[6],'|',source[7],'|',source[8])
        print("-----")
        if source==target:
            print("Success")
            return
        poss_moves_to_do=[]
        poss_moves_to_do=possible_moves(source,exp)
        #print("possible moves",poss_moves_to_do)
        for move in poss_moves_to_do:
            if move not in exp and move not in queue:
                #print("move",move)
                queue.append(move)

def possible_moves(state,visited_states):
    b=state.index(0)

    #direction array
    d=[]
```



```

if b not in [0,1,2]:
    d.append('u')
if b not in [6,7,8]:
    d.append('d')
if b not in [0,3,6]:
    d.append('l')
if b not in [2,5,8]:
    d.append('r')

pos_moves_it_can=[]

for i in d:
    pos_moves_it_can.append(gen(state,i,b))
return [move_it_can for move_it_can in pos_moves_it_can if move_it_can not in visited_states]

```

```

def gen(state,m,b):
    temp=state.copy()
    if m=='d':
        temp[b+3],temp[b]=temp[b],temp[b+3]
    if m=='u':
        temp[b-3],temp[b]=temp[b],temp[b-3]
    if m=='l':
        temp[b-1],temp[b]=temp[b],temp[b-1]
    if m=='r':
        temp[b+1],temp[b]=temp[b],temp[b+1]
    return temp

```

```

src=[1,2,3,4,5,6,0,7,8]
target=[1,2,3,4,5,6,7,8,0]
bfs(src,target)

```

Observation:

Output:

1	2	3
4	5	6
0	7	8

1	2	3
0	5	6
4	7	8

1	2	3
4	5	6
7	0	8

0	2	3
1	5	6
4	7	8

1	2	3
5	0	6
4	7	8

1	2	3
4	0	6
7	5	8

1	2	3
4	5	6
7	8	0

Success

Program 3 : 8 Puzzle Iterative Deepening Search Algorithm

Code:

8 Puzzle problem using Iterative deepening depth first search algorithm

```
def id_dfs(puzzle, goal, get_moves):
```

```
    import itertools
```

```
    #get_moves -> possible_moves
```

```
    def dfs(route, depth):
```

```
        if depth == 0:
```

```

    return
if route[-1] == goal:
    return route
for move in get_moves(route[-1]):
    if move not in route:
        next_route = dfs(route + [move], depth - 1)
        if next_route:
            return next_route

```

```

for depth in itertools.count():
    route = dfs([puzzle], depth)
    if route:
        return route

```

```

def possible_moves(state):
    b = state.index(0) # ) indicates White space -> so b has index of it.
    d = [] # direction

    if b not in [0, 1, 2]:
        d.append('u')
    if b not in [6, 7, 8]:
        d.append('d')
    if b not in [0, 3, 6]:
        d.append('l')
    if b not in [2, 5, 8]:
        d.append('r')

    pos_moves = []
    for i in d:
        pos_moves.append(generate(state, i, b))
    return pos_moves

```

```

def generate(state, m, b):
    temp = state.copy()

    if m == 'd':

```

```
    temp[b + 3], temp[b] = temp[b], temp[b + 3]
if m == 'u':
    temp[b - 3], temp[b] = temp[b], temp[b - 3]
if m == 'l':
    temp[b - 1], temp[b] = temp[b], temp[b - 1]
if m == 'r':
    temp[b + 1], temp[b] = temp[b], temp[b + 1]

return temp
```

calling ID-DFS

```
initial = [1, 2, 3, 0, 4, 6, 7, 5, 8]
```

```
goal = [1, 2, 3, 4, 5, 6, 7, 8, 0]
```

```
route = id_dfs(initial, goal, possible_moves)
```

```
if route:
```

```
    print("Success!! It is possible to solve 8 Puzzle problem")
```

```
    print("Path:", route)
```

```
else:
```

```
    print("Failed to find a solution")
```

Observation:

Output:

Success!! It is possible to solve 8 Puzzle problem

Path: [[1, 2, 3, 0, 4, 6, 7, 5, 8], [1, 2, 3, 4, 0, 6, 7, 5, 8], [1, 2, 3, 4, 5, 6, 7, 0, 8], [1, 2, 3, 4, 5, 6, 7, 8, 0]]

Program 4 : 8 Puzzle A* Search Algorithm

Code:

class Node:

def __init__(self,data,level,fval):

""" Initialize the node with the data, level of the node and the calculated fvalue """

self.data = data

self.level = level

self.fval = fval

def generate_child(self):

""" Generate child nodes from the given node by moving the blank space
either in the four directions {up,down,left,right} """

x,y = self.find(self.data,'_')

""" val_list contains position values for moving the blank space in either of
the 4 directions [up,down,left,right] respectively. """

val_list = [[x,y-1],[x,y+1],[x-1,y],[x+1,y]]

children = []

for i in val_list:

child = self.shuffle(self.data,x,y,i[0],i[1])

if child is not None:

child_node = Node(child,self.level+1,0)

```
        children.append(child_node)
    return children
```

```
def shuffle(self,puz,x1,y1,x2,y2):
    """ Move the blank space in the given direction and if the position value are out
        of limits the return None """
    if x2 >= 0 and x2 < len(self.data) and y2 >= 0 and y2 < len(self.data):
        temp_puz = []
        temp_puz = self.copy(puz)
        temp = temp_puz[x2][y2]
        temp_puz[x2][y2] = temp_puz[x1][y1]
        temp_puz[x1][y1] = temp
        return temp_puz
    else:
        return None
```

```
def copy(self,root):
    """ Copy function to create a similar matrix of the given node"""
    temp = []
    for i in root:
        t = []
        for j in i:
            t.append(j)
        temp.append(t)
    return temp
```

```
def find(self,puz,x):
    """ Specifically used to find the position of the blank space """
    for i in range(0,len(self.data)):
        for j in range(0,len(self.data)):
            if puz[i][j] == x:
                return i,j
```

```
class Puzzle:
    def __init__(self,size):
        """ Initialize the puzzle size by the specified size,open and closed lists to empty """
```



```
self.n = size
self.open = []
self.closed = []
```

```
def accept(self):
    """ Accepts the puzzle from the user """
    puz = []
    for i in range(0,self.n):
        temp = input().split(" ")
        puz.append(temp)
    return puz
```

```
def f(self,start,goal):
    """ Heuristic Function to calculate heuristic value  $f(x) = h(x) + g(x)$  """
    return self.h(start.data,goal)+start.level
```

```
def h(self,start,goal):
    """ Calculates the different between the given puzzles """
    temp = 0
    for i in range(0,self.n):
        for j in range(0,self.n):
            if start[i][j] != goal[i][j] and start[i][j] != '_':
                temp += 1
    return temp
```

```
def process(self):
    """ Accept Start and Goal Puzzle state """
    print("Enter the start state matrix \n")
    start = self.accept()
    print("Enter the goal state matrix \n")
    goal = self.accept()

    start = Node(start,0,0)
    start.fval = self.f(start,goal)
    """ Put the start node in the open list """
    self.open.append(start)
    print("\n\n")
```

```

while True:
    cur = self.open[0]
    print("")
    print(" | ")
    print(" | ")
    print(" \\\ / \n")
    for i in cur.data:
        for j in i:
            print(j,end=" ")
        print("")
    """ If the difference between current and goal node is 0 we have reached the goal node"""
    if(self.h(cur.data,goal) == 0):
        break
    for i in cur.generate_child():
        i.fval = self.f(i,goal)
        self.open.append(i)
    self.closed.append(cur)
    del self.open[0]

    """ sort the opne list based on f value """
    self.open.sort(key = lambda x:x.fval,reverse=False)

```

```

puz = Puzzle(3)
puz.process()

```

Observation:

Output:

Enter the start state matrix

```
1 2 3
4 5 6
_ 7 8
```

Enter the goal state matrix

```
1 2 3
4 5 6
7 8 _
```

```
  |
  |
 \'/
```

```
1 2 3
4 5 6
_ 7 8
```

```
  |
  |
 \'/
```

```
1 2 3
4 5 6
7 _ 8
```

```
  |
  |
 \'/
```

```
1 2 3
4 5 6
7 8 _
```

Program 5 : Vacuum Cleaner

Code:

```
def clean_room(floor, room_row, room_col):
    if floor[room_row][room_col] == 1:
        print(f"Cleaning Room at ({room_row + 1}, {room_col + 1}) (Room was dirty)")
        floor[room_row][room_col] = 0
        print("Room is now clean.")
    else:
```

```
print(f"Room at ({room_row + 1}, {room_col + 1}) is already clean.")
```

```
def main():
```

```
    rows = 2
```

```
    cols = 2
```

```
    floor = [[0, 0], [0, 0]] # Initialize a 2x2 floor with clean rooms
```

```
    for i in range(rows):
```

```
        for j in range(cols):
```

```
            status = int(input(f"Enter clean status for Room at ({i + 1}, {j + 1}) (1 for dirty, 0 for clean): "))
```

```
            floor[i][j] = status
```

```
    for i in range(rows):
```

```
        for j in range(cols):
```

```
            clean_room(floor, i, j)
```

```
print("Returning to Room at (1, 1) to check if it has become dirty again:")
```

```
clean_room(floor, 0, 0) # Checking Room at (1, 1) after cleaning all rooms
```

```
if __name__ == "__main__":
```

```
    main()
```

Four rooms:

```
def clean_room(room_name, is_dirty):
```

```
    if is_dirty:
```

```
        print(f"Cleaning {room_name} (Room was dirty)")
```

```
        print(f"{room_name} is now clean.")
```

```
        return 0 # Updated status after cleaning
```

```
    else:
```

```
        print(f"{room_name} is already clean.")
```

```
        return 0 # Status remains clean
```

```
def main():
```

```
    rooms = ["Room 1", "Room 2"]
```

```
    room_statuses = []
```

```

for room in rooms:
    status = int(input(f'Enter clean status for {room} (1 for dirty, 0 for clean): '))
    room_statuses.append((room, status))
print(room_statuses)

for i, (room, status) in enumerate(room_statuses):
    room_statuses[i] = (room, clean_room(room, status)) # Update status after cleaning

print(f'Returning to {rooms[0]} to check if it has become dirty again:')
room_statuses[0]=status = (rooms[0], clean_room(rooms[0], room_statuses[0][1])) # Checking
Room 1 after cleaning all rooms

print(f'{rooms[0]} is {'dirty' if room_statuses[0][1] else 'clean'} after checking.')

if __name__ == "__main__":
    main()

```


Observation:

Output:

```
0 indicates clean and 1 indicates dirty
Enter Location of VacuumA
Enter status of A1
Enter status of other room0
Vacuum is placed in Location A
Location A is Dirty.
Cost for CLEANING A 1
Location A has been Cleaned.
No action1
Location B is already clean.
GOAL STATE:
{'A': '0', 'B': '0'}
Performance Measurement: 1
```

Program 6 : Knowledge Base Entailment

Code:

```
from sympy import symbols, And, Not, Implies, satisfiable

def create_knowledge_base():
    # Define propositional symbols
    p = symbols('p')
    q = symbols('q')
    r = symbols('r')

    # Define knowledge base using logical statements
    knowledge_base = And(
        Implies(p, q),    # If p then q
        Implies(q, r),    # If q then r
        Not(r)            # Not r
    )

    return knowledge_base

def query_entails(knowledge_base, query):
    # Check if the knowledge base entails the query
    entailment = satisfiable(And(knowledge_base, Not(query)))

    # If there is no satisfying assignment, then the query is entailed
    return not entailment

if __name__ == "__main__":
    # Create the knowledge base
```

```
kb = create_knowledge_base()

# Define a query
query = symbols('p')

# Check if the query entails the knowledge base
result = query_entails(kb, query)

# Display the results
print("Knowledge Base:", kb)
print("Query:", query)
print("Query entails Knowledge Base:", result)
```

Observation:

Output:

```
Knowledge Base: ~r & (Implies(p, q)) & (Implies(q, r))
Query: p
Query entails Knowledge Base: False
```

Program 7 : Knowledge Base Resolution

Code:

```
def tell(kb, rule):  
    kb.append(rule)  
  
combinations = [(True, True, True), (True, True, False),
```

```
(True, False, True), (True, False, False),  
(False, True, True), (False, True, False),  
(False, False, True), (False, False, False)]
```

```
def ask(kb, q):  
    for c in combinations:  
        s = all(rule(c) for rule in kb)  
        f = q(c)  
        print(s, f)  
        if s != f and s != False:  
            return 'Does not entail'  
    return 'Entails'
```

```
kb = []
```

```
# Get user input for Rule 1
```

```
rule_str = input("Enter Rule 1 as a lambda function (e.g., lambda x: x[0] or x[1] and (x[0] and  
x[1]): ")
```

```
r1 = eval(rule_str)
```

```
tell(kb, r1)
```

```
# Get user input for Query
```

```
query_str = input("Enter Query as a lambda function (e.g., lambda x: x[0] and x[1] and (x[0] or  
x[1]): ")
```

```
q = eval(query_str)
```

```
# Ask KB Query
```

```
result = ask(kb, q)
```

```
print(result)
```

Observation:

Output:

```
Enter Rule 1 as a lambda function (e.g., lambda x: x[0] or x[1] and (x[0] and x[1]): lambda x: x[0] or x[1] and (x[0] and x[1])
Enter Query as a lambda function (e.g., lambda x: x[0] and x[1] and (x[0] or x[1]): lambda x: x[0] and x[1] or x[2]
True True
True True
True True
True False
Does not entail
```

Program 8. Simulated Annealing

Code:

```
import random
import math

class Solution:
    def __init__(self, CVRMSE, configuration):
        self.CVRMSE = CVRMSE
        self.config = configuration

# Function prototype
def gen_rand_sol():
    a = [1, 2, 3, 4, 5]
    return Solution(-1.0, a)

# global variables
T = 1
Tmin = 0.0001
alpha = 0.9
num_iterations = 100
M = 5
N = 5
source_array = [['X' for _ in range(N)] for _ in range(M)]
temp = []
mini = Solution(float('inf'), temp)
current_sol = gen_rand_sol()

def neighbor(current_sol):
    return current_sol

def cost(input_configuration):
    return -1.0
```



```

# Mapping from [0, M*N] --> [0, M]x[0, N]
def index_to_points(index):
    return [index % M, index // M]

# Returns minimum value based on optimization
while T > Tmin:
    for _ in range(num_iterations):
        # Reassigns global minimum accordingly
        if current_sol.CVRMSE < mini.CVRMSE:
            mini = current_sol
            new_sol = neighbor(current_sol)
            ap = math.exp((current_sol.CVRMSE - new_sol.CVRMSE) / T)
            if ap > random.random():
                current_sol = new_sol
        T *= alpha # Decreases T, cooling phase

print(mini.CVRMSE, "\n")

for i in range(M):
    for j in range(N):
        source_array[i][j] = 'X'

# Displays
for obj in mini.config:
    coord = index_to_points(obj)
    source_array[coord[0]][coord[1]] = '-'

# Displays optimal location

```

```

for i in range(M):
    row = ""
    for j in range(N):
        row += source_array[i][j] + " "
    print(row)

```

Observation:

Output:

-1.0

```

X - X X X
- X X X X
- X X X X
- X X X X
- X X X X

```

Program 9 : Unification

Code:

```
import re
```

```

def getAttributes(expression):
    expression = expression.split("(")[1:]
    expression = "(" .join(expression)
    expression = expression[:-1]
    expression = re.split("(?<!(.),(?!\\.))", expression)
    return expression

```

```

def getInitialPredicate(expression):
    return expression.split("(")[0]

```

```

def isConstant(char):
    return char.isupper() and len(char) == 1

```

```
def isVariable(char):  
    return char.islower() and len(char) == 1
```

```
def replaceAttributes(exp, old, new):  
    attributes = getAttributes(exp)  
    for index, val in enumerate(attributes):  
        if val == old:  
            attributes[index] = new  
    predicate = getInitialPredicate(exp)  
    return predicate + "(" + ",".join(attributes) + ")"
```

```
def apply(exp, substitutions):  
    for substitution in substitutions:  
        new, old = substitution  
        exp = replaceAttributes(exp, old, new)  
    return exp
```

```
def checkOccurs(var, exp):  
    if exp.find(var) == -1:  
        return False  
    return True
```

```
def getFirstPart(expression):  
    attributes = getAttributes(expression)  
    return attributes[0]
```

```
def getRemainingPart(expression):  
    predicate = getInitialPredicate(expression)  
    attributes = getAttributes(expression)  
    newExpression = predicate + "(" + ",".join(attributes[1:]) + ")"  
    return newExpression
```

```
def unify(exp1, exp2):  
    if exp1 == exp2:  
        return []  
  
    if isConstant(exp1) and isConstant(exp2):
```

```
if exp1 != exp2:  
    return False
```

```
if isConstant(exp1):  
    return [(exp1, exp2)]
```

```
if isConstant(exp2):  
    return [(exp2, exp1)]
```

```
if isVariable(exp1):  
    if checkOccurs(exp1, exp2):  
        return False  
    else:  
        return [(exp2, exp1)]
```

```
if isVariable(exp2):  
    if checkOccurs(exp2, exp1):  
        return False  
    else:  
        return [(exp1, exp2)]
```

```
if getInitialPredicate(exp1) != getInitialPredicate(exp2):  
    print("Predicates do not match. Cannot be unified")  
    return False
```

```
attributeCount1 = len(getAttributes(exp1))  
attributeCount2 = len(getAttributes(exp2))  
if attributeCount1 != attributeCount2:  
    return False
```

```
head1 = getFirstPart(exp1)  
head2 = getFirstPart(exp2)  
initialSubstitution = unify(head1, head2)  
if not initialSubstitution:  
    return False  
if attributeCount1 == 1:  
    return initialSubstitution
```

```

tail1 = getRemainingPart(exp1)
tail2 = getRemainingPart(exp2)

if initialSubstitution != []:
    tail1 = apply(tail1, initialSubstitution)
    tail2 = apply(tail2, initialSubstitution)

remainingSubstitution = unify(tail1, tail2)
if not remainingSubstitution:
    return False

initialSubstitution.extend(remainingSubstitution)
return initialSubstitution

exp1 = "knows(X)"
exp2 = "knows(Richard)"
substitutions = unify(exp1, exp2)

print("Substitutions:")
print(substitutions)
exp1 = "knows(A,x)"
exp2 = "knows(y,mother(y))"
substitutions = unify(exp1, exp2)
print("Substitutions:")
print(substitutions)

```

Observation :

Output:

```
exp1 = "knows(X)"
exp2 = "knows(Richard)"
substitutions = unify(exp1, exp2)
print("Substitutions:")
print(substitutions)
```



```
Substitutions:
[('X', 'Richard')]
```

Program 10 : FOL to CNF

Code:

```
def getAttributes(string):
    expr = '\([^)]+\)'
    matches = re.findall(expr, string)
    return [m for m in str(matches) if m.isalpha()]

def getPredicates(string):
    expr = '[a-z~]+\([A-Za-z,]+\)'
    return re.findall(expr, string)

def DeMorgan(sentence):
    string = ".join(list(sentence).copy())
    string = string.replace('~~',"
    flag = '[' in string
    string = string.replace('~[',"
```

```

string = string.strip('}')
for predicate in getPredicates(string):
    string = string.replace(predicate, f'~{predicate}')
s = list(string)
for i, c in enumerate(string):
    if c == '|':
        s[i] = '&'
    elif c == '&':
        s[i] = '|'
string = ''.join(s)
string = string.replace('~~','')
return f'[{string}]' if flag else string

```

```

def Skolemization(sentence):
    SKOLEM_CONSTANTS = [f'{chr(c)}' for c in range(ord('A'), ord('Z')+1)]
    statement = ''.join(list(sentence).copy())
    matches = re.findall('[ $\forall \exists$ ].', statement)
    for match in matches[::-1]:
        statement = statement.replace(match, '')
        statements = re.findall('\[([ $\w$ ]+)\]', statement)
        for s in statements:
            statement = statement.replace(s, s[1:-1])
        for predicate in getPredicates(statement):
            attributes = getAttributes(predicate)
            if ''.join(attributes).islower():
                statement = statement.replace(match[1], SKOLEM_CONSTANTS.pop(0))
            else:
                aL = [a for a in attributes if a.islower()]
                aU = [a for a in attributes if not a.islower()][0]
                statement = statement.replace(aU, f'{SKOLEM_CONSTANTS.pop(0)}({aL[0] if len(aL)
else match[1]})')
    return statement
import re

```

```

def fol_to_cnf(fol):

    statement = fol.replace("<=>", "_")
    while '_' in statement:
        i = statement.index('_')

```



```

    new_statement = '[' + statement[:i] + '=>' + statement[i+1:] + ']'&['+ statement[i+1:] + '=>' +
statement[:i] + ']
    statement = new_statement
statement = statement.replace("=>", "-")
expr = '\([([^\)]+)\)'
statements = re.findall(expr, statement)
for i, s in enumerate(statements):
    if '[' in s and ']' not in s:
        statements[i] += ']'
for s in statements:
    statement = statement.replace(s, fol_to_cnf(s))
while '-' in statement:
    i = statement.index('-')
    br = statement.index('[') if '[' in statement else 0
    new_statement = '~' + statement[br:i] + '[' + statement[i+1:]
    statement = statement[:br] + new_statement if br > 0 else new_statement
while '~∇' in statement:
    i = statement.index('~∇')
    statement = list(statement)
    statement[i], statement[i+1], statement[i+2] = '∃', statement[i+2],
'~'

    statement = ''.join(statement)
while '~∃' in statement:
    i = statement.index('~∃')
    s = list(statement)
    s[i], s[i+1], s[i+2] = '∇', s[i+2], '~'
    statement = ''.join(s)
statement = statement.replace('~[∇', '~∇')
statement = statement.replace('~[∃', '~∃')
expr = '(~[∇ | ∃].)'
statements = re.findall(expr, statement)
for s in statements:
    statement = statement.replace(s, fol_to_cnf(s))
expr = '~\([([^\)]+)\)'
statements = re.findall(expr, statement)
for s in statements:
    statement = statement.replace(s, DeMorgan(s))
return statement

```

```
print(Skolemization(fol_to_cnf("animal(y)<=>loves(x,y)"))))  
print(Skolemization(fol_to_cnf("∀ x[ ∀ y[animal(y)=>loves(x,y)]]=>[ ∃ z[l  
oves(z,x)]]"))))  
print(fol_to_cnf("[american(x)&weapon(y)&sells(x,y,z)&hostile(z)]=>criminal(x)"))
```

Observation:

Output:

```
[~animal(y)|loves(x,y)]&[~loves(x,y)|animal(y)]  
[animal(G(x))&~loves(x,G(x))]|[loves(F(x),x)]  
[~american(x)|~weapon(y)|~sells(x,y,z)|~hostile(z)]|criminal(x)
```

Program 11 : Forward Reasoning

Code:

```
import re

def isVariable(x):
    return len(x) == 1 and x.islower() and x.isalpha()

def getAttributes(string):
    expr = '\([^)]+\)'
    matches = re.findall(expr, string)
    return matches

def getPredicates(string):
    expr = '([a-z~])\([^&]+\)'
    return re.findall(expr, string)
```

```

class Fact:
    def __init__(self, expression):
        self.expression = expression
        predicate, params = self.splitExpression(expression)
        self.predicate = predicate
        self.params = params
        self.result = any(self.getConstants())

    def splitExpression(self, expression):
        predicate = getPredicates(expression)[0]
        params = getAttributes(expression)[0].strip('(').split(',')
        return [predicate, params]

    def getResult(self):
        return self.result

    def getConstants(self):
        return [None if isVariable(c) else c for c in self.params]

    def getVariables(self):
        return [v if isVariable(v) else None for v in self.params]

    def substitute(self, constants):
        c = constants.copy()
        f = f'{self.predicate}({','.join([constants.pop(0) if isVariable(p) else p for p in self.params])})'
        return Fact(f)

class Implication:
    def __init__(self, expression):
        self.expression = expression
        l = expression.split('=>')
        self.lhs = [Fact(f) for f in l[0].split('&')]
        self.rhs = Fact(l[1])

    def evaluate(self, facts):
        constants = {}

```

```

new_lhs = []
for fact in facts:
    for val in self.lhs:
        if val.predicate == fact.predicate:
            for i, v in enumerate(val.getVariables()):
                if v:
                    constants[v] = fact.getConstants()[i]
            new_lhs.append(fact)
    predicate, attributes = getPredicates(self.rhs.expression)[0],
str(getAttributes(self.rhs.expression)[0])
    for key in constants:
        if constants[key]:
            attributes = attributes.replace(key, constants[key])
    expr = f'{predicate} {attributes}'
    return Fact(expr) if len(new_lhs) and all([f.getResult() for f in new_lhs]) else None

```

class KB:

```

def __init__(self):
    self.facts = set()
    self.implications = set()

def tell(self, e):
    if '=>' in e:
        self.implications.add(Implication(e))
    else:
        self.facts.add(Fact(e))
    for i in self.implications:
        res = i.evaluate(self.facts)
        if res:
            self.facts.add(res)

```

```

def query(self, e):
    facts = set([f.expression for f in self.facts])
    i = 1
    print(f'Querying {e}:')
    for f in facts:
        if Fact(f).predicate == Fact(e).predicate:
            print(f'\t{i}. {f}')
            i += 1

```

```
def display(self):
    print("All facts: ")
    for i, f in enumerate(set([f.expression for f in self.facts])):
        print(f'\t{i+1}. {f}')
```

```
kb = KB()
kb.tell('missile(x)=>weapon(x)')
kb.tell('missile(M1)')
kb.tell('enemy(x,America)=>hostile(x)')
kb.tell('american(West)')
kb.tell('enemy(Nono,America)')
kb.tell('owns(Nono,M1)')
kb.tell('missile(x)&owns(Nono,x)=>sells(West,x,Nono)')
kb.tell('american(x)&weapon(y)&sells(x,y,z)&hostile(z)=>criminal(x)')
kb.query('criminal(x)')
kb.display()
```

```
kb_ = KB()
kb_.tell('king(x)&greedy(x)=>evil(x)')
kb_.tell('king(John)')
kb_.tell('greedy(John)')
kb_.tell('king(Richard)')
kb_.query('evil(x)')
```

Observation:

Output:


```
        print(f'\t{i+1}. {f}')
kb = KB()
kb.tell('missile(x)=>weapon(x)')
kb.tell('missile(M1)')
kb.tell('enemy(x,America)=>hostile(x)')
kb.tell('american(West)')
kb.tell('enemy(Nono,America)')
kb.tell('owns(Nono,M1)')
kb.tell('missile(x)&owns(Nono,x)=>sells(West,x,Nono)')
kb.tell('american(x)&weapon(y)&sells(x,y,z)&hostile(z)=>criminal(x)')
kb.query('criminal(x)')
kb.display()
```

⇒ Querying criminal(x):
1. criminal(West)
All facts:
1. missile(M1)
2. criminal(West)
3. weapon(M1)
4. enemy(Nono,America)
5. owns(Nono,M1)
6. hostile(Nono)
7. american(West)
8. sells(West,M1,Nono)