

WEEK 4

Write a C program to simulate Real-Time CPU Scheduling algorithms:

a) Rate- Monotonic

b) Earliest-deadline First

CODE:

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
int et[10], i, n, dl[10], p[10], ready[10], flag = 1;
```

```
int lcm(int a, int b) {  
    int max = (a > b) ? a : b;  
    while (1) {  
        if (max % a == 0 && max % b == 0)  
            return max;  
        max++;  
    }  
}
```

```
int lcmArray(int arr[], int n) {  
    int result = arr[0];  
    for (int i = 1; i < n; i++) {  
        result = lcm(result, arr[i]);  
    }  
    return result;  
}
```

```
void mono() {  
    int time = lcmArray(dl, n);  
    int op = 0, pr = 0, pre = pr;
```

```
    while (op <= time) {  
        for (i = 0; i < n; i++) {
```

```

        if (op % dl[i] == 0) {
            ready[i] = 1;
        }
    }
}

```

```

flag = 0;
for (i = 0; i < n; i++) {
    if (ready[i] == 1) {
        flag = 1;
        break;
    }
}

```

```

if (flag == 0) {
    pr = -1;
} else {
    pr = -1;
    for (i = 0; i < n; i++) {
        if (ready[i] == 1) {
            if (pr == -1 || dl[i] < dl[pr]) {
                pr = i;
            }
        }
    }
}

```

```

if (pr != pre) {
    if (pr == -1) {
        printf("%d Idle ",op);
    } else {
        printf("%d P%d ",op, pr + 1);
    }
}

```

```

op++;
if (pr != -1) {
    p[pr] = p[pr] - 1;
    if (p[pr] == 0) {
        p[pr] = et[pr];
    }
}

```

```

        ready[pr] = 0;
    }
}

pre = pr;
}

printf("\n");
}

```

```

void edf() {
    int time = lcmArray(dl, n);
    int op = 0, pr = 0, pre = -1;
    int flag, i;

    while (op <= time) {
        for (i = 0; i < n; i++) {
            if (op % dl[i] == 0) {
                ready[i] = 1;
            }
        }

        flag = 0;
        for (i = 0; i < n; i++) {
            if (ready[i] == 1) {
                flag = 1;
                break;
            }
        }

        if (flag == 0) {
            pr = -1;
        } else {
            pr = -1;
            for (i = 0; i < n; i++) {
                if (ready[i] == 1) {
                    if (pr == -1 || p[i] < p[pr]) {
                        pr = i;
                    }
                }
            }
        }
    }
}

```

```

        }
    }
}

if (pr != pre) {
    if (pr == -1) {
        printf("%d Idle ", op);
    } else {
        printf("%d P%d ", op, pr + 1);
    }
}

op++;

if (pr != -1) {
    p[pr] = p[pr] - 1;
    if (p[pr] == 0) {
        p[pr] = et[pr];
        ready[pr] = 0;
    }
}

pre = pr;
}

printf("\n");
}

int main() {
    int ch, k = 1;
    while (k) {
        printf("Enter your choice: \n1. Monotonic \n2. EDF \n3. Proportional \n4. Exit\n");
        scanf("%d", &ch);
        if(ch==3)
            exit(0);
        printf("Enter the number of processes: ");
        scanf("%d", &n);
        printf("Enter execution times: \n");
        for (i = 0; i < n; i++)

```

```
    scanf("%d", &et[i]);

    printf("Enter deadlines: \n");
    for (i = 0; i < n; i++)
        scanf("%d", &dl[i]);

    for (i = 0; i < n; i++)
        p[i] = et[i];

    for (i = 0; i < n; i++)
        ready[i] = 0;

    switch (ch) {
        case 1:
            mono();
            break;

        case 2:
            edf();
            break;

        case 3:
            k = 0;
            break;

        default:
            printf("Invalid choice.\n");
    }
}

return 0;
}
```

OBSERVATION:

```

10/7/23
Lab-4
Write a c program to simulate Real-Time CPU
scheduling algorithms.
a) Rate-Monotonic
b) Earliest-deadline First

#include <stdio.h>
#include <stdlib.h>

int lt [10], i, n, dl [10], p [10], ready [10], lag = 1;

int lcm (int a, int b) {
    int max = (a > b) ? a : b;
    while (1) {
        if (max % a == 0 & max % b == 0)
            return max;
        max++;
    }
}

int lcmArray (int arr[], int n) {
    int result = arr[0];
    for (int i = 1; i < n; i++) {
        result = lcm(result, arr[i]);
    }
    return result;
}

void mono() {
    int time = lcmArray(dl, n);
    int op = 0, pr = 0, pre = pr;
    while (op <= time) {
        for (i = 0; i < n; i++) {

```

```

if (op % dl[i] == 0) {
    ready[i] = 1;
}
}

lag = 0;
for (i = 0; i < n; i++) {
    if (ready[i] == 1) {
        lag = 1;
        break;
    }
}

if (lag == 0) {
    pr = -1;
} else {
    pr = -1;
    for (i = 0; i < n; i++) {
        if (ready[i] == 1) {
            if (pr == -1 || dl[i] < dl[pr]) {
                pr = i;
            }
        }
    }
}

if (pr != pre) {
    if (pr == -1) {
        printf("%d idle", op);
    } else {
        printf("%d P%d", op, pr+1);
    }
}

op++;

```



```

if (pr == -1) {
    P[pr] = P[pr-1];
    if (P[pr] == 0) {
        P[pr] = el[pr];
        ready[pr] = 0;
    }
}
pre = pr;
}

```

```

void edf() {
    int time = lenArray (dl, n);
    int op = 0, pr = 0, pre = 1;
    int flag, i;
    while (op <= time) {
        for (i = 0; i < n; i++) {
            if (op % dl[i] == 0) {
                ready[i] = 1;
            }
        }
    }
}

```

```

flag = 0;
for (i = 0; i < n; i++) {
    if (ready[i] == 1) {
        flag = 1;
        break;
    }
}

```

```

if (flag == 0) {
    pr = -1;
} else {
    pr = -1;
    for (i = 0; i < n; i++) {

```

```

if (ready[i] == 1) {
    if (pr == -1 || P[i] < P[pr]) {
        pr = i;
    }
}
}
}
if (pr != pre) {
    if (pr == -1) {
        printf ("%d Idle", op);
    } else {
        printf ("%d P %d", op, pr+1);
    }
}

```

```

op++;
if (pr == -1) {
    P[pr] = P[pr-1];
    if (P[pr] == 0) {
        P[pr] = el[pr];
        ready[pr] = 0;
    }
}

```

```

pre = pr;
}
}

```

```

int main() {
    int ch, K = 1;
    while (K) {
        printf ("Enter Your choice: 1. Monotonic 2. EDF 3. proportional 4. Exit\n");
        scanf ("%d", &ch);
        if (ch == 3) {
            exit (0);
        }
    }
}

```


RANKA
DATE / /
PAGE

```

print("Enter number of processes:");
scanf("%d", &n);
print("Enter execution times: \n");
for (i=0; i<n; i++)
    scanf("%d", &et[i]);
print("Enter deadlines: \n");
for (i=0; i<n; i++)
    scanf("%d", &dl[i]);
for (i=0; i<n; i++)
    p[i] = et[i];
for (i=0; i<n; i++)
    ready[i] = 0;
switch(ch)
{
    case 1: mono();
        break;
    case 2: edf();
        break;
    case 3: K=0;
        break;
    default: print("Invalid \n");
}
}
return 0;
}

```

OUTPUT:

Enter your choice :

1. Monotonic

2. EDF

3. Exit

1

Enter the Number of processes: 3

Enter Execution times:

3 2 2

Enter Deadlines:

20 5 10

0 P₁ 2 P₃ 4 P₁ 5 P₃ 7 P₁ 9 Idl 10 P₂ 12 P₃ 14 Idl 15
P₂ 17 Idl 20 P₂

Enter Your choice :

1. Monotonic

2. EDF

3. Exit

2.

Enter the Number of processes: 2

Enter Execution times:

20 35

Enter deadlines:

50 80

0 P₁ 20 P₂ 55 P₁ 75 Idl 80 P₂ 115 P₁ 135 Idl 150 P₁ 170 P₂
205 P₁ 225 Idl 240 ..

~~14/7/23~~

16/10

OUTPUT:

```
"C:\Users\ysrmo\OneDrive - Base PU College\Desktop\4thsem\OS\oslab\edfrm\bin\Debug\edfrm.exe"
Enter your choice:
1. Monotonic
2. EDF
3. Exit
1
Enter the number of processes: 3
Enter execution times:
3 2 2
Enter deadlines:
20 5 10
0 P2 2 P3 4 P1 5 P2 7 P1 9 Idle 10 P2 12 P3 14 Idle 15 P2 17 Idle 20 P2
Enter your choice:
1. Monotonic
2. EDF
3. Exit
2
Enter the number of processes: 2
Enter execution times:
20 35
Enter deadlines:
50 80
0 P1 20 P2 55 P1 75 Idle 80 P2 115 P1 135 Idle 150 P1 170 P2 205 P1 225 Idle 240 P2 250 P1 270 P2 295 Idle 300 P1 320 P2 355 P1 375 Idle 400 P1
Enter your choice:
1. Monotonic
2. EDF
3. Exit
```