

SQLite and PHP

Wez Furlong
Marcus Boerger



LinuxTag 2003 Karlsruhe

SQLite

- ✓ Started in 2000 by D. Richard Hipp
- ✓ Single file database
- ✓ Subselects, Triggers, Transactions, Views
- ✓ Very fast, 2-3 times faster than MySQL, PostgreSQL for many common operations
- ✓ 2TB data storage limit
- ✗ Views are read-only
- ✗ No foreign keys
- ✗ Locks whole file for writing




PHP with SQLite


- ☑ SQLite library integrated with PHP extension
- ☑ PHP extension available via PECL for PHP 4.3
- ☑ Bundled with PHP 5
- ☑ API designed to be logical, easy to use
- ☑ High performance
- ☑ Convenient migration from other PHP database extensions
- ☑ Call PHP code from within SQL




Dedicated Host



ISP/Shared Host



Embedded



Opening and Closing

resource **sqlite_open**(string filename [, int mode [, string & error_message]])

- ☑ Creates a non existing database file
- ☑ Checks all security relevant INI options
- ☑ Also has a persistent (popen) variant

void **sqlite_close**(resource db)

- ☑ Closes the database file and all file locks





```
<?php
```

```
// Opening and Closing
```

```
// Open the database (will create if not exists)
```

```
$db = sqlite_open("foo.db");
```

```
// simple select
```

```
$result = sqlite_query($db, "SELECT * from foo");
```

```
// grab each row as an array
```

```
while ($row = sqlite_fetch_array($result)) {  
    print_r($row);  
}
```

```
// close the database
```

```
sqlite_close($db);
```

```
?>
```


Query Functions

resource **sqlite_query** (\$db, \$sql [, int result_type])

- ✓ Buffered query = Flexible
- ✗ More memory usage
- ✓ Also have an unbuffered variant = Fast

array **sqlite_array_query** (\$db, \$sql [,int result_type])

- ✓ Flexible, Convenient
- ✗ Slow with long result sets



```
<?php
    // Default result type SQLITE_BOTH

    $result = sqlite_query($db,
        "SELECT first, last from names");
    $row = sqlite_fetch_array($result);

    print_r($row);
?>
```

```
Array
(
    [0] => Joe
    [1] => Internet
    [first] => Joe
    [last] => Internet
)
```

```
<?php
    // column names only

    $result = sqlite_query($db,
        "SELECT first, last from names");
    $row = sqlite_fetch_array($result, SQLITE_ASSOC);

    print_r($row);
?>
```

```
Array
(
    [first] => Joe
    [last] => Internet
)
```

The PHP logo, consisting of the lowercase letters 'php' in a stylized font, enclosed within an oval border.

```
<?php
    // column numbers only

    $result = sqlite_query($db,
        "SELECT first, last from names");
    $row = sqlite_fetch_array($result, SQLITE_NUM);

    print_r($row);
?>
```

```
Array
(
    [0] => Joe
    [1] => Internet
)
```

The PHP logo, consisting of the letters 'php' in a stylized, lowercase font, enclosed within an oval border.



```
<?php
    // Collecting all rows from a query

    // Get the rows as an array of arrays of data
    $rows = array();

    $result = sqlite_query($db,
        "SELECT first, last from names");

    // grab each row
    while ($row = sqlite_fetch_array($result)) {
        $rows[] = $row;
    }

    // Now use the array; maybe you want to
    // pass it to a Smarty template
    $template->assign("names", $rows);

?>
```

```
<?php
```

```
// The same but with less typing and  
// more speed
```

```
// Get the rows as an array of arrays of data  
$rows = sqlite_array_query($db,  
    "SELECT first, last from names");
```

```
// give it to Smarty  
$template->assign("names", $rows);
```

```
?>
```

The PHP logo, consisting of the letters "php" in a stylized, lowercase font, enclosed within an oval border.

Array Interface

array **sqlite_fetch_array** (resource result [,
int result_type [, bool decode_binary]])

- ✓ Flexible
- ✗ Slow for large result sets

array **sqlite_fetch_all** (resource result [,
int result_type [, bool decode_binary]])

- ✓ Flexible
- ✗ Slow for large result sets; better use
sqlite_array_query ()

Single Column Interface

mixed **sqlite_single_query** (\$db, \$sql
[, bool first_row_only])

✓ Fast

✗ Only returns the first column

string **sqlite_fetch_single** (\$result)

✓ Fast

✗ Slower than sqlite_single_query

mixed **sqlite_fetch_single** (\$result,
\$index_or_name)

✓ Flexible, Faster than array functions

✗ Slower than other single functions




```
<?php
```

```
$count = sqlite_single_query($db,  
    "SELECT count(first) from names");
```

```
echo "There are $count names";
```

```
?>
```

```
There are 3 names
```



```
<?php
```

```
$first_names = sqlite_single_query($db,  
    "SELECT first from names");
```

```
print_r($first_names);
```

```
?>
```

```
Array
```

```
(
```

```
    [0] => Joe
```

```
    [1] => Peter
```

```
    [2] => Fred
```

```
)
```

The PHP logo, consisting of the letters 'php' in a stylized, lowercase font, enclosed within an oval border.

Meta information

int **sqlite_num_rows** (resource result)

- ▣ Number of rows in a SELECT

int **sqlite_num_fields** (resource result)

- ▣ Number of columns in a SELECT

int **sqlite_field_name** (resource result, int field_index)

- ▣ Name of a selected field

int **sqlite_changes** (resource db)

- ▣ Number of rows changed by a UPDATE/REPLACE

int **sqlite_last_insert_rowid** (resource db)

- ▣ ID of last inserted row



Iterator Interface

array **sqlite_current** (resource result [, int result_type [,
bool decode_binary]])

- ▣ Returns the current selected row

bool **sqlite_rewind** (resource result)

- ▣ Rewind to the first row of a buffered query

bool **sqlite_next** (resource result)

- ▣ Moves to next row

bool **sqlite_has_more** (resource result)

- ▣ Returns true if there are more rows

bool **sqlite_seek** (resource result, int row)

- ▣ Seeks to a specific row of a buffered query

Using Iterators

```
<?php
```

```
    $db = sqlite_open("...");
```

```
    for ($res = sqlite_query ("SELECT...", $db);  
        sqlite_has_more ($res);  
        sqlite_next ($res))
```

```
    {
```

```
        print_r (sqlite_current ($res));
```

```
    }
```

```
?>
```

The PHP logo, consisting of the lowercase letters 'php' in a stylized font, enclosed within an oval border.

Calling PHP from SQL

bool **sqlite_create_function** (resource db,
string funcname, mixed callback [,
long num_args])

- ▣ Registers a "regular" function

bool **sqlite_create_aggregate** (resource db,
string funcname, mixed step,
mixed finalize [, long num_args])

- ▣ Registers an aggregate function



```
<?php
    function md5_and_reverse($string) {
        return strrev(md5($string));
    }

    sqlite_create_function($db,
        'md5rev', 'md5_and_reverse');

    $rows = sqlite_array_query($db,
        'SELECT md5rev(filename) from files');
?>
```

The PHP logo, consisting of the lowercase letters 'php' in a stylized font, enclosed within an oval border.

<?php

```
function max_len_step(&$context, $string) {  
    if (strlen($string) > $context) {  
        $context = strlen($string);  
    }  
}
```

```
function max_len_finalize(&$context) {  
    return $context;  
}
```

```
sqlite_create_aggregate($db,  
    'max_len', 'max_len_step',  
    'max_len_finalize');
```

```
$rows = sqlite_array_query($db,  
    'SELECT max_len(a) from strings');
```

```
print_r($rows);
```

?>

The PHP logo, consisting of the word "php" in a stylized, lowercase font inside an oval shape.

Handling binary data in UDF

string **sqlite_udf_encode_binary** (string data)

- ▣ Apply binary encoding (if required) to a string to be returned from an UDF

string **sqlite_udf_decode_binary** (string data)

- ▣ Decode binary encoding on a string parameter passed to an UDF



Handling Binary Data

string **sqlite_escape_string** (string data)

- ▣ Escapes quotes appropriately for SQLite
- ▣ Applies a safe binary encoding for use in SQLite queries
- ▣ Values must be read with the `decode_binary` flag turned on (default!)



Utility Functions

void **sqlite_busy_timeout** (resource db, int ms)

- ▣ Set busy retry duration.
- ▣ If ms ≤ 0, no waiting if performed

int **sqlite_last_error** (resource db)

- ▣ Returns last error code from database

string **sqlite_error_string** (int error_code)

- ▣ Converts error code to a readable string

string **sqlite_libversion** ()

- ▣ Returns version of the linked SQLite library

string **sqlite_libencoding** ()

- ▣ Returns charset encoding used by SQLite library



Resources



Documentation at

<http://docs.php.net/?q=ref.sqlite>

