FedMATRIX-LoRA: Client-Aware Matrix-Level Adaptation for Resource-Constrained Federated Fine-Tuning

Anonymous Authors

***Abstract*—Federated fine-tuning must allocate limited training resources across clients with heterogeneous data and device capabilities. For low-rank adaptation (LoRA), this requires deciding not only adapter capacity but also which target projections receive updates. Grouping projections into indivisible Transformer blocks restricts this placement decision. A controlled study at a matched parameter budget finds larger short-term validation-loss reductions with independent matrix selection than with whole-layer allocation in all 12 setting-level comparisons, using either local or server-proxy importance scores. Motivated by this observation, we present FedMATRIX-LoRA, a client-aware matrix-level adaptation framework. Clients estimate update priorities from local gradient profiles and construct resource-feasible matrix configurations; the server coordinates participation and configuration choice under a shared budget and latency objective. Matrix-wise aggregation combines the resulting heterogeneous updates. A conditional stationarity analysis characterizes the roles of update bias and matrix coverage. Experiments spanning image classification, language understanding, and dialogue summarization evaluate the complete framework, while controlled studies examine selection granularity, scoring reliability, and the contributions of individual components. The results support importance-guided matrix selection as a useful adaptation dimension under constrained training budgets.**

***Index Terms*—Federated fine-tuning, low-rank adaptation, client-aware matrix selection, resource heterogeneity**

I. Introduction

Foundation models provide reusable representations, but adapting them to downstream applications often requires data held by different institutions or devices. Federated learning enables these data holders to optimize a shared model without pooling their raw examples [3], [4]. Full-parameter updates remain costly for clients with limited memory, computation, and communication capacity. Low-rank adaptation (LoRA) reduces this burden by representing updates through compact trainable factors while keeping the pretrained backbone fixed [5]. Federated LoRA therefore makes collaborative adaptation more accessible, but still requires deciding which adapter parameters each client should update with its available resources.

Adapter size alone does not determine training feasibility. Memory is also required for the frozen backbone, optimizer states, and intermediate activations retained for backpropagation. Reducing rank shrinks adapter-related state without necessarily shortening the backward path to a trainable location. Fed-HeLLo identifies this distinction and reports limited total-memory savings from rank reduction when activations dominate [8]. Selecting trainable locations thus complements rank adaptation: it changes where updates occur and, under partial-adapter execution, which activation dependencies must be retained. We study this placement decision at a fixed rank, separating target selection from capacity allocation within each selected adapter.

A Transformer block contains distinct target projections, including Query, Key, Value, and feed-forward transformations. Each projection can receive its own LoRA update. Existing placement studies and importance-aware rank allocation show that adaptation value need not be uniform across matrices or layers [5], [38]. Layer-level allocation nevertheless binds candidate projections within a block into one decision. Under a limited budget, selecting a useful projection can therefore require allocating capacity to other projections in the same block, while excluding useful targets elsewhere. This motivates a more specific question than whether different locations matter: with the importance criterion and parameter budget held fixed, does relaxing whole-layer binding improve the configurations selected for adaptation?

To examine this question, we compare independent matrix selection with whole-layer allocation on CIFAR100 using ViT-base. Matrix-level allocation selects 12 Q/K/V target matrices across the 12 Transformer blocks; layer-level allocation selects all three projections in four blocks. Both use rank eight and the same trainable parameter count. Within each scoring source, they maximize the same profiled utility subject to the same analytical resource limits. We evaluate local and server-proxy scores separately, using IID data and Dirichlet partitions with concentration parameters 1.0 and 0.1. Paired configurations start from the same adapter at initialization or after a shared warm-up and undergo 20 local training steps. Holding unselected adapters fixed in the forward model isolates the effect of the trainable subset. Section V-C details the protocol.

Figure 1 reports the matrix-level minus layer-level difference in held-out validation-loss reduction. The mean difference is positive in all 12 partition–checkpoint–source settings; 35 of the 36 within-seed paired means, each averaged over five clients, are positive. These improvements occur with both local and server-proxy importance scores. The observation supports independent target selection as a useful adaptation dimension beyond whole-layer allocation, rather than attributing its benefit to a particular scoring source. The measured outcome is short-term loss reduction at a fixed parameter budget.

Exploiting this flexibility requires an assessment of candidate updates before the training budget is committed. Gradient-




Fig. 1. Matrix-level minus layer-level validation-loss reduction. Positive values favor matrix-level selection under the fixed protocol; error bars show standard deviation across seeds.

and Fisher-based criteria offer established ways to prioritize trainable parameters and LoRA layers [8], [39]. Such priorities depend on both the current model and the data used to evaluate its loss. In a federated system, each client already holds data defining its local objective. Evaluating that objective provides a client-conditioned assessment without requiring an additional server-held profiling dataset. Fed-pilot also incorporates local and aggregated importance information into LoRA allocation [40]; our focus is to expose individual projection choices within blocks and coordinate these choices under coupled resource constraints. Local profiling is the assessment mechanism, while the motivating comparison isolates the value of selection granularity.

A high-scoring subset, however, is useful only if it can be trained. Memory feasibility depends on the locations of selected targets as well as their number, and client computation and bandwidth determine whether the configuration meets a round deadline. Independently feasible choices can also exceed the shared round budget when executed together. The design therefore has two connected requirements: estimate update priorities at the target-matrix level, and translate those priorities into feasible client configurations that can be coordinated in a training round. A ranking alone does not resolve this second requirement.

We address these requirements with FedMATRIX-LoRA, a client-aware matrix-level adaptation framework. During profiling refreshes, each client evaluates the LoRA factors of candidate projections on a local mini-batch at the current global adapter. The resulting scores guide configurations at different matrix-equivalent costs, subject to local memory and latency constraints. The server selects client configurations under the shared budget and synchronization-latency objective. Clients train the assigned factors, and matrix-wise aggregation updates the shared global adapter. Local evidence informs the preferred targets; resource-aware allocation determines which proposed updates can be executed together.

Our contributions are threefold:

- We formulate importance-guided target-matrix selection for resource-constrained federated fine-tuning, allowing projections within a Transformer block to be selected independently. A matched-budget controlled study motivates this granularity using actual short-term adaptation gains under both local and server-proxy scoring.
- We develop FedMATRIX-LoRA to connect local matrix profiling with resource-feasible configuration generation, shared-budget coordination, and matrix-wise aggregation. Clients can update distinct target subsets while contributing to a common global adapter.
- We provide a conditional stationarity analysis of selective aggregation and evaluate the framework across image classification, language understanding, and dialogue summarization. Controlled scoring and ablation studies examine the mechanisms separately from the complete system's performance.

Section II positions the work relative to prior studies. Section III defines the system model and allocation problem. Section IV presents the framework and its analysis, and Section V reports the evaluation. Section VI concludes the paper.

II. Related Work

Parameter-efficient and importance-guided adaptation. Parameter-efficient fine-tuning reduces the parameters updated when adapting a pretrained model. LoRA expresses updates through low-rank factors attached to selected weight matrices, while QLoRA combines a quantized frozen backbone with trainable adapters [5], [10]. These mechanisms address different components of the adaptation footprint. Selecting the target subset introduces a further decision about where the trainable capacity is placed, rather than only its size or storage precision.

Importance-aware adaptation has already established that a limited parameter budget need not be distributed uniformly. AdaLoRA assigns nonuniform rank budgets across weight matrices through importance-guided pruning of an SVD-style update parameterization [38]. FISH selects a sparse trainable-parameter mask using Fisher-based scores [39]. FedMATRIX-LoRA builds on importance-guided selection at a different allocation level: it chooses fixed-rank target subsets for individual federated clients. Whereas importance-aware rank allocation controls capacity within weight updates, the proposed formulation coordinates independently selectable target projections under heterogeneous client and round-level constraints.

Heterogeneous federated LoRA allocation. HetLoRA supports different client ranks through local rank self-pruning and sparsity-weighted aggregation, while FAH-QLoRA jointly

considers quantization and LoRA rank [6], [7]. These approaches adapt capacity or numerical precision to client resources. Fed-HeLLo identifies an additional memory concern: reducing rank primarily affects optimizer-related state in the activation-dominated settings it studies, motivating partial-layer training [8]. LEGEND jointly configures tuning depth and rank distribution, explicitly linking trainable locations to resource use [32]. Target selection and rank allocation are consequently complementary dimensions, rather than mutually exclusive alternatives.

Fed-HeLLo accounts for unequal layer importance through server-proxy scores and geometric allocation strategies [8]. Its score-guided strategy converts a shared assessment into allocation probabilities, so clients can receive different layer masks. FedMATRIX-LoRA instead permits separate choices among projections within a block and evaluates the scoring criterion on client data. The controlled comparison in Fig. 1 distinguishes the granularity question from the scoring-source question by applying both matrix-level and layer-level selection to each source. It compares allocation constraints within a common pipeline, not a full reproduction of Fed-HeLLo.

Fed-pilot is a closely related importance-guided allocation method. Its block-indexed formulation combines local and aggregated gradient-based information-gain scores with memory-constrained allocation and compensated aggregation [40]. FedMATRIX-LoRA exposes individual target-projection indicators within blocks and coordinates their configurations across clients under memory limits, latency constraints, and a shared round budget. The relevant distinction is the allocation decision and its coupled constraints, not local scoring or knapsack optimization alone.

Aggregation and resource coordination. FedEx-LoRA addresses the mismatch associated with aggregating low-rank factors, and LoRA-FAIR refines aggregation and initialization [16], [17]. These studies concern how local updates are combined. Oort, FedBalancer, and PyramidFL address participant selection or training-work coordination under heterogeneous conditions [26]–[28]. FedMATRIX-LoRA includes the trainable target subset in the configuration assigned to a participating client. Configuration generation connects local update priorities to resource feasibility, while server coordination determines which configurations can execute together. The matrix-wise convergence analysis characterizes the selective update pattern produced by this process.

III. System Model and Problem Formulation

A. System Model and Federated LoRA Preliminaries

We consider a heterogeneous federated LoRA fine-tuning system consisting of one server and N clients. Each client i owns a private local dataset $\mathcal{D}_i$, an on-device training-memory capacity $M_i^{\max}$ (corresponding to the available GPU device memory in our implementation), an estimated communication bandwidth B_i, and heterogeneous computational resources. To preserve data privacy, all local datasets remain on their corresponding clients throughout the training process and are never uploaded to the server. The server initializes a pretrained backbone model Θ^0, which remains frozen during federated fine-tuning, and maintains the global LoRA adapter parameters θ^k at communication round k.

Let $n_i = |\mathcal{D}_i|$ denote the number of local training samples at client i. Federated LoRA fine-tuning aims to minimize the following global objective

$$F(\theta) = \frac{1}{N} \sum_{i=1}^{N} F_i(\theta), \tag{1}$$

where

$$F_i(\theta) = \frac{1}{n_i} \sum_{z \in \mathcal{D}_i} \ell(\Theta^0, \theta; z), \tag{2}$$

and $\ell(\cdot)$ denotes the task loss evaluated using the frozen backbone Θ^0 and trainable LoRA parameters θ.

For a target linear transformation $W_j \in \mathbb{R}^{d_{\text{out}} \times d_{\text{in}}}$, LoRA parameterizes its update as

$$\Delta W_j = B_j A_j, \tag{3}$$

where $A_j \in \mathbb{R}^{r \times d_{\text{in}}}$ and $B_j \in \mathbb{R}^{d_{\text{out}} \times r}$ are low-rank matrices with rank $r \ll \min(d_{\text{in}}, d_{\text{out}})$.

We treat the trainable adapter subset as a client-specific decision. A target matrix denotes a pretrained projection, such as Query, Key, or Value; selecting it means updating its associated LoRA factors, not the frozen pretrained matrix itself. The rank of every selected adapter is fixed to the same value, so configuration differences arise from target selection.

B. Client-Aware Matrix-Level LoRA Allocation

We formulate federated LoRA allocation at the target-matrix granularity. Let

$$\mathcal{A} = \{W_1, W_2, \ldots, W_L\} \tag{4}$$

denote the ordered set of LoRA-compatible target matrices extracted from the backbone. These matrices include the Query, Key, Value, output, and feed-forward projection matrices in Transformer blocks.

For client i at communication round k, the matrix activation decision is represented by the binary vector

$$\mathbf{m}_i^k = [m_{i,1}^k, \cdots, m_{i,L}^k], \tag{5}$$

where

$$m_{i,j}^k = \begin{cases} 1, \text{if } W_j \text{ is activated for local training;} \\ 0, \text{otherwise.} \end{cases} \tag{6}$$

Each activation vector therefore specifies the subset of LoRA target matrices trained by client i during communication round k.

Let $V_i^k(\mathbf{m}_i^k)$ denote the profiled utility of client i's matrix configuration. It is computed from local data at the current global adapter and summarizes the estimated priority of the selected updates. We set $V_i^k(\mathbf{0}) = 0$. The profiling procedure is defined in Section IV-B.

Layer-group allocation is recovered by constraining all candidate matrices in a Transformer block to share the same selection indicator.

C. Resource Constraints and Problem Formulation

The activation decision of LoRA target matrices determines the resource consumption of each participating client. We model the training cost, training-memory usage, and training latency separately.

First, let $c_i(\mathbf{m}_i^k)$ denote the normalized training cost associated with matrix configuration $\mathbf{m}_i^k$. We approximate this cost by the number of activated rank-8 matrices, $c_i(\mathbf{m}_i^k) = \sum_{j=1}^{L} m_{i,j}^k$. This standardized count is not a measurement of matrix-specific computation or memory, which can differ even at the same rank; memory is modeled separately below.

Training-memory consumption depends on both the number and positions of activated matrices. For any nonzero $\mathbf{m}$, let $\mathcal{J}(\mathbf{m}) = \{j \mid m_j = 1\}$ and $j_{\min}(\mathbf{m}) = \min \mathcal{J}(\mathbf{m})$. Following the training-memory decomposition commonly adopted in partial-layer federated LoRA fine-tuning [8], we set $M_i(\mathbf{0}) = M_i^{\text{fixed}}$, while a nonzero configuration uses

$$M_i(\mathbf{m}) = M_i^{\text{fixed}} + q_i(r)c_i(\mathbf{m}) + \sum_{j=j_{\min}(\mathbf{m})}^{L} \mu_{i,j}, \quad (7)$$

where M_i^{fixed} denotes the memory occupied by the frozen backbone and fixed runtime buffers, $q_i(r)$ is the parameter-and-optimizer memory per activated rank-r LoRA matrix, and $\mu_{i,j}$ is retained activation memory. The last term reflects the position-dependent memory characteristic of Transformer fine-tuning: activating an earlier matrix requires retaining a longer backward propagation path and therefore consumes more activation memory.

The latency of client i consists of local computation and communication. Let γ_i denote its computation coefficient, σ_i the communication size per activated matrix, and B_i its available bandwidth. Its latency is

$$\begin{aligned} T_i^{\text{comp}}(\mathbf{m}_i) &= \gamma_i c_i(\mathbf{m}_i), \\ T_i^{\text{comm}}(\mathbf{m}_i) &= \frac{\sigma_i c_i(\mathbf{m}_i)}{B_i}, \\ T_i(\mathbf{m}_i) &= T_i^{\text{comp}}(\mathbf{m}_i) + T_i^{\text{comm}}(\mathbf{m}_i). \end{aligned} \quad (8)$$

The coefficients define an analytical resource profile; equal matrix-equivalent costs need not correspond to identical measured hardware costs.

At communication round k, the server jointly determines the participating clients and their matrix configurations under a shared resource budget. Let S_k denote the set of candidate clients, $z_i^k \in \{0, 1\}$ indicate whether client i participates in the current round, C^k denote the round-level training budget, and τ^k represent the latency of the current communication round. Let $\ell_i^{\min}$ and $\ell_i^{\max}$ bound the number of matrices activated by participating client i, and let $\lambda > 0$ control the utility–latency trade-off.

$$\max_{\{\mathbf{m}_i^k, z_i^k\}, \tau^k} \quad \sum_{i \in S_k} V_i^k(\mathbf{m}_i^k) - \lambda \tau^k \quad (9)$$

$$\text{s.t.} \quad \sum_{i \in S_k} c_i(\mathbf{m}_i^k) \le C^k, \quad (10)$$

$$m_{i,j}^k \le z_i^k, \quad (11)$$

$$\ell_i^{\min} z_i^k \le \sum_{j=1}^{L} m_{i,j}^k \le \ell_i^{\max} z_i^k, \quad (12)$$

$$M_i(\mathbf{m}_i^k) \le M_i^{\max}, \quad \forall i : z_i^k = 1, \quad (13)$$

$$T_i(\mathbf{m}_i^k) \le \tau^k \le T_{\max}, \quad \forall i : z_i^k = 1. \quad (14)$$

The objective maximizes the aggregated client-conditioned adaptation utility while minimizing round latency. Equations (10)–(14) impose the round-level matrix-equivalent budget, participation consistency, activated-matrix bounds, per-client training-memory limits, and the round deadline. In particular, Eqs. (11) and (12) together ensure that an inactive client selects no matrix, whereas an active client selects between $\ell_i^{\min}$ and $\ell_i^{\max}$ matrices.

The formulation couples client-level feasibility with a shared round budget. We implement it by constructing feasible configurations locally and coordinating these configurations at the server.

IV. FedMATRIX-LoRA Design

A. Framework Overview

FedMATRIX-LoRA implements importance-guided matrix selection through client-conditioned assessment and resource-feasible allocation. Figure 2 separates these roles. Clients profile the current adapter on local data and form configurations of independently selectable targets. The server coordinates the configurations under the round budget and latency objective. Clients then update the assigned factors, and their contributions are aggregated matrix-wise into the next shared adapter. The following subsections specify the scoring rule, allocation procedure, training protocol, and conditional analysis.

B. Client-Conditioned Matrix Profiling

Client-conditioned assessment. The motivating study isolates the value of allowing individual projections to be selected. To use that flexibility during federated training, the allocation procedure needs a priority score for each candidate target. At a common global adapter, a client's loss gradient reflects parameter sensitivity under its own examples. Local assessment therefore supplies priorities associated with that client's objective without requiring a server-held profiling dataset. The configuration generator combines these priorities with resource constraints rather than treating an isolated ranking as the final training decision.

A single-pass gradient score. Gradient- and Fisher-based criteria have been used to select trainable parameters and LoRA layers [8], [39]. We use a gradient-squared criterion that evaluates all candidate targets in one backward pass, rather than trial-training individual configurations. During a refresh




Fig. 2. FedMATRIX-LoRA workflow: client-conditioned profiling, local feasible configuration generation, budget- and latency-aware server coordination, and local training with matrix-wise aggregation.

at round k, client i attaches LoRA modules to the candidate projections, loads the current global adapter θ^k, and evaluates the average loss on a local mini-batch $\mathcal{B}_i^k$. Let θ_j^k denote the LoRA factors associated with target matrix j. Its raw score is

$$g_{i,j}^k = \sum_{p \in \theta_j^k} \left(\nabla_p \mathcal{L}_i(\theta^k; \mathcal{B}_i^k) \right)^2 . \tag{15}$$

The score aggregates the magnitude of the batch-loss gradient over the adapter's trainable coordinates. Squaring makes coordinate contributions nonnegative; summation yields a block-level sensitivity measure rather than a mean per parameter. For a fixed parameterization, the gradient norm measures the largest first-order sensitivity to a unit-norm perturbation of that block. This motivates using its square as an update-priority signal. The calculation uses the gradient of a batch-averaged loss, so the score is a Fisher-inspired proxy rather than exact Fisher information. Its empirical relation to short-term training gains is evaluated in Section V-D.

Both the local examples and the current adapter enter the score. Clients can therefore assign different priorities to a common target, and refreshes allow those priorities to evolve with the global model. Each profiling pass evaluates the candidate set, including targets not updated by that client in the preceding round. The next allocation is consequently informed by more than the client's previously active subset. The single-pass design supplies this information without a separate optimization run for every candidate configuration.

Shared positional calibration. The raw scores are supplemented by a structural preference over candidate positions. Prior partial-LoRA work reports favorable performance–resource trade-offs for deeper adaptation in its studied settings [32]. We implement a multiplicative factor:

$$\widetilde{g}_{i,j}^k = g_{i,j}^k (1 + d_j)^\rho, \tag{16}$$

where $d_j = (j-1)/(L-1)$ is the normalized position in the ordered candidate set. The evaluated schedule is $\rho = 1 + 1.5\mathbb{I}_{\text{pair}} + \eta$, where $\mathbb{I}_{\text{pair}}$ indicates a sentence-pair task and $\eta = 0, 1, 2$ corresponds to IID, ordinary non-IID, and severe non-IID settings. The schedule is fixed by the configuration, while the client-dependent component remains $g_{i,j}^k$.

The common multiplier can change a client's ranking but does not replace its data-dependent evidence or enforce a common mask. It is an auxiliary preference, distinct from the decision to permit individual target selection. The controlled granularity study holds it fixed within every matrix–layer pair. Section V-E separately evaluates the end-to-end effect of removing it.

Configuration utility and refresh. Server coordination compares configurations proposed by different clients. The calibrated scores therefore use a common normalization scale:

$$G_{\max}^k = \max_{\substack{h \in S_k \\ 1 \le j \le L}} \widetilde{g}_{h,j}^k, \qquad v_{i,j}^k = \frac{\widetilde{g}_{i,j}^k}{\max\{G_{\max}^k, \delta\}} \in [0,1], \tag{17}$$

where $\delta > 0$ prevents division by zero. A common divisor retains relative calibrated magnitudes across clients and matrices and sets the utility scale in the server's utility–latency objective. The assignment utility is $V_i^k(\mathbf{m}_i^k) = \sum_{j=1}^L m_{i,j}^k v_{i,j}^k$. This additive score supplies a tractable selection objective; it does not require the full training loss to decompose into independent matrix losses. Local evidence, the positional preference, and the common scale have separate roles in constructing that objective.

Profiles are cached between designated refresh rounds and recomputed when missing or due for refresh. Reuse avoids an additional backward pass at every allocation decision; refreshing reconnects the scores to the current adapter. Raw examples and profiling gradients remain local, while coordination uses matrix scores and configuration summaries. Section V-D

evaluates the ranking information supplied by the score, and Section V-E distinguishes scoring-source, granularity, and calibration effects within the complete training pipeline.

C. Resource-Feasible Matrix Allocation

For a fixed round k, superscripts are omitted from configuration attributes and scheduling variables when unambiguous. Each feasible configuration κ generated by client i is represented as

$$\kappa = (V_{i\kappa}, c_{i\kappa}, T_{i\kappa}, M_{i\kappa}, \mathbf{m}_{i\kappa}),$$

where $V_{i\kappa}$, $c_{i\kappa}$, $T_{i\kappa}$, $M_{i\kappa}$, and $\mathbf{m}_{i\kappa}$ denote the profiled adaptation utility, normalized matrix-equivalent cost, estimated latency, estimated training-memory consumption, and binary target-matrix assignment, respectively. Each client uploads a compact configuration menu $\mathcal{K}_i^k$.

Local configurations. Under the adopted memory model, feasibility depends on the selected-matrix count and the earliest selected position through the retained-activation term. For each count c, the client therefore searches over feasible earliest positions and retains a configuration with the largest profiled utility. Let $Q_{i,e}^k(t)$ denote the maximum utility of selecting t matrices from the suffix $\{e, \dots, L\}$. Its recursion and the utility for configurations whose earliest selected position is e are: $Q_{i,e}^k(0) = 0$ and $Q_{i,L+1}^k(t > 0) = -\infty$.

$$\begin{aligned} Q_{i,e}^k(t) &= \max\left\{Q_{i,e+1}^k(t), v_{i,e}^k + Q_{i,e+1}^k(t-1)\right\}, \quad t \geq 1, \\ \Phi_{i,e}^k(c) &= v_{i,e}^k + Q_{i,e+1}^k(c-1). \end{aligned} \tag{18}$$

Only configurations satisfying the matrix-count, memory, and latency constraints are retained. Under the current count-based latency model, configurations with the same cost consume the same server budget and have the same latency; retaining the highest-utility feasible configuration at each cost therefore suffices for subsequent coordination.

Server coordination. The server enumerates the distinct feasible latency thresholds $\tau \leq T_{\max}$. For each threshold, it removes configurations exceeding τ and solves the remaining multiple-choice knapsack problem, choosing at most one configuration per client. With $H_i(w)$ denoting the largest utility attainable from the first i client menus at budget w, the recursion is:

$$H_i(w) = \max_{\kappa \in \mathcal{K}_i^k(\tau) \cup \{\varnothing\} : c_{i\kappa} \leq w} \left\{H_{i-1}(w - c_{i\kappa}) + V_{i\kappa}\right\}, \tag{19}$$

Here $\mathcal{K}_i^k(\tau)$ is the menu after latency filtering, $\varnothing$ is the zero-utility inactive choice with zero cost, and $H_0(w) = 0$.

The server selects the threshold and configuration assignment with the largest total utility minus $\lambda\tau$. This procedure optimizes the stated profiled objective; its role is to realize client-conditioned selection under the resource model. Algorithm 1 summarizes the complete training round.

Algorithm 1 FedMATRIX-LoRA in communication round k

Require: Global adapter θ^k, candidate matrix set $\mathcal{A}$, candidate clients S_k, budget constraint C^k, latency bound $T_{\max}$

Client-conditioned matrix profiling and allocation:
for all $i \in S_k$ **do**
  if profiling cache is unavailable or refresh is required **then**
    Insert LoRA modules on candidate matrices $\mathcal{A}$
    Compute matrix importance scores $g_{i,j}^k$ using one local mini-batch
    Apply position-aware calibration to obtain $\widetilde{g}_{i,j}^k$
  else
    Reuse cached matrix importance scores
  end if
  Normalize matrix utilities to obtain $v_{i,j}^k$
  Generate feasible configuration menu $\mathcal{K}_i^k$ via suffix dynamic programming
end for

Resource-feasible server coordination:
Initialize best objective value $U^* \leftarrow -\infty$
for all distinct feasible latency thresholds $\tau \leq T_{\max}$ **do**
  Remove configurations satisfying $T_{i\kappa} > \tau$
  Solve MCKP using dynamic programming under budget constraint C^k
  Compute objective value $\sum_i \sum_\kappa x_{i\kappa} V_{i\kappa} - \lambda\tau$
  if current objective $> U^*$ **then**
    Update the best configuration assignment
  end if
end for

Local training and matrix-wise aggregation:
Dispatch selected matrix assignments and θ^k to clients
for all selected clients **do**
  Train LoRA parameters only on assigned matrices
end for
Perform matrix-wise aggregation to obtain θ^{k+1}
return updated global adapter θ^{k+1}

D. Local Training and Matrix-Wise Aggregation

After determining the optimal configuration assignment, the server dispatches the global adapter θ^k together with the selected matrix assignments to corresponding clients. Only selected LoRA parameters are updated locally. Task-specific trainable modules, if required by the downstream task, are optimized jointly with the selected LoRA parameters.

Since different clients may update different subsets of LoRA matrices, the aggregation process is performed independently for each trainable matrix. Let $\mathcal{U}_j^k$ denote the clients returning updates for matrix j, and let $\theta_{i,j}^{k+1}$ be the corresponding locally updated LoRA parameters from client i. The server performs matrix-wise client-uniform aggregation:

$$\theta_j^{k+1} = \begin{cases} |\mathcal{U}_j^k|^{-1} \displaystyle\sum_{i \in \mathcal{U}_j^k} \theta_{i,j}^{k+1}, & |\mathcal{U}_j^k| > 0, \\ \theta_j^k, & |\mathcal{U}_j^k| = 0. \end{cases} \tag{20}$$

The updated global adapter is used to initialize the next round. Because the updating client set can differ across target matrices, the aggregation averages only the clients contributing to each matrix and preserves the previous value when no update is available.

E. Convergence of Matrix-Wise Aggregation

We analyze the effective update induced by the matrix-wise aggregation rule. For this analysis, θ includes the LoRA parameters and any jointly trained shared task modules. Let P^k project onto the parameter blocks selected for update in round k, as determined before local training. For a common positive round scale γ, define the actual aggregated direction by $v^k = (\theta^k - \theta^{k+1})/\gamma$. Conditioning on the current model, profiling information, and selected configuration, denoted by $\mathcal{H}_k$, write

$$b^k = \mathbb{E}[v^k \mid \mathcal{H}_k] - P^k \nabla F(\theta^k), \tag{21}$$

$$\xi^k = v^k - \mathbb{E}[v^k \mid \mathcal{H}_k]. \tag{22}$$

Thus $\mathbb{E}[\xi^k \mid \mathcal{H}_k] = 0$, and the update is

$$\theta^{k+1} = \theta^k - \gamma\big(P^k \nabla F(\theta^k) + b^k + \xi^k\big). \tag{23}$$

The bias b^k accounts for selective aggregation and the difference between local optimizer updates and the selected global gradient. This representation does not replace the experimental AdamW optimizer with SGD.

Assumptions. Assume that F is β-smooth on the relevant update segments and bounded below by $F_{\inf}$. Suppose the effective update errors satisfy

$$\mathbb{E}\|b^k\|^2 \le B_{\mathrm{upd}}^2, \qquad \mathbb{E}\|\xi^k\|^2 \le S_{\mathrm{upd}}^2. \tag{24}$$

We additionally assume effective matrix coverage: for some $0 < \alpha_{\mathrm{cov}} \le 1$ and $\varepsilon_{\mathrm{cov},k} \ge 0$,

$$\mathbb{E}\|P^k \nabla F(\theta^k)\|^2 \ge \alpha_{\mathrm{cov}} \mathbb{E}\|\nabla F(\theta^k)\|^2 - \varepsilon_{\mathrm{cov},k}. \tag{25}$$

This condition quantifies the global gradient energy captured by the selected blocks.

Theorem 1 (Expected stationarity)**.** *Under the stated assumptions, for $0 < \gamma \le 1/\beta$ and K rounds,*

$$\frac{1}{K}\sum_{k=0}^{K-1} \mathbb{E}\|\nabla F(\theta^k)\|^2 \le \frac{2D_0}{\alpha_{\mathrm{cov}}\gamma K} + \frac{B_{\mathrm{upd}}^2 + \beta\gamma S_{\mathrm{upd}}^2 + \bar{\varepsilon}_{\mathrm{cov}}}{\alpha_{\mathrm{cov}}}, \tag{26}$$

where $D_0 = F(\theta^0) - F_{\inf}$ for a fixed initialization and $\bar{\varepsilon}_{\mathrm{cov}} = K^{-1}\sum_k \varepsilon_{\mathrm{cov},k}$.

For a fixed horizon, setting $\gamma = c/\sqrt{K} \le 1/\beta$ yields an $O(K^{-1/2})$ optimization and noise term when the error bounds and coverage constant are uniform across the analyzed runs. The residual is governed by effective-update bias and uncovered gradient energy. The result characterizes average stationarity, rather than optimal test accuracy.

The contribution of client selection can be made explicit. Let $n_j = |\mathcal{U}_j| > 0$, $g_{i,j} = \nabla_j F_i(\theta)$, $g_j = N^{-1}\sum_i g_{i,j}$, and $\zeta_j^2 = N^{-1}\sum_i \|g_{i,j} - g_j\|^2$.

Lemma 1 (Matrix-wise selection bias)**.** *For any updating-client set $\mathcal{U}_j$,*

$$\left\| \frac{1}{n_j}\sum_{i\in\mathcal{U}_j} g_{i,j} - g_j \right\|^2 \le \left(\frac{N}{n_j} - 1\right)\zeta_j^2. \tag{27}$$

The bound relates aggregation bias to participation and gradient heterogeneity at each target matrix. Proofs are provided in Appendix A.

V. Experiments

We evaluate the complete framework on the main benchmark settings and use controlled studies to distinguish selection granularity, scoring reliability, and component effects. Resource-efficiency comparisons use the stated analytical client profiles.

A. Evaluation Setup

We evaluate image classification on CIFAR100 [33], language understanding on MNLI, QNLI, QQP, and SST-2 from GLUE [34], and dialogue summarization on SAMSum [35].

Table I gives the backbones, partitions, rounds, and rank-8 matrix-cost budgets; each round has ten clients. Classification uses equal random IID partitions or Dirichlet non-IID partitions with $\alpha = 1.0$ or 0.1. SAMSum uses contiguous length-sorted shards for severe skew and randomly assigned length-sorted shards for mild skew.

Federated runs use NVIDIA A800-SXM4-80GB GPUs. Table II gives the analytical client resource profiles and training settings. The main comparisons use seed 2024 with shared partitions and resource draws. The additional scoring and ablation studies report their seed sets and data splits separately. Cumulative training cost $\overline{C}^K = \sum_{k=1}^K \sum_i c_i(\mathbf{m}_i^k)$ excludes profiling. Elapsed-time curves accumulate the analytical latency in Eq. (8), not end-to-end wall-clock time.

We report final and best Accuracy for classification and ROUGE-L for SAMSum, without averaging the two metrics.

We compare FedMATRIX-LoRA with representative baselines, including homogeneous LoRA training (FedAvg-LoRA) [3], [5], uniform matrix allocation (Uniform), layer-wise allocation (Fed-HeLLo) [8], layer-group heuristic allocation (MS), heterogeneous-rank allocation (LEGEND [32] and HETLoRA-style [6]), and joint quantization/rank allocation (FAH-QLoRA-style) [7]. These baselines represent different adaptation granularities and resource-allocation strategies, enabling a comprehensive comparison with our client-aware matrix scheduling. For a fair comparison, all methods use the same backbone models, data partitions, communication rounds, local training settings, and evaluation protocol.

B. Task Performance and Resource Efficiency

Fig. 3 compares the best observed task metric across 14 evaluation settings. As shown in Fig. 3, FedMATRIX-LoRA consistently ranks first across all CIFAR100, GLUE, and SAMSum settings, covering both IID and heterogeneous data partitions. Compared with heterogeneous-rank and quantization-based baselines, FedMATRIX-LoRA also delivers substantially higher peak performance. For example, on MNLI IID, HETLoRA-style and FAH-QLoRA-style achieve 0.796 and 0.808, respectively, whereas FedMATRIX-LoRA reaches 0.880. On CIFAR100 IID, the corresponding accuracies are 0.806, 0.810, and 0.900, showing the performance of the complete framework under the reported evaluation protocol.

TABLE I

EVALUATION SETTINGS. NON-IID x: DIRICHLET $\alpha = x$; LEN-M/S: MILD/SEVERE LENGTH SKEW; SLASH-SEPARATED BUDGETS FOLLOW PARTITION ORDER.

Dataset	Task	Backbone	Partitions	Rounds	Cum. budget	Metric
CIFAR100	Image classification	ViT-base [2]	IID, Non-IID 1.0/0.1	180	7,200/12,000	Accuracy
MNLI	Language inference	DeBERTa-v3-large [36]	IID, Non-IID 1.0	50	9,500	Accuracy
QNLI	Sentence-pair classification	RoBERTa-base [37]	IID, Non-IID 1.0	80	4,800/7,200	Accuracy
QQP	Paraphrase classification	DeBERTa-v3-large [36]	IID, Non-IID 1.0	50	9,500	Accuracy
SST-2	Sentiment classification	RoBERTa-base [37]	IID, Non-IID 1.0	80	7,200	Accuracy
SAMSum	Dialogue summarization	OPT-1.3B [1]	IID, Len-M, Len-S	40	10,000	Rouge-L




Fig. 3. Best task metric across 14 settings. Boxes mark row maxima; SAMSum uses Rouge-L and all other rows Accuracy.

TABLE II

SYSTEM AND TRAINING PROFILE.

Control	Reported configuration
Clients	10
Training-memory budget	40/25/15 GB; ratio 6:3:1
Compute factor	0.8–2.0 s per rank-8 matrix-equivalent
Bandwidth	5–50 MB/s
LoRA rank / profiling	8 / one local mini-batch
Local training cap	one epoch, at most 50 mini-batch steps
Optimizer	AdamW
Batch size / learning rate	1–32 / 10^{-5}–10^{-4}
Default latency cap	200 s per round

TABLE III

RESOURCES REQUIRED TO MATCH EACH STRONGEST BASELINE'S PEAK ACCURACY; POSITIVE SAVINGS FAVOR FEDMATRIX-LORA.

Scenario	Ref.	Target	$\Delta\overline{C}$ (%)	ΔT (%)
CIFAR / Non-IID 0.1	FAH-style	.746	+53.9	+59.4
CIFAR / Non-IID 1.0	Uniform	.882	+42.9	+42.4
CIFAR / IID	Uniform	.886	+54.4	+48.3
MNLI / Non-IID 1.0	LEGEND	.854	+5.6	+27.7
MNLI / IID	MS	.840	+33.2	+42.3
QNLI / Non-IID 1.0	FedAvg	.762	+0.7	+3.2
QNLI / IID	FedAvg	.758	+17.4	+3.2
QQP / Non-IID 1.0	LEGEND	.862	+14.9	+21.7
QQP / IID	LEGEND	.868	+41.3	+44.2
SST-2 / Non-IID 1.0	FedAvg	.902	+44.4	+45.2
SST-2 / IID	HET-style	.930	+47.8	+38.5

The budget–quality trajectories in Fig. 4 characterize the performance obtained as the cumulative matrix-equivalent cost increases. Together with the matched-target comparison in Table III, they quantify the resource trade-off of the complete framework.

Figure 5 reports the corresponding trajectories against cumulative modeled latency under the same analytical client profiles. The matched-target results in Table III summarize the modeled-time savings; these values are distinct from end-to-end measured runtime.

We additionally compare the resources required to reach the peak classification accuracy. Table III reports the cumulative-cost and modeled-time savings ($\Delta\overline{C}$ and ΔT) of FedMATRIX-LoRA relative to the least-resource baseline reaching the same target. Across all 11 classification scenarios, FedMATRIX-LoRA uses fewer resources, with median savings of 41.3% in cumulative budget and 42.3% in modeled elapsed time, demonstrating consistently higher resource efficiency across diverse workloads.

C. Controlled Study of Selection Granularity

The study in Fig. 1 isolates the trainable-subset decision from the choice of scoring data. We use CIFAR100/ViT-base with 36 Q/K/V candidates, five clients, IID and Dirichlet-$1.0/0.1$ partitions, and seeds 2024–2026. An independent server-proxy




Fig. 4. Budget–quality trajectories for 11 classification scenarios; FedMATRIX-LoRA is emphasized.




Fig. 5. Modeled-time–quality trajectories for all 11 classification scenarios under the same analytical client profiles as Fig. 4.

pool and a warm-up split are reserved from the training partition before client data are formed. Each client holds out 100 examples for validation. Local profiling uses 16 client-training examples; Proxy averages five disjoint 16-example proxy batches. The two checkpoints are adapter initialization and the result of 100 warm-up steps on the disjoint reserve, not two federated communication rounds.

For each client, checkpoint, and source, the matrix selector maximizes the profiled score over feasible 12-target subsets. The layer selector evaluates all four-block combinations, with Q/K/V tied within each selected block. Both use the same source scores, depth factor, resource limits, and rank eight; the LoRA and jointly trained classifier parameter counts match. All 360 method records are feasible under the adopted resource model. Unselected adapters remain in the forward model but are frozen, and each configuration starts from the same validation loss. The 20-step AdamW runs use learning rate 10^{-3}, identical data order within each pair, and controlled random states. This protocol measures adaptation from matched starting functions rather than the memory benefit of removing adapters.

The matrix–layer differences are averaged over five clients within each seed, then summarized over three seeds. All 12 setting-level means are positive; 35 of 36 within-seed paired means and 161 of 180 client-level pairs favor matrix-level selection. The full numerical summary appears in Appendix B. Because improvements are observed under both scoring sources, the study supports relaxing whole-layer binding without requiring local scores to dominate proxy scores. Depth calibration follows the same partition-specific schedule as the method and is held fixed within each pair.

D. Scoring Reliability

We next examine whether the additive utility supplies useful ranking information for configurations beyond the selected matrix–layer pair. At each client and checkpoint of the CIFAR100 study, we evaluate the original pool of 12 distinct feasible configurations, including score-guided and random subsets. Every configuration uses 12 rank-8 targets, the same training length, and a matched starting adapter. The outcome is its pre-training minus post-training loss on the held-out local examples. The layer configurations added for the granularity comparison are not appended to this pool.

Spearman correlation is computed separately within each client–checkpoint pool for raw and depth-calibrated scores. We average the five client coefficients within each seed before reporting the three-seed mean and sample standard deviation. The statistics use the paired-random-state outcomes; configuration identities and score values remain unchanged.

The six setting-level mean correlations for the calibrated score range from 0.657 to 0.876; 90 of 90 client–checkpoint coefficients are positive. The positive setting-level associations support using the profiled utility to prioritize configurations in this controlled protocol. Table IV reports raw and calibrated scores against the same outcomes, separating the informativeness of the gradient signal from the effect of the positional factor. This experiment concerns short-horizon configuration ranking; the following ablation evaluates the designs within full federated training.




Fig. 6. Final and best validation accuracy across three seeds for four ablation variants. Error bars show standard deviation; all variants consume the same cumulative matrix budget.

TABLE IV
WITHIN-CLIENT CONFIGURATION-RANKING RELIABILITY. ENTRIES REPORT THE THREE-SEED MEAN ± SAMPLE STANDARD DEVIATION OF CLIENT-AVERAGED SPEARMAN COEFFICIENTS. WARM-UP DENOTES THE SHARED 100-STEP CHECKPOINT.

Partition	State	Raw	Calibrated
IID	Initial	0.688 ± 0.114	0.746 ± 0.067
IID	Warm-up	0.595 ± 0.094	0.657 ± 0.070
Dir. 1.0	Initial	0.792 ± 0.012	0.841 ± 0.042
Dir. 1.0	Warm-up	0.556 ± 0.141	0.664 ± 0.136
Dir. 0.1	Initial	0.885 ± 0.028	0.772 ± 0.028
Dir. 0.1	Warm-up	0.801 ± 0.023	0.876 ± 0.036

TABLE V
SST-2 COMPONENT ABLATION AT A CUMULATIVE MATRIX-EQUIVALENT BUDGET OF 7,200. VALIDATION ACCURACY IS REPORTED IN PERCENT AS MEAN ± SAMPLE STANDARD DEVIATION OVER THREE SEEDS. BEST DENOTES THE PEAK WITHIN EACH RUN. BOLD MARKS THE LARGEST MEAN IN EACH METRIC COLUMN.

Variant	Final Accuracy	Best Accuracy
Full	$\mathbf{90.60} \pm 0.72$	90.87 ± 0.50
Server-Proxy	90.47 ± 0.81	90.80 ± 0.87
Layer-Level	90.07 ± 1.33	90.73 ± 0.42
No-Depth	90.47 ± 0.61	$\mathbf{90.93} \pm 0.42$

E. Ablation of Matrix-Level Adaptation

We isolate three components using SST-2/RoBERTa-base with a Dirichlet-1.0 partition. Full is compared with Server-Proxy, which replaces local scores by a shared score computed on a reserved training-only proxy set; Layer-Level, which retains local scoring but ties Q/K/V choices within each block; and No-Depth, which removes only the positional multiplier. All variants use the same private-data and proxy splits within each seed, rank eight, local optimizer settings, candidate-client protocol, resource limits, and 80-round horizon. Their actual selected clients and target subsets remain outcomes of allocation. The three seeds are 2024–2026, and each run consumes a cumulative matrix-equivalent budget of 7,200. This controlled study has its own proxy reservation and is reported separately from the historical main comparison.

Table V reports both final and best Accuracy, and Fig. 6 visualizes their variation across seeds. Full attains the highest final mean, exceeding Server-Proxy, Layer-Level, and No-Depth by 0.13, 0.53, and 0.13 percentage points, respectively. The largest final-mean change in this setting occurs when whole-layer binding is imposed, complementing the short-horizon granularity study. The differences are modest relative to run-to-run variation. Local and proxy-based assessment produce close observed means, while No-Depth achieves the slightly higher best mean of 90.93%. The ablation thus distinguishes the target-granularity contribution from the smaller endpoint effects of scoring source and calibration, rather than attributing the complete framework's main-benchmark gains to any single component.

VI. CONCLUSION

FedMATRIX-LoRA treats individual LoRA target projections as selectable adaptation units under heterogeneous client resources. Its motivating controlled study shows larger short-term gains from matrix-level selection than from whole-layer binding across the tested setting means, using either local or server-proxy scores. The framework evaluates priorities on local data, constructs feasible configurations, and coordinates their execution under a shared budget before matrix-wise aggregation. A conditional analysis relates the resulting selective updates to effective-update bias and matrix coverage. The main benchmarks and controlled ablations assess complementary aspects of this design: the complete framework's performance and resource trade-offs, and the effects of the scoring and allocation mechanisms. Together, these results motivate importance-guided target selection as a practical dimension of resource-constrained federated adaptation.

APPENDIX A
PROOFS FOR MATRIX-WISE AGGREGATION

Proof of Theorem 1. Condition on $\mathcal{H}_k$ and set $a = P^k \nabla F(\theta^k)$ and $\bar{v} = \mathbb{E}[v^k \mid \mathcal{H}_k] = a + b^k$. Because the update is supported

TABLE VI
COMPLETE MATRIX-MINUS-LAYER DIFFERENCES IN 20-STEP HELD-OUT VALIDATION-LOSS REDUCTION. ENTRIES ARE MEAN ± SAMPLE STANDARD DEVIATION OVER THREE WITHIN-SEED CLIENT MEANS.

Partition	Checkpoint	Local scores	Proxy scores
IID	Initial	$+0.00219 \pm 0.00140$	$+0.00191 \pm 0.00125$
IID	Warm-up	$+0.00669 \pm 0.00319$	$+0.00582 \pm 0.00591$
Dir. 1.0	Initial	$+0.01328 \pm 0.00211$	$+0.01335 \pm 0.00335$
Dir. 1.0	Warm-up	$+0.01411 \pm 0.00179$	$+0.01130 \pm 0.00330$
Dir. 0.1	Initial	$+0.13752 \pm 0.01708$	$+0.13907 \pm 0.01669$
Dir. 0.1	Warm-up	$+0.03412 \pm 0.00757$	$+0.02726 \pm 0.01002$

on P^k, smoothness gives

$$\mathbb{E}[F(\theta^{k+1}) \mid \mathcal{H}_k] \le F(\theta^k) - \gamma\langle a, \bar{v}\rangle + \frac{\beta\gamma^2}{2}\left(\|\bar{v}\|^2 + \mathbb{E}[\|\xi^k\|^2 \mid \mathcal{H}_k]\right). \tag{28}$$

Use $2\langle a, \bar{v}\rangle = \|a\|^2 + \|\bar{v}\|^2 - \|b^k\|^2$ and $\gamma \le 1/\beta$ to discard the nonpositive term $-\gamma(1-\beta\gamma)\|\bar{v}\|^2/2$. Taking total expectations yields

$$\mathbb{E}F(\theta^{k+1}) \le \mathbb{E}F(\theta^k) - \frac{\gamma}{2}\mathbb{E}\|P^k\nabla F(\theta^k)\|^2 + \frac{\gamma}{2}B_{\mathrm{upd}}^2 + \frac{\beta\gamma^2}{2}S_{\mathrm{upd}}^2. \tag{29}$$

Summing over k telescopes the loss terms. The lower bound on F gives

$$\frac{1}{K}\sum_k \mathbb{E}\|P^k\nabla F(\theta^k)\|^2 \le \frac{2D_0}{\gamma K} + B_{\mathrm{upd}}^2 + \beta\gamma S_{\mathrm{upd}}^2. \tag{30}$$

Apply the coverage condition and divide by α_{cov}. □

Proof of Lemma 1. Let $d_i = g_{i,j} - g_j$ and $w_i = \mathbf{1}\{i \in \mathcal{U}_j\}/n_j$. Since $\sum_i d_i = 0$, the selection bias equals $\sum_i (w_i - 1/N)d_i$. Cauchy–Schwarz gives

$$\left\|\sum_i (w_i - 1/N)d_i\right\|^2 \le \sum_i (w_i - 1/N)^2 \sum_i \|d_i\|^2 \tag{31}$$

$$= (1/n_j - 1/N)N\zeta_j^2, \tag{32}$$

which is the claimed bound. For the full effective bias, define the remaining local-update discrepancy as $r = b - s$, with zero selection-bias blocks when no client updates a block. Then $\|b\|^2 \le 2\|s\|^2 + 2\|r\|^2$. The latter term includes local drift, optimizer effects, and any local-model mismatch; the selection lemma alone does not bound it. □

APPENDIX B
COMPLETE CONTROLLED-STUDY RESULTS

Table VI lists every partition–checkpoint–source condition from the matched-budget granularity study. Each entry first averages the paired differences across five clients within a seed and then reports their three-seed mean and sample standard deviation. Initialization and the 100-step warm-up checkpoint are distinguished explicitly. These are loss differences, not Accuracy percentage points.

APPENDIX C
SCORING-SOURCE CONTROL

The original scoring-source comparison is summarized separately from the granularity motivation. Local evaluates each client's data; Local-Mean averages the five raw client-score vectors; Proxy averages five disjoint server-proxy batches. Local uses 16 examples per client, and Proxy uses 80 in total. The same calibration, fixed matrix count, training length, and held-out evaluation protocol are used. Table VII reports paired Local-minus-comparator loss-reduction differences after the same random-state correction used for the scoring study. Positive and negative differences are retained. The main motivation is based on matrix–layer comparisons within each source; this table characterizes the complementary comparison between sources.

TABLE VII
COMPLETE SCORING-SOURCE CONTROL AFTER PAIRED-RANDOM-STATE CORRECTION. VALUES ARE LOCAL-MINUS-COMPARATOR DIFFERENCES IN HELD-OUT VALIDATION-LOSS REDUCTION, WITH THREE-SEED SAMPLE STANDARD DEVIATIONS.

Partition	State	Local minus Proxy	Local minus Local-Mean
IID	Initial	-0.00011 ± 0.00038	-0.00011 ± 0.00038
IID	Warm-up	-0.00125 ± 0.00274	-0.00243 ± 0.00338
Dir. 1.0	Initial	-0.00040 ± 0.00076	-0.00029 ± 0.00056
Dir. 1.0	Warm-up	-0.00090 ± 0.00122	-0.00028 ± 0.00068
Dir. 0.1	Initial	-0.00440 ± 0.00467	-0.00049 ± 0.00816
Dir. 0.1	Warm-up	-0.00050 ± 0.00015	-0.00141 ± 0.00133

REFERENCES

[1] S. Zhang *et al.*, "OPT: Open pre-trained transformer language models," *arXiv preprint arXiv:2205.01068*, 2022.

[2] A. Dosovitskiy *et al.*, "An image is worth 16x16 words: Transformers for image recognition at scale," in *Proceedings of the International Conference on Learning Representations (ICLR)*, 2021.

[3] B. McMahan, E. Moore, D. Ramage, S. Hampson, and B. A. y Arcas, "Communication-efficient learning of deep networks from decentralized data," in *Proceedings of the 20th International Conference on Artificial Intelligence and Statistics (AISTATS)*, 2017, pp. 1273–1282.

[4] P. Kairouz *et al.*, "Advances and open problems in federated learning," *Foundations and Trends in Machine Learning*, vol. 14, nos. 1–2, pp. 1–210, 2021, doi: 10.1561/2200000083.

[5] E. J. Hu, Y. Shen, P. Wallis, Z. Allen-Zhu, Y. Li, S. Wang, L. Wang, and W. Chen, "LoRA: Low-rank adaptation of large language models," in *Proceedings of the International Conference on Learning Representations (ICLR)*, 2022.

[6] Y. J. Cho, L. Liu, Z. Xu, A. Fahrezi, and G. Joshi, "Heterogeneous LoRA for federated fine-tuning of on-device foundation models," in *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, 2024, pp. 12903–12913, doi: 10.18653/v1/2024.emnlp-main.717.

[7] Z. Gao, Z. Zhang, Y. Guo, and Y. Gong, "Federated adaptive fine-tuning of large language models with heterogeneous quantization and LoRA," in *Proceedings of IEEE Conference on Computer Communications (INFOCOM)*, 2025, pp. 1–10, doi: 10.1109/INFOCOM55648.2025.11044641.

[8] Z. Zhang, P. Liu, J. Xu, and R. Hu, "Fed-HeLLo: Efficient federated foundation model fine-tuning with heterogeneous LoRA allocation," *IEEE Transactions on Neural Networks and Learning Systems*, vol. 36, no. 10, pp. 17556–17569, 2025, doi: 10.1109/TNNLS.2025.3580495.

[9] Q. Li, B. He, and D. Song, "Model-contrastive federated learning," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2021, pp. 10713–10722, doi: 10.1109/CVPR46437.2021.01057.

[10] T. Dettmers, A. Pagnoni, A. Holtzman, and L. Zettlemoyer, "QLoRA: Efficient finetuning of quantized LLMs," in *Advances in Neural Information Processing Systems*, vol. 36, 2023, pp. 10088–10115.

[11] N. Houlsby, A. Giurgiu, S. Jastrzebski, B. Morrone, Q. de Laroussilhe, A. Gesmundo, M. Attariyan, and S. Gelly, "Parameter-efficient transfer learning for NLP," in *Proceedings of the 36th International Conference on Machine Learning*, vol. 97, 2019, pp. 2790–2799.

[12] X. L. Li and P. Liang, "Prefix-tuning: Optimizing continuous prompts for generation," in *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, 2021, pp. 4582–4597, doi: 10.18653/v1/2021.acl-long.353.

[13] Z. Zhang, Y. Yang, Y. Dai, Q. Wang, Y. Yu, L. Qu, and Z. Xu, "FedPETuning: When federated learning meets the parameter-efficient tuning methods of pre-trained language models," in *Findings of the Association for Computational Linguistics: ACL 2023*, 2023, pp. 9963–9977, doi: 10.18653/v1/2023.findings-acl.632.

[14] J. Chen, W. Xu, S. Guo, J. Wang, J. Zhang, and H. Wang, "FedTune: A deep dive into efficient federated fine-tuning with pre-trained transformers," *arXiv preprint arXiv:2211.08025*, 2022.

[15] T. Che, J. Liu, Y. Zhou, J. Ren, J. Zhou, V. Sheng, H. Dai, and D. Dou, "Federated learning of large language models with parameter-efficient prompt tuning and adaptive optimization," in *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, 2023, pp. 7871–7888, doi: 10.18653/v1/2023.emnlp-main.488.

[16] R. Singhal, K. Ponkshe, and P. Vepakomma, "FedEx-LoRA: Exact aggregation for federated and efficient fine-tuning of large language models," in *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, 2025, pp. 1316–1336, doi: 10.18653/v1/2025.acl-long.67.

[17] J. Bian, L. Wang, L. Zhang, and J. Xu, "LoRA-FAIR: Federated LoRA fine-tuning with aggregation and initialization refinement," in *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, 2025, pp. 3737–3746.

[18] Z. Li, B. Xu, X. Shu, J. Zhang, Y. Yao, G.-S. Xie, and J. Tang, "Tensor-aggregated LoRA in federated fine-tuning," in *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, 2025, pp. 1058–1067.

[19] H. Wang, X. Wang, Y. Li, J. Chen, J. Zhang, N. Yan, K. He, and W. Wang, "Federated LoRA fine-tuning with pipelined error-mitigated aggregation and matrix-wise freezing," in *Findings of the Association for Computational Linguistics: ACL 2026*, 2026, pp. 5749–5762, doi: 10.18653/v1/2026.findings-acl.284.

[20] J. Bai, D. Chen, B. Qian, L. Yao, and Y. Li, "Federated fine-tuning of large language models under heterogeneous tasks and client resources," in *Advances in Neural Information Processing Systems*, vol. 37, 2024, pp. 14457–14483, doi: 10.52202/079017-0461.

[21] J. Koo, M. Jang, and J. Ok, "Towards robust and efficient federated low-rank adaptation with heterogeneous clients," in *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, 2025, pp. 416–429, doi: 10.18653/v1/2025.acl-long.19.

[22] X. Huang, Y. Hu, Y.-J. Gong, and X. Zhang, "GMFL: Efficient global masking for federated LLM fine-tuning," in *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, 2026, pp. 25293–25312, doi: 10.18653/v1/2026.acl-long.1160.

[23] H. Ban and K. Ji, "Rethinking parameter sharing for LLM fine-tuning with multiple LoRAs," in *Findings of the Association for Computational Linguistics: ACL 2026*, 2026, pp. 12843–12863, doi: 10.18653/v1/2026.findings-acl.625.

[24] E. Diao, J. Ding, and V. Tarokh, "HeteroFL: Computation and communication efficient federated learning for heterogeneous clients," in *Proceedings of the International Conference on Learning Representations (ICLR)*, 2021.

[25] S. Alam, L. Liu, M. Yan, and M. Zhang, "FedRolex: Model-heterogeneous federated learning with rolling sub-model extraction," in *Advances in Neural Information Processing Systems*, vol. 35, 2022, pp. 29677–29690.

[26] F. Lai, X. Zhu, H. V. Madhyastha, and M. Chowdhury, "Oort: Efficient federated learning via guided participant selection," in *Proceedings of the 15th USENIX Symposium on Operating Systems Design and Implementation (OSDI)*, 2021, pp. 19–35.

[27] J. Shin, Y. Li, Y. Liu, and S.-J. Lee, "FedBalancer: Data and pace control for efficient federated learning on heterogeneous clients," in *Proceedings of the 20th Annual International Conference on Mobile Systems, Applications and Services (MobiSys)*, 2022, pp. 436–449, doi: 10.1145/3498361.3538917.

[28] C. Li, X. Zeng, M. Zhang, and Z. Cao, "PyramidFL: A fine-grained client selection framework for efficient federated learning," in *Proceedings of the 28th Annual International Conference on Mobile Computing and Networking (MobiCom)*, 2022, pp. 158–171, doi: 10.1145/3495243.3517017.

[29] Y. G. Kim and C.-J. Wu, "AutoFL: Enabling heterogeneity-aware energy efficient federated learning," in *Proceedings of the 54th Annual IEEE/ACM International Symposium on Microarchitecture (MICRO)*, 2021, pp. 183–198, doi: 10.1145/3466752.3480129.

[30] B. Luo, X. Li, S. Wang, J. Huang, and L. Tassiulas, "Cost-effective federated learning in mobile edge networks," *IEEE Journal on Selected Areas in Communications*, vol. 39, no. 12, pp. 3606–3621, 2021, doi: 10.1109/JSAC.2021.3118436.

[31] J. Kirkpatrick *et al.*, "Overcoming catastrophic forgetting in neural networks," *Proceedings of the National Academy of Sciences of the United States of America*, vol. 114, no. 13, pp. 3521–3526, 2017, doi: 10.1073/pnas.1611835114.

[32] J. Liu, Y. Liao, H. Xu, Y. Xu, J. Liu, and C. Qian, "Adaptive parameter-efficient federated fine-tuning on heterogeneous devices," *IEEE Transactions on Mobile Computing*, vol. 24, no. 11, pp. 12533–12549, 2025, doi: 10.1109/TMC.2025.3586644.

[33] A. Krizhevsky, "Learning multiple layers of features from tiny images," Department of Computer Science, University of Toronto, Toronto, ON, Canada, Technical Report, 2009.

[34] A. Wang, A. Singh, J. Michael, F. Hill, O. Levy, and S. R. Bowman, "GLUE: A multi-task benchmark and analysis platform for natural language understanding," in *Proceedings of the International Conference on Learning Representations (ICLR)*, 2019.

[35] B. Gliwa, I. Mochol, M. Biesek, and A. Wawer, "SAMSum corpus: A human-annotated dialogue dataset for abstractive summarization," in *Proceedings of the 2nd Workshop on New Frontiers in Summarization*, 2019, pp. 70–79, doi: 10.18653/v1/D19-5409.

[36] P. He, X. Liu, J. Gao, and W. Chen, "DeBERTa: Decoding-enhanced BERT with disentangled attention," in *Proceedings of the International Conference on Learning Representations (ICLR)*, 2021.

[37] Y. Liu *et al.*, "RoBERTa: A robustly optimized BERT pretraining approach," *arXiv preprint arXiv:1907.11692*, 2019.

[38] Q. Zhang, M. Chen, A. Bukharin, N. Karampatziakis, P. He, Y. Cheng, W. Chen, and T. Zhao, "AdaLoRA: Adaptive budget allocation for parameter-efficient fine-tuning," *arXiv preprint arXiv:2303.10512*, version 2, 2023.

[39] Y.-L. Sung, V. Nair, and C. Raffel, "Training neural networks with fixed sparse masks," in *Advances in Neural Information Processing Systems*, vol. 34, 2021.

[40] Z. Zhang, R. Hu, P. Liu, and J. Xu, "Fed-pilot: Optimizing LoRA allocation for efficient federated fine-tuning with heterogeneous clients," *arXiv preprint arXiv:2410.10200*, version 2, 2025.