CS 566, Fall 2026
Introduction to Computer Vision
Prof. Mohit Gupta

*Mid-term Report*
*October 29, 2026*

# Temporal Anti-Aliasing for Single-Photon Reconstruction

Adrian Gottwein  Limo Kemei  Jack Chen  Ethan Shao

University of Wisconsin–Madison

Code: https://github.com/1immy/cs566-project  Webpage: https://1immy.github.io/cs566-project/




**Figure 1:** Reconstructions of burst 0 of `kitchen1` (300×304 crop). Naive averaging blurs the moving scene. Aligning to the first group of frames is sharp but offset from the ground truth. Aligning to the last group matches it, with visible photon noise. Default TAA, also with a last-group reference, is noisier still. Each result is scaled by one gain for display.

**Abstract**

*We investigate whether history-validation heuristics from temporal anti-aliasing (TAA), namely neighborhood clamping and motion-adaptive blending, can improve classical align-and-merge reconstruction of single-photon bursts. Both stages of our pipeline now run on real Single Photon Challenge data. Two early findings shape the rest of the project. First, the scene moves substantially* inside *a single burst. Second, the ground truth is at the pose of the* last *frames, so the choice of reference frame decides whether alignment helps at all. With the correct reference, block alignment improves on naive averaging by 2.5 to 4.4 dB PSNR on the bursts we tested, while our first TAA configuration is 1 to 4 dB worse than alignment alone. We report these results, the difficulties behind them, and the changes they imply for our plan.*

## 1. Introduction

A single-photon camera records a burst of binary frames, each reporting only whether a photon arrived at a pixel during a very short exposure. Averaging many frames recovers brightness, but if the scene or the camera moves during the burst, averaging blurs the result. Aligning the frames before merging removes the blur, at the price of a new failure mode: wrongly aligned content is merged into the output and appears as ghosting.

Real-time rendering faces a closely related problem. Temporal anti-aliasing (TAA) accumulates samples over consecutive frames, reprojects them to compensate for motion, and uses *history validation* to decide how much of the accumulated result to trust [1]. Two validation tools are central: neighborhood clamping, which restricts the history to the color range seen in the current frame [3], and adaptive blending, which lowers the weight of history when motion or disagreement is large [2]. Our project asks whether these tools carry over to single-photon bursts, where the samples are binary and far noisier than in rendering.

This report covers the first half of the project. We describe the pipeline and its current state (Sec. 2), present the first results on real data (Sec. 3), discuss the difficulties we met (Sec. 4), and list the changes to our proposal and the remaining plan (Sec. 5 and Sec. 6).

## 2. Progress

### 2.1. Pipeline overview

Figure 2 shows the pipeline. A loader reads a burst and splits it into groups of consecutive frames, be-





**Figure 2:** Schematic of the reconstruction pipeline. Green blocks are the components under study, blue blocks are infrastructure.

cause a single binary frame carries too little signal to align. Each group is averaged and aligned to a reference group. The warped history is then validated against the incoming group and merged. The four stages follow our fixed interfaces, so each team member can work on one stage independently.

### 2.2. Data and infrastructure

The dataset stores each burst as 1,024 binary frames of $800 \times 800$ RGB, bit-packed along the width. A full burst unpacks to about 2 GB, so our loader supports frame and crop selection directly on the packed array. A 1 MB sample is committed to the repository and a 10-scene slice (about 5 GB) is shared with the team. The full set stays on a private NAS and is used only for final runs. Work is tracked as GitHub issues against course milestones.

### 2.3. Alignment

Each group $g$ is averaged into a frame $\bar{x}_g$. The aligner estimates a motion field by coarse-to-fine $8 \times 8$ block matching on a three-level pyramid and warps $\bar{x}_g$ to the reference, leaving invalid pixels undefined outside the source. The same aligner is used by every method, so differences between methods are attributable to the merge stage. The naive and aligned baselines and a sample runner are covered by 14 unit tests.

### 2.4. History validation

Following the TAA formulation, we maintain a history $h$ with a per-pixel weight $W$ (the number of frame-equivalents it represents, initialized from the first group). Each warped group $\tilde{x}_g$ of $n$ frames is merged as a weighted mean in which the history is discounted by a per-pixel confidence $c \in (0, 1]$:

$$h' = \frac{c\,W\,\hat{h} + n\,\tilde{x}_g}{c\,W + n}, \qquad W' = c\,W + n, \tag{1}$$

where $\hat{h}$ is the history clamped, per channel, to the $3 \times 3$ neighborhood range of $\tilde{x}_g$ widened by a margin of 0.05. The confidence falls with the disagreement $\delta = \max_k |h_k - \hat{h}_k|$ (how far the history lies outside that range) and with the displacement $d$ in pixels reported by the aligner:

$$c = \frac{\exp(-\delta/0.1)}{1 + d/8}. \tag{2}$$

| PSNR (dB) | b0 | b1 | b10 |
|---|---|---|---|
| Naive average | 16.2 | 14.7 | 16.8 |
| Aligned, first-group ref. | 14.0 | 12.5 | 13.9 |
| Aligned, last-group ref. | **19.7** | **19.1** | **19.3** |
| Clamp only, last-group ref. | 19.7 | 18.5 | 19.3 |
| TAA (default), last-group ref. | 17.3 | 15.3 | 18.3 |

**Table 1:** Gain-matched PSNR on `kitchen1`, bursts 0, 1 and 10. Last-group reference results come from running the same code on the time-reversed burst.

Pixels with no valid observation keep their history and weight unchanged. Component switches recover the aligned baseline exactly, and the full suite of 44 tests passes. Synthetic experiments showed both helpful and harmful rejection regimes, which motivated testing on real data.

## 3. Current Results

### 3.1. Setup

All numbers use scene `kitchen1`, bursts 0, 1 and 10, a $300 \times 304$ central crop, all 1,024 frames, in groups of 64. The ground truth is much brighter than the photon average, with a least-squares gain of about 3 to 4 on these crops. We therefore multiply each reconstruction $\hat{y}$ by a single gain $g^\star$ before computing PSNR:

$$g^\star = \frac{\langle \hat{y}, y \rangle}{\langle \hat{y}, \hat{y} \rangle}. \tag{3}$$

This rule is preliminary and has not yet been fixed by our evaluation track. The results come from one scene and no held-out data, so they are indicative, not a benchmark.

### 3.2. Motion inside a burst

Phase correlation between 256-frame windows shows a mostly horizontal drift from the first to the last window of about 9, 20 and 2 px for the three bursts. The offset between the ground truth and the first window is 13, 25 and 2 px along $x$, and it falls to about 1 px or less at the last window. The ground truth is therefore the pose at the end of the burst, not the start.

### 3.3. Reconstruction quality

Table 1 lists the PSNR of each method. Aligning to the last group beats naive averaging by 2.5 to 4.4 dB. The fixed first-group reference used in our first runs is 2.2 to 2.9 dB *worse* than naive averaging, because it moves the output away from the ground-truth pose. The clamp alone is inert on two bursts at its default margin and costs 0.6 dB on the third. The full TAA configuration loses 1.0 to 3.8 dB against plain alignment, most on the fastest burst.

## 4. Difficulties

**Reference frame.** The ground-truth pose is the end of the burst. A fixed first-group reference, the natural default, makes alignment look harmful. We found this only after comparing against the ground truth at several time offsets.

**Noise versus motion.** Single binary frames cannot be aligned, so we align 64-frame groups. Photon noise in flat regions still produces apparent motion, which makes displacement an unreliable proxy for alignment error.

**TAA tuning.** Our confidence term lowers the history weight with displacement. Once alignment has compensated for the motion, this discards correct frames and raises noise.

**Intensity mismatch.** Photon averages and the ground-truth image differ in brightness response, so raw PSNR is misleading. A single rule must be applied to every method, and this decision is still open.

**Data format and memory.** Bursts are bit-packed and a full cube unpacks to about 2 GB, so we load by frame and crop and the team works from samples and a shared slice.

## 5. Changes to the Proposal

- **Alignment unit.** Alignment runs within a burst, on groups of frames, with the last group as reference.
- **Motion sweeps.** Real bursts already span roughly 2 to 20 px of motion, so the `visionsim` sweeps become optional and the motion study uses real bursts binned by measured speed.
- **Data size.** The average archive is about 2.7 GB (133 GB compressed in total), not 8.5 GB as proposed. We use a 10-scene shared slice and run final experiments on the full set.
- **Hypothesis.** The initial TAA result is negative: when alignment is accurate, displacement-based rejection hurts. We now plan a confidence based on alignment residual, and we will report the failure analysis either way.

## 6. Next Steps

We will fix the evaluation rule and add SSIM, then run all methods on a motion-binned scene set. We will replace the displacement term with a residual-based confidence and run ablations (clamp, blend, confidence) together with a failure analysis against motion speed. Experiments freeze on Nov. 30. The final presentation is on Dec. 8 and the project webpage is due Dec. 10.

## References

[1] L. Yang, S. Liu, M. Salvi. A survey of temporal antialiasing techniques. *Computer Graphics Forum*, 39(2), 2020.

[2] L. Yang, D. Nehab, P. V. Sander, P. Sitthi-amorn, J. Lawrence, H. Hoppe. Amortized supersampling. *ACM Trans. Graphics*, 28(5), 2009.

[3] B. Karis. High-quality temporal supersampling. SIGGRAPH Advances in Real-Time Rendering course, 2014.