



SMART CONTRACT AUDIT REPORT

for

1inch Aggregation (v6)



Prepared By: Xiaomi Huang

PeckShield
April 7, 2023

Document Properties

Client	1inch Protocol
Title	Smart Contract Audit Report
Target	1inch Aggregation
Version	1.0
Author	Xiaotao Wu
Auditors	Xiaotao Wu, Xuxian Jiang
Reviewed by	Patrick Lou
Approved by	Xuxian Jiang
Classification	Public

Version Info

Version	Date	Author(s)	Description
1.0	April 7, 2023	Xiaotao Wu	Final Release
1.0-rc	April 3, 2023	Xiaotao Wu	Release Candidate

Contact

For more information about this document and its contents, please contact PeckShield Inc.

Name	Xiaomi Huang
Phone	+86 183 5897 7782
Email	contact@peckshield.com

Contents

1	Introduction	4
1.1	About 1inch Aggregation	4
1.2	About PeckShield	5
1.3	Methodology	5
1.4	Disclaimer	7
2	Findings	9
2.1	Summary	9
2.2	Key Findings	10
3	Detailed Results	11
3.1	Accommodation of Non-ERC20-Compliant Tokens	11
4	Conclusion	14
	References	15

1 | Introduction

Given the opportunity to review the design document and related smart contract source code of the `1inch Aggregation (v6)` protocol, we outline in the report our systematic approach to evaluate potential security issues in the smart contract implementation, expose possible semantic inconsistencies between smart contract code and design document, and provide additional suggestions or recommendations for improvement. Our results show that the given version of smart contracts is well designed and engineered, though it can be further improved by addressing our suggestions. This document outlines our audit results.

1.1 About 1inch Aggregation

The `1inch Aggregation` protocol is a DeFi aggregator and a decentralized exchange with smart routing. The core protocol connects a large number of decentralized and centralized platforms in order to minimize price slippage and find the optimal trade for the users. The audited smart contracts are designed to create a universal exchange for tokens. Major changes within the scope are numerous gas optimization, the `Permit2` integration, as well as the `Curve` support. The basic information of the audited protocol is as follows:

Table 1.1: Basic Information of 1inch Aggregation

Item	Description
Name	1inch Protocol
Website	https://app.1inch.io/
Type	EVM Smart Contract
Platform	Solidity
Audit Method	Whitebox
Latest Audit Report	April 7, 2023

In the following, we show the Git repository of reviewed files and the commit hash value used in this audit.

- <https://github.com/1inch/1inch-contract.git> (1bdd5e8)

And here is the commit ID after fixes for the issue found in the audit have been checked in::

- <https://github.com/1inch/1inch-contract.git> (TBD)

1.2 About PeckShield

PeckShield Inc. [5] is a leading blockchain security company with the goal of elevating the security, privacy, and usability of current blockchain ecosystems by offering top-notch, industry-leading services and products (including the service of smart contract auditing). We are reachable at Telegram (<https://t.me/peckshield>), Twitter (<http://twitter.com/peckshield>), or Email (contact@peckshield.com).

Table 1.2: Vulnerability Severity Classification

Impact	High	Critical	High	Medium
	Medium	High	Medium	Low
	Low	Medium	Low	Low
		High	Medium	Low
		Likelihood		

1.3 Methodology

To standardize the evaluation, we define the following terminology based on the OWASP Risk Rating Methodology [4]:

- Likelihood represents how likely a particular vulnerability is to be uncovered and exploited in the wild;
- Impact measures the technical loss and business damage of a successful attack;
- Severity demonstrates the overall criticality of the risk.

Likelihood and impact are categorized into three ratings: *H*, *M* and *L*, i.e., *high*, *medium* and *low* respectively. Severity is determined by likelihood and impact and can be classified into four categories accordingly, i.e., *Critical*, *High*, *Medium*, *Low* shown in Table 1.2.

Table 1.3: The Full Audit Checklist

Category	Checklist Items
Basic Coding Bugs	Constructor Mismatch
	Ownership Takeover
	Redundant Fallback Function
	Overflows & Underflows
	Reentrancy
	Money-Giving Bug
	Blackhole
	Unauthorized Self-Destruct
	Revert DoS
	Unchecked External Call
	Gasless Send
	Send Instead Of Transfer
	Costly Loop
	(Unsafe) Use Of Untrusted Libraries
	(Unsafe) Use Of Predictable Variables
	Transaction Ordering Dependence
	Deprecated Uses
Semantic Consistency Checks	Semantic Consistency Checks
Advanced DeFi Scrutiny	Business Logics Review
	Functionality Checks
	Authentication Management
	Access Control & Authorization
	Oracle Security
	Digital Asset Escrow
	Kill-Switch Mechanism
	Operation Trails & Event Generation
	ERC20 Idiosyncrasies Handling
	Frontend-Contract Integration
	Deployment Consistency
	Holistic Risk Management
Additional Recommendations	Avoiding Use of Variadic Byte Array
	Using Fixed Compiler Version
	Making Visibility Level Explicit
	Making Type Inference Explicit
	Adhering To Function Declaration Strictly
	Following Other Best Practices

To evaluate the risk, we go through a checklist of items and each would be labeled with a severity category. For one check item, if our tool or analysis does not identify any issue, the contract is considered safe regarding the check item. For any discovered issue, we might further deploy contracts on our private testnet and run tests to confirm the findings. If necessary, we would additionally build a PoC to demonstrate the possibility of exploitation. The concrete list of check items is shown in Table 1.3.

In particular, we perform the audit according to the following procedure:

- Basic Coding Bugs: We first statically analyze given smart contracts with our proprietary static code analyzer for known coding bugs, and then manually verify (reject or confirm) all the issues found by our tool.
- Semantic Consistency Checks: We then manually check the logic of implemented smart contracts and compare with the description in the white paper.
- Advanced DeFi Scrutiny: We further review business logics, examine system operations, and place DeFi-related aspects under scrutiny to uncover possible pitfalls and/or bugs.
- Additional Recommendations: We also provide additional suggestions regarding the coding and development of smart contracts from the perspective of proven programming practices.

To better describe each issue we identified, we categorize the findings with Common Weakness Enumeration (CWE-699) [3], which is a community-developed list of software weakness types to better delineate and organize weaknesses around concepts frequently encountered in software development. Though some categories used in CWE-699 may not be relevant in smart contracts, we use the CWE categories in Table 1.4 to classify our findings. Moreover, in case there is an issue that may affect an active protocol that has been deployed, the public version of this report may omit such issue, but will be amended with full details right after the affected protocol is upgraded with respective fixes.

1.4 Disclaimer

Note that this security audit is not designed to replace functional tests required before any software release, and does not give any warranties on finding all possible security issues of the given smart contract(s) or blockchain software, i.e., the evaluation result does not guarantee the nonexistence of any further findings of security issues. As one audit-based assessment cannot be considered comprehensive, we always recommend proceeding with several independent audits and a public bug bounty program to ensure the security of smart contract(s). Last but not least, this security audit should not be used as investment advice.


Table 1.4: Common Weakness Enumeration (CWE) Classifications Used in This Audit

Category	Summary
Configuration	Weaknesses in this category are typically introduced during the configuration of the software.
Data Processing Issues	Weaknesses in this category are typically found in functionality that processes data.
Numeric Errors	Weaknesses in this category are related to improper calculation or conversion of numbers.
Security Features	Weaknesses in this category are concerned with topics like authentication, access control, confidentiality, cryptography, and privilege management. (Software security is not security software.)
Time and State	Weaknesses in this category are related to the improper management of time and state in an environment that supports simultaneous or near-simultaneous computation by multiple systems, processes, or threads.
Error Conditions, Return Values, Status Codes	Weaknesses in this category include weaknesses that occur if a function does not generate the correct return/status code, or if the application does not handle all possible return/status codes that could be generated by a function.
Resource Management	Weaknesses in this category are related to improper management of system resources.
Behavioral Issues	Weaknesses in this category are related to unexpected behaviors from code that an application uses.
Business Logic	Weaknesses in this category identify some of the underlying problems that commonly allow attackers to manipulate the business logic of an application. Errors in business logic can be devastating to an entire application.
Initialization and Cleanup	Weaknesses in this category occur in behaviors that are used for initialization and breakdown.
Arguments and Parameters	Weaknesses in this category are related to improper use of arguments or parameters within function calls.
Expression Issues	Weaknesses in this category are related to incorrectly written expressions within code.
Coding Practices	Weaknesses in this category are related to coding practices that are deemed unsafe and increase the chances that an exploitable vulnerability will be present in the application. They may not directly introduce a vulnerability, but indicate the product has not been carefully developed or maintained.

2 | Findings

2.1 Summary

Here is a summary of our findings after analyzing the implementation of the `1inch Aggregation (v6)` smart contracts. During the first phase of our audit, we study the smart contract source code and run our in-house static code analyzer through the codebase. The purpose here is to statically identify known coding bugs, and then manually verify (reject or confirm) issues reported by our tool. We further manually review business logic, examine system operations, and place DeFi-related aspects under scrutiny to uncover possible pitfalls and/or bugs.

Severity	# of Findings	
Critical	0	
High	0	
Medium	0	
Low	0	
Informational	1	
Total	1	

We have so far identified a potential issue for improvement: accommodate the possible idiosyncrasy about ERC20-related `approve()`. More information can be found in the next subsection, and its detailed discussions can be found in [Section 3](#).

2.2 Key Findings

Overall, the smart contract is well-designed and engineered, though the implementation can be improved by resolving the identified issue (shown in Table 2.1), including 1 informational recommendation.

Table 2.1: Key 1inch Aggregation Audit Findings

ID	Severity	Title	Category	Status
PVE-001	Informational	Accommodation of Non-ERC20-Compliant Tokens	Business Logic	Fixed

Besides recommending specific countermeasure to mitigate the issue, we also emphasize that it is always important to develop necessary risk-control mechanisms and make contingency plans, which may need to be exercised before the mainnet deployment. The risk-control mechanisms need to kick in at the very moment when the contracts are being deployed in mainnet. Please refer to Section 3 for details.



3 | Detailed Results

3.1 Accommodation of Non-ERC20-Compliant Tokens

- ID: PVE-002
- Severity: Informational
- Likelihood: N/A
- Impact: N/A
- Target: UnoswapRouter
- Category: Business Logic [2]
- CWE subcategory: CWE-841 [1]

Description

Though there is a standardized ERC-20 specification, many token contracts may not strictly follow the specification or have additional functionalities beyond the specification. In this section, we examine the `approve()` routine and analyze possible idiosyncrasies from current widely-used token contracts.

In particular, we use the popular stablecoin, i.e., USDT, as our example. We show the related code snippet below. On its entry of `approve()`, there is a requirement, i.e., `require(!((_value != 0) && (allowed[msg.sender][_spender] != 0)))`. This specific requirement essentially indicates the need of reducing the allowance to 0 first (by calling `approve(_spender, 0)`) if it is not, and then calling a second one to set the proper allowance. This requirement is in place to mitigate the known `approve()/transferFrom()` race condition (<https://github.com/ethereum/EIPs/issues/20#issuecomment-263524729>).

```

194  /**
195  * @dev Approve the passed address to spend the specified amount of tokens on behalf
      of msg.sender.
196  * @param _spender The address which will spend the funds.
197  * @param _value The amount of tokens to be spent.
198  */
199  function approve(address _spender, uint _value) public onlyPayloadSize(2 * 32) {

201      // To change the approve amount you first have to reduce the addresses'
202      // allowance to zero by calling 'approve(_spender, 0)' if it is not
203      // already 0 to mitigate the race condition described here:
204      // https://github.com/ethereum/EIPs/issues/20#issuecomment-263524729
205      require(!((_value != 0) && (allowed[msg.sender][_spender] != 0)));

```


[illegible]

Listing 3.2: LooksRareAggregator::approve()

Recommendation	Accommodate the above-mentioned idiosyncrasy about ERC20-related <code>approve()</code> .
-----------------------	---

Status This issue has been fixed in the following commits: 66955d8.

4 | Conclusion

In this audit, we have analyzed the design and implementation of the `1inch Aggregation (v6)` protocol. The `1inch Aggregation` protocol is a DeFi aggregator and a decentralized exchange with smart routing. The core protocol connects a large number of decentralized and centralized platforms in order to minimize price slippage and find the optimal trade for the users. The audited `1inch Aggregation (v6)` implements an upgrade for the old one and the major changes within the scope are numerous gas optimization, the `Permit2` integration, as well as the `Curve` support. The current code base is well structured and neatly organized. Those identified issues are promptly confirmed and addressed.

Moreover, we need to emphasize that `Solidity`-based smart contracts as a whole are still in an early, but exciting stage of development. To improve this report, we greatly appreciate any constructive feedbacks or suggestions, on our methodology, audit findings, or potential gaps in scope/coverage.



References

- [1] MITRE. CWE-841: Improper Enforcement of Behavioral Workflow. <https://cwe.mitre.org/data/definitions/841.html>.
- [2] MITRE. CWE CATEGORY: Business Logic Errors. <https://cwe.mitre.org/data/definitions/840.html>.
- [3] MITRE. CWE VIEW: Development Concepts. <https://cwe.mitre.org/data/definitions/699.html>.
- [4] OWASP. Risk Rating Methodology. https://www.owasp.org/index.php/OWASP_Risk_Rating_Methodology.
- [5] PeckShield. PeckShield Inc. <https://www.peckshield.com>.