



MySQL5.6双机热备高可用方案配置手册

- Author: BooBooWei
- Version: V.2019.08.08
- Description: MySQLHA-Keepalived-2Nodes

MySQL5.6双机热备高可用方案配置手册

概述

- 方案说明
- 环境说明
- 软件版本
- 自动安装配置脚本

MySQL 主从搭建

- 主机配置
 - 双机hosts文件配置
 - 双机NTP时钟同步
 - 双机互信配置

数据库配置

- 数据库基础安装
- 数据库安全加固
- 半同步复制配置

服务启动和停止命令

自定义脚本

- 脚本语言和版本
- 数据库健康检查
 - 检测算法
 - 检测脚本
 - config.py
 - mysql_helper.py
 - check_mysql.py
- 数据库角色切换
 - 算法
 - notify.py

冷备策略

物理备份：全备+增备

磁盘快照

Keepalived配置

切换原理

四种故障切换原理

MySQL主库故障

MySQL从库故障

Keepalived主故障

Keepalived备故障

总结状态变化

Keepalived的安装

Keepalived的配置

主库配置

从库配置

变更配置文件和日志路径

服务启动和停止命令

故障切换验证

MySQL故障

MySQL主库故障

MySQL从库故障

Keepalived故障

Master故障

Backup故障

日志文件

日志路径

MySQL双机高可用告警规则

其他问题

OS需要关注

客户需要关注

概述

方案说明


MySQL双机热备是一种只有两个节点的高可用集群。高可用性 $\geq 99.95\%$ ，一年内累计不能超过4个小时的不可服务时间。

基于MySQL 5.6的半同步复制 Semisynchronous Replication，加Keepalived 构建的高可用结构。

集群中两台服务器互为备份，当一台服务器出现故障时，可由另一台服务器承担服务任务，从而在无人工干预的情况下，自动保证系统能持续对外提供服务。

金融云华东2 上海

MySQL双机热备架构



技术	说明
MySQL AB Replication	MySQL官方主从复制技术是一种非常简单、便捷的解决方案，在高可用集群中，MySQL主从保证两台MySQL 数据的一致性
Keepalived	实现MySQL故障时的自动切换
Havip	阿里云产品，利用可在ECS进行私网IP宣告的功能，可以实现VRRP协议的高可用

环境说明

HOSTNAME	IP	PORT	ROLE
node1	192.168.14.128	3306	Master
node2	192.168.14.129	3306	Slave
vip	192.168.14.88		

软件版本

软件	版本	软件包	官网
MySQL	5.6	mysql-5.6.45-linux-glibc2.12-x86_64.tar.gz	MySQL
KeepAlived	2.0.18	keepalived-2.0.18.tar.gz	Keepalived

自动安装配置脚本

联系驻云DBA

MySQL 主从搭建

主机配置

双机hosts文件配置

双机hosts文件配置，需要在两台主机上分别修改/etc/hosts文件，如下所示：

```
192.168.14.128 node1
192.168.14.129 node2
```

双机NTP时钟同步

生产环境要求主备机，必须进行时钟同步。

双机互信配置

node1上执行：

```
ip=192.168.14.129
yes | ssh-keygen -f $HOME/.ssh/id_rsa -t rsa -N ''
ssh-copy-id root@$ip
```

node2上执行：

```
ip=192.168.14.128
yes | ssh-keygen -f $HOME/.ssh/id_rsa -t rsa -N ''
ssh-copy-id root@$ip
```

验证：

```
ssh root@$ip hostname
```

不需要使用密码则说明配置成功。

数据库配置

数据库基础安装

运行mysql-5.6.46.sh安装脚本

配置文件中有以下参数需要提前与客户确认：

1. 字符集，默认utf8mb4
2. 事务隔离级别，默认RC

```
cat > /etc/my.cnf <<END
#my.cnf
[client]
port                = 3306
socket              = /tmp/mysql3306.sock

[mysql]
prompt="\\u@\\h [\\d]>"
no-auto-rehash

[mysqld]

user = mysql
basedir = /alidata/mysql
datadir = /alidata/mysql/data
port = 3306
socket = /tmp/mysql3306.sock
event_scheduler = 0

tmpdir = /alidata/mysql/tmp
#timeout
interactive_timeout = 28800
wait_timeout = 28800

#character set
character-set-server = utf8mb4

open_files_limit = 65535
max_connections = 1000
max_connect_errors = 100000
lower_case_table_names =1

#symi replication

#rpl_semi_sync_master_enabled=1
#rpl_semi_sync_master_timeout=1000 # 1 second
#rpl_semi_sync_slave_enabled=1
```

```
#logs
log-output=file
slow_query_log = 1
slow_query_log_file = /alidata/mysql/data/slow.log
log-error = /alidata/mysql/data/error.log
log_warnings = 2
pid-file = mysql.pid
long_query_time = 1
#log-slow-admin-statements = 1
#log-queries-not-using-indexes = 1
log-slow-slave-statements = 1

#binlog
binlog_format = row
server-id = 2003306
log-bin = /alidata/mysql/log/mysql-bin
binlog_cache_size = 4M
sync_binlog = 1
expire_logs_days = 10
#procedure
log_bin_trust_function_creators=1

# gtid
gtid-mode = on
enforce-gtid-consistency=1

#relay log
skip_slave_start = 1
max_relay_log_size = 128M
relay_log_purge = 1
relay_log_recovery = 1
relay-log=relay-bin
relay-log-index=relay-bin.index
log_slave_updates
#slave-skip-errors=1032,1053,1062
#skip-grant-tables

#buffers & cache
table_open_cache = 2048
table_definition_cache = 2048
table_open_cache = 2048
max_heap_table_size = 96M
sort_buffer_size = 128K
join_buffer_size = 128K
thread_cache_size = 200
query_cache_size = 0
query_cache_type = 0
query_cache_limit = 256K
query_cache_min_res_unit = 512
```

```
thread_stack = 192K
tmp_table_size = 96M
key_buffer_size = 8M
read_buffer_size = 2M
read_rnd_buffer_size = 16M
bulk_insert_buffer_size = 32M

#myisam
myisam_sort_buffer_size = 128M
myisam_max_sort_file_size = 10G
myisam_repair_threads = 1

#innodb
innodb_buffer_pool_size = $(num1=`cat /proc/meminfo | sed -n '1p'|awk '{print $2}'`;awk 'BEGIN{printf "%.0f\n",'$num1'*1024*0.75}')
innodb_buffer_pool_instances = 8
innodb_buffer_pool_load_at_startup = 1
innodb_buffer_pool_dump_at_shutdown = 1
innodb_data_file_path = ibdata1:1G:autoextend
innodb_flush_log_at_trx_commit = 1
innodb_log_buffer_size = 32M
innodb_log_file_size = 2G
innodb_log_files_in_group = 2

# mem bug
performance_schema_max_table_instances=600

[mysqldump]
quick
max_allowed_packet = 32M

END
```


数据库安全加固

1. 修改root用户密码
2. 清除所有不安全账号

```
mysql_bin=/alidata/mysql/bin/  
root_pwd=Zyadmin123  
keepalived_user=keepalived  
keepalived_pwd=Keepalived@123  
{mysql_bin}/mysqladmin -uroot password $root_pwd  
{mysql_bin}/mysql -uroot -p$root_pwd -e "delete from mysql.user where  
user='' or host='' or password='';"  
{mysql_bin}/mysql -uroot -p$root_pwd -e "grant all on *.* to  
'{keepalived_user}'@ '%' identified by '{keepalived_pwd}';"
```

半同步复制配置

```
install plugin rpl_semi_sync_master soname 'semisync_master.so';  
install plugin rpl_semi_sync_slave soname 'semisync_slave.so';  
  
rpl_semi_sync_master_enabled=1  
rpl_semi_sync_master_timeout=1000 # 1 second  
rpl_semi_sync_slave_enabled=1
```

主库：

```
mysql_bin=/alidata/mysql/bin/
root_pwd=Zyadmin123
${mysql_bin}/mysql -uroot -p$root_pwd -e "install plugin rpl_semi_sync_master
soname 'semisync_master.so';"
${mysql_bin}/mysql -uroot -p$root_pwd -e "install plugin rpl_semi_sync_slave
soname 'semisync_slave.so';"
${mysql_bin}/mysql -uroot -p$root_pwd -e "set global sync_binlog=1;set global
innodb_flush_log_at_trx_commit=1;"
sed -i "s/^server-id.*$/server_id=1003306/" /etc/my.cnf
sed -i "s/#rpl_semi_sync_master_enabled=1/rpl_semi_sync_master_enabled=1/"
/etc/my.cnf
sed -i "s/#rpl_semi_sync_master_timeout=1000 # 1
second/rpl_semi_sync_master_timeout=1000 # 1 second/" /etc/my.cnf
sed -i "s/#rpl_semi_sync_slave_enabled=1/rpl_semi_sync_slave_enabled=1/"
/etc/my.cnf
```

从库:

```
mysql_bin=/alidata/mysql/bin/
root_pwd=Zyadmin123
${mysql_bin}/mysql -uroot -p$root_pwd -e "install plugin rpl_semi_sync_master
soname 'semisync_master.so';"
${mysql_bin}/mysql -uroot -p$root_pwd -e "install plugin rpl_semi_sync_slave
soname 'semisync_slave.so';"
${mysql_bin}/mysql -uroot -p$root_pwd -e "set global sync_binlog=0;set global
innodb_flush_log_at_trx_commit=0;"
sed -i "s/^server-id.*$/server_id=2003306/" /etc/my.cnf
sed -i "s/#rpl_semi_sync_master_enabled=1/rpl_semi_sync_master_enabled=1/"
/etc/my.cnf
sed -i "s/#rpl_semi_sync_master_timeout=1000 # 1
second/rpl_semi_sync_master_timeout=1000 # 1 second/" /etc/my.cnf
sed -i "s/#rpl_semi_sync_slave_enabled=1/rpl_semi_sync_slave_enabled=1/"
/etc/my.cnf
```

服务启动和停止命令

```
/etc/init.d/mysqld start
/etc/init.d/mysqld stop
/etc/init.d/mysqld restart
```

自定义脚本

脚本语言和版本

语言

版本

Python

2.7.4

```
#!/bin/bash

install_epel(){
    cd /aliyun/install
    rpm -ivh epel-release-latest-7.noarch.rpm
    yum clean all
    yum make cache
}

python_requiere(){
    yum install -y python-pip python-devel
    pip install --upgrade pip
    pip install pymysql
    pip install filelock
}

install_epel
python_requiere
```

数据库健康检查

check_mysql.py 为了检查数据库服务是否正常的脚本，如果判断服务异常，则自动把keepalived进程kill，让VIP进行漂移；

检测算法

1. 判断数据库是否能够正常连接
2. 判断监听端口为3306的mysqld_safe进程是否存在
3. 判断监听端口是否存在

若 数据库能够正常连接；则 返回数据正常；

否则 判断进程和端口是否存在：

- 若此时进程和端口均存在，则连续check 5次 数据库连接情况是否正常，每次check后等待1秒；若5次check后都无法正常连接数据库，则返回数据库异常；若在完成5次check前恢复数据库连接，则返回数据库正常。
- 若此时进程不存在 or 监听端口 不存在；则直接返回数据库异常；

检测脚本

config.py

```
#!/usr/bin/python

dbhost='192.168.14.131'
dbport=3306
dbuser='keepalived'
dbpassword='Keepalived@123'
log_dir="/alidata//keepalived-2.0.18/logs"
other_node='192.168.14.132'
```

mysql_helper.py

```
# -*- coding:utf8 -*-

import sys
import pymysql
import json

class MysqlHelper:
    def __init__(self, **kwargs):
        self.url = kwargs['url']
        self.port = kwargs['port']
        self.username = kwargs['username']
```

```

        self.password = kwargs['password']
        self.dbname = kwargs['dbname']
        self.charset = "utf8"
        self.conn = pymysql.connect(host=self.url, user=self.username,
        passwd=self.password, port=self.port,
                                charset=self.charset, db=self.dbname)
        self.cur = self.conn.cursor(cursor=pymysql.cursors.DictCursor)

    def col_query(self, sql):
        """
        打印表的列名
        :return list
        """
        self.cur.execute(sql)
        return self.cur.fetchall()

    def commit(self):
        self.conn.commit()

    def close(self):
        self.cur.close()
        self.conn.close()

if __name__ == "__main__":
    print("This is mysql api.")

```

check_mysql.py

```

#!/usr/bin/python
# coding: utf-8

import time
import sys
import os
import logging
import json

# Third-part
import mysql_helper
import filelock
import config

preSlaveSQL = "set global read_only=1;"
preMasterSQL = "set global read_only=0;"
log_dir = config.log_dir

logging.basicConfig(level=logging.DEBUG,
                    format='%(asctime)s %(filename)s[line:%(lineno)d] %
                    (levelname)s %(message)s',
                    datefmt='%a, %d %b %Y %H:%M:%S',
                    filename='{0}/notify.log'.format(log_dir),

```

```

        filemode='a',
        maxBytes=10485760, # 10MB 设置日志文件的大小
        backupCount=20, # 文件最大的个数
        encoding='utf8')

```

```

class DBase:
    def __init__(self, **kwargs):
        self.params = kwargs["mysql"]
        self.keepalived = kwargs["keepalived"]
        self.other_node = kwargs["other_node"]
        try:
            self.conn = mysql_helper.MysqlHelper(**self.params)
        except Exception as e:
            logging.info("数据库连接异常 " + str(e))
            exit(1)

    def alert(self):
        print("{}".format(self.keepalived))

    def make_master(self):
        """
        将从库切换为主库
        1. 获取从库slave状态
        2. 判断主从是否存在延迟
        3. 如存在延迟等待1分钟
        4. 停止slave
        :return:
        """
        slave_status = self.conn.col_query("show slave status")[0]
        logging.info(json.dumps(slave_status, indent=2))
        Master_Host = slave_status["Master_Host"]
        Master_Log_File = slave_status["Master_Log_File"]
        Read_Master_Log_Pos = slave_status["Read_Master_Log_Pos"]
        Relay_Master_Log_File = slave_status["Relay_Master_Log_File"]
        Exec_Master_Log_Pos = slave_status["Exec_Master_Log_Pos"]

        if Master_Log_File == Relay_Master_Log_File and Read_Master_Log_Pos
        == Exec_Master_Log_Pos:
            self.conn.col_query("stop slave;")
            self.conn.col_query("set global sync_binlog=1;")
            self.conn.col_query("set global
            innodb_flush_log_at_trx_commit=1;")
            self.conn.col_query("set global read_only=0;")
            master_status = self.conn.col_query("show master status;")[0]
            logging.info("stop slave;show master status;")
            logging.info("记录新主库的binlog位置: ")
            logging.info(json.dumps(master_status, indent=2))
            with open("/alidata/keepalived-2.0.18/logs/master_info", 'w') as
            f:
                f.write(json.dumps(master_status, indent=1))

```

```

else:
    time.sleep(60)
    slave_status = self.conn.col_query("show slave status")[0]
    logging.info(json.dumps(slave_status, indent=2))
    self.conn.col_query("stop slave;")
    self.conn.col_query("set global sync_binlog=1;")
    self.conn.col_query("set global
innodb_flush_log_at_trx_commit=1;")
    self.conn.col_query("set global read_only=0;")
    master_status = self.conn.col_query("show master status;")[0]
    logging.info(json.dumps(master_status, indent=2))
    with open("/alidata/keepalived-2.0.18/logs/master_info", 'w') as
f:
        f.write(json.dumps(master_status, indent=1))

# 记录主库真实的binlog文件和position编号
try:
    os.popen(
        "scp root@{0}:/alidata/mysql/log/mysql-bin.index
/alidata/keepalived-2.0.18/logs/{0}-mysql-bin.index".format(
            Master_Host))
    master_binlog_file_real = \
        open("/alidata/keepalived-2.0.18/logs/{0}-mysql-
bin.index".format(Master_Host)).readlines()[-1].strip()
    os.popen(
        "scp root@{0}:{1} /alidata/keepalived-2.0.18/logs/{0}-
{2}".format(Master_Host, master_binlog_file_real,

master_binlog_file_real.split('/')[

-1]))
    master_binlog_file_slave = "/alidata/keepalived-2.0.18/logs/{0}-
{1}".format(Master_Host,

master_binlog_file_real.split(

'/')[-1])
    cmd = "/alidata/mysql/bin/mysqlbinlog -vv " +
master_binlog_file_slave + " | tail -n 100|grep end_log_pos|tail -n 2|head -n
1|awk '{print $7}'"
    master_binlog_pos_real = os.popen(cmd).read()
except Exception as e:
    logging.error(str(e))

else:
    logging.info("主库 {0} 最后一个binlog日志文件 {1} 位置编号为
{2}".format(Master_Host, master_binlog_file_real,

master_binlog_pos_real))
    logging.info("从库 {0} 重演主库binlog日志文件 {1} 位置编号为
{2}".format(
        self.params["url"],

```

```

        slave_status["Relay_Master_Log_File"],
        slave_status["Exec_Master_Log_Pos"])))

def make_slave(self):
    """
    清空slave配置，重新获取远程日志文件及位置编号，并开启半同步复制；
    :return:
    """
    try:
        os.popen(
            "scp root@{0}:/alidata/keepalived-2.0.18/logs/master_info
/alidata/keepalived-2.0.18/logs/{0}-master_info".format(
                self.other_node))
        master_info = json.loads(
            open("/alidata/keepalived-2.0.18/logs/{0}-
master_info".format(self.other_node)).read())
        except Exception as e:
            logging.error("无法获取远程日志文件及位置编号")
            logging.error(str(e))
        else:
            self.conn.col_query("stop slave;")
            logging.info("stop slave;")
            sql = "change master to
master_user='slave',master_password='Slave@replication',master_host='{0}',mas
ter_auto_position=0;"
            self.conn.col_query(sql)
            logging.info(sql)
            sql = "change master to
master_user='slave',master_password='Slave@replication',master_host='{0}',mas
ter_log_file='{1}',master_log_pos={2};".format(
                self.other_node, master_info["File"],
                master_info["Position"])
            self.conn.col_query(sql)
            self.conn.col_query("start slave;")
            self.conn.col_query("set global read_only=1;")
            logging.info("start slave;")
            logging.info("set global read_only=1;")
            logging.info(sql)
            slave_status = self.conn.col_query("show slave status;")[0]
            logging.info(json.dumps(slave_status, indent=2))

def stop_mysql(self):
    try:
        master_status = self.conn.col_query("show master status;")[0]
    except:
        logging.error("数据库服务异常")
    else:
        logging.info("数据库正常")
        logging.info(json.dumps(master_status, indent=2))
        logging.info("主库 {0} 最后一个binlog日志文件 {1} 位置编号为
{2}".format(

```



```

        self.params["url"], master_status["File"],
        master_status["Position"])))

    try:
        slave_status = self.conn.col_query("show slave status;")[0]
    except:
        logging.error("数据库服务异常")
    else:
        logging.info("数据库正常")
        logging.info(json.dumps(slave_status, indent=2))
        logging.info("从库 {0} 重演主库binlog日志文件 {1} 位置编号为
{2}".format(
            self.params["url"],
            slave_status["Relay_Master_Log_File"],
            slave_status["Exec_Master_Log_Pos"])))

def start(self):
    if self.Keepalived == "MASTER":
        self.make_master()
        logging.info("切换状态为MASTER")
    elif self.Keepalived == "BACKUP":
        self.make_slave()
        logging.info("切换状态为BACKUP")
    elif self.Keepalived == "STOP":
        self.stop_mysql()
        logging.info("切换状态为STOP")
    else:
        logging.error("keepalived配置有误或脚本执行异常")

    self.conn.close()

if __name__ == "__main__":
    lock = filelock.FileLock("/tmp/kps.txt")
    if lock:
        logging.info("ZST Get Lock.start!!!")
    try:
        with lock.acquire(timeout=5):
            pass
    except filelock.timeout:
        print "timeout"
        logging.warning("get file lock timeout")

mysql = {
    "url": config.dbhost,
    "port": config.dbport,
    "username": config.dbuser,
    "password": config.dbpassword,
    "dbname": "mysql",
}

```

```
params = {  
    "mysql": mysql,  
    "keepalived": sys.argv[3].upper(),  
    "other_node": config.other_node,  
}  
  
db = DBase(**params)  
db.start()
```

数据库角色切换

算法

- 如果参数为backup，则调用make_slave()函数：清空slave配置，重新获取远程日志文件及位置编号，并开启半同步复制，set global read_only=1;;
- 如果参数为master，则调用make_master()函数：先判断同步复制是否执行完成，如果未执行完成等待1分钟后，停止同步（stop slave;），并且记录切换后的日志和位置编号，set global read_only=0;
- 如果参数为stop，则调用stop_mysql()函数：记录当前主或从的日志信息，为故障修复做准备；
- 如果参数为fault，则调用alert()函数：keepalived本身配置或调用的脚本执行异常，记录异常。

notify.py

```
#!/usr/bin/python
# coding: utf-8

import time
import sys
import os
import logging
import json

# Third-part
import mysql_helper
import filelock
import config

preSlaveSQL = "set global read_only=1;"
preMasterSQL = "set global read_only=0;"
log_dir = config.log_dir

logging.basicConfig(level=logging.DEBUG,
                    format='%(asctime)s %(filename)s[line:%(lineno)d] %(
(levelname)s %(message)s',
                    datefmt='%a, %d %b %Y %H:%M:%S',
                    filename='{0}/notify.log'.format(log_dir),
                    filemode='a',
                    maxBytes=10485760, # 10MB 设置日志文件的大小
                    backupCount=20, # 文件最大的个数
                    encoding='utf8')

class DBase:
    def __init__(self, **kwargs):
        self.params = kwargs["mysql"]
        self.keepalived = kwargs["keepalived"]
```

```

self.other_node = kwargs["other_node"]
try:
    self.conn = mysql_helper.MysqlHelper(**self.params)
except Exception, e:
    logging.info("数据库连接异常 " + str(e))
    exit(1)

def alert(self):
    print("{}".format(self.keepalived))

def make_master(self):
    """
    将从库切换为主库
    1. 获取从库slave状态
    2. 判断主从是否存在延迟
    3. 如存在延迟等待1分钟
    4. 停止slave
    :return:
    """
    slave_status = self.conn.col_query("show slave status")[0]
    logging.info(json.dumps(slave_status, indent=2))
    Master_Host = slave_status["Master_Host"]
    Master_Log_File = slave_status["Master_Log_File"]
    Read_Master_Log_Pos = slave_status["Read_Master_Log_Pos"]
    Relay_Master_Log_File = slave_status["Relay_Master_Log_File"]
    Exec_Master_Log_Pos = slave_status["Exec_Master_Log_Pos"]

    if Master_Log_File == Relay_Master_Log_File and Read_Master_Log_Pos
    == Exec_Master_Log_Pos:
        self.conn.col_query("stop slave;")
        self.conn.col_query("set global sync_binlog=1;")
        self.conn.col_query("set global
innodb_flush_log_at_trx_commit=1;")
        self.conn.col_query("set global read_only=0;")
        master_status = self.conn.col_query("show master status;")[0]
        logging.info("stop slave;show master status;")
        logging.info("记录新主库的binlog位置: ")
        logging.info(json.dumps(master_status, indent=2))
        with open("/alidata/keepalived-2.0.18/logs/master_info", 'w') as
f:
            f.write(json.dumps(master_status, indent=1))

    else:
        time.sleep(60)
        slave_status = self.conn.col_query("show slave status")[0]
        logging.info(json.dumps(slave_status, indent=2))
        self.conn.col_query("stop slave;")
        self.conn.col_query("set global sync_binlog=1;")
        self.conn.col_query("set global
innodb_flush_log_at_trx_commit=1;")
        self.conn.col_query("set global read_only=0;")
        master_status = self.conn.col_query("show master status;")[0]

```

```

        logging.info(json.dumps(master_status, indent=2))
        with open("/alidata/keepalived-2.0.18/logs/master_info", 'w') as
f:
            f.write(json.dumps(master_status, indent=1))

# 记录主库真实的binlog文件和position编号
try:
    os.popen(
        "scp root@{0}:/alidata/mysql/log/mysql-bin.index
/alidata/keepalived-2.0.18/logs/{0}-mysql-bin.index".format(
            Master_Host))
    master_binlog_file_real = \
        open("/alidata/keepalived-2.0.18/logs/{0}-mysql-
bin.index".format(Master_Host)).readlines()[-1].strip()
    os.popen(
        "scp root@{0}:{1} /alidata/keepalived-2.0.18/logs/{0}-
{2}".format(Master_Host, master_binlog_file_real,

        master_binlog_file_real.split('/')[
-1]))
    master_binlog_file_slave = "/alidata/keepalived-2.0.18/logs/{0}-
{1}".format(Master_Host,

        master_binlog_file_real.split(
            '/')[-1])
    cmd = "/alidata/mysql/bin/mysqlbinlog -vv " +
master_binlog_file_slave + " | tail -n 100|grep end_log_pos|tail -n 2|head -n
1|awk '{print $7}'"
    master_binlog_pos_real = os.popen(cmd).read()
except Exception as e:
    logging.error(str(e))

else:
    logging.info("主库 {0} 最后一个binlog日志文件 {1} 位置编号为
{2}".format(Master_Host, master_binlog_file_real,
master_binlog_pos_real))
    logging.info("从库 {0} 重演主库binlog日志文件 {1} 位置编号为
{2}".format(
        self.params["url"],
        slave_status["Relay_Master_Log_File"],
        slave_status["Exec_Master_Log_Pos"]))

def make_slave(self):
    """
    清空slave配置，重新获取远程日志文件及位置编号，并开启半同步复制；
    :return:
    """
    try:
        os.popen(

```

```

        "scp root@{0}:/alidata/keepalived-2.0.18/logs/master_info
/alidata/keepalived-2.0.18/logs/{0}-master_info".format(
            self.other_node))
        master_info = json.loads(
            open("/alidata/keepalived-2.0.18/logs/{0}-
master_info".format(self.other_node)).read())
        except Exception as e:
            logging.error("无法获取远程日志文件及位置编号")
            logging.error(str(e))
        else:
            self.conn.col_query("stop slave;")
            logging.info("stop slave;")
            sql = "change master to
master_user='slave',master_password='Slave@replication',master_host='{0}',mas
ter_auto_position=0;"
            self.conn.col_query(sql)
            logging.info(sql)
            sql = "change master to
master_user='slave',master_password='Slave@replication',master_host='{0}',mas
ter_log_file='{1}',master_log_pos={2};"
            self.other_node, master_info["File"],
master_info["Position"])
            self.conn.col_query(sql)
            self.conn.col_query("set global read_only=1;")
            logging.info("set global read_only=1;")
            logging.info(sql)
            slave_status = self.conn.col_query("show slave status;")[0]
            logging.info(json.dumps(slave_status, indent=2))

def stop_mysql(self):
    try:
        master_status = self.conn.col_query("show master status;")[0]
    except:
        logging.error("数据库服务异常")
    else:
        logging.info("数据库正常")
        logging.info(json.dumps(master_status, indent=2))
        logging.info("主库 {0} 最后一个binlog日志文件 {1} 位置编号为
{2}".format(
            self.params["url"], master_status["File"],
master_status["Position"]))

    try:
        slave_status = self.conn.col_query("show slave status;")[0]
    except:
        logging.error("数据库服务异常")
    else:
        logging.info("数据库正常")
        logging.info(json.dumps(slave_status, indent=2))
        logging.info("从库 {0} 重演主库binlog日志文件 {1} 位置编号为
{2}".format(

```

```

        self.params["url"],
        slave_status["Relay_Master_Log_File"],
        slave_status["Exec_Master_Log_Pos"]))

def start(self):
    if self.Keepalived == "MASTER":
        self.make_master()
        logging.info("切换状态为MASTER")
    elif self.Keepalived == "BACKUP":
        self.make_slave()
        logging.info("切换状态为BACKUP")
    elif self.Keepalived == "STOP":
        self.stop_mysql()
        logging.info("切换状态为STOP")
    else:
        logging.error("keepalived配置有误或脚本执行异常")

    self.conn.close()

if __name__ == "__main__":
    lock = filelock.FileLock("/tmp/kps.txt")
    if lock:
        logging.info("ZST Get Lock.start!!!")
    try:
        with lock.acquire(timeout=5):
            pass
    except filelock.timeout:
        print "timeout"
        logging.warning("get file lock timeout")

    mysql = {
        "url": config.dbhost,
        "port": config.dbport,
        "username": config.dbuser,
        "password": config.dbpassword,
        "dbname": "mysql",
    }

    params = {
        "mysql": mysql,
        "keepalived": sys.argv[3].upper(),
        "other_node": config.other_node,
    }

    db = DBase(**params)
    db.start()

```

冷备策略

物理备份：全备+增备

1. 备份工具：innobackupex
2. 备份分类：物理备份、在线热备、全备+增备
3. 备份策略：每天1:59开始执行备份脚本；周一全备份，周二到周日增量；每周自动删除上一周过期备份数据
4. 备份文件：/alidata/backup
5. 其他信息：备份索引/alidata/xtrabackup_cron/var/mysql_increment_hot_backup.index

磁盘快照

通过阿里云ECS的快照功能做冷备。

Keepalived配置

切换原理

四种故障切换原理

MySQL主库故障

当前node1为MySQL MASTER; node2为MySQL SLAVE

1. node1,数据库宕机时pkill keepalived, keepalived的状态由master变为stop
2. node2, 数据库服务正常, keepalived的状态由backup 变为master
3. node1, 故障手动恢复后, keepalived的状态进入backup

MySQL从库故障

当前node1为MySQL MASTER; node2为MySQL SLAVE

1. 从库node2宕机时pkill keepalived, keepalived的状态由backup变为stop
2. 从库node2故障手动恢复后, keepalived的状态进入backup

Keepalived主故障

当前node1为MySQL MASTER; node2为MySQL SLAVE

- node1, keepalived故障, keepalived的状态由master改为stop
- node2, keepalived服务正常, keepalived的状态由backup改为master
- node1, 故障手动恢复后, keepalived的状态进入backup

Keepalived备故障

当前node1为MySQL MASTER; node2为MySQL SLAVE

- node2, keepalived故障, keepalived的状态由backup改为stop
- node2, 故障手动恢复后, keepalived的状态进入backup

总结状态变化

类型	说明	变化前	变化后
1	因MySQL Master 服务不可用将Keepalived被关闭	master	stop
2	Keepalived服务异常	master	fault
3	MySQL Master 服务不可用 或 Keepalived服务不可用	backup	master
4	因MySQL Slave 服务不可用将Keepalived被关闭	backup	stop
5	Keepalived服务异常	backup	fault

node1 测试

```
['/alidata/keepalived-2.0.18/scripts/notify.py', 'INSTANCE', 'VI_1',  
'BACKUP', '100']  
['/alidata/keepalived-2.0.18/scripts/notify.py', 'INSTANCE', 'VI_1',  
'MASTER', '100']  
['/alidata/keepalived-2.0.18/scripts/notify.py', 'INSTANCE', 'VI_1', 'STOP',  
'100']  
['/alidata/keepalived-2.0.18/scripts/notify.py', 'INSTANCE', 'VI_1',  
'BACKUP', '100']  
['/alidata/keepalived-2.0.18/scripts/notify.py', 'INSTANCE', 'VI_1',  
'MASTER', '100']  
['/alidata/keepalived-2.0.18/scripts/notify.py', 'INSTANCE', 'VI_1', 'FAULT',  
'100']  
['/alidata/keepalived-2.0.18/scripts/notify.py', 'INSTANCE', 'VI_1',  
'MASTER', '100']
```

node2 测试

```
['/alidata/keepalived-2.0.18/scripts/notify.py', 'INSTANCE', 'VI_1',  
'BACKUP', '90']  
['/alidata/keepalived-2.0.18/scripts/notify.py', 'INSTANCE', 'VI_1',  
'MASTER', '90']  
['/alidata/keepalived-2.0.18/scripts/notify.py', 'INSTANCE', 'VI_1', 'STOP',  
'90']  
['/alidata/keepalived-2.0.18/scripts/notify.py', 'INSTANCE', 'VI_1',  
'BACKUP', '90']  
['/alidata/keepalived-2.0.18/scripts/notify.py', 'INSTANCE', 'VI_1',  
'MASTER', '90']  
['/alidata/keepalived-2.0.18/scripts/notify.py', 'INSTANCE', 'VI_1', 'FAULT',  
'90']  
['/alidata/keepalived-2.0.18/scripts/notify.py', 'INSTANCE', 'VI_1',  
'BACKUP', '90']
```

切换速度 < 1秒

Keepalived的安装

```
#!/bin/bash

# https://www.keepalived.org/doc/
# version keepalived-2.0.18.tar.gz

# Install Prerequisites on RHEL/CentOS
yum install -y curl gcc openssl-devel libnl3-devel net-snmp-devel

cd /root
mkdir -p /alidata/install
mv keepalived-2.0.18.tar.gz /alidata/install/
cd /alidata/install
tar -xvf keepalived-2.0.18.tar.gz
cd keepalived-2.0.18
./configure --prefix=/alidata/keepalived-2.0.18 --with-init=systemd
make
make install
mkdir -p /alidata//keepalived-2.0.18/scripts
mkdir -p /alidata//keepalived-2.0.18/logs
```

Keepalived的配置

配置	说明
state BACKUP	主从两端都配置成了backup，结合使用nopreempt，设置为非抢占模式
virtual_router_id 51	分组id，主从节点应配置相同
priority	优先级，数据库主节点配置高一些
nopreempt	不主动抢占资源，设置非抢占模式
notify	状态变更以后执行的脚本

主库配置

```
global_defs {
    router_id MySQL-HA
}

vrrp_script check_run {
    script "/alidata//keepalived-2.0.18/scripts/check_mysql.py"
    interval 10
}

vrrp_sync_group VG1 {
    group {
        VI_1
    }
}

vrrp_instance VI_1 {
    state BACKUP
    interface eth1
    virtual_router_id 51
    priority 100
    advert_int 1
    nopreempt
    authentication {
        auth_type PASS
        auth_pass 1111
    }
    track_script {
        check_run
    }

    notify /alidata//keepalived-2.0.18/scripts/notify.py

    virtual_ipaddress {
        192.168.14.88
    }
}
```

从库配置

```
global_defs {
    router_id MySQL-HA
}

vrrp_script check_run {
    script "/alidata//keepalived-2.0.18/scripts/check_mysql.py"
    interval 10
}

vrrp_sync_group VG1 {
    group {
        VI_1
    }
}

vrrp_instance VI_1 {
    state BACKUP
    interface eth1
    virtual_router_id 51
    priority 90
    advert_int 1
    authentication {
        auth_type PASS
        auth_pass 1111
    }
    track_script {
        check_run
    }

    notify /alidata//keepalived-2.0.18/scripts/notify.py

    virtual_ipaddress {
        192.168.14.88
    }
}
```

变更配置文件和日志路径

```
sed -i "s@-D@-f /alidata/keepalived-2.0.18/etc/keepalived/keepalived.conf -D  
-d -S 0@" /alidata/keepalived-2.0.18/etc/sysconfig/keepalived  
cat >> /etc/rsyslog.conf << ENDF  
local0.*  
/var/log/keepalived.log  
ENDF  
systemctl restart rsyslog
```

服务启动和停止命令

```
systemctl status|start|stop|restart keepalived
```

故障切换验证

MySQL故障

MySQL主库故障

| Node1 主 Node2 从

- Node1 数据库（主）故障后，Node2 自动升级为主库
- Node1 数据库故障修复后，启动 keepalived 服务，自动完成主从重构，成为 Node2 的从库

MySQL从库故障

| Node1 主 Node2 从

- Node2 数据库（从）故障后，keepalived 进入stop状态
- Node2 数据库故障修复后，启动 keepalived 服务，自动完成主从重构，成为 Node1 的从库

Keepalived故障

Master故障

| Node1 主 Node2 从

- Node1 keepalived (Master) 故障后, 进入stop状态，如果数据库正常，则记录当前主库的明细；否则，记录数据库异常信息
- Node1 数据库正常，启动 keepalived 服务，自动完成主从重构，成为 Node2 的从库
- Node1 数据库异常，手动修复故障后，启动 keepalived 服务

Backup故障

| Node1 主 Node2 从

- Node2 keepalived (Backup) 故障后，进入stop状态，如果数据库正常，记录当前从库的明细；否则记录数据库异常信息

- Node2 数据库正常，启动 keepalived 服务
- Node2 数据库异常，手动修复故障后，启动 keepalived 服务

日志文件

日志路径

日志	路径	功能	备注
MySQL	/alidata/mysql/data/slow.log	慢查询日志	
	/alidata/mysql/data/error.log	错误日志	
	/aliata/mysql/log/	二进制日志	保留近10天
Keepalived	/var/log/keepalived.log	错误日志	
	/alidata//keepalived-2.0.18/logs/check_mysql.log	数据库健康检查日志	日志文件的大小10MB；文件最大的个数20
	/alidata//keepalived-2.0.18/logs/notify.log	数据库切换日志	日志文件的大小10MB；文件最大的个数20

MySQL双机高可用告警规则

此处仅重点罗列双机高可用架构中的告警规则；关于MySQL本身的告警指标（1400+）和告警规则（10+）较多此处不一一罗列。

告警规则（6项）	监控间隔	连续N次触发	等级
MySQL 数据库主从I/O线程异常	3min	1次	严重
MySQL 数据库主从SQL线程异常	3min	1次	严重
MySQL 数据库半同步复制状态异常	3min	1次	严重
MySQL 数据库主从延迟（超过5秒）	3min	1次	严重
MySQL 数据库有未提交的长事务（超过60秒）	3min	1次	严重
Keepalived状态变化（Master/Backup/Stop/Fault）	10s	1次	严重

其他问题

OS需要关注

- 服务器规格配置要一致，否则容易导致复制延迟；
- 操作系统建议使用RedHat，易于维护管理（运维人员更熟悉Redhat/CentOS）；

客户需要关注

- 数据库版本选择5.6存在延迟的风险：MySQL5.6 延迟问题没有彻底解决，如果对延迟比较敏感应升级至MySQL 5.7或8.0最新版本，利用多线程复制的方式可以很大程度降低复制延迟；