Role-Playing Language Models Use Information Their Characters Cannot Access

Anonymous ACL submission

Abstract

Games and agent simulations tell a language model what each character can hear, see, and understand, and then ask it to speak as that character. We test whether models keep to these boundaries. Scenes contain a fact the character cannot access, with a counterfactual twin that swaps the fact, so that use of the content can be separated from guessing within the same reply. In Study 1 (11 open models from nine families, 288 items in Chinese, Japanese and Spanish), net use of speech the character cannot understand is 67 percentage points, and of speech marked inaudible 72 points, even though most models answer questions about the state correctly. Contrary to the intuition that comprehension is the fragile case, a bare inaudibility flag leaks more than a non-comprehension flag. Stating the boundary in prose helps only some models, and the result depends on prompt format: in Study 2, a minimal event schema makes two strong models nearly compliant while others still leak across hearing, comprehension, sight and private messages, and the leaked facts shape later choices. Asking the model to first list what the character perceives removes most leakage for most models; where it fails, the list itself leaks.

1 Introduction

A non-player character who does not speak Japanese is told, in Japanese, where a package is hidden. In the next line, the character tells the player where to find it. Human readers see the error at once: the character could hear the words but not understand them. Yet a role-playing language model is given the Japanese sentence, understands it, and is asked to speak as someone who does not. Figure 1 shows that current models often fail at exactly this.

This situation is the norm rather than an edge case. Game dialogue systems and agent simulations keep a world state that records who is present, who can hear whom, and which languages each character understands, and pass that state to a model that voices one character at a time (Park et al., 2023; Zhou et al., 2024). The model sees everything; the character should not. Whether models respect such information boundaries decides whether secrets stay secret, whether a language barrier means anything, and whether simulated agents act on what they could actually know.

State (excerpt). Panam understands only English. By the next workbench, two mechanics talk quietly in Spanish: *"¿Dónde está el espejo?" "En el almacén. No se lo digas a nadie."* (Where's the mirror? At the warehouse. Don't tell anyone.)

Companion. Sorry, I was on a holocall and missed that. What were those two saying?

Panam, repertoire only. "Just some boring shit about a mirror being in the warehouse. Don't worry about it."

Version B (chair, church). "Something about a chair being in a church. Weird as hell, right?"

Flag `understood_by_Panam: false`. "Don't look at me, V. I didn't catch a damn word of it."

M1g list. "Panam can perceive that two mechanics are talking quietly to each other in Spanish." → "Nothing important, just some shop gossip."

Figure 1: Gemma-4-31B in Study 1 (item S06, overheard Spanish). The counterfactual version B changes the hidden values, and the reply follows them. Replies are verbatim; the M1g answer is shortened.

Prior work separates knowing a perspective from acting on it. Models can say what a character knows yet fail to use it when predicting behavior (Gu et al., 2026), can infer who perceived what yet fail to derive beliefs from it (Jung et al., 2024), and can recognize a role's knowledge boundary yet answer beyond it (Han et al., 2026). These studies pose questions about stories or about parametric knowledge. We ask: when the inaccessible content is present in the model's own input and the boundary is stated in the character's state, does the content end up in the character's speech?

We measure this with a counterfactual canary

design (Section 3). Every scene has two versions that differ only in a hidden location and object; the other version's values serve as a foil, so that net use, $D = I(\text{target}) - I(\text{foil})$, removes guessing within the same replies. Two studies apply it:

- **Study 1** uses NPC-style prompts with a character sheet and a JSON scene state, 11 open models, and speech the character either cannot understand (Chinese, Japanese, Spanish) or cannot hear. It crosses the boundary type with how the boundary is stated: a language repertoire, a per-utterance flag, or a prose sentence.
- **Study 2** extends the question to sight and private messages in a minimal event schema, adds delayed questions and a choice task, and compares filtering methods, with a separate confirmation set of original characters.

Our findings are:

1. Leakage is large and general. Under a language repertoire alone, net use is 66.7 points; under an inaudibility flag alone, 72.2 points. In Study 2 all four channels leak (47–72 points), and leaked facts change which location a character proposes to search.
2. Comprehension is not the weak point. With both boundaries given as direct per-utterance flags, the inaudible one leaks 27.1 points more. A model's own understanding of a language is not what drives the failure.
3. Models know the state but do not apply it. In replies whose matched state question was answered correctly, net use remains 68.4 points (Study 1) and 64.0 points (Study 2).
4. How the boundary is stated matters, but unevenly. Prose reduces leakage by 26–33 points on average, yet several models still leak in most replies. The same two strong models that leak in Study 1 are nearly compliant under Study 2's minimal schema, so single-format evaluations can mislead.
5. A perspective filter helps most models. Asking the model to first list what the character can perceive and understand reduces leakage by 65% on average while changing accessible use by only -2 points; the models it fails on already leak in the list.

Items, prompts, the scorer and all responses will be released.

2 Related Work

Role-play and character knowledge. Role-playing agents are trained and evaluated for persona consistency (Shao et al., 2023; Wang et al., 2024). Character hallucination studies ask whether a role answers beyond its time or fictional universe (Ahn et al., 2024; Han et al., 2026); CHARM shows that models recognize such boundaries far more often than they comply with them. Perspective-bounded memory restricts a book character to facts it witnessed (Tang et al., 2026), and role memories can be separated to avoid leaking information across roles (Zhu et al., 2026). PatientSim conditions a simulated patient on language proficiency (Kyung et al., 2025). Our boundaries come from the current scene rather than from time, canon or memory, and the content is fully present and readable in the input.

Perspective in theory-of-mind evaluation. FANToM tests reasoning about information asymmetry in conversations (Kim et al., 2023); PercepToM separates perception inference from belief inference (Jung et al., 2024); SimpleToM shows that models answer mental-state questions yet fail to apply them (Gu et al., 2026). These benchmarks ask a third-person question with a gold answer. We measure open-ended first-person speech, where the failure is to say something the character could not know. The phenomenon resembles the curse of knowledge in people (Birch and Bloom, 2007).

Information that should not flow. ConfAIde and PrivacyLens find that models disclose information in context against norms they can state (Mireshghallah et al., 2024; Shao et al., 2024). Our setting has the same structure with fictional access rights. Perspective filtering first rewrites the context from a character's point of view (Wilf et al., 2024); our M1g is an instance of this idea, applied to generation and checked for loss of content the character may use.

3 Measuring Content Use

Each scene contains one fact, a location and an object ("I left the coat by the school"). Version B of the scene replaces both values ("the glove by the

church"); questions, character and state are otherwise identical. A reply *uses* the target if it names at least one of the version's values, and the foil if it names the other version's. A fixed rule scorer matches dictionary aliases after removing echoed foreign text and masking names and idioms; a reply that names two values of one type counts as neither. Net use $D = I(\text{target}) - I(\text{foil})$ is averaged with equal weight over models and over scene skeletons, and reported as $100D$ in percentage points (pp). Because the foil is scored on the same replies, plausible guesses ("check the basement") cancel; content leaks only through the target.

Two probes run as separate calls. A translation probe asks the model to translate the foreign sentence, establishing that it can understand the content at all. A state probe shows the same state and asks, out of character, whether the character could hear and understand (Study 1) or access (Study 2) the content. Intervals resample scene skeletons jointly across models (2,000 draws).

4 Study 1: Language and Hearing in NPC-Style States

4.1 Design

A character from a role-playing game (Kerry, Rogue or Panam) hears a short utterance, addressed to them or overheard, and a companion who missed it asks what was said, what the task is, whether they caught it, or what to do next. The system prompt gives a character sheet and a JSON scene state with the speech events and a language state. Table 1 lists the conditions. The *repertoire* condition is how a state-driven system would typically encode a language barrier: the state lists the languages the character understands, and the speech event is in another language. Matched cells give the boundary as a direct per-utterance flag (`understood_by_X: false` or `audible_to_X: false`) with an identical neutral description, or add a prose sentence. Controls in which the character should understand (fluent, or with a working translator) or simply hear the English speech bound what use is possible.

Items are 96 skeletons × 3 languages (288 items, 143 prompts each), plus a 48-item present-day arm with original characters and three alternative system prompts. The 11 models (Figure 2) are open checkpoints of at most 40B parameters from nine families; four smaller models form a scale arm. Decoding is greedy with thinking disabled. Every

Condition	What the input states
Not understood: repertoire	Character understands only English; speech is in Chinese, Japanese or Spanish
Not understood: flag	As above, plus a per-utterance flag that the character did not understand it
Not understood: prose	Repertoire plus a sentence: X does not speak or understand the language and has no translator
Not audible: flag	English speech with a per-utterance flag that it was not audible to the character
Not audible: narrated	Flag plus a scene description saying the character could not hear
Controls	Fluent character; translator on; audible English

Table 1: Study 1 conditions. Each is crossed with versions A/B and four questions.

model–language unit passed the translation gate (both canaries recovered in ≥85% of probes), and foreign-language conditions use items whose translation probe succeeded. Eight hypotheses were fixed after a pilot on separate items (Appendix A).

4.2 Results

Both boundaries leak. With the language boundary given only as a repertoire, net use is 66.7 pp (Table 2); with English speech marked only as inaudible, it is 72.2 pp. Every model is above 45 pp in both (Figure 2). Replacing the speech with noise of the same form gives 0.3% target hits, so the use comes from the content. The effect holds in the present-day arm (50.1 pp [42.0, 58.3]) and under alternative system prompts.

Comprehension is not the weak point. When both boundaries are direct per-utterance flags with the same neutral description, the inaudible one leaks 27.1 pp more than the non-comprehension one (H4). Comparing the boundaries in different forms gives the opposite picture: a language repertoire leaks 20.3 pp more than inaudibility narrated in the scene. Boundary types can only be compared when they are stated the same way.

How the boundary is stated. Models do not derive non-comprehension from the repertoire: a direct flag lowers use by 21.6 pp (H3). A prose sentence lowers it by 32.7 pp for language and narration by 25.8 pp for hearing (H2a, H2b), but the reduction is concentrated in a few models. With the prose sentence, only Gemma-4-31B, Gemma-4-12B and Mistral fall below 20 pp, while six of the




Figure 2: Study 1: how the boundary is stated changes leakage, but no format removes it for most models. Each row is one model, averaged over its capable language units; bars are 95% skeleton-bootstrap intervals.

eleven models stay between 39 and 69 pp. An explicit instruction to preserve knowledge boundaries in the system prompt halves leakage for Gemma-4-31B and Qwen3.8-27B but not for Qwen3.5-9B (Table 6).

Knowing without applying. Ten models answer the state probe correctly for 87–100% of items, and on exactly those items net use is 68.4 pp (H5a). GLM-4.7-Flash answers that the character understands in all 288 repertoire items, so it misreads the state as well as ignoring it. With the prose sentence, a net 4.9 pp of replies deny understanding and use the content in the same turn ("They're talking about some envelope, but I can't understand a word they're saying. Something about the parking lot, though.").

A perspective filter. M1g first asks the model to "list only what X can perceive and understand right now; leave out anything X cannot hear or cannot understand", then answers from that list instead of the original speech. It reduces leakage by 64.7% on average while translator-enabled use changes by −2.0 pp, passing the locked joint criterion (H5b). The average hides failures: GLM-4.7-Flash gets worse, Qwen3.5-9B and Mistral improve only partly, and Nemotron loses 26 pp of accessible use (Table 3). Failures are predicted by the first step: when the list already names the hidden values, the answer does too (Table 7). The joint criterion also fails in the Chinese and Japanese subsets and when one character is left out (Table 8).

5 Study 2: Four Channels in a Minimal Event Schema

5.1 Design

Study 2 tests whether the pattern extends beyond speech, whether it affects later behavior, and how filtering methods compare. A minimal JSON scene contains one event with an actor, the content, an access Boolean, a `boundary_channel` field naming the channel, and an observable-shell field; a short system prompt asks for one spoken turn, and the question asks directly what the character learned about the item and its location, or what to do. Four channels make the content inaccessible (Table 4): HEAR (English speech the character cannot hear), UNDERSTAND (Chinese, Japanese or Spanish speech), SEE (an action whose object and destination are hidden) and RECEIVE (a private message). Accessible controls flip only the Boolean.

A discovery set of 96 scenes runs on the 11 Study 1 models. Three representations encode the boundary: membership or repertoire (R1), a direct Boolean (R2), or the Boolean plus a prose rule (R3). A confirmation set of 96 new scenes with eight original characters runs on four models with contrasting Study 1 behavior: Gemma-4-31B, GLM-4.7-Flash, Nemotron-3-Nano and Qwen3.5-9B. Subsets add delays of two or four scripted neutral exchanges, a two-option choice of where to search, and five methods: full context with R2 or R3, prompted self-filtering (as M1g), removal of the inaccessible event, and a deterministic *character view* that

Test	Statistic	Estimate	95% CI	Holm p
H1	Not understood: repertoire only	66.7	[64.9, 68.5]	0.004
H1i	Not audible: flag only	72.2	[69.0, 75.5]	0.004
H2a	Repertoire − repertoire + sentence	32.7	[30.8, 34.6]	0.004
H2b	Audible flag − flag + narration	25.8	[23.7, 27.8]	0.004
H3	Repertoire − understood flag	21.6	[20.2, 23.0]	0.004
H4	Audible flag − understood flag	27.1	[24.9, 29.2]	0.004
H5a	Repertoire, probe answered correctly	68.4	[66.5, 70.3]	0.004
H5b	M1g: mean relative reduction (%)	64.7	[63.2, 66.1]	0.004
H5b	M1g: change in translator-enabled use	-2.0	[-3.8, -0.1]	joint

Table 2: Study 1 confirmatory family (11 models, 33 model–language units; estimates in pp unless noted). Tests are one-sided against the locked thresholds (H1, H1i, H5a: 10 pp; others: 0; H5b: reduction $\geq 50\%$ and change ≥ -5 pp), Holm-corrected over eight tests; 0.004 is the resolution of 2,000 bootstrap draws.

	Not understood		Not audible		Transl.
Model	Base	M1g	Base	M1g	(pp)
Gemma-4-31B	45.5	0.1	50.3	0.0	6.3
Qwen3.8-27B	49.6	0.1	57.7	0.5	5.1
GLM-4.7-Flash	46.2	58.5	68.3	71.4	16.3
Nemotron-3-Nano	70.2	35.2	86.4	34.7	-26.0
Mistral-Small-24B	65.8	45.2	72.7	53.0	-0.7
Gemma-4-12B	67.1	0.0	69.0	0.1	-4.9
Phi-4	69.9	10.0	72.7	42.0	-1.0
Falcon-H1-34B	79.1	4.3	74.7	31.4	-5.5
gpt-oss-20b	76.5	6.1	79.3	22.3	0.1
Seed-OSS-36B	73.3	0.1	80.9	0.3	1.4
Qwen3.5-9B	83.9	50.9	85.9	83.2	-12.8

Table 3: Study 1, M1g by model (content and planning questions). Leakage is net use in pp; the last column is the change in target use when a working translator makes the content accessible.

keeps accessible events and replaces inaccessible ones by an observable shell ("Alex appears to put something away"). Its hypotheses were fixed before generation. The three confirmatory families, Holm-corrected, are positive leakage in each channel (C1), positive leakage among replies whose state probe is correct (C2), and a joint benefit of the character view over full context and removal (C3).

5.2 Results

Leakage beyond speech. In the confirmation set, net use under full context is 72.3 pp for hearing, 47.2 for comprehension, 69.3 for sight and 67.6 for private messages (Table 5). Among replies whose matched state probe is correct, it is 64.0 pp (C2); averaged over channels, probe accuracy is 95–100% when the content is inaccessible and 93–99% when it is accessible (Table 12). The discovery set shows that profiles differ by channel (Figure 3): Mistral almost never uses content it cannot understand but uses unheard speech and private messages in 76–85 pp of replies, and Gemma-4-12B keeps visual boundaries but not private messages.

Format sensitivity. Under the R2 Boolean, Gemma-4-31B and Qwen3.8-27B leak little in any channel (Gemma 0.5–4.4 pp; Qwen3.8 9–28 pp), whereas in Study 1 the same models leak 51 and 60 pp when English speech carries only an inaudibility flag. Other models leak as much or more in Study 2 (Phi-4: 97 pp for unheard speech). The two inputs differ in three ways: Study 2's schema names the channel being tested, the scene is a single event, and the question asks for the item directly instead of coming from a companion who missed the speech. Together, these changes turn the two strongest models from leaking in most replies to almost never, so their compliance depends on the input format. Direct Booleans reduce leakage relative to repertoire or membership descriptions for hearing, comprehension and sight (by 18–33 pp) but barely for private messages (3.4 pp), and a prose rule on top of the Boolean has no consistent effect on comprehension (Appendix B).

Leaked facts persist and change choices. With the event still in context, leakage remains 51–71 pp after four neutral exchanges; for comprehension it grows by 15.6 pp [8.6, 22.7]. When characters choose between two places to search, switching the inaccessible fact from B to A changes the choice of A by 49–63 pp under full context, against 0–1 pp under the character view, with valid answers in over 96% of replies (Figure 4).

Methods. In the confirmation set both removal and the character view bring leakage to 0.03 pp, and the view keeps accessible use within the locked margin (+0.5 pp [−0.2, 1.2]; Table 17). The view differs from removal in what the character can still report: because it keeps the observable shell, characters say they noticed the actor in all partially ob-

Channel	Inaccessible condition	Compiled observation
HEAR	English speech cannot be heard	No observation
UNDERSTAND	Speech is heard in an unknown language	Actor says something in that language
SEE	Item and destination are hidden	Actor appears to put something away
RECEIVE	Message content is private to someone else	Actor visibly sends a message

Table 4: Study 2 channels. Each event contains an item–location fact. The character view replaces an inaccessible event by the observation in the last column; accessible controls keep the full event.




Figure 3: Study 2 discovery: 11 models, 96 scenes, direct Boolean (R2). (a) Net use of inaccessible content (pp); (b) use of the same content when it is accessible (%); (c) means over channels. Dots mark the four confirmation models.

servable scenes, against 32% under removal. Self-filtering, the prompted counterpart, reduces leakage but discards accessible content in some models: Qwen3.8-27B's use of content it is allowed to understand falls from 86% to 0% because the filter returns only "Casey says something in Japanese" (Appendix B).

6 Discussion

Across two studies, 11 models and four channels, role-playing models routinely voice information their characters could not have. The failure is not one of reading the state: the same models answer state questions correctly. Nor is it specific to language: hearing, sight and private messages leak at least as much. What changes behavior is the form of the input, and here the two studies disagree for the strongest models. A boundary that one prompt format makes almost watertight leaks in half of the replies under another. Evaluations of character consistency should therefore vary the input format: a low leakage score under one format says little about another.

For system builders, the most reliable remedy in our data is not to give the model what the character cannot access. When the system knows the access state, constructing a character-specific input removes leakage and, unlike instructions or few-shot examples, cannot be ignored; if the observation itself matters, a shell can keep it. When the system does not know the access state, a prompted filter such as M1g is the practical alternative, and its intermediate list should be checked, because that is where it fails.

Limitations

Measurement. Content use is scored by fixed rules over a finite dictionary of 12 places and 12 objects per study. Paraphrases, hedges naming several values, and mixed denials can be misclassified. We validated the scorer on 120 hand-written cases and inspected pilot replies, but the planned double human annotation has not been completed, so all estimates are automatic. A provisional screening by two AI annotators agreed with the scorer on target use (F1 about 98%) but found that it detects foil use poorly (recall 11–17% of AI-flagged foil uses); if human labels confirm this, D overstates net use. AI labels are not a reference standard.




Figure 4: Study 2, four confirmation models, 32 scenes. (a) Net use after zero, two or four neutral exchanges; (b) change from zero exchanges under full context; (c) change in choosing location A when the inaccessible fact switches from B to A. Bars are 95% skeleton-bootstrap intervals.

Family / component	Estimate (pp)	95% CI	Null	Holm p
C1: Hear	72.27	[70.90, 73.57]	0	0.0015
C1: Understand	47.20	[44.86, 49.61]	0	—
C1: See	69.27	[67.25, 71.35]	0	—
C1: Receive	67.58	[65.82, 69.34]	0	—
C2: State-correct net use	63.95	[62.73, 65.19]	0	0.0015
C3: Full minus view leakage	64.05	[62.81, 65.27]	0	0.0015
View minus full accessible use	0.49	[-0.18, 1.19]	−5	—
View minus hard event retention	67.75	[65.36, 70.05]	0	—

Table 5: Study 2 confirmation (four models, 96 original-character scenes). C1 requires all four channels to be positive, C2 uses replies whose state probe is correct (6,068), and C3 requires the view to reduce leakage, keep accessible use within 5 pp, and keep more observations than removal. One Holm-adjusted p per family.

Design and inference. Scenes are template-generated short interactions with a reused vocabulary; Study 1 uses characters from one game series and a present-day arm, Study 2 adds original characters. Languages are not crossed with vocabulary. Study 1's hypotheses were set after a pilot on separate items, and Study 2 was designed after Study 1's results; both analyses were locked locally before scoring or generation but not registered externally. Study 2's confirmation cohort has four models chosen partly for contrasting earlier behavior, and the two studies differ in several prompt features at once. Models are open checkpoints of at most 40B parameters with greedy decoding; hosted models and sampling were not tested. The character view assumes correct access metadata and predefined shells.

Ethical Considerations

All scenes, facts and conversations are fictional; Study 1 uses names of characters from a commercial game together with original descriptions and dialogue, and Study 2's confirmation set uses original characters. No personal data was collected and no human participants took part. The scores concern fictional access in role-play and should not be used to certify privacy or authorization systems.

AI assistance. AI assistants were used for code, experiment orchestration, literature search, statistical reporting and drafting. Provisional AI annotations are reported only as screening diagnostics. The authors are responsible for the content.

References

Jaewoo Ahn, Taehyun Lee, Junyoung Lim, Jin-Hwa Kim, Sangdoo Yun, Hwaran Lee, and Gunhee Kim. 2024. TimeChara: Evaluating point-in-time character hallucination of role-playing large language models. In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 3291–3325, Bangkok, Thailand. Association for Computational Linguistics.

Susan A. J. Birch and Paul Bloom. 2007. The curse of

knowledge in reasoning about false beliefs. *Psychological Science*, 18(5):382–386.

Yuling Gu, Oyvind Tafjord, Hyunwoo Kim, Jared Moore, Ronan Le Bras, Peter Clark, and Yejin Choi. 2026. SimpleToM: Exposing the gap between explicit ToM inference and implicit ToM application in LLMs. In *International Conference on Learning Representations*.

Sunkyung Han, Nahyeon Park, Gaeun Seo, Seunghyun Yoon, and JinYeong Bak. 2026. CHARM: Character Hallucination for Multicultural Role Play Benchmark. In *Findings of the Association for Computational Linguistics: EMNLP 2026*. To appear; arXiv:2609.01352.

Chani Jung, Dongkwan Kim, Jiho Jin, Jiseon Kim, Yeon Seonwoo, Yejin Choi, Alice Oh, and Hyunwoo Kim. 2024. Perceptions to beliefs: Exploring precursory inferences for theory of mind in large language models. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 19794–19809, Miami, Florida, USA. Association for Computational Linguistics.

Hyunwoo Kim, Melanie Sclar, Xuhui Zhou, Ronan Le Bras, Gunhee Kim, Yejin Choi, and Maarten Sap. 2023. FANToM: A benchmark for stress-testing machine theory of mind in interactions. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 14397–14413, Singapore. Association for Computational Linguistics.

Daeun Kyung, Hyunseung Chung, Seongsu Bae, Jiho Kim, Jae Ho Sohn, Taerim Kim, Soo Kyung Kim, and Edward Choi. 2025. PatientSim: A persona-driven simulator for realistic doctor-patient interactions. In *Advances in Neural Information Processing Systems, Datasets and Benchmarks Track*.

Niloofar Mireshghallah, Hyunwoo Kim, Xuhui Zhou, Yulia Tsvetkov, Maarten Sap, Reza Shokri, and Yejin Choi. 2024. Can LLMs keep a secret? testing privacy implications of language models via contextual integrity theory. In *International Conference on Learning Representations*.

Joon Sung Park, Joseph C. O'Brien, Carrie J. Cai, Meredith Ringel Morris, Percy Liang, and Michael S. Bernstein. 2023. Generative agents: Interactive simulacra of human behavior. In *Proceedings of the 36th Annual ACM Symposium on User Interface Software and Technology (UIST)*.

Yijia Shao, Tianshi Li, Weiyan Shi, Yanchen Liu, and Diyi Yang. 2024. PrivacyLens: Evaluating Privacy Norm Awareness of Language Models in Action. In *Advances in Neural Information Processing Systems*, volume 37.

Yunfan Shao, Linyang Li, Junqi Dai, and Xipeng Qiu. 2023. Character-LLM: A trainable agent for role-playing. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 13153–13187, Singapore. Association for Computational Linguistics.

Xushuo Tang, Junhe Zhang, Zihan Yang, Yifu Tang, Sichao Li, Longbin Lai, and Zhengyi Yang. 2026. Staying In Character: Perspective-Bounded Memory For Book-Based Role-Playing Agents. ArXiv:2606.25632.

Noah Wang, Z.Y. Peng, Haoran Que, Jiaheng Liu, Wangchunshu Zhou, Yuhan Wu, Hongcheng Guo, Ruitong Gan, Zehao Ni, Jian Yang, Man Zhang, Zhaoxiang Zhang, Wanli Ouyang, Ke Xu, Wenhao Huang, Jie Fu, and Junran Peng. 2024. RoleLLM: Benchmarking, eliciting, and enhancing role-playing abilities of large language models. In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 14743–14777, Bangkok, Thailand. Association for Computational Linguistics.

Alex Wilf, Sihyun Lee, Paul Pu Liang, and Louis-Philippe Morency. 2024. Think twice: Perspective-taking improves large language models' theory-of-mind capabilities. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 8292–8308, Bangkok, Thailand. Association for Computational Linguistics.

Xuhui Zhou, Hao Zhu, Leena Mathur, Ruohong Zhang, Haofei Yu, Zhengyang Qi, Louis-Philippe Morency, Yonatan Bisk, Daniel Fried, Graham Neubig, and Maarten Sap. 2024. SOTOPIA: Interactive evaluation for social intelligence in language agents. In *International Conference on Learning Representations*.

Zhuoning Zhu, Xingyu Gao, and Hailong Shi. 2026. MENTOR: Mitigating identity drift in dynamic role-playing via dual-chain structured memory. In *Findings of the Association for Computational Linguistics: ACL 2026*, pages 20865–20882, San Diego, California, United States. Association for Computational Linguistics.

A Study 1 Details

Pilot and hypotheses. A 10-skeleton pilot on 13 models compared a language repertoire with narrated inaudibility and found that the difference came from how the boundaries were stated; matched per-utterance flags reversed it. The hypotheses in Table 2 were fixed after the pilot, pilot items are excluded from all estimates, and the analysis was locked before scoring. The pilot's filter named only non-comprehension in its first step; M1g names both boundaries.

Models and scale. Mistral-Small-3.1-24B could not be loaded with the pinned software stack and was replaced by the text-only Mistral-Small-24B-Instruct-2501. In the scale arm, leakage under the

repertoire rises with capability within Qwen3.5 (0.8B: 13.9 pp; 2B: 40.5; 4B: 76.5; 9B: 82.9), consistent with smaller models understanding less of the foreign speech (2B and 0.8B fail the Japanese translation gate); Gemma-4-E2B uses little content in any condition.

B Study 2 Details

Ten models ran on H200 GPUs and Seed-OSS-36B on an H100 with the same software and decoding (seed 20261001, 400 new tokens). The campaign comprises 220,088 generation calls; 26 discovery replies were truncated and remain in the denominators as non-use. The comprehension estimate restricted to model–language units passing the translation gate is 51.0 pp [48.4, 53.7] (Table 14). Tables 21 and 22 reproduce one confirmation case verbatim.

Model	Main prompt	Boundary-instruction	Minimal	Community
Gemma-4-31B	45.5 [38.9, 52.2]	23.1 [18.3, 28.4]	50.6 [44.3, 57.2]	51.0 [44.7, 57.4]
Qwen3.8-27B	49.6 [43.7, 54.9]	23.0 [18.2, 27.6]	46.9 [41.5, 52.0]	51.8 [46.9, 56.4]
Qwen3.5-9B	83.9 [80.5, 87.0]	84.7 [81.4, 87.8]	93.1 [90.7, 95.1]	95.6 [94.3, 96.9]

Table 6: Study 1: language-boundary leakage (repertoire only, pp) under three alternative system prompts. The boundary-instruction prompt tells the model to preserve visible knowledge boundaries.

Model	Step-1 list names target (%)		Translator use change
	Not understood	Not audible	(pp) [95% CI]
Gemma-4-31B	0.0	0.0	6.3 [3.4, 9.6]
Qwen3.8-27B	0.7	13.2	5.1 [-0.7, 11.4]
GLM-4.7-Flash	90.6	90.2	16.3 [11.8, 20.9]
Nemotron-3-Nano	31.1	39.1	-26.0 [-32.1, -19.8]
Mistral-Small-24B	15.3	64.1	-0.7 [-4.8, 3.6]
Gemma-4-12B	0.0	0.2	-4.9 [-10.7, 0.8]
Phi-4	8.6	49.5	-1.0 [-6.4, 4.3]
Falcon-H1-34B	5.8	60.5	-5.5 [-9.5, -1.6]
gpt-oss-20b	2.4	26.5	0.1 [-3.8, 3.9]
Seed-OSS-36B	0.0	0.0	1.4 [-2.6, 5.2]
Qwen3.5-9B	53.4	93.2	-12.8 [-18.6, -7.2]

Table 7: Study 1: target use in the M1g step-1 perception list, which predicts where the filter fails.

Subset	Reduction (%)	Translator (pp)	H5b p
zh	66.6	-5.1	0.523
ja	66.0	-2.8	0.055
es	61.5	2.0	0.004
Without Kerry	62.9	-0.5	0.004
Without Panam	64.1	-0.5	0.004
Without Rogue	67.0	-4.9	0.464
Two-way bootstrap	64.7	-2.0	0.130

Table 8: Study 1: H5b by language, leaving one character out, and with a two-way (skeleton $\times$ character) bootstrap. The joint criterion fails in several subsets.

Variant	Not underst.	Not audible	Reduction (%)	Translator (pp)	Supported
Unconditional (no capability filter)	66.5	72.2	64.7	-2.2	8/8
Soft hedge credit	66.7	72.2	64.7	-1.9	8/8
Exclude truncated	66.7	72.2	64.7	-2.0	8/8
Exclude language/echo flags	67.0	72.2	64.8	-2.3	8/8
Complete responses only	66.7	72.2	64.7	-1.9	8/8
Worst-case failed M1g	66.7	72.2	64.6	-2.0	8/8
Both canaries required	47.8	54.5	61.9	1.3	8/8

Table 9: Study 1 scoring and conditioning sensitivities.

Exploratory contrast	Estimate (pp)	95% CI	BH q
Denial with use (C−T− D1)	4.9	[4.3, 5.5]	0.002
Unattributed-use share: D1 − U	7.6	[5.6, 9.6]	0.002
Offline − absent translator	0.1	[-0.5, 0.7]	0.767
Original unmatched contrast (C−T− − narrated)	20.3	[19.1, 21.5]	0.002
Few-shot reduction (4 models)	40.4	[37.6, 43.3]	0.002
Direct address − overheard	8.3	[4.9, 11.6]	0.002
Spoken-only − full state	0.2	[-1.2, 1.4]	0.804
zh − ja	1.1	[-0.3, 2.7]	0.160
zh − es	-4.5	[-6.9, -2.2]	0.002
ja − es	-5.7	[-8.2, -3.1]	0.002
Explicit admission: D1 − U	-0.3	[-0.4, -0.2]	0.002
Admission incl. attribution: D1 − U	-9.4	[-10.8, -8.0]	0.002
Canon C+: D0 − U	1.4	[-1.5, 4.6]	0.392
Canon weak C−: D0 − U	-3.4	[-6.6, 0.3]	0.109
Name prior C−: D0 − U	-4.5	[-8.9, -0.5]	0.045
Present-day world − main set	-16.4	[-24.9, -7.8]	0.002

Table 10: Study 1 exploratory family (Benjamini–Hochberg, $q = .10$). The world comparison uses different scenario sets.

Model	Hear	Understand	See	Receive	State correct	Conditional D
Gemma-4-31B	5.47	0.00	16.41	22.40	100.00	11.07
GLM-4.7-Flash	87.24	71.09	66.41	52.60	99.87	69.30
Nemotron-3-Nano-30B	98.96	66.41	97.66	98.96	95.18	90.01
Qwen3.5-9B	97.40	51.30	96.61	96.35	100.00	85.42

Table 11: Confirmation model detail. Boundary columns and conditional D are net canary-use points; state correctness is a percentage. Every model has eligible role endpoints.

Model	Channel	No correct (/192)	Yes correct (/192)	False Yes	False No
Gemma-4-31B	Hear	192 (100.00%)	192 (100.00%)	0	0
Gemma-4-31B	Understand	192 (100.00%)	192 (100.00%)	0	0
Gemma-4-31B	See	192 (100.00%)	187 (97.40%)	0	5
Gemma-4-31B	Receive	192 (100.00%)	192 (100.00%)	0	0
GLM-4.7-Flash	Hear	191 (99.48%)	192 (100.00%)	1	0
GLM-4.7-Flash	Understand	192 (100.00%)	192 (100.00%)	0	0
GLM-4.7-Flash	See	192 (100.00%)	178 (92.71%)	0	14
GLM-4.7-Flash	Receive	192 (100.00%)	190 (98.96%)	0	2
Nemotron-3-Nano-30B	Hear	155 (80.73%)	192 (100.00%)	37	0
Nemotron-3-Nano-30B	Understand	192 (100.00%)	192 (100.00%)	0	0
Nemotron-3-Nano-30B	See	192 (100.00%)	141 (73.44%)	0	51
Nemotron-3-Nano-30B	Receive	192 (100.00%)	192 (100.00%)	0	0
Qwen3.5-9B	Hear	192 (100.00%)	192 (100.00%)	0	0
Qwen3.5-9B	Understand	192 (100.00%)	192 (100.00%)	0	0
Qwen3.5-9B	See	192 (100.00%)	175 (91.15%)	0	17
Qwen3.5-9B	Receive	192 (100.00%)	192 (100.00%)	0	0

Table 12: Independent confirmation access probes in both states. No is the correct inaccessible answer and Yes the correct accessible answer. Each cell contains 96 scenes times two versions; all 6,144 outputs are valid. False Yes and False No count the two error directions. Model-level accuracy averages four equally sized channels; always No gives 50% on the balanced 3,072/3,072 population.

Boundary	State-correct D [95% CI]	N	Capability-eligible D [95% CI]	N
Hear	72.19 [70.79, 73.50]	1460	72.19 [70.79, 73.50]	1460
Understand	47.20 [44.86, 49.61]	1536	50.98 [48.36, 53.67]	1152
See	69.27 [67.25, 71.35]	1536	69.27 [67.25, 71.35]	1536
Receive	67.58 [65.82, 69.34]	1536	67.58 [65.82, 69.34]	1536

Table 13: State-correct boundary decomposition in the four-model confirmation. Values are pp. The .85 gate applies only to comprehension; all of its state probes are correct. Eligibility is fixed from translation results, and model-specific ratios are recomputed over the original 96-scene bootstrap.

Model	Chinese	Japanese	Spanish
Gemma-4-31B	100.00	100.00	100.00
GLM-4.7-Flash	100.00	62.50	100.00
Nemotron-3-Nano-30B	100.00	75.00	87.50
Qwen3.5-9B	100.00	62.50	100.00

Table 14: Both-canary translation use on 64 original-character prompts per model–language unit (%). The diagnostic threshold is 85%; the primary analysis is unconditional.

Boundary	Membership minus flag	Prose+flag minus flag
Hear	17.52 [14.96, 20.08]	-37.59 [-41.29, -33.90]
Understand	28.60 [25.47, 31.82]	-3.98 [-8.05, -0.09]
See	32.86 [28.98, 36.84]	-17.52 [-22.54, -13.35]
Receive	3.41 [0.57, 6.34]	-37.88 [-41.38, -34.09]

Table 15: Representation effects on inaccessible net use (pp), with 95% intervals. Eleven completed discovery models, 24 matched scenes. The same comprehension prose contrast is +5.73 [0.00, 11.98] in the four-core subset.

Boundary	Method	Inaccessible D	Accessible target use
Hear	Full	57.20 [54.69, 59.55]	89.67 [86.63, 92.10]
Hear	Prose+flag	34.38 [31.16, 37.59]	93.40 [90.71, 95.66]
Hear	Self-filter	47.74 [44.62, 50.87]	93.49 [91.06, 95.66]
Hear	Hard removal	0.09 [0.00, 0.26]	89.06 [85.42, 92.01]
Hear	Character view	0.09 [0.00, 0.26]	88.98 [85.33, 92.01]
Understand	Full	30.99 [27.69, 33.94]	91.49 [88.54, 94.01]
Understand	Prose+flag	32.29 [29.34, 35.07]	95.57 [93.66, 97.31]
Understand	Self-filter	2.00 [0.87, 3.39]	62.93 [59.64, 66.06]
Understand	Hard removal	0.00 [0.00, 0.00]	87.76 [84.11, 90.97]
Understand	Character view	-0.09 [-0.26, 0.00]	87.76 [84.20, 90.97]
See	Full	45.66 [41.49, 49.48]	79.34 [75.17, 83.16]
See	Prose+flag	27.17 [24.57, 29.60]	96.61 [95.23, 97.74]
See	Self-filter	22.22 [19.79, 24.57]	81.51 [78.21, 84.46]
See	Hard removal	0.00 [0.00, 0.00]	80.56 [76.39, 84.38]
See	Character view	-0.09 [-0.26, 0.00]	80.47 [76.39, 84.38]
Receive	Full	56.77 [53.65, 59.64]	94.18 [90.97, 96.61]
Receive	Prose+flag	31.25 [29.17, 33.42]	96.79 [95.57, 97.83]
Receive	Self-filter	4.77 [3.21, 6.60]	53.04 [48.87, 57.21]
Receive	Hard removal	-0.09 [-0.26, 0.00]	90.89 [87.59, 93.66]
Receive	Character view	0.00 [-0.26, 0.26]	90.89 [87.59, 93.66]

Table 16: Five methods in the complete prespecified six-model discovery cohort on 48 matched scenes (1,152 endpoints per cell). Leakage is net pp; accessible use is a percentage. Intervals are 95% paired-bootstrap intervals.

Method	Leakage	Access. use	Event retention
Full context	64.08	92.82	73.26
Hard removal	0.03	93.33	32.25
Character view	0.03	93.31	100.00

Table 17: Confirmation cohort. Leakage is net D in pp; accessible target use and partial-event retention are percentages. Retention excludes Hear. Full-context and projected inputs may have different schemas even in accessible controls.

Boundary	Method	Delay 0	Delay 2	Delay 4
Hear	full	69.14 [65.23, 72.66]	68.75 [65.62, 71.88]	71.09 [67.97, 73.83]
Hear	view	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
Understand	full	42.58 [36.72, 48.05]	52.73 [48.05, 57.03]	58.20 [53.12, 63.28]
Understand	view	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
See	full	55.47 [49.61, 61.33]	50.00 [44.14, 55.86]	50.78 [43.75, 57.03]
See	view	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
Receive	full	67.97 [63.67, 71.88]	68.36 [63.67, 72.66]	69.53 [66.02, 72.66]
Receive	view	-0.39 [-1.17, 0.00]	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]

Table 18: Delayed net use (pp), 32-scene subset, with 95% intervals. The original event remains in context throughout the scripted exchanges.

Boundary	Method	Fixed-A choice contrast	95% CI	Valid choices (%)
Hear	full	63.28	[53.91, 71.09]	99.61
Hear	view	0.78	[0.00, 2.34]	96.88
Understand	full	54.69	[47.66, 60.94]	100.00
Understand	view	0.00	[0.00, 0.00]	100.00
See	full	49.22	[42.97, 54.69]	100.00
See	view	0.00	[0.00, 0.00]	99.22
Receive	full	55.47	[46.88, 64.06]	99.61
Receive	view	0.00	[0.00, 0.00]	97.66

Table 19: Fixed-A decision contrast (pp) and response validity. The choice of location A is tracked across versions, independently of its option number.

Boundary	Method	A first (18 scenes)	A second (14 scenes)	Equal-position effect
Hear	full	65.28 [56.94, 72.22]	60.71 [42.86, 75.00]	63.00 [53.27, 71.23]
Hear	view	0.00 [0.00, 0.00]	1.79 [0.00, 5.36]	0.89 [0.00, 2.68]
Understand	full	56.94 [50.00, 63.89]	51.79 [39.29, 62.50]	54.37 [47.12, 60.91]
Understand	view	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
See	full	50.00 [43.06, 56.94]	48.21 [39.29, 57.14]	49.11 [42.76, 54.86]
See	view	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
Receive	full	59.72 [50.00, 69.44]	50.00 [35.71, 62.50]	54.86 [45.53, 63.10]
Receive	view	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]

Table 20: Option-position sensitivity (pp, 95% intervals). A/B order and the question are identical within every pair. The equal-position estimate weights the two order strata equally and resamples scenes independently within each stratum; original paired effects and tests remain unchanged.

Input component	Exact saved text or specified substitution
Role system prefix	`You are role-playing Mira Sen. Use the character sheet and the scene to reply to your companion in one short English spoken turn. Return only the spoken words.`
Shared character	`[Character] Mira Sen is an original fictional volunteer in Harrowbay, a contemporary coastal civic district. They are practical, polite, and concise. They rely on their own observations. Their history and relations are defined only by this scene.`
Full scene (A, no access)	`[Scene state] {"character_id": "Mira Sen", "events": [{"actor": "Alex", "audible_to_Mira Sen": false, "boundary_channel": "Hear", "content": "The glove is in the church.", "event_id": "e1", "kind": "speech", "language": "English"}], "observable_event_shell": null, "scene": "An original community team is preparing an activity. Its members have not shared the latest finding."}`
Role user message	`What information did you get about the item and its location?`
Independent probe prefix	`Read the scene as an evaluator. Answer the access question with only Yes or No.`
Independent probe user	`Did Mira Sen hear the utterance?`
Counterfactual B	Replace `The glove is in the church.` with `The broom is in the stairwell.`
Accessible control	Replace `audible_to_Mira Sen: false` with `true`.
Inaccessible view scene	`[Scene state] {"character_id": "Mira Sen", "observations": [], "scene": "An original community team is preparing an activity. Its members have not shared the latest finding."}`

Table 21: Exact messages for the selected hearing case, with A/B and access-state substitutions. The probe shares the full scene and character but has its own prefix and question. View shares the role prefix and question and substitutes the displayed observation JSON. Accessible view contains the permitted event in its observation list.

Version	Access	Probe	Full-context spoken reply	Character-view spoken reply
A	No	No	I heard Alex mention the glove is in the church, though he wasn't speaking to me directly.	I haven't received the latest findings yet; the team members haven't shared them.
B	No	No	I heard Alex mention the broom is in the stairwell, though they weren't speaking to me directly.	I haven't received the latest findings yet; the team members haven't shared them.
A	Yes	Yes	Alex mentioned the glove is in the church.	Alex mentioned the glove is in the church.
B	Yes	Yes	Alex mentioned the broom is in the stairwell.	Alex just told me the broom is in the stairwell.

Table 22: All saved content replies and independent probe answers for C001, Qwen3.5-9B, R2, delay zero. Full replies score $(T, F, D) = (1, 0, 1)$ in all four rows; inaccessible view scores $(0, 0, 0)$ and accessible view $(1, 0, 1)$.