

AXI4-Lite VVC – Quick Reference

axilite_write (VVCT, vvc_instance_idx, addr, data, [byte_enable], msg)

Example: axilite_write(AXILITE_VVCT, 1, x"6000", x"F102", "Writing data to Peripheral 1");

axilite_read (VVCT, vvc_instance_idx, addr, msg)

Example: axilite_read(AXILITE_VVCT, 1, x"6000", "Read from Peripheral 1");

axilite_check (VVCT, vvc_instance_idx, addr, data, msg, [alert_level])

Example: axilite_check(AXILITE_VVCT, 1, x"6000", x"393B", "Check data from Peripheral 1");

VVC



axilite_vvc.vhd

AXI4-Lite VVC Configuration record 'vvc_config'

Parameter name	Type	C_AXILITE_VVC_CONFIG_DEFAULT
inter_bfm_delay	t_inter_bfm_delay	C_AXILITE_INTER_BFM_DELAY_DEFAULT
cmd_queue_count_max	natural	C_CMD_QUEUE_COUNT_MAX
cmd_queue_count_threshold	natural	C_CMD_QUEUE_COUNT_THRESHOLD
cmd_queue_count_threshold_severity	t_alert_level	C_CMD_QUEUE_COUNT_THRESHOLD_SEVERITY
bfm_config	t_axilite_bfm_config	C_AXILITE_BFM_CONFIG_DEFAULT
msg_id_panel	t_msg_id_panel	C_VVC_MSG_ID_PANEL_DEFAULT

AXI4-Lite VVC Status record signal 'vvc_status'

Parameter name	Type
current_cmd_idx	natural
previous_cmd_idx	natural
pending_cmd_cnt	natural

Common VVC procedures applicable for this VVC

- See UVVM Methods QuickRef for details.

await_completion()

enable_log_msg()

disable_log_msg()

fetch_result()

flush_command_queue()

terminate_current_command()

terminate_all_commands()

insert_delay()



UVVM™

VVC target parameters

Name	Type	Example(s)	Description
VVCT	t_vvc_target_record	AXILITE_VVCT	VVC target type compiled into each VVC in order to differentiate between VVCs.
vvc_instance_idx	integer	1	Instance number of the VVC

VVC functional parameters

Name	Type	Example(s)	Description
addr	unsigned	x"325A"	The address of a SW accessible register. Could be offset or full address depending on the DUT
data	std_logic_vector	x"F1A332D3"	The data to be written (in axilite_write) or the expected data (in axilite_check).
byte_enable	std_logic_vector	(others => '1')	This argument selects which bytes to use (all '1' means all bytes are updated)
msg	string	"Send to peripheral 1"	A custom message to be appended in the log/alert
alert-level	t_alert_level	ERROR or TB_WARNING	Set the severity for the alert that may be asserted by the method.

VVC entity signals

Name	Type	Description
clk	std_logic	VVC Clock signal
axilite_vvc_master_if	t_axilite_if	See AXI4-Lite BFM documentation

VVC entity generic constants

Name	Type	Default	Description
GC_ADDR_WIDTH	integer	8	Width of the AXI4-Lite address bus
GC_DATA_WIDTH	integer	32	Width of the AXI4-Lite data bus
GC_INSTANCE_IDX	natural	1	Instance number to assign the VVC
GC_AXILITE_CONFIG	t_axilite_bfm_config	C_AXILITE_BFM_CONFIG_DEFAULT	Configuration for the AXI4-Lite BFM, see AXI4-Lite BFM documentation.
GC_CMD_QUEUE_COUNT_MAX	natural	1000	Absolute maximum number of commands in the VVC command queue
GC_CMD_QUEUE_COUNT_THRESHOLD	natural	950	An alert will be generated when reaching this threshold to indicate that the command queue is almost full. The queue will still accept new commands until it reaches C_CMD_QUEUE_COUNT_MAX.
GC_CMD_QUEUE_COUNT_THRESHOLD_SEVERITY	t_alert_level	WARNING	Alert severity which will be used when command queue reaches GC_CMD_QUEUE_COUNT_THRESHOLD.

VVC details

All VVC procedures are defined in `vvc_methods_pkg` (dedicated this VVC), and `uvvm_vvc_framework.uvvm_methods_pkg` and `uvvm_vvc_framework.uvvm_support_pkg` (common VVC procedures)

1 VVC procedure details and examples

Procedure	Description
axilite_write()	<p>The <code>axilite_write()</code> VVC procedure adds a write command to the AXI4-Lite VVC executor queue, which will run as soon as all preceding commands have completed. When the write command is scheduled to run, the executor calls the AXI4-Lite BFM <code>axilite_write()</code> procedure, described in the AXI4-Lite BFM QuickRef.</p> <p><code>axilite_write</code> can be called with or without <code>byte_enable</code> constant. When not set, <code>byte_enable</code> is set to all '1', indicating that all bytes are valid.</p> <p>axilite_write(VVC, instance_idx, addr, data, [byte_enable,] msg)</p> <p>e.g.:</p> <ul style="list-style-type: none"> - <code>axilite_write(AXILITE_VVCT, 1, x"0011A000", x"F102", "Writing data to Peripheral 1");</code> - <code>axilite_write(AXILITE_VVCT, 1, C_ADDR_PERIPHERAL_1, x"F102", b"11", "Writing data to Peripheral 1");</code> - <code>axilite_write(AXILITE_VVCT, 1, C_ADDR_DMA, x"1155F102", "Writing data to DMA");</code>
axilite_read()	<p>The <code>axilite_read()</code> VVC procedure adds a read command to the AXI4-Lite VVC executor queue, which will run as soon as all preceding commands have completed. When the read command is scheduled to run, the executor calls the AXI4-Lite BFM <code>axilite_read()</code> procedure, described in the AXI4-Lite BFM QuickRef.</p> <p>The read value will not be returned in this procedure call since it is non-blocking for the sequencer/caller, but the read data will be stored in the VVC for a potential future fetch. The data will be available until overwritten by new read-data depending on the read-data buffer size.</p> <p>axilite_read(VVC, instance_idx, addr, msg)</p> <p>e.g.</p> <ul style="list-style-type: none"> - <code>axilite_read(AXILITE_VVCT, 1, x"00099555", "Read from Peripheral 1");</code> - <code>axilite_read(AXILITE_VVCT, 1, C_ADDR_IO, "Read from IO device");</code>
axilite_check()	<p>The <code>axilite_check()</code> VVC procedure adds a check command to the AXI4-Lite VVC executor queue, which will run as soon as all preceding commands have completed. When the check command is scheduled to run, the executor calls the AXI4-Lite BFM <code>axilite_check()</code> procedure, described in the AXI4-Lite BFM QuickRef. The <code>axilite_check()</code> procedure will perform a read operation, then check if the read data is equal to the 'data' parameter. If the read data is not equal to the expected 'data' parameter, an alert with severity 'alert_level' will be issued. The read data will not be stored by this procedure.</p> <p>axilite_check(VVC, instance_idx, addr, data, msg, [alert_level])</p> <p>e.g.</p> <ul style="list-style-type: none"> - <code>axilite_check(AXILITE_VVCT, 1, x"00099555", x"393B", "Check data from Peripheral 1", ERROR);</code> <p>The procedure can also be called without using the optional parameter, e.g.:</p> <ul style="list-style-type: none"> - <code>axilite_check(AXILITE_VVCT, 1, C_ADDR_IO, x"393B", "Check data from IO device");</code>

2 VVC Configuration

Name	Type	C_AXILITE_BFM_CONFIG_DEFAULT	Description
inter_bfm_delay	t_inter_bfm_delay	C_AXILITE_INTER_BFM_DELAY_DEFAULT	Minimum delay between BFM accesses from the VVC. If parameter delay_type is set to NO_DELAY, BFM accesses will be back to back, i.e. no delay.
cmd_queue_count_max	natural	C_MAX_COMMAND_QUEUE	Maximum pending number in command queue before queue is full. Adding additional commands will result in an ERROR.
cmd_queue_count_threshold	natural	C_CMD_QUEUE_COUNT_THRESHOLD	An alert with severity "cmd_queue_count_threshold_severity" will be issued if command queue exceeds this count. Used for early warning if command queue is almost full. Will be ignored if set to 0.
cmd_queue_count_threshold_severity	t_alert_level	C_CMD_QUEUE_COUNT_THRESHOLD_SEVERITY	Severity of alert to be initiated if exceeding cmd_queue_count_threshold
bfm_config	t_axilite_bfm_config	C_AXILITE_BFM_CONFIG_DEFAULT	Configuration for AXI4-Lite BFM. See quick reference for AXI4-Lite BFM
msg_id_panel	t_msg_id_panel	C_VVC_MSG_ID_PANEL_DEFAULT	VVC dedicated message ID panel

The configuration record can be accessed from the Central Testbench Sequencer through the shared variable array, e.g.:

```
shared_axilite_vvc_config(1).inter_bfm_delay.delay_in_time := 50 ns;
shared_axilite_vvc_config(1).bfm_config.clock_period      := 10 ns;
```

3 VVC Status

The current status of the VVC can be retrieved during simulation. This is achieved by reading from the shared variable shared_axilite_vvc_status record from the test sequencer. The record contents can be seen below:

Name	Type	Description
current_cmd_idx	natural	Command index currently running
previous_cmd_idx	natural	Previous command index to run
pending_cmd_cnt	natural	Pending number of commands in the command queue

4 VVC Interface

In this VVC, the interface has been encapsulated in a signal record of type *t_axilite_if* in order to improve readability of the code. Since the AXI4-Lite interface busses can be of arbitrary size, the interface std_logic_vectors have been left unconstrained. These unconstrained SLVs needs to be constrained when the interface signals are instantiated. For this interface, the could look like:

```
signal axilite_if_1 : t_axilite_if( write_address_channel( awaddr( C_ADDR_WIDTH -1 downto 0)),
                                   write_data_channel    ( wdata ( C_DATA_WIDTH -1 downto 0),
                                                            wstrb(( C_DATA_WIDTH/8)-1 downto 0)),
                                   read_address_channel   ( araddr( C_ADDR_WIDTH -1 downto 0)),
                                   read_data_channel      ( rdata ( C_DATA_WIDTH -1 downto 0)) );
```

5 Additional Documentation

Additional documentation about UVVM and its features can be found under “/uvvm_vvc_framework/doc/”.

For additional documentation on the AXI4-Lite standard, please see the AXI4-Lite specification “AMBA® AXI™ and ACE™ Protocol Specification - AXI3™, AXI4™, and AXI4-Lite™ ACE and ACE-Lite™”, available from ARM.

6 Compilation

AXI4-Lite VVC must be compiled with VHDL 2008.

It is dependent on the following libraries

- **UVVM Utility Library (UVVM-Util), version 1.0.0 and up**
- **UVVM VVC Framework, version 1.0.0 and up**
- **AXI4-Lite BFM**

Before compiling the AXI4-Lite VVC, assure that uvvm_vvc_framework and uvvm_util have been compiled.

Compile order for the AXI4-Lite VVC:

Compile to library	File	Comment
bitvis_vip_axilite	axilite_bfm_pkg.vhd	AXI4-Lite BFM
bitvis_vip_axilite	vvc_cmd_pkg.vhd	AXI4-Lite VVC command types and operations
bitvis_vip_axilite	../uvvm_vvc_framework/src_target_dependent/td_target_support_pkg.vhd	UVVM VVC target support package, compiled into the AXI4-Lite VVC library.
bitvis_vip_axilite	../uvvm_vvc_framework/src_target_dependent/td_vvc_framework_common_methods_pkg.vhd	UVVM framework common methods compiled into the AXI4-Lite VVC library
bitvis_vip_axilite	vvc_methods_pkg.vhd	AXI4-Lite VVC methods
bitvis_vip_axilite	../uvvm_vvc_framework/src_target_dependent/td_queue_pkg.vhd	UVVM queue package for the VVC
bitvis_vip_axilite	../uvvm_vvc_framework/src_target_dependent/td_vvc_entity_support_pkg.vhd	UVVM VVC entity support compiled into the AXI4-Lite VVC library
bitvis_vip_axilite	axilite_vvc.vhd	AXI4-Lite VVC

7 Simulator compatibility and setup

This VVC has been compiled and tested with Modelsim version 10.3d and Riviera-PRO version 2015.10.85.

For required simulator setup see **UVVM-Util** Quick reference.

IMPORTANT

This is a simplified Verification IP (VIP) for AXI4-Lite. The given VIP complies with the basic AXI4-Lite protocol and thus allows a normal access towards an AXI4-Lite interface. This VIP is not AXI4-Lite protocol checker. For a more advanced VIP please contact Bitvis AS at support@bitvis.no

**INTELLECTUAL
PROPERTY**

Disclaimer: This IP and any part thereof are provided "as is", without warranty of any kind, express or implied, including but not limited to the warranties of merchantability, fitness for a particular purpose and noninfringement. In no event shall the authors or copyright holders be liable for any claim, damages or other liability, whether in an action of contract, tort or otherwise, arising from, out of or in connection with this IP.